MILITARY SPECIFICATION

BODY ASSEMBLY, TANK PERISCOPE: 10513599

This amendment forms a part of Military Specification MIL-B-60135(MU), dated 22 January 1965.

Paragraph 3.11: Delete paragraph and substitute:

"3.11 Image tilt. The image of a target line originally perpendicular to a plane, defined by the 2-inch-long shoulder (generated by the machining of the two pads) adjacent to Valve Assembly 8201751, shall emerge perpendicular to the same plane within 45 minutes of arc."

Paragraph 3.13: Delete "7.0 minutes" and substitute "4.0 minutes".

* Paragraph 4.4.2.4: Delete and substitute:

"4.4.2.4 Devices to test optical performance requirements. The device used to determine the acceptability of the optical requirements shall provide for the positioning of the four mounting pads in a plane perpendicular to the incident line of sight. Centrally position the body assembly in the device by locating against the 2-inch-long shoulder adjacent to the valve assembly. This device shall also provide two target images, each consisting of a horizontal and vertical line and appropriate resolving target pattern for resolution testing (see MIL-O-13830). The intersecting point of these lines shall be placed on the optical axis of a projector collimator. The optical axis of each collimator projector shall lie in the same plane when both vertical lines are parallel to a plumb line. Illumination of these targets (reticles) shall be by means of a Tungsten radiation source and an infrared filter. This filter shall not pass visible light rays below 0.65 microns. This testing device shall also incorporate features for holding two unity-power viewing telescopes arranged in a pair to be utilized as viewing collimators. The reticles of the viewing collimators shall consist of a horizontal and vertical center line, the intersecting point of which shall be on the optical axis. The reticles shall also be provided with a grid pattern located on the optical axis. Each horizontal and vertical line shall represent an angle of five minutes. The optical axis of the viewing collimators shall be positioned perpendicular to the optical axis of the projector collimators when the vertical reticle lines are parallel to a plumb line. This device shall also provide a power supply of 24 Vdc to illuminate the body assembly under test and provide a power source to illuminate the reticles of the two projector collimators.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:12Z
Check the source to verify that this is the current version before use.

* The outside margin has been marked to indicate where an addition to the previous amendment has been made. This has been done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content as written irrespective of the marginal notation and relationship to the last previous issue.

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1240-A493Y

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:12Z
Check the source to verify that this is the current version before use.