MILITARY SPECIFICATION

CONTROL INDICATOR C-8157( )/ARC

Page 1

2.1: Delete "MIL-T-5422 Testing, Environmental, Aircraft Electronic Equipment".

Page 6

3.12.1: Delete in its entirety and substitute:

"3.12.1 Temperature-Altitude Combination (See 4.7.1). - The equipment shall be subjected to and meet the temperature-altitude combination requirements as Class 2 equipment non-operating from -62°C to +95°C, intermittent from 71°C to 95°C, operating and conforming to limits from -54°C to 71°C. Altitude shall be a maximum of 70,000 feet."

3.12.2: Delete in its entirety.

3.12.5: Add - "NOTE: Light bulb failures during vibration are considered irrelevant."

Page 8

3.13.2, Column "Resistance Reading in Ohms", first line: Delete "0.3" and substitute "0.4".

Page 9

4.1: Delete in its entirety and substitute:

"4.1 Responsibility for inspection. - Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements."

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:56Z
Check the source to verify that this is the current version before use.

Page 10

4.5: Add at end of paragraph - "Each equipment of each lot of equipment shall be subjected to the Burn-In, Debugging (3.15) prior to inspection. Failure to meet any requirements as a result of the Burn-In, Debugging shall be classified as a defect and recorded as such."

4.5.1: Delete in its entirety and substitute the following:

"4.5.1 Group A inspection. - Each unit of each lot of equipment shall be inspected for conformance to all the inspection and test requirements of Table I. Each lot will be subject to verification and utilizing the procedures of MIL-STD-105 using the general inspection levels and the AQL's indicated in Table I. Group A inspection shall be performed in any order which is satisfactory to the Government, except that the operational inspection 4.10 shall be last (See 6.3)."

Page 12

4.5.4, Table III, Subgroup I, first line: Delete "Temperature" substitute "Temperature-Altitude Combination, second line: Delete in its entirety.

Page 13

4.7, lines 2 and 4: Delete "MIL-T-5422" and substitute "MIL-STD-810".

4.7.1: Delete entire paragraph and substitute the following:

"4.7.1 Temperature-Altitude Combination. - The equipment shall be subjected to the test of Method 504 of MIL-STD-810 utilizing Table 504-1 for Class 2 equipment."

Page 14

4.7.2: Delete in its entirety.

4.7.3: Delete entire paragraph and substitute:

"4.7.3 Relative Humidity. - The equipment shall be subjected to the test of Method 507 of MIL-STD-810 Procedure II."

4.7.4: Delete entire paragraph and substitute:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:56Z
Check the source to verify that this is the current version before use.

"4.7.4 Sand & Dust. - The unit(s) shall be subjected to the Sand & Dust test specified in Method 510 of MIL-STD-810 to determine compliance with 3.12.4."

4.7.5: Delete entire paragraph and substitute:

"4.7.5 Vibration. - The unit(s) shall be subjected to the Vibration test of Method 514.1 of MIL-STD-810 for compliance with 3.12.5.

NOTE: Lamp failures during vibration testing are considered irrelevant. Upon completion of Vibration test, replace all failed bulbs prior to conducting electrical test."

4.7.6.1: Delete entire paragraph and substitute:

"4.7.6.1 Bench Handling. - The unit shall be subjected to the test of Method 516, Procedure V of MIL-STD-810. Performance tests shall be conducted before, during and after shock to verify compliance with 4.10 at supply voltage of 27.5 volts."

4.7.6.2: Delete entire paragraph and substitute:

"4.7.6.2 Equipment. - The equipment shall be subjected to the test of Method 516, Procedures I and III of MIL-STD-810. The shock pulses shall be in accordance with Figure 516-2 for flight vehicle equipment."

4.7.9: Delete entire paragraph and substitute:

"4.7.9 Explosive Conditions. - The equipment shall be subjected to the test of Method 511 of MIL-STD-810 for compliance with 3.12.9."

CUSTODIAN
ARMY - EL

Preparing Activity
ARMY - EL
Project No. 5821-A101

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:56Z
Check the source to verify that this is the current version before use.