MIL-F-50520 (AR)
Amendment 1
10 August 1981

MILITARY SPECIFICATION

FUZE, PD, M536; DELAY DETONATOR
ASSEMBLY FOR: LOADING, ASSEMBLING AND PACKING

This amendment forms a part of Military Specification MIL-F-50520 (MU), dated 27 March 1970.

PAGE 1

Add the following Preamble underneath the title: "This specification is approved by the U.S. Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense."

PAGE 3

3.3, last line: Delete "baffle."

PAGE 7

4.3.2.4: Delete "8886832" and substitute "9206731."

4.3.2.5: Delete "8886832" and substitute "9206731."

4.3.2.6: Delete "8886832" and substitute "9206731."

PAGE 8

4.3.2.7: Delete "8886833" and substitute "9206732."

4.3.2.8: Delete "8886833" and substitute "9206732."

PAGE 9

4.3.2.9: Delete in its entirety.

4.3.2.10: Delete in its entirety.

4.3.2.11: Delete in its entirety.

FSC: 1390

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:27Z
Check the source to verify that this is the current version before use.

PAGE 10

4.3.2.12: Delete in its entirety.

4.3.2.13: Delete in its entirety.

4.3.2.14: Delete in its entirety.

PAGE 11

4.3.3.1: Delete in its entirety and substitute the following:
"4.3.3.1 Moisture content of delay composition (See Dwg. 8864620), Major defect, Code No. 15001. -The contractor shall provide adequate controls to insure compliance with the applicable requirement. The moisture content of each lot of delay composition shall be determined at the loading station at the time of loading the delay assemblies. This determination shall be made at least once for each eight (8) hours of production. A sample of approximately ten (10) grams shall be selected for this test. The sample shall be stored in air tight container until this test is performed. If the moisture content fails to comply with the requirement specified on the applicable drawing and loading gun has not begun, the lot shall be redried for a period of 24 hours and a second sample selected for the moisture content determination. If loading has begun, delay assemblies loaded with non-conforming delay composition shall be rejected. This test shall be performed as specified in 4.4.1."

4.3.3.2; line 2: Delete "At the loading station at the time of loading, a sample shall be selected in accordance with Specification MIL-P-45486." and substitute "Prior to pelleting, select a composite sample of approximately 20 grams from each blend and submit to Chemical laboratory."

PAGE 12

4.3.3.6: Delete "(See Dwg. 8886832 or when applicable dwg 8886937)" and substitute "(See Dwg. 9206731)."

4.4.1: Delete in its entirety and substitute the following:
"4.4.1 Transfer an accurately weighed portion of approximately two (2) grams of the sample to a tared shallow receptacle and dry in an oven for two (2) hours at a temperature of 100 $\pm$ 5 degrees centigrade (C). Cool in a desiccator and weigh. Calculate the loss in weight of the receptacle and contents to percent moisture in the sample and compare with drawing requirements. This test is a destructive test. Samples shall not be returned to the lot."

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:27Z
Check the source to verify that this is the current version before use.

4.4.3, line 2: Delete "baffle."

PAGE 13

5.2.1, line 3: Delete "8886833 and 8886832, or as an alternate dwgs. 8886938 and 8886937" and substitute "9206731, 9271924 and 9206732."

5.3, line 2: Delete "8886833 and 8886832, or as an alternate dwgs. 8886938 and 8886839" and substitute "9271931, 9206732, and 9271924."

Custodian:
Army-AR

Preparing Activity:
Army-AR

Project No. 1390-A312

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:27Z
Check the source to verify that this is the current version before use.