MIL-P-60646B (AR)
AMENDMENT 2
19 September 1984
SUPERSEDING
AMENDMENT 1
15 June 1984

MILITARY SPECIFICATION

PROJECTILE, 105MM, HEAT-T, M456A1
METAL PARTS

This amendment forms a part of Military Specification MIL-P-60646B (AR), dated 24 April 1984, and is approved by the US Army Armament, Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 6

4.3.1: Delete "Plug and Disc Assembly.....8597489.....20".

PAGE 7

TABLE I: Category I, delete "9. 8597489 - Plug and Disc Assy.....20.....3.1.....4.4.2.9".

PAGE 29

4.4.2.9: Delete this paragraph in its entirety.

PAGE 43

* 4.5.5.2.4: Delete this paragraph in its entirety and substitute:

"4.5.5.2.4 Weapon zeroing - boresight and superelevation. Actual superelevation of the weapon shall be measured and recorded for all target dispersion test phases. This requires that the weapon be zeroed at the beginning, end and during any extended breaks (30 minutes or longer) in target impact test phases using a conventional collimated M26 Pye Watson boresight (or equivalent). Record the weapon elevation and azimuth which aligns the boresight zero on the target center. Then record weapon elevation and azimuth data for all test and calibration phases. The gun superelevation is the weapon

FSC 1315

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:52Z
Check the source to verify that this is the current version before use.

elevation during the test phases minus the weapon elevation which produced a muzzle boresight on target center. This data shall be obtained when using either a fixed mount or a service tank weapon system. This information shall be recorded for information only and included in the ballistic test report."

* 4.5.5.2.4.1: Add new paragraph 4.5.5.2.4.1:

"4.5.5.2.4.1 Gun tube backlash removal. After loading and locking a round in the chamber, the gun tube shall be traversed off the target center, dropped down below the target center, traversed to the opposite side of the target center, elevated to the target center elevation, and traversed onto the target center. The distance traversed and dropped should be sufficient to remove the backlash from the system. If the sight is above or beyond the target center, do not reverse direction of gun tube movement, but repeat the sequence."

PAGE 47

5.1.1.3: Delete this paragraph in its entirety.

NOTE: The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to last previous amendment.

Custodian:
Army-AR

Preparing Activity
Army-AR

(Project 1315-A646)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:52Z
Check the source to verify that this is the current version before use.