INCH-POUND

MIL-P-63238B(AR)
AMENDMENT 2
21 October 1993
SUPERSEDING
AMENDMENT 1
27 July 1991

MILITARY SPECIFICATION

PROJECTILE, 155MM, AT M718/M741
LOADING, ASSEMBLING AND PACKING OF

This Amendment forms a part of Military Specification MIL-P-63238B(AR), dated 1 May 1986, and is approved for use within the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 10

4.4.1 subparagraph a: Delete in its entirety and substitute "Projectile metal parts (Body Assembly) from one lot interfix number from one manufacturer."

Add new subparagraph:

"e. Bases from one lot interfix number from one manufacturer."

PAGE 23

4.4.2.11, Major 104: Change "Sealant" to Sealing Compound".

PAGE 24

4.4.2.12:

Major 102: Change "Gage" to Gage/4.5.11" under PARAGRAPH REFERENCE/INSPECTION METHOD and change "0.40%" to "100%" under AQL.

Add Minor defect 202 as follows:

"202 Sealant not present between projectile body and base (360°0 0.65% 3.2 Visual".

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:27Z
Check the source to verify that this is the current version before use.

PAGE 38

* 4.4.3.9: Delete in its entirety and substitute the following:

"4.4.3.9 Ballistic test. The quantity and type of projectile from each lot to be subjected to ballistic tests shall be as specified below. Lots of projectiles shall conform to the lotting provisions of 4.4.1 but in no case shall exceed one (1) months production. HE Projectiles shall be randomly selected from the lot. Non-Hazardous Projectiles (para. 6.4.b) shall comply with the lotting requirements of MIL-P-63430.

TEST CONFIGURATION/TEST ZONE (SEE 6.4)

TOTAL TEST QTY PER SYSTEM	HE TYPE QTY	HE TYPE ZONE	NON HAZ TEST QTY	NON HAZ TEST ZONE	TEST QTY OF MINES/ TEST PERFORMED
6-M718 Proj	1	3	2	3	6/Self Dest. 12/Sensor
	1	7	2	7	6/Self Dest. 12/Sensor
6-M741 Proj	1	3	2	3	6/Self Dest. 12/Sensor
	1	7	2	7	6/Self Dest. 12/Sensor

PAGE 44

4.5.11: Add new paragraph:

"4.5.11 Inspection of gap between projectile body and base. Gap shall be inspected using an approved feeler gage as specified on drawing 9215220. The feeler gage shall be cleaned with a clean dry rag immediately after each inspection such that the gage is free of any base/body gap sealant. No solvent or other substance other than a clean dry rag shall be used to clean the gage. The gap between the projectile body and base shall be inspected within fifteen (15) minutes after the sealant is applied to the shoulder of the base."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:27Z
Check the source to verify that this is the current version before use.

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relation to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1320-AD10)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:27Z
Check the source to verify that this is the current version before use.