MIL-W-60305A
6 January 1969
SUPERSEDING
MIL-W-60305(MU)
11 January 1968

MILITARY SPECIFICATION

WARHEAD, 2.75 INCH ROCKET, SMOKE, WP, M156

(WITH BURSTER AND FUZE)

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers a complete 2.75 inch rocket warhead.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-1235 - Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes.

DRAWINGS

US Army MUNITONS COMMAND

EDGEWOOD ARSENAL

DL90-1-44 - Warhead, 2.75 Inch Rocket, Smoke, WP, M156.

FSC 1340

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:27Z
Check the source to verify that this is the current version before use.

PICATINNY ARSENAL

F8886811 - Container, Ammo, Fiber, M523, for Warhead 2.75 Inch Rocket, HE, M151; Smoke WP M156 and Practice XM230.
C8886810 - Box, Packing, Ammunition, for Warhead, 2.75 Inch Rocket, HE, M151; Smoke WP M156 and Practice XM230.
C9209570 - Box, Packing, Ammunition, for Warhead 2.75 Inch Rocket, Smoke, WP, M156.

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3, REQUIREMENTS

3.1 Materials and components. All materials and components cited on Drawing DL90-1-44 and subsidiary drawings shall conform to the specifications listed thereon or to the specific characteristics set forth on the drawings.

3.2 Assembly. The warhead shall be assembled in accordance with Drawing D90-1-44 (see 6.3).

3.3 Ballistic test (proof testing). Warheads shall be provided for Government proof testing (see 4.1.2, 4.2.2.2, 4.2.4, and 4.2.5). The warheads shall be activated, and each shall produce a high-order detonation upon impact in the designated target area.

3.4 Workmanship The warhead shall be free from contamination and damage such as cracks or deformation which could affect its intended use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.

4.1.1 Supplier's responsibility. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to specified requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:27Z
Check the source to verify that this is the current version before use.

4.1.2 Government's responsibility. The Government shall be responsible for proof testing. Samples shall be forwarded to the proving ground designated by the contracting officer (see 6.2).

4.1.3 Objective evidence. The supplier shall provide objective evidence acceptable to the contracting officer that the requirements of 3.1 and section 5 for which specific inspection has not been provided in this specification have been satisfied.

4.2 Quality conformance inspection.

4.2.1 Lotting. A lot shall consist of the M156 rocket warheads, of one interfix number, produced by one manufacturer, in one unchanged process in accordance with the same drawings, the same drawing revision, the same specification and the same specification revision. However, no more than one lot of loaded fuzes of one interfix number from one manufacturer, and one lot of loaded bursters of one interfix number from one manufacturer shall be represented in any one lot of finished warheads.

4.2.2 Sampling.

4.2.2.1 For examination. Sampling shall be conducted in accordance with MIL-STD-105 or MIL-STD-1235. .

4.2.2.2 For ballistic test (proof testing). A random sample of 24 warheads shall be selected from each lot. Each such warhead shall be marked with an identification number.

4.2.3 Inspection Procedure.

4.2.3.1 For examination. Sample warheads shall be examined in accordance with the classification of defects and MIL-STD-105 or MIL-STD-1235 as applicable. If MIL-STD-1235 is used an AQL of 2.5 percent defective shall be applied to each major defect.

4.2.3.2 For ballistic test (proof testing). Sample warheads shall be tested in accordance with 4.2.4 and 4.2.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:27Z
Check the source to verify that this is the current version before use.

4.2.3.3 Classification of defects.

(a) Warhead, 2.75 inch rocket, smoke, WP, M156 (with burster and fuze) (Drawing D90-1-44).

Categories		Defects
Critical:		None defined
Major:		AQL 1.0 percent defective
	101	Components missing
	102	Fuze torque incorrect
	103	Cement missing
	104	Identification marking incorrect or illegible
	105	Protective finish missing
	106	Silicone grease missing from acme threads
	107	Workmanship (3.4)

(b) Preparation for delivery (section 5).

Categories		Defects
Critical:		None defined
Major:		AQL 2.5 percent defective
	101	Loose package or pack
	102	Support ring missing
	103	Spacer incorrect or missing
	104	Lot number incorrect or illegible
	105	Marking incorrect or illegible
	106	Container closure incorrect

4.2.4 Ballistic test (proof testing). Prior to firing, each sample warhead shall be X-rayed for radiographic record of the condition of the fuze and of the entire warhead. The X-ray shall be identified by the number of the warhead and examined by prooving ground personnel prior to firing of accepted lot. Each sample warhead shall be attached to an accepted motor and fired into the designated target area.

4.2.5 Ballistic test procedure. The M156 warhead shall be assembled in accordance with 3.2 and function fired at 10 degrees quandrant elevation for impact on a-land range.

4.2.6 Acceptance/rejection criteria. If one or more warheads fail to produce high-order detonation, the lot shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:27Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Packaging, level A. The assembled warhead shall be packaged in fiver cans in accordance with Drawing F8886811.

5.2 Packing, level A. Four warheads packaged as specified in 5.1 shall be packed in two layers of two each within wood ammunition boxes as specified on Drawing C8886810. When warheads are shipped as part of a complete unassembled round, packing shall conform to Picatinny Arsenal Drawing 9209570.

5.3 Marking. Marking of unit packages and snipping containers shall be accomplished in accordance with the instructions shown on Drawings F8886811 and C8886810, except that the descriptive nomenclature shall be "Warhead 2.75 inch Rocket, Smoke, WP, M156." The container shall be marked with arrows and the word “UP” in accordance with the requirements of MIL-STD-129.

6. NOTES

6.1 Intended use. This item is intended for use as a conponent of an air to ground rocket carried by aircraft.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number and date of this specification.
(b) The proving around that will proof test the rockets.
(c) The agency that will supply the rocket motor if supplier is to assemble rocket motor to warhead.
(d) The agency that will assemble the rocket if supplier is not to assemble rocket motor to warhead.
(e) Record of proof testing results shall be sent to the Commanding Officer, Edgewood Arsenal, ATTN: SMUEA-[illegible]E-S, Edgewood Arsenal, Maryland 21010.

6.3 Caution. Due to the hazards of loading warheads, installations are advised to take all possible precautions to protect personnel from injury while loading warheads.

6.4 Cleaning. The exterior surface of the loaded warhead may be cleaned by passing through a hot water and detergent spray washer prior to fuzing.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:27Z
Check the source to verify that this is the current version before use.

6.5 Component specifications. The following specifications are requires for the manufacture of the 2.75 inch warhead.

MIL-W-60307(MU) - Warhead, 2.75 Inch Rocket, Smoke, WP, M156 (Metal Parts)
MIL-W-60306(MU) - Warhead, 2.75 Inch Rocket, Smoke, WP, M156 (WP Filling)

Custodians:

Army - MU
Air Force - 70

Review activities:

Air Force - 70

User activities:

Navy - AS
Air Force - 15

Preparing activity:

Army - MU(EA)

Project No. 1340-0048

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:27Z
Check the source to verify that this is the current version before use.

TO DETACH FORM – CUT ON THIS LINE

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel either Government or contractor involved in the use of the specification in procurement of products for military use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

SPECIFICATION

ORGANIZATION

CITY AND STATE | TYPE OF ORGANIZATION

MATERIAL PROCURED UNDER A
DIRECT GOVERNMENT CONTRACT SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?
YES NO (If "yes", in what way?)

4. REMARKS (Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.)

SUBMITTED BY (Printed or typed name and activity – Optional) | DATE

DD FORM 1 JAN 64 1426 REPLACES DD FORM 1426, 1 APR 58, WHICH IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:27Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID

OFFICIAL BUSINESS

Commanding Officer
Edgewood Arsenal
ATTN: SMUEA-QAES
Edgewood Arsenal, Maryland 21010

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:27Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:27Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:27Z
Check the source to verify that this is the current version before use.

INTERIM AMENDMENT

MILITARY SPECIFICATION

WARHEAD, 2.75 INCH ROCKET, SMOKE, WP, M156

(WITH BURSTER AND FUZE)

This amendment forms a part of Military Specification MIL-W-60305A, dated 7 July 1971, and is approved for use by all Departments and Agencies of the Department of Defense.

Page 1

2.1: Delete "MIL-STD-129" in its entirety.

Under "DRAWINGS" delete "C9209570" in its entirety and substitute the following:

8796521 - Marking and Sealing for Ammunition Fiber Containers.
8796522 - Marking Diagram and Sealing for Wood Packing Boxes.

Under "DRAWINGS" delete "US ARMY MUNITIONS COMMAND" and substitute, "US ARMY ARMAMENT COMMAND."

Add: "19-48-4015-12P1000 - Palletization of White Phosphorus (WP) and Plasticized White Phosphorus (PWP) Load Ammunition."

Page 3

4.2.1: Delete the second sentence in its entirety and substitute the following:

"In the lot of finished warheads the loaded fuzes shall be from one manufacturer made under one interfix number and the loaded bursters shall be from one manufacturer made under one interfix number, but no more than 5 lots of loaded fuzes or bursters shall be in any one lot of finished warheads."

FSC 1340

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:27Z
Check the source to verify that this is the current version before use.

4.2.2.2: Delete in its entirety and substitute the following:

"4.2.2.2 For ballistic test (proof testing). A random sample of 24 warheads shall be selected from each lot. Each warhead shall be marked with an identification number. Should one round fail to produce high order detonation an additional sample of 24 warheads shall be randomly selected and marked with an identification number."

Page 4

4.2.3.3(a): Under "Critical" add "WP leakage or evidence of leakage."

4.2.3.3(a): Delete 103 characteristic in its entirety.

4.2.6: Delete in its entirety and substitute the following:

"4.2.6 Acceptance/rejection criteria. If two warheads fail to produce high order detonation the lot shall be rejected. If one warhead fails to produce high order detonation; test an additional 24 samples. Should one or more of these additional 24 samples fail to produce a high order detonation; the lot shall be rejected."

Page 5

5.1: Change "in fiber cans" to "in a fiber can."

5.2: Delete last sentence in its entirety.

5.3: Delete in its entirety and Substitute the following:

"5.3 Marking. Marking of unit packages and shipping containers will be accomplished in accordance with the instructions shown on drawings 8796521 and 8796522, except that the descriptive nomenclature shall be “Warhead, 2.75 Inch Rocket, Smoke, WP, M156."

Add the following:

“5.4 Palletization. When specified in the contract or order, warheads, packed as specified in 5.2, shall be palletized in accordance with Drawing 19-48-4015-12P1000, unit 14 on page 8, except that the arrangement shall be 5 by 5."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:27Z
Check the source to verify that this is the current version before use.

6.6: Add the following:

"6.6 Lot formation. The provisions of 4.2.1 are designed to avoid proliferation of small lots during LAP of warheads, because of discrepancies in the delivered lot sizes of fuzes and bursters with planned lot sizes of warheads. They are not intended to permit indiscriminate mixing of fuzes and bursters in warhead lots. Fuzes and bursters should be introduced into the LAP process in an orderly manner to insure that the practical minimum number lots of fuzes and bursters appear In each warhead lot."

Custodian:

Army - EA

Preparing activity:

Army - EA

Project No. 1340-A509

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:27Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:27Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:27Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:27Z
Check the source to verify that this is the current version before use.

NOTICE OF INACTIVATION FOR NEW DESIGN

INCH-POUND

MIL-W-60305A
NOTICE 2
25 March 1996

SUPERSEDING
NOTICE 1
5 December 1986

MILITARY SPECIFICATION

WARHEAD, 2.75 INCH ROCKET, SMOKE, WP, M156 (WITH BURSTER AND FUZE)

This notice should be filed in front of MIL-W-60305A, dated 6 January 1969, with Amendment 2, dated 4 March 1976.

MIL-W-60305A is inactive for new design and is no longer used except for replacement purposes.

Custodian:

Army - EA

Preparing activity:

Army - EA

(Project 1340-0978)

AMSC N/A

FSC 1340

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:27Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:27Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:27Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:27Z
Check the source to verify that this is the current version before use.