MILITARY SPECIFICATION SHEET

CAPACITORS, FIXED, PLASTIC (OR PAPER-PLASTIC) DIELECTRIC, AXIAL-WIRE TERMINAL, TUBULAR (INSULATED) (HERMETICALLY SEALED IN METAL CASES), ESTABLISHED RELIABILITY, STYLE CQR39

This amendment forms a part of Military Specification Sheet MIL-C-19978/16A, dated 30 September 1982, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Note 4, delete and substitute:

"4. Capacitors with dimension L of 1.562 or D of .562 and larger, are not intended to be supported by their leads. These capacitors shall be supported with a supplementary means of mounting, such as a wrap-around band. The supporting device will not be supplied with the capacitor."

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Army - AR, MI
Navy - AS, TD
Air Force - 11, 17, 99
DLA - ES

User activities:
Army - AT, Av, ME
Navy - AS, MC, OS, SH

Agent:
DLA - ES

Preparing activity:
Air Force - 85

(Project 5910-1503-8)

FSC 5910

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:07Z
Check the source to verify that this is the current version before use.