MILITARY SPECIFICATION SHEET

CAPACITORS, FIXED, PLASTIC (OR PAPER-PLASTIC) DIELECTRIC, AXIAL-WIRE TERMINAL, TUBULAR (INSULATED) (HERMETICALLY SEALED IN METAL CASES), STYLE CQ05

This amendment forms a part of Military Specification Sheet MIL-C-19978/19A, dated 7 April 1975, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

*Note 4, delete and substitute:

"4. Capacitors with dimension L of 1.438 or D of .562 and larger, are not intended to be supported by their leads. These capacitors shall be supported with a supplementary means of mounting, such as a wrap-around band. The supporting device will not be supplied with the capacitor."

FIGURE 1, NOTES: After note 4, add the following:

"5. Lead length may be a minimum of 1-inch long for use in tape and reel packaging when specified in the ordering data."

NOTE: The margin of this amendment is marked with an asterisk to indicate where a change (addition) from the previous amendment was made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notation and relationship to the last previous amendment.

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Army - AR, MI
Navy - AS, TD
Air Force - 11, 17, 99
DLA - ES

User activities:
Army - AT, AV, ME
Navy - AS, MC, OS, SH

Agent:
DLA - ES

Preparing activity:
Air Force - 85

(Project 5910-1503-9)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T07:09Z
Check the source to verify that this is the current version before use.