MIL-C-12918C (MU)
10 September 1971
SUPERSEDING
MIL-C-12918B (MU)
28 February 1964

MILITARY SPECIFICATION

CHARGE, DEMOLITION, BLOCK, M5A1, ASSEMBLY PARTS FOR, LOADING, ASSEMBLING AND PACKING

1. SCOPE

1.1 This specification covers the parts for, loading, assembling and packing for one type of demolition block designated as Charge, Demolition, Block, M5A1, Assembly.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-2550 - Ammunition and Special Weapons; General Specification for

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105)
MIL-STD-109 - Quality Assurance Terms and Defintions
MIL-STD-1168 - Lot Numbering of Ammunition
MIL-STD-1235 - Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes

FSC: 1375

Source: https://assist.dla.mil -- Downloaded: 20261O-17T23:40Z
Check the source to verify that this is the current version before use.

DRAWINGS

U.S. ARMY MUNITIONS COMMAND

7549132 - Box, Packing, Ammunition, for Charge, Demolition Block, M5 or M5A1
8833395 - Charge, Demolition, Block, M5A1, Assembly

PUBLICATIONS

U.S. ARMY MUNITIONS COMMAND

ET-8833395 - Equipment Tabulation

(Copies of specifications, standards, drawings and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer).

3. REQUIREMENTS

3.1 Material.-Materials and parts shall be in accordance with applicable drawings and specifications.

3.2 The demolition block assemblies shall comply with all requirements specified on Drawing (dwg.) 8833395 and with all requirements specified in applicable specifications.

3.3 Workmanship.-All parts and assemblies shall be fabricated and loaded in a thorough, workmanlike manner. They shall be free of explosive on exterior, cracks, holes, tears, surface defects, voids, grease and other foreign matter. Colors shall be uniform. Exterior surface coatings shall be continuous except for a few light scratches not exposing base material. The cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agent. All required markings shall be neat and sharply defined.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.-Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance

Source: https://assist.dla.mil -- Downloaded: 20261O-17T23:40Z
Check the source to verify that this is the current version before use.

of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Reference shall be made to MIL-STD-109 to define terms used herein. The provisions of MIL-A-2550 shall apply.

4.1.1 Submission of product.-At the time each completed lot of items deliverable under the contract is submitted to the Government for acceptance, the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

a. A statement that the lot complies with all of the quality assurance provisions specified in this specification.
b. Drawing and specification number and date, together with identification and date of changes thereto.
c. A statement that all material purchased by the contractor meets requirements, when such material is controlled by Government or commercial specifications referenced in any of the contractual documents, and that certificates of conformance are on file and available for review.
d. Number of items in the lot.
e. Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless during the course of the contract, this authority is vested in another agent of the certifying organization

4.2 Inspection provisions

4.2.1 Lot formation.-The term "inspection lot" as used in this specification is defined as an essentially homogeneous collection of units of product from which a representative sample is drawn and inspected to determine conformance with applicable requirements. The sample selected shall represent only that quantity of units from which the sample was drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the inspection lot has been produced by one manufacturer, in one unchanged process, using the same materials and methods, in accordance with the same drawings, same drawing revisions, same specifications and same

Source: https://assist.dla.mil -- Downloaded: 202610-17T23:40Z
Check the source to verify that this is the currentversion before use.

specification revisions and complies with the provisions for submission of product as specified in MIL-STD-105. Changes to the process, specifications, or drawings not affecting safety, performance, interchangeability, or storage, as determined by the Government, shall not be deemed to alter the homogeneity of an inspection lot. All material submitted for inspection in accordance with this specification shall comply with the homogeneity criteria specified herein regardless of the type of sampling procedure which is being applied to determine conformance with requirements. Lot numbering, as required, shall be in accordance with MIL-STD-1168. Each lot of demolition block assemblies shall contain:

a. Parts or parts assemblies from not more than one lot interfix number from one manufacturer.
b. Composition C-4 from not more than 2 lots from one manufacturer.

4.2.2 Examination.-The examinations listed in the following subparagraphs shall be performed on inspection lots (see 4.2.1) of the components or assemblies designated in the applicable paragraph headings. Inspection for critical defects (and major defects, when so specified) shall be 100 percent. Sampling plans for major and minor defects shall be in accordance with MIL-STD-105 except that continuous sampling plans in accordance with MIL-STD-1235 may be used if approved by the Government. Instead of applying the AQL's designated herein to the groups of major and minor defects listed, the contractor may elect to apply AQL's to individual defects using an AQL of 0.40 percent for each major defect and an AQL of 0.65 percent for each minor defect. When this method is elected, it shall be applied to all of the major and minor defects listed in the applicable subparagraph of this section, except where 100 percent inspection is specified, and be documented as part of the contractor's inspection system. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.2.4.

4.2.2.1 Charge, block (see dwg. 8833396 covering a detail of dwg. 8833395).

Categories	Defects	Method of Inspection	Code No. (see 6.2)
Critical: None defined.			
Major:	AQL 0.40 percent		
101.	Weight of charge.....	Balance	01001

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:40Z
Check the source to verify that this is the current version before use.

Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.3)	Visual	01002

4.2.2.2 Plate, end (see dwg. 8833397 covering a detail of dwg. 8833395).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.40 percent		
101.	Pitch diameter, maximum (max.)	Gage	02001
102.	Minor diameter, max	Gage	02002
Minor:	AQL 1.0 percent		
201.	Length of side	Gage	02003
202.	Evidence of poor workmanship (see 3.3)	Visual	02004

4.2.2.3 Body (see dwg. 8833398 covering a detail of dwg. 8833395).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	None defined.		
Minor:	AQL 1.5 percent		
201.	Wall thickness	Gage	03001
202.	Length	Gage	03002
203.	Evidence of poor workmanship (see 3.3)	Visual	03003

4.2.2.4 Assembly (see dwg. 8833395)

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	None defined.		
Minor:	AQL 4.0 percent		
201.	Length, max	Gage	04001

Source: https://assist.dla.mil -- Downloaded: 20261O-17T23:40Z
Check the source to verify that this is the current version before use.

202.	Width, max	Gage	04002
203.	Height, max	Gage	04003
204.	Sides warped or wrinkled	Visual	04004
205.	Improper voids after assembly	Visual	04005
206.	Marking missing, incorrect or illegible	Visual	04006
207.	Heat seal missing or incomplete	Visual	04007
208.	Evidence of poor workmanship (see 3.3)	Visual	04008

4.2.2.5 Box, packing, prior to sealing (see dwg. 7549132).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.40 percent		
101.	Incorrect number of demolition charges	Visual	05001
Minor:	AQL 0.65 percent		
201.	Insufficient filler material	Visual	05002

4.2.2.6 Box, packing (see dwg. 7549132)

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.40 percent		
101.	Strapping missing, broken or loose	Visual-Manual	06001
102.	Box damaged so that contents are exposed or liable to become exposed	Visual	06002
Minor:	AQL 2.5 percent		
201.	Strapping improperly assembled	Visual-Manual	06003
202.	Handle loose or missing	Visual-Manual	06004

Source: https://assist.dla.mil -- Downloaded: 20261O-17T23:40Z
Check the source to verify that this is the current version before use.

203.	Car seal missing, unsealed or improperly positioned.....	Visual	06005
204.	Contents loose when box is tilted.....	Manual	06006
205.	Marking missing, incorrect, or illegible.....	Visual	06007

4.2.3 Testing

4.2.3.1 Specific gravity of block charge (see dwg.8833396 - Major defect - Code No. 07001.-The specific gravity of the block charge shall be determined for each lot of composition C-4 at the time of loading. A sample of ten (10) block charges shall be selected at random from each lot and tested as specified in 4.3.1, using equipment in accordance with 4.2.4. If two or more units fail to meet the specified requirement, the lot shall be rejected. If one unit fails to meet the requirement, a second sample of ten block charges shall be selected at random from the lot and tested. If in the combined test and retest, two or more failures occur, the lot shall be rejected.

4.3.4 Inspection equipment.-Equipment Tabulation Number ET-8833395 identifies the inspection equipment required to perform the examinations prescribed in this section. The contractor shall design inspection equipment in accordance with the instructions in 6.3.

4.3.4.1 Government rights to documentation.-Inspection equipment drawings and lists provided and revised in accordance with the requirements of the ET may be used by DOD activities for design, procurement, manufacture, testing, evaluation, production and receiving inspection, overhaul, shipping, storage, identification of stock, ordering and storage of replacement parts, inspection of items at overhaul, general maintenance of equipment, construction, survey and whenever inspection equipment drawings are needed.

4.3 Test methods and procedures

4.3.1 Determination of specific gravity of the explosive charge.-The specific gravity shall be determined as follows: Weigh the block charge to the nearest .01 pound. A suitable container provided with an overflow pipe approximately one-half inch in length shall be filled with water (at a temperature of 25 degrees Centigrade (C.) plus or minus 5 degrees C.) level with the overflow pipe. Insert a suitable stopper in the overflow pipe. Carefully place the block charge in the container so that it it completely submerged, taking care to remove all air bubbles remaining on the surfaces of the block charge. Place a tared container under the overflow pipe. Carefully remove the stopper from the pipe, collect the water which overflows and weigh to the nearest .01 pound. Calculate the specific gravity as follows:

Source: https://assist.dla.mil -- Downloaded: 202610-17T23:40Z
Check the source to verify that this is the current version before use.

$$\text{Specific gravity} = \frac{A}{B}$$

where:

A = weight of block charge
B = weight of water displaced

5. PREPARATION FOR DELIVERY

5.1 Preservation and packing

5.1.1 Packing and preservation for levels A, B, and C shall be as specified in dwg. 7549132.

5.2 Marking.-Marking of all packaging and packing shall comply with dwg. 7549132.

6. NOTES

6.1 Ordering data.-Procurement documents shall specify the following:

a. Title, number and date of this specification.

b. Data cards.-Data cards shall be prepared for each lot in accordance with the information specified in Standard MIL-STD-1167.

6.2 Inspection code numbers.-The five digit code numbers assigned to the inspection herein are to facilitate future data collection and analysis by the Government. These code numbers are also used to correlate the characteristics cited on Equipment Lists with the inspections listed in this specification. In addition, they should be cited as references on drawings of equipment designs submitted by the contractor to the Government for approval (see 6.3.5).

6.3 Inspection equipment.-The contractor shall design inspection equipment as required by the inspection Equipment Lists (EL) referenced on the applicable ET in accordance with the instructions of paragraphs 6.3.1 through 6.3.5.

6.3.1 Inspection equipment lists (EL).-Inspection equipment lists indicate the availability of inspection equipment designs by showing in the "number" column of the list of inspection equipment (Form SMUPA 1010) the numbers of drawings or Federal Stock numbers of existing equipment designs, or codes as indicated in paragraph 6.3.2. Design action required of the contractor is described in paragraphs 6.3.3 and 6.3.4. The contractor will be required to prepare detailed drawings in accordance with 6.3.4 for all the equipment coded as "Contractor Design" in the number column.

Source: https://assist.dla.mil -- Downloaded: 202610-17T23:40Z
Check the source to verify that this is the current version before use.

These contractor designs must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.5.

6.3.2 Inspection equipment list codes.-The inspection equipment as defined in 6.3.3 and 6.3.4 will be designated in the EL by the following codes:

CD - Contractor design on controlled contractor format and/or commercial equipment
MU - Army design, mandatory for use

6.3.3 Army designs.-Army designs are reflected on detailed drawings which completely depict all the information necessary for the fabrication of the item of inspection equipment. The contractor need provide no design when an Army design is listed for an item of inspection equipment. Army designs fall into two basic classifications; mandatory (designated "MU") and non-mandatory (indicated by drawing or Federal Stock Number). When an inspection equipment list references mandatory Army designs, the contractor shall comply with, and use these designs accordingly. The contractor may, however, in connection with non-mandatory designs, design alternate inspection equipment or use comparable commercial equipment to facilitate his operations. Such contractor prepared designs or commercial equipment selections must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.5.

6.3.4 Contractor designs.-Contractor designs are designs of inspection equipment for which the Government has assigned design responsibility to the contractor. Contractor designs shall be supported by detailed drawings which depict all information necessary to completely fabricate, calibrate and operate an item of inspection equipment. This requires that the necessary views, dimensions, materials, finish, notes, operating and calibration instructions be properly depicted in accordance with approved practices to the extent that further calculation or clarification will not be required. Unless otherwise specified, contractor designs may be developed on the format the contractor normally employs in his equipment design procedure provided such format reflects the detail and information specified above, subject to the following controls: All submitted contractor designs shall conform to MIL-D-1000, Category A, Form 2. Legibility and reproducibility shall permit conventional making of clearly understandable, high contrast reproductions. Contractors shall submit three copies of final designs as a flat set. Designs shall be submitted for approval as specified in 6.3.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:40Z
Check the source to verify that this is the current version before use.

6.3.5 Submission of contractor designs.-All submitted designs shall contain a reference to the applicable five digit Code Number contained in Section 4 of this specification and the appropriate component or assembly drawing number and revision letter to which the specific design applies. Unless otherwise specified on the EL, all design of equipment for inspection of defects classified as critical and major shall be submitted for approval to the Commanding Officer, Picatinny Arsenal, ATTN: SMUPA-ND 5. All other designs of inspection equipment shall be approved by the inspection element of the agency administering the contract; submission shall be as directed by the Contracting Officer. Partial submission of inspection equipment designs is permissible and encouraged. However, the Arsenal completion date for design review will be based on the date of the final submission of designs. Picatinny Arsenal design review will be accomplished normally within one month after receipt.

6.4 International standardization agreements.-Certain provisions of this specification (sections 3 and 4.2.2) are the subject of international standardization agreement (STANAG No. 2818). When amendment, revision, or cancellation of this specification is proposed which will effect or violate the international agreement concerned, the preparing activity will take appropriate reconciliation action through international standardization channels including departmental standardization offices, if required.

Custodian:
Army-MU

Preparing activity:
Army-MU

Project No. 1375-A138

Source: https://assist.dla.mil -- Downloaded: 202610-17T23:40Z
Check the source to verify that this is the currentversion before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity.

SPECIFICATION

ORGANIZATION | CITY AND STATE

CONTRACT NO. | QUANTITY OF ITEMS PROCURED | DOLLAR AMOUNT $

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)* | DATE

DD FORM 1 OCT 64 1426

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:40Z
Check the source to verify that this is the current version before use.