MIL-C-12926E (AR)
17 March 1981
SUPERSEDING
MIL-C-12926D (MU)
28 January 1964

MILITARY SPECIFICATION

CARTRIDGE, 4.2 INCH, ILLUMINATING, M335A2 LOADING, ASSEMBLING AND PACKING

This specification is approved for use by the US Army Armament Research and Development Command, and is available for use by all Departments and Agencies for the Department of Defense.

1. SCOPE

1.1 This specification contains requirements not covered by the drawings and provides quality assurance provisions for the loading, assembling and packing for one type of cartridge designated as Cartridge, 4.2 Inch, Illuminating, M335A2 with Fuze, MT, M565.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification for

MIL-C-50513 - Cartridge, Ignition, M2A2 Parts for, Loading, Assembling and Packing

FSC: 1315

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:41Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes

DRAWINGS (see 6.4)

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND (ARRADCOM)

7549247 - Container, Ammunition, Fiber, M251A1 for 4.2 Inch Mortar Ammo., Assembly, Details and Packing
7549248 - Box, Packing, Ammunition for 4.2 Inch Mortar Ammo., in Fiber Container M251A1 in Jungle Wrap
8886595 - Cartridge, 4.2 Inch, Illum., M335A2 Assembly

3. REQUIREMENTS

3.1 Materials. Materials shall be in accordance with applicable drawings and specifications.

3.2 Components and assemblies. The components and assemblies shall comply with all requirements specified on drawing (dwg.) 8886595 and with all requirements specified in applicable specification and standards.

3.3 Proving ground. The cartridge shall comply with the following requirements when tested as specified in 4.5.1.

3.3.1 Functioning. The cartridge shall fire and function satisfactorily (see 6.5) and shall provide effective illumination (see 6.6) for 60 seconds (sec.) minimum (min.)

3.3.2 Premature burst and security of parts. There shall be no premature burst or evidence of metal parts failure in the bore of the weapon or in the first 200 yards horizontal range. Separation of the cartridge container extension outside the gun bore is not considered a safety hazard.

3.4 Ignition cartridge check test for deterioration. If the total elapsed time between original acceptance of the

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:41Z
Check the source to verify that this is the current version before use.

ignition cartridge lot and the assembly of that lot into the complete round exceeds two years, or if the ignition cartridge has been subjected to adverse conditions for any period of time since previous tests, the ignition cartridge shall be subjected to, and must satisfactorily comply with the tests specified in MIL-C-50513 before the ignition cartridges are assembled into the complete round (see 6.9).

3.5 First article inspection. This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.6 Workmanship. The parts and assemblies shall be free from chips, dirt, grease and other foreign matter that may impair proper functioning. The cleaning method used shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agent.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspection. The following types of inspection shalll be conducted on this item:

a. First article inspection

b. Quality conformance inspection

4.3 First article inspection

4.3.1 Submission. The contractor snall submit a first article sample as designated by the contracting officer for evaluation in accordance with provisions of 4.3.2. This requirement is applicable when loading of projectile and assembly of cartridge is accomplished at the same contractor facility. The first article sample shall consist of fifteen cartridge assemblies.

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:41Z
Check the source to verify that this is the current version before use.

TABLE I - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-12926E (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
	Cartridge Assembly				8886595
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Examination for defects	15	100%	3.2	4.4.2.8
	Proving Ground	15	100%	3.3	4.4.3.1/4.5.1

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:41Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, inspection lots shall contain:

a. Loaded items of one lot interfix from one manufacturer
   1. Projectiles
   2. Fuzes
   3. Ignition cartridges
   4. Expelling charges

b. Items from one lot
   1. Propellant
   2. Bag loading assemblies

4.4.2 Examination. See MIL-A-48078. Unless otherwise specified in the Classification of Defects and Test tables, sampling plans and procedures for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:41Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-12926E (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.1	Projectile, Prior to Assembling Fuze and Obturating Mechanism	1 OF 1	8886453
			NEXT HIGHER ASSEMBLY 8886595

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major 101	Any component missing, damaged or loose		0.40%	3.2	Visual/Manual
Minor 201	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:41Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-12926E (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.2	Cartridge Assembly, Prior to Assembling Pressure Plate				886595
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Cartridge container fails to withstand reapplication of required assembly torque		0.40%	3.2	Gage
102	Rotating disc assembled improperly		0.40%	3.2	Visual
Minor					
201	Evidence of excessive sealing compound		0.65%	3.2	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:41Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-12926E (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.3	Cartridge Assembly, After Assembly of Pressure Plate and Pressure Plate Nut	1 OF 1	8886595
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Pressure plate assembled incorrectly (red face is visible)		100%	3.2	Visual
102	Movement of pressure plate nut on reapplication of assembly torque, prior to staking		0.40%	3.2	Gage
103	Nut improperly staked		0.40%	3.2	Visual
Minor	None defined				

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:41Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-12926E (AR)

PARAGRAPH	TITLE		SHEET	DRAWING NUMBER
4.4.2.4	Cartridge Assembly After Assembling Ignition Cartridge and Striker Nut Assembly		1 OF 1	8886595
				NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Striker nut fails to withstand disassembly torque		0.40%	3.2	Gage
102	Ignition cartridge missing		0.40%	3.2	Gage
103	Striker point missing or loose		0.40%	3.2	Visual/Manual
Minor	None defined				

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:41Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-12926E (AR)

PARAGRAPH	TITLE		SHEET		DRAWING NUMBER
4.4.2.5	Cartridge Assembly After Assembling Extension and Pin		1 OF 1		8886595
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major 101	Pin missing		0.40%	3.2	Visual
Minor	None defined				

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:41Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-12926E (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.6	Cartridge Assembly After Assembling Propelling Charge				8886595
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Excessive number of increments		100%	3.2	Visual
2	Warning label missing		100%	3.2	Visual
Major					
101	Insufficient number of increments		0.40%	3.2	Visual
102	Bag loading assembly missing		0.40%	3.2	Visual
103	Propellant holder missing		0.40%	3.2	Visual
Minor	None defined				

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:41Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.7	Cartridge Assembly, Prior to Assembling Fuze				8886595
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Expelling charge missing		0.40%	3.2	Visual
102	Adapter damaged		0.40%	3.2	Visual
Minor	None defined				

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:41Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-12926E (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.8	Cartridge Assembly, Prior to Packing				8886595
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Premature burst (Proving Ground)	48/15		3.3.2	4.4.3.1/4.5.1
Major					
101	Fuze fails to withstand disassembly torque		0.40%	3.2	Gage
102	Component damaged or improperly assembled		0.40%	3.2	Visual
103	Profile and alignment		100%	3.2	Gage
104	Functioning (Proving Ground)	48/15		3.3.1	4.4.3.1/4.5.1
105	Five inch pound disassembly torque, min.	(a)	0.65%	3.2	Gage
106	Fifty inch pound disassembly torque	(b)		3.2	Gage
Minor					
201	Fuze not staked		0.65%	3.2	Visual
202	Marking misleading or unidentifiable		0.65%	3.2	Visual
203	Protective coating with bare area in excess of 1/4 square inch		0.65%	3.2	Visual
204	Evidence of poor workmanship		0.65%	3.2	Visual

NOTES: (a) MIL-STD-1235 (b) One of each 25 cartridges produced shall be tested after profile-alignment. If the cartridge fails the requirement the cartridges represented by the Sample shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:41Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-12926E (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.9	Unsealed Fiber Container				7549247
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Spacer tube missing		0.40%	5.1	Visual
102	Support tube missing		0.40%	5.1	Visual
103	Gap between body and cover of container exceeding 1/8 inch		0.40%	5.1	Visual
Minor	None defined				

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:41Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-12926E (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.10	Sealed Fiber Container Wrapped in Barrier Material Prior to Waxing Jungle Wrap				7549247
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Sealing tape incomplete or badly wrinkled		0.40%	5.1	Visual
102	Barrier material improperly assembled		0.40%	5.1	Visual
103	Barrier material ends improperly folded or taped		0.40%	5.1	Visual
Minor					
201	Contents loose		0.65%	5.1	Manual
202	Tear tab length inadequate		0.65%	5.1	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:41Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-12926E (AR)

PARAGRAPH	TITLE		SHEET	DRAWING NUMBER
4.4.2.11	Sealed Fiber Container After Waxing Jungle Wrap		1 OF 1	7549247
				NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Wax coating incomplete or damaged		0.40%	5.1	Visual
Minor					
201	Marking missing or unidentifiable		0.65%	5.2	Visual
202	Kraft paper improperly placed on container		0.65%	5.1	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:41Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-12926E (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.12	Sealed Packing Box				7549248
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Box damaged exposing contents		0.40%	5.2	Visual
102	Hardware or strapping missing or loose		0.40%	5.2	Visual/Manual
Minor					
201	Car seal improrly installed		0.65%	5.2	Visual
202	Marking misleading or unidentifiable		0.65%	5.2	Visual

NOTES:

DRMAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:41Z
Check the source to verify that this is the current version before use.

4.4.3 Testing.

4.4.3.1 Proving ground.

4.4.3.1.1 First article. The fifteen sample cartridge assemblies shall be fired in three groups of five rounds each in accordance with 4.5.1. Observations shall be made for compliance with the criteria specified in Table I.

4.4.3.1.2 Production

4.4.3.1.2.1 Beginining with the first lot produced and continuing until three consecutive lots have been found to be acceptable, forty eight sample cartridges shall be randomly selected from each lot for this test. The cartridges shall be fired in three groups of sixteen rounds each in accordance with 4.5.1. Observatons shall be made for compliance with the criteria specified in Table I.

4.4.3.1.2.2 After three consecutive lots have complied with the criteria of 4.4.3.1.2.1, fifteen sample cartridges shall be randomly selected from each lot for this test. The cartridges shall be fired in three groups of five rounds each in accordance with 4.5.1. Observations shall e made for compliance with the criteria specified in Table I. In the event that three successive lots fail to comply with the requirements the acceptance criteria shall revert to 4.4.3.1.2.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:41Z
Check the source to verify that this is the current version before use.

TABLE I

Category	Defect	Acceptance Criteria Sample Size 48		Sample Size 15	
		Accept	Reject	Accept	Reject
Critical	Premature burst	0	1	0	1
Major	Separation of cartridge container extension outside bore of the mortar	2	3	1	2
Major	Failure to fire	0	1	0	1
Major	Functioning	2	3	1	2
Major	Effective illumination for 40 seconds or less	(see a)		(see b)	
Minor	Effective illuminating for more than 40 sec. but less than 60 sec.	(see a)		(see b)	

a. The lot shall be rejected if the total number of major and minor defects is 7 or more or the number of major defects is 3 or more.

b. The lot shall be rejected if the total number of major and minor defects is 5 or more or the number of major defects is 2 or more.

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the "Paragraph Reference/Inspection Method" column in the tables starting with paragraph 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.3 herein.

4.5 Methods of inspection

4.5.1. Proving ground. The cartridge shall be fired from a 4.2" mortar for which the round is standard and in accordance with Table II. However, if meteorological conditions or time of fuze functioning so dictate, the proving ground shall adjust the fuze in order to increase the height of burst and insure effective illumination (see 6.6). Observation shall be made for compliance with the requirements

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:41Z
Check the source to verify that this is the current version before use.

specified for fuze functioning, failure to fire, premature burst, security of parts, parachute functioning and effective illumination (see 6.6). In addition, muzzle velocity, time of fuze functioning, height of first light, delay time from fuze functioning to chute opening and rate of descent shall be recorded for information only for each round tested. Any malfunction occuring during the test shall be reported in the firing record. Meteorological data shall also be reported in the official firing record.

TABLE II

Propellant Phase	Fuze Setting (sec)	Mortar Elevation(mils)
12	8.5	900
25 1/2	26.0	800
41	32.0	800

4.5.2 Refiring. If for any reason the proof director considers the test conditions have detrimentally affected the test results, he shall declare the results invalid and perform a new test.

5. PACKAGING

5.1 Packaging requirements. Packaging shall be as specified on dwg. 7549247.

5.2 Packing and marking. Packing and marking shall be as specified on dwgs. 7549247 and 7549248.

6. NOTES

6.1 Intended use. The cartridge covered by this specification is intended for use in the 4.2" Mortar System.

6.2 Ordering data. See MIL-A-48078.

6.3 Submission of inspection equipment for design approvals. See MIL-A-48078. Submit designs as required to Commander, US Army Armament Research and Development Command, ATTN: DRDAR-QAR-I, Dover, NJ 07801.

6.4 Drawings. Drawings listed in Section 2 of this specification under the heading US Army Armament Research and Development Command (ARRADCOM) may also include drawings

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:41Z
Check the source to verify that this is the current version before use.

prepared by, and identified as Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under the cognizance of ARRADCOM.

6.5 Satisfactory functioning. Satisfactory functioning shall be defined as ejection of the parachute and illuminant assembly and proper suspension and ignition of the illuminant.

6.6 Effective illumination. Effective illumination is defined as burning of the canister without exploding or breaking up while suspended by the parachute. The time recorded for "effective illumination" shall be considered as the time from the appearance of first light from the candle to either (1) burnout of the candle while still in the air (normal burst) or (2) burning of the candle until ground impact. Burning of the canister after striking the ground shall not be considered as "effective illumination". Any occurrences which detract from "effective illumination" as herein defined, shall be recorded on the official firing record.

6.7 Combining of proving ground tests. When the contractor for the cartridge is the contractor for one or more of the components thereof, the proving ground tests of the components may be combined with the proving ground tests of the cartridge, upon agreement between the procuring activity and the contractor. In all cases where the cartridge specification does not cover all the proving ground tests specified for the component, the additional tests specified in the component specifications shall be conducted.

6.8 Recovery of malfunctions. The proving ground shall make the necessary arrangements to recover all malfunctions which may occur during the ballistic test unless otherwise directed by the procuring activity. The terrain from the gun site down range to impact shall be suitable so that all rounds fired including malfunctions will be accessible for recovery.

6.9 Cost of deterioration check test. The contracting officer shall arrange to have the contractor reimbursed for costs incurred in the performance of the check test.

Custodian:
ARMY-AR

Preparing Activity:
ARMY-AR

Project Number: 1315-A345

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:41Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE MIL-C-12926E, CARTRIDGE, 4.2 INCH, ILLUMINATING, M335A2 LOADING, ASSEMBLING AND PACKING

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 78 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:41Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY CARD

FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Armament R & D Command
ATTN: DRDAR-QAR
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:41Z
Check the source to verify that this is the current version before use.