MIL-C-12927B (MU)
AMENDMENT 1
28 April 1964

MILITARY SPECIFICATION

CARTRIDGE, IGNITION, M2E1
PARTS FOR, LOADING, ASSEMBLING AND PACKING

This Amendment forms a part of Military Specification MIL-C-12927B (MU) dated 12 November 1963.

Page 2, under drawings at top of page: Add "8863614 - Bag loading assembly."

Page 3, paragraph 3.4.2, delete and substitute:

"3.4.2 Functioning

3.4.2.1 The primer and body assembly shall function under an applied energy value of 1920 inch ounces maximum (max.) when tested as specified in 4.3.2.2.1.

3.4.2.2 The primer and body assembly shall function under an applied energy value of 640 inch ounces (max.) when tested as specified in 4.3.2.2.2."

Page 3, add new paragraph:

"3.7 Proving ground.-The ignition cartridge shall function on first attempt with no audible hang fire when tested as specified in 4.3.4."

Page 9, paragraph 4.2.3.2.2.1, line 3: Delete "for this test ... as specified in 4.3.2.2" and substitute "for each test shall be in accordance with Standard MIL-STD-105D, Table III A, Code Letter M and AQL of 0.25 percent. The tests shall be performed as specified in 4.3.2.2.1 and 4.3.2.2.2."

Page 9, paragraph 4.2.3.2.2.2, line 2: Delete "for this test ... as specified in 4.3.2.2" and substitute "for each test shall be in accordance with Standard MIL-STD-105D, Table III A, Code Letter L and AQL of 0.25 percent. The tests shall be performed as specified in 4.3.2.2.1 and 4.3.2.2.2."

FSC: 1315

Source: https://assist.dla.mil -- Downloaded: 20260-17T23:41Z
Check the source to verify that this is the current version before use.

Page 9, add new paragraphs:

"4.2.3.4 Proving ground test (see 3.7) Major defect, Code No. 07001.-Beginning with the first lot produced and continuing until three consecutive lots have complied with the acceptance criteria specified, the sampling plan for this test shall be in accordance with Standard MIL-STD-105D, Table III A, Code Letter K and an AQL of 0.40 percent. The test shall be performed as specified in 4.3.4.

4.2.3.4.1 After three consecutive lots have met the criteria of 4.2.3.4, the sampling plan for this test shall be in accordance with Standard MIL-STD-105D, Table III A, Code Letter H, and an AQL of 1.0 percent. The test shall be performed as specified in 4.3.4."

Page 10, paragraph 4.3.2.2, delete and substitute:

"4.3.2.2 Functioning test

4.3.2.2.1 The procedure used shall be the same as in 4.3.2.1 except that a steel ball of 10-0.2 pounds shall be dropped on the firing pin from a height of (approx.) 12 inches which will impart 1920 inch ounces (max.) of energy.

4.3.2.2.2 The procedure used shall be the same as in 4.3.2.1 except that a steel ball of 20-0.2 pounds shall be dropped on the firing pin from a height of (approx.) 2 inches which will impart 640 inch ounces (max.) of energy."

Page 10, add new paragraph:

"4.3.4 Proving ground.-This test shall be performed at a Government proving ground. The loaded ignition cartridges shall be assembled to mortar rounds for which the ignition cartridge was designed and which are sand-loaded to a total individual weight of apprioximately 26.00 pounds (without extension). The sand loaded rounds shall be fired, utilizing charges, in accordance with drawing 8863614. The mortar tube shall be elevated to an angle of 45 degrees. In lieu of sand-loaded rounds, proof projectiles of acceptable types may be used. Observation shall be made for compliance with the applicable requirements."

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:41Z
Check the source to verify that this is the current version before use.

Page 14, paragraph 6.4.1.2, delete and substitute:

"6.4.1.2 Functioning.-The sampling plan for each test shall be in accordance with Standard MIL-STD-105D, Table IIA, Code Letter L and AQL of 0.65 percent. The tests shall be performed as specified in 4.3.2.2.1 and 4.3.2.2.2."

Custodian:
Army-MU

Preparing activity:
Army-MU

Project Number 1315-A395

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T23:41Z
Check the source to verify that this is the current version before use.