MILITARY SPECIFICATION

BELT, INDIVIDUAL EQUIPMENT, M-1936

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers an adjustable belt, in one type and size, made of cotton webbing.

1.2 Classification. The individual belts shall be of the following classes as specified (see 6.2):

Class 1 - Olive drab

Class 2 - White

2. APPLICABLE DOCUMENTS

2.1 Government documents.

* 2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specification and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

V-T-285	Thread Polyester
NN-P-71	Pallet, Material Handling, Wood, Stringent Construction, 2-Way and 4-Way (Partial).
UU-P-268	Paper, Kraft, Wrapping.
DDD-L-20	Label for Clothing, Equipage, and Tentage, (General Use).
PPP-B-636	Box, Shipping, Fiberboard.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: the Engineering Division, San Antonio Air Logistics Center/MMEDO, Kelly AFB, TX 78241-5000 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 8465

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:40Z
Check the source to verify that this is the current version before use.

MILITARY

	MIL-P-150	Pallet, Material Handling, Wood, Post Construction, 4-Way Entry.
	MIL-F-411	Fastener, Belt, Clips, End, Strap with Hook, and Keepers, Slide.
	MIL-W-530	Webbing, Textile, Cotton, General Purpose, Natural or in Colors.
	MIL-H-9890	Hardware, Individual Load Carrying Equipment, and Hardware, Miscellaneous.
	MIL-F-10884	Fasteners, Snap.
	MIL-E-20652	Eyelet, Metallic, and Eyelet Washers, Metallic, General Specification for.
*	MIL-E-20652/1	Eyelet, Metallic, Rolled Flange Type, with Eyelet Washer.

STANDARDS

FEDERAL

	FED-STD-751	Stitches, Seams, and Stitchings.

MILITARY

	MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes.
	MIL-STD-129	Marking for Shipment and Storage.
*	MIL-STD-147	Palletized Unit Loads.
*	MIL-STD-794	Parts and Equipment, Procedures for Packaging of.

DRAWINGS

Army - Quartermaster Corps

	D2-4-39	Belt, Individual Equipment, M-1936

* (Copies of specifications, standards, and drawings required by the contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

* 2.2 Other publications. The following document forms a part of this specification to the extent specified herein. Unless specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issue of the nongovernment documents which is current on the date of the solicitation.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

*	ASTM D 3951	Packaging, Commercial.

(Application for copies of ASTM publications should be addressed to the American Society for Testing and Materials, 1916 Race St., Philadelphia, PA 19103.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:40Z
Check the source to verify that this is the current version before use.

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, (except for associated detail specifications, specification sheets or MS standards) the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

* 3.1 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection (see 4.3 and 6.5).

3.2 Materials.

3.2.1 Cotton webbing. The 2 1/4 inch wide, 3.40 ounce per linear yard, cotton webbing for class 1 belt shall be dyed olive drab No. 7 and shall conform in all respects to the requirements for type IV, class 4 of MIL-W-530, and for class 2 belt the webbing shall be white and shall conform in all respects to type IV, class 2 of MIL-W-530.

3.2.2 Polyester thread. The thread shall conform to type I or II, class 1 sub-class A, size FF of V-T-285.

3.2.2.1 Color. The thread shall be dyed shade S-1 (C.A. 66022) for class 1. For white belts, the thread shall be AG white (C.A. 66049).

3.2.3 Eyelets and washer. The eyelets and washer shall conform to MIL-E-20652 and MIL-E-20652/1A. The eyelets shall conform to ABE115, BBE117, BBE110, ABE111, ABE112, BBE104, BBE105, and ABE106. The washer shall conform to BBW101 or ABW100, as applicable.

3.2.4 Belt fasteners. The belt fasteners shall be brass conforming to type I and type II of MIL-H-9890.

3.2.5 Snap fasteners. The snap fasteners shall be female conforming to style 2, finish 2, 24 line button size 1 or 2 of MIL-F-10884.

3.2.6 End fastenings. The end fastenings shall be brass conforming to type II of MIL-F-411.

3.2.7 Belt keeper sliding. The belt keepers shall be brass conforming to type XI, class A of MIL-H-9890.

3.3 Construction. The construction shall conform in all respects to drawing D2-4-39 and as specified herein.

3.3.1 Type of stitching. Stitching shall conform to FED-STD-751 as follows: For all stitching - type 301, 6 to 8 stitches to the inch.

3.3.1.1 Type 301 stitching. Thread breaks in stitching shall be back-stitched not less than one inch from the specified stitch lines. Thread tension shall be maintained so that there will be no loose stitching and that the lock will be embedded in the center of the materials sewed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:40Z
Check the source to verify that this is the current version before use.

3.3.2 Setting of eyelets. The eyelets shall be securely clinched without splitting.

3.3.3 Setting of style 2 female snap fasteners. When a hole is punched before inserting the snap fastener, it shall be smaller than the outside diameter of the fastener tube so that the tube must be forced through the hole. The fasteners shall be securely clinched.

3.3.4 Attaching the type II end fastening. The end fastenings shall be inserted the full depth of the fastening and securely attached without cutting the webbing. The webbing shall be within the width of the fastening so that there will be no projecting edges of the webbing.

3.4 Marking.

3.4.1 Marking. The identification marking shall be applied in the location shown on the drawing and shall conform to type IV, class 5 of DDD-L-20. The letters "U.S." shall be applied in the size characters and in the location indicated on the drawing and shall conform to type IV, class 9 of DDD-L-20. Fastness of the class 9 marking shall be as specified for class 5 marking.

3.5 Workmanship. The finished belt shall conform to the quality and grade of product established by this specification. Occurrence of defects shall not exceed the applicable acceptable quality levels.

4. QUALITY ASSURANCE PROVISIONS

* 4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

* 4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).

b. Quality conformance inspection (see 4.4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:40Z
Check the source to verify that this is the current version before use.

4.3 First article inspection. When required, the first article sample submitted in accordance with 3.1 shall be inspected as specified in 4.4.3 for compliance with design, construction, workmanship and dimensional requirements.

4.4 Quality conformance inspection. Inspection shall be in accordance with MIL-STD-105, except where otherwise indicated herein.

4.4.1 Component and material inspection. In accordance with 4.1 above, components and materials shall be tested in accordance with the requirements of referenced specifications, drawings and standards unless otherwise excluded, amended, modified or qualified in this specification or applicable purchase documents.

4.4.2 Inspection of partly fabricated belts prior to setting end fastening, belt fasteners and sliding keepers. Defects found in this examination shall be classified in accordance with the following list. The sample unit shall be one partially fabricated belt. The inspection level shall be S-3 and the acceptable quality levels shall be 4.0 major defects and 15.0 total (major and minor combined) defects per one hundred units.

Examine	Defect	Classification	
		Major	Minor
Length of belt	Not within specified tolerances		X
Location dimensions:			
Eyelets	Outer edge eyelets set with rim of washer extending beyond edge of webbing	X	
	Center eyelets set off center line of webbing by more than 1/8 inch		X
	Not within specified tolerances		X
Snap fasteners	Snap fastener not set within specified tolerances		X

4.4.3 Examination of the end item. The defects found during the end item examination shall be classified in accordance with the following list. The sample unit for this examination shall be one completely fabricated belt. The inspection level shall be level II and the acceptable quality level shall be 2.5 major and 6.5 total defects (major and minor combined) per hundred units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:40Z
Check the source to verify that this is the current version before use.

Examine	Defeat	Classification	
		Major	Minor
Webbing	Any hole, cut or tear	X	
	Not firmly and tightly woven, edges frayed or scalloped	X	
	Webbing defects, seriously affecting serviceability or appearance	X	
	Webbing defects, affecting serviceability or appearance but not seriously		X
Hardware	Broken or malformed; burrs or sharp edges; failing to serve intended purpose, finish omitted; corroded areas	X	
	Not as specified, finish not adherent or peeling	X	
End fastenings	Not securely clinched or clinched excessively tight, cutting the webbing surface		X
	Hook portion on end fastenings insufficiently or excessively bent failing to engage center eyelets or to keep fasteners in hooked position	X	
	Edge of webbing extending beyond end of fastening		X
	Webbing not inserted full depth of fastening		X
Sliding keepers	Fails to slide through when force is applied at location of eyelets	X	
	Tongue end not securely bent down, resulting in disengagement of keeper or causing injury in handling	X	
Belt fasteners	Male or female fastener set in reversed position failing to effect a smooth and secure fastening of belt	X	
	Any defect of belt fastener causing difficulty in securely engaging male and female fasteners		X
	NOTE: The male and female belt fasteners of each belt in the sample shall be examined to determine whether the fasteners effect a smooth and secure engagement		

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:40Z
Check the source to verify that this is the current version before use.

Examine	Defeat	Classification	
		Major	Minor
Components and assembly	Any component part or required operation omitted (unless otherwise classified herein).	X	
Seams and stitching:			
Open seams	One-half inch or less		X
	More than 1/2 inch	X	
	NOTE: A seam shall be considered open when one or more stitches joining a seam are broken or when two or more continuous skipped stitches or run-offs occur.		
Runoffs (see open seams)			
Seam and stitch type	Wrong seam or stitch type	X	
Stitch tension	Loose, resulting in a loosely exposed bobbin or top thread, tight, resulting in excessive tightness of webbing on seams	X	
Stitches per inch	One to two stitches less than minimum specified		X
	Three or more stitches less than minimum specified	X	
	One or more stitches in excess of maximum specified		X
Stitching margins	Under or over specified width by more than 1/16 inch		X
Stitching ends	Not backstitched as specified	X	
Thread breaks	Backstitched less than 1 inch		X
	NOTE: Thread breaks not backstitched shall be classified as open seams.		
Box stitching	Any row of box stitching not stitched through turnunder, i.e., through three plies of webbing		X
	Any required row or box stitching omitted	X	
	Less than specified length by more than 1/16 inch		X
Marking "U.S." and identification	Omitted, illegible, incorrect, misplaced or size of character not as specified		X
Cleanness	Spots or stains not removable:		
	Seriously affecting appearance	X	
	Affecting appearance but not seriously		X
	Thread ends not trimmed throughout		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:40Z
Check the source to verify that this is the current version before use.

4.4.4 Examination of packaging requirements. An examination shall be made to determine that packaging, packing and marking requirements of Section 5 of this specification are complied with. Defects shall be scored in accordance with the list below. The sample unit shall be one shipping container fully prepared for delivery. Defects of closure listed below shall be examined on shipping containers fully prepared for delivery. Defects of closure listed below shall be examined on shipping containers in the end item inspection lot. The inspection level shall be S-2 and the AQL shall be 2.5 defects per 100 units of MIL-STD-105.

Examine	Defect
Marking (exterior and interior)	Omitted, incorrect, illegible, of improper size, location, sequence or method of application.
Materials	Any component missing. Any component damaged, affecting serviceability.
Workmanship	Inadequate application of components, such as incomplete closure of container flaps, loose strapping, inadequate stapling, improper taping Bulging or distortion of containers.
Content	Number of bundles per shipping container is more or less than required. Number of belts per bundle is more or less than required. 1/

1/ For this defect, 2 bundles from each shipping container in the sample shall be examined.

* 5. PACKAGING

* 5.1 Packaging. Packaging shall be level A, C or Commercial as specified (see 6.2).

5.1.1 Level A. Each belt shall be adjusted to a length of 32 inches and then folded in half lengthwise to approximately 16 inches with the "U.S." facing out. When packaging white belts, wrap each belt individually in good commercial tissue before stacking and tying into bundles. Ten folded belts shall be neatly stacked one on top of the other with fasteners alternately reversed and securely tied at each end with cotton tape or twine. The tied bundle placed on edge shall approximate 16 inches in length, 7 inches in width, and 2 3/4 inches in depth.

* 5.1.2 Level C. The level C preservation for belts shall conform to the MIL-STD-794 requirements for this level.

* 5.1.3 Commercial. Belts shall be packaged in accordance with the applicable requirements of ASTM D 3951.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:40Z
Check the source to verify that this is the current version before use.

* 5.2 Packing. Packing shall be level A, B, or Commercial as specified (see 6.2).

5.2.1 Level A. One hundred belts, packaged as specified in 5.1, shall be packed in a fiberboard shipping container conforming to V2s, style RSC-L of PPP-B-636. The inside of each container shall be fitted with a taped liner conforming to V3c of PPP-B-636. Level A packages shall be packed on edge one in length, two in width, and five in depth within a shipping container. Inside dimensions of the shipping container shall approximate 16 1/2 inches in length, 14 1/2 inches in width, and 13 3/4 inches in depth. Approximate dimensions are furnished as a guide only. Each shipping container shall have the contents completely covered on the top and bottom with a sheet of 30 pound minimum basis weight kraft paper conforming to grade B of UU-P-268. Each shipping container shall be closed waterproofed and reinforced with flat strapping or tape banding in accordance with the appendix of the container specification.

5.2.2 Level B. One hundred belts, packaged as specified in 5.1, shall be packed in a fiberboard shipping container conforming to type CF or SF, variety SW, class domestic, grade 275 of PPP-B-636. The inside of each shipping container shall be fitted with a taped liner conforming to type CF, variety SW, grade 275 of PPP-B-636. Inside dimensions of the shipping container shall approximate 16 1/2 inches in length, 14 1/2 inches in width, and 13 3/4 inches in depth. Approximate dimensions are furnished as a guide only. Each shipping container shall have the contents completely covered on the top and bottom with a sheet of 30 pound minimum basis weight kraft paper conforming to grade B of UU-P-268. Each container shall be closed in accordance with method II in the appendix of the container specification.

5.2.2.1 When specified, shipping containers shall be fabricated from V3c or V3s fiberboard (see 6.2).

* 5.2.3 Level C. The level C packing for belts shall conform to the MIL-STD-794 requirement for this level.

* 5.2.4 Commercial. The preserved belts shall be packed in accordance with the applicable requirements of ASTM D 3951.

* 5.3 Marking. In addition to any special marking required by the contract or order (see 6.2), each unit pack, intermediate and exterior container and unitized load shall be marked in accordance with MIL-STD-129 or ASTM D 3951 as applicable.

5.4 Palletization. When specified (see 6.2), items packed as specified in 5.2 shall be palletized on a type I (4-way entry), type IV, or type V pallet in accordance with load type I or Ia of MIL-STD-147. The pallet shall be 4-way, type IV; type V, class 1, size 2; or type VIII, fabricated from wood groups I, II, III, or IV, grade A of NN-P-71, or the pallet shall be 4-way, type I, style 1A, or 1B, size A, class 1, fabricated from wood group specified, of MIL-P-15011. Each prepared load shall be bonded with the applicable strap bonding or film bonding means specified in MIL-STD-147. The pallet pattern shall be in accordance with the appendix of MIL-STD-147. Interlocking of loads shall be effected by reversing the pattern of each course. If the container is of a size which does not conform to any of the patterns specified in MIL-STD-147, the pallet pattern used shall be approved by the contracting officer.

Source: https://assist.dla.mil -- Downloaded: 202610-16T12:40Z
Check the source to verify that this is the current version before use.

6.1 Intended use. The belt covered by this specification is worn primarily by military personnel armed with a pistol or carbine and is used to carry various items of individual equipment such as .45 caliber pistol holster; M1923, enlisted men's ammunition magazine pocket; .30 caliber, M-1 carbine or rifle ammunition magazine pocket; 30 round carbine magazine pocket; M-1942, first packet pouch; M-1910, dismounted canteen cover, which are attached to the belt by means of either belt loops or a double hook. Eyelets spaced to accommodate a double hook are provided along the bottom edge of the belt while other eyelets are located along the top edge of the belt loops or a double hook. Eyelets spaced to accommodate a double hook are provided along the bottom edge of the belt while other eyelets are located along the top edge of the belt so that when wearing the cargo and combat field pack suspenders, the suspender snaps can be attached to these eyelets and the suspenders used to help support the weight of the belt and its attached equipment.

* 6.2 Ordering data.

6.2.1 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number and date of this specification.

b. When first article sample is required (see 3.1, 4.3 and 6.5).

c. Selection of applicable levels of packaging and packing (see 5.1 and 5.2).

d. Color required (see 1.2).

e. Whether V-board containers are required for level B shipments (see 5.2.2.1).

* f. When palletization is required (see 5.4).

6.3 For access to a standard shade sample of webbing and a standard sample of thread, address the procuring office issuing the invitation for bids.

6.4 The M-1936 individual equipment belt weighs approximately .57 pound.

* 6.5 First article. When a first article inspection is required, the item(s) should be a first article sample. The first article should consist of one unit. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examinations, approval of first article test results and disposition of first articles. Invitations for bids should provide that the Government reserves the right to waive the requirements for samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the Government, and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:40Z
Check the source to verify that this is the current version before use.

* 6.6 Subject term (key word) listing.

Belt, adjustable
Belt, individual equipment, M-1936
Belt, fasteners - brass
Cotton, webbing
Colors - olive drab and white
Eyelets top and bottom edges
Military personnel
Thread, polyester

* 6.7 The margins of this specification are marked with asterisks (or vertical lines) to indicate where changes (additions, modifications corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:
Army - MI
Navy - MC
Air Force - 99

Review activities:
Army - MD
Navy - SA
DLA - CT

User activity:
Navy - CG
Air Force - 45

Preparing activity:
Air Force - 82

(Project 8465-0937)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:40Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

☆ U.S. Government Printing Office: 1982—360-879/5804

(Fold along this line)

(Fold along this line)

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 73236 WASH DC

POSTAGE WILL BE PAID BY HQ U.S. AIR FORCE

San Antonio ALC/MMEDO
Kelly AFB, TX 78241

Source: https://assist.dla.mil -- Downloaded: 202640-16T12:40Z
Check the source to verify that this is the currentversion before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-B-1107G	Belt Individual Equipment, M-1936

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
	☐ USER
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:40Z
Check the source to verify that this is the current version before use.