MIL-C-1002J
30 September 1986
SUPERSEDING
MIL-C-1002H
28 April 1983

MILITARY SPECIFICATION

CASE, FIELD, FIRST AID DRESSING, LEATHER (MILITARY POLICE)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers one type of leather first aid case.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Documents. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these docu-ments shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

A-A-1249	-	Paper, Wrapping, Tissue.
V-T-285	-	Thread, Polyester.
KK-L-271	-	Leather, Cattlehide, Strap, Vegetable Tanned.
PPP-B-566	-	Boxes, Folding, Paperboard.
PPP-B-636	-	Boxes, Shipping, Fiberboard.
PPP-B-676	-	Boxes, Setup.
PPP-T-45	-	Tape, Gummed, Paper, Reinforced and Plain, for Sealing and Securing.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Research, Development and Engineering Center, Center, Natick, MA 01760-5014 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 8465

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:34Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-F-10884 - Fasteners, Snap.
MIL-L-35078 - Loads, Unit: Preparation of Semiperishable Subsistence Items; Clothing, Personal Equipment and Equipage; General Specification For

STANDARDS

FEDERAL

FED-STD-751 - Stitches, Seams, and Stitchings.

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-130 - Identification Marking of U.S. Military Property.
MIL-STD-147 - Palletized Unit Loads.
MIL-STD-731 - Quality of Wood Members for Containers and Pallets

DRAWING

U.S. ARMY NATICK RESEARCH, DEVELOPMENT AND ENGINEERING CENTER

2-2-87 - Case, Field, First Aid Dressing, Leather (Military Police).

(Copies of documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Other publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issues of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issues of the nongovernment documents which are current on the date of the solicitation.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3951 - Standard Practice for Commercial Packaging

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:34Z
Check the source to verify that this is the current version before use.

(Technical society and technical association documents are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document shall take precedence. Nothing in this document, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Guide sample. Guide samples of the end item, when furnished, are solely for guidance and information to the contractor (see 6.3). Variation from this document may appear in the sample, in which case this document shall govern.

3.2 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection (see 4.3, 6.2, and 6.4).

3.3 Materials. Materials specified shall conform to the applicable documents and requirements specified herein.

3.3.1 Leather. The leather shall be 4/64 and 6/64 inch thick conforming to types I, II, III or IV, class 1 of KK-L-271 except that the thickness tolerance shall be plus 1/64, minus 1/128 inch. The grain side of the leather shall be dyed black and smooth finished, insuring a long-lasting lustrous finish. The color of the flesh side shall be natural.

3.3.2 Thread, polyester. The polyester thread for all stitching shall conform to type I, class 1 subclass A, size 3 of V-T-285. The thread shall be dyed black and shall show fastness to perspiration equal to or better than the standard sample. When no standard sample is available, the thread shall show good fastness to perspiration.

3.3.3 Sealer. The edges and the laps of the leather shall be finished with a tragacanth gum sealer commercial grade W.O.3.

3.3.4 Fastener, snap. The snap fastener shall conform to style 1 of MIL-F-10884. The female components shall consist of a long prong socket and a clinch plate. The male components shall be an eyelet base, size 1 stud, with washer. The finish for all components shall conform to finish 2 of MIL-F-10884.

3.4 Construction. The construction shall conform in all respects to Drawing 2-2-87 and as specified herein.

3.4.1 Stitches, seams and stitchings. All seams and stitching shall conform to type 301 of FED-STD-751 with 4 to 6 stitches per inch and 1/8 inch stitching margin.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:34Z
Check the source to verify that this is the current version before use.

3.4.1.1 Type 301 stitching. Ends of stitching shall be backstitched or overstitched not less than 1 inch except where ends are turned under or caught in other seams and stitching. Thread tensions shall be maintained so that there will be no loose stitching resulting in loose bobbin or top thread or excessively tight stitching resulting in puckering of the materials sewn. The lock shall be imbedded in the materials sewn. All thread ends shall be tied and fused.

3.4.1.2 Repairs of type 301 stitching. Repairs of 301 stitching shall be as follows:

a. When thread breaks or bobbin run-outs occur during sewing, the stitching shall be repaired by restarting the stitching a minimum of 1 inch in back of the end of stitching.

b. Thread breaks or two or more consecutive skipped or runoff stitches noted during inspection of the item shall be repaired by overstitching. The stitching shall start a minimum of 1 inch in back of the defective area, continue over the defective area, and continue a minimum of 1 inch beyond the defective area onto the existing stitching. Loose or excessively tight stitching shall be repaired by removing the defective stitching without damaging the materials and restitching in the required manner. 1/

1/ When making the above repairs, the ends of the stitching are not required to be backstitched.

3.4.2 Setting of snap fastener. A hole shall be prepunched to receive the button and eyelet components of the snap fastener. The hole shall be smaller than the out side diameter of the button and eyelet barrels so that the barrel must be forced through the hole. The hole shall not be punched in the setting operation with the button or eyelet barrel.

3.4.3 Replacement of defective components. During the cutting and manufacturing process, components having material defects or damages that are classified as defects in 4.4.2 shall be removed from production and replaced with non-defective and properly matched components.

3.5 Marking. The letters "U.S.", the year manufactured, and the manufacturer's name, or trademark of a character to be easily identifiable with the manufacturer shall be permanently and legibly indented on the back of each leather case as indicated on Drawing 2-2-87. Marking shall be in accordance with MIL-STD-130.

3.6 Workmanship. The finished case shall conform to the quality of product established by this document. The occurrence of defects shall not exceed the applicable acceptable quality levels (AQL).

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:34Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the document where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this document shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the document shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.1.2 Responsibility for dimensional requirements. Unless otherwise specified in the contract or purchase order, the contractor is responsible for assuring that all specified dimensions have been met. When dimensions cannot be examined on the end item, inspection shall be made at any point, or at all points in the manufacturing process necessary to assure compliance with all dimensional requirements.

4.1.3 Certificate of compliance. When certificates of compliance are submitted, the Government reserves the right to inspect such items to determine the validity of the certification.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4.).

4.3 First article inspection. When a first article is required (see 3.2), it shall be examined for the defects specified in 4.4.2 and 4.4.3. The presence of any defect shall be cause for rejection of the first article.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:34Z
Check the source to verify that this is the current version before use.

4.4.1 Components and materials inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this document or applicable purchase document.

4.4.1.1 Certification. The contractor shall furnish a certificate of compliance certifying that the sealer conforms to the requirements specified in 3.3.3.

4.4.2 End item visual examination. The end item shall be examined for the defects listed below. The lot size shall be expressed in units of cases. The sample unit shall be one case. The inspection level shall be II and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 2.5 for major defects and 6.5 for total (major and minor combined) defects.

Examine	Defect	Classification Major	Minor
Finish of leather components	Not specified color.	X	
	Color not uniform.	X	
	Leather embossed or printed.	X	
	Grain side not smooth finished.	X	
	Tacky or cracky finish.	X	
	Any leather part refinished after assembly.	1/	
Thread	Not specified color.	X	
Material	Any component not fabricated of the specified material.	X	
Construction and workmanship (general)	Any component or assembly omitted or misplaced, operation omitted or not properly performed (i.e., snap fastener not properly clinched; edges of leather not creased or irregular; fastener not in alignment)	1/	
	Any part fractured, ripped, punctured, torn, defective, malformed, or damaged.	1/	

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:34Z
Check the source to verify that this is the current version before use.

Examine	Defect	Classification Major	Minor
Quality of leather	Nut full grain or not full grain lightly snuffed.	X	
	Any hole, cut, or rupture.	X	
	Brand mark, healed grub damage, scar tissue, hip mark, or brittle or bony area.	1/	
	Abraded, scratched, or other grain damage.	1/	
	Flanky, spongy, pipey, or stretchy leather.	1/	
	Any wrinkle.	1/	
	Slaughter cut.	1/	
	Flesh side not smooth, or contains areas of loose flesh.		X
Snap fastener	Snap fastener components not securely affixed and may become detached in service.	X	
	Snap fastener components not securely attached but will adequately retain assembly.		X
	Snap fastener does not function.	X	
	Sharp edge, burr, or metal sliver.	X	
	Not specified finish or area of no finish.	X	
	Coating flaked or blistered.		X
Open seam	Any open seam not repaired.	X	
	Repair of open seam not as specified.		X
	NOTE: A seam shall be classified as open when one or more stitches joining a seam are broken or when two or more consecutive skipped or runoff stitches occur.		
Runoffs (see open seam)			
Stitch type	Wrong stitch type.	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:34Z
Check the source to verify that this is the current version before use.

Examine	Defect	Classification Major	Minor
Stitch tension	Loose, resulting in a loosely exposed top or bobbin thread; tight, resulting in tightness of seams.		X
Stitches per inch	One less than minimum specified.		X
	Two or mre less than minimum specified.	X	
	One or more in excess of maximum specified.	1/	
Stitching margin	Not as specified, affecting serviceability.		X
Thread ends	Not tied.		X
	Not fused.		X
Marking	Missing, illegible, incorrect, not applied in specified manner, misplaced, or not specified type or size.	X	
Cleanness	Any non-removable stain or spot.	X	
	Any spot or stain removable with cleaning agent.		X

1/ Defect shall be scored as a major defect when seriously affecting serviceability or appearance, and as a minor defect when affecting serviceability or appearance but not seriously.

4.4.3 End item dimensional examination. The end item shall be examined for conformance to the specified dimensions. Any dimension not within the specified tolerance shall be classified as a defect. The lot size shall be expressed in units of cases. The sample unit shall be one case. The inspection level shall be S-3 and the AQL, expressed in terms of defects per hundred units, shall be 4.0.

4.4.4 Packaging examination. The fully packaged end items shall be examined for the defects listed below. The lot size shall be expressed in units of shipping containers. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:34Z
Check the source to verify that this is the current version before use.

Examine	Defect
Markings	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.
Materials	Any component missing. Any component damaged or not as specified.
Workmanship	Inadequate application of components, such as: incomplete closure of container flaps, improper taping, loose strapping, or inadequate stapling. Bulged or distorted container.
Content	Number of intermediate containers is more or less than specified. Number of cases per intermediate container is more or less than specified. 1/

1/ For this defect, two intermediate containers shall be examined.

4.4.5 Palletization examination. The fully packaged and palletized end items shall be examined for the defects listed below. The lot size shall be expressed in units of palletized unit loads. The sample unit shall be one palletized unit load, fully packaged. The inspection level shall be S-1 and the AQL, expressed in terms of defects per hundred units, shall be 6.5.

Examine	Defects
Finished dimensions	Length, width or height exceeds specified maximum requirement.
Palletization	Pallet pattern not as specified. Interlocking of loads not as specified. Load not bonded with required straps as specified.
Weight	Exceeds maximum load limits.
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial as specified (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:34Z
Check the source to verify that this is the current version before use.

5.1.1 Level A. Each closed case shall be completely wrapped in not less than two thicknesses of tissue paper conforming to type I of A-A-1249. Ten unit wrapped cases shall be packed upright ten in length within an intermediate folding paperboard box conforming to variety 1, style III, type G, class 1 of PPP-B-566; or set up paperboard box conforming to type I, variety 1, class A, style 4 of PPP-B-676. Inside dimensions of each paperboard box shall be 16-1/2 inches in length, 5-1/8 inches in width, and 3-1/8 inches in depth. Box closure shall be secured with 2-inch minimum width gummed paper tape conforming to type III, grade B of PPP-T-45, applied at the center of the length opening and extending along the bottom and up the sides at least 1 inch.

5.1.2 Commercial. Cases shall be preserved in accordance with ASTM D 3951.

5.2 Packing. Packing shall be level A, B, or Commercial as specified (see 6.2).

5.2.1 Level A packing. Two hundred cases preserved as specified in 5.1, shall be packed in a fiberboard shipping container conforming to style RSC, grade V2s of PPP-B-636. Level A intermediate packs shall be packed flat four in length, one in width, and five in depth. Inside dimensions of each shipping container shall approximate 21-1/2 inches in length, 17-1/2 inches in width, and 16-1/4 inches in depth. Each shipping container shall be closed in accordance with method III, water proofed in accordance with method V, and reinforced as specified in the appendix of PPP-B-636, except that inspection shall be in accordance with 4.4.4. Shipping containers shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified (see 6.2). Strapping shall be limited to nonmetallic strapping, except for type II, class F loads.

5.2.2 Level B packing. Two hundred cases preserved as specified in 5.1, shall be packed in a fiberboard shipping container conforming to style RSC, type CF (variety SW) or SF, class domestic, grade 275 of PPP-B-636. Level A intermediate packs shall be packed flat four in length, one in width, and five in depth. Inside dimensions of each shipping container shall approximate 21-1/2 inches in length, 17-1/2 inches in width, and 16-1/4 inches in depth. Each shipping container shall be closed in accordance with method II as specified in the appendix of PPP-B-636, except that inspection shall be in accordance with 4.4.4.

5.2.2.1 Weather-resistant fiberboard containers. When specified (see 6.2), the shipping container shall be a grade V3c, V3s, or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with method III as specified in the appendix of PPP-B-636, except that the inspection shall be in accordance with 4.4.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:34Z
Check the source to verify that this is the current version before use.

5.2.3 Commercial packing. Cases, preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

5.3 Palletization. When specified (see 6.2), cases, packed as specified in 5.2.2 and 5.2.3 shall be palletized on a 4-way entry pallet in accordance with load type Ia of MIL-STD-147. Pallet types shall be type I (4-way entry), type IV, or type V in accordance with MIL-STD-147. Pallets shall be fabricated from wood groups I, II, III, or IV of MIL-STD-731. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means K and L or film bonding means O and P. Pallet pattern shall be number 90 in accordance with the appendix of MIL-STD-147. Interlocking of loads shall be effected by reversing the pattern of each course.

5.4 Marking. In addition to any special marking required by the contract or purchase order, interior packs, shipping containers, and palletized unit loads shall be marked in accordance with MIL-STD-129 or ASTM D 3951 as applicable.

6. NOTES

6.1 Intended use. The first aid case is intended for use by members of the Military Police of the U.S. Army and Air Force and are worn with a leather belt. The case is designed to hold a Dressing, First Aid, Individual Troop, Camouflage (First Aid Packet).

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this document.
b. When first article sample is required (see 3.2, 4.3 and 6.4).
c. Selection of applicable levels of preservation and packing (see 5.1 and 5.2).
d. Type and class of unit load required (see 5.2.1).
e. When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).
f. When palletization is required (see 5.3).

6.4 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should include specific instructions in all acquisition documents, regarding arrangements for selection, inspection, and approval of the first article.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:34Z
Check the source to verify that this is the current version before use.

6.5 Subject term (key word) listing.

Case, field
First aid
Leather
Military police equipment

6.6 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodians:

Army - GL
Air Force - 99

Review activities:

Army - MD
Air Force - 11, 82
DLA - CT

User Activity:

Air Force - 45

Preparing activity:

Army - GL

Project No. 8465-0916

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:34Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-C-1002J	Case, Field, First Aid Dressing, Leather (Military Police)

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

NATICK OP-1, Feb 86

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:34Z
Check the source to verify that this is the current version before use.