MIL-C-1029E

28 September 1973

SUPERSEDING
MIL-C-001029D(GL)
31 December 1970, and
MIL-C-1043D
27 March 1968, and
MIL-C-1029C
15 September 1966

MILITARY SPECIFICATION

COOKIES, OATMEAL WITH CHOCOLATE CHIPS AND SANDWICH: CANNED

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers canned cookies, oatmeal with chocolate chips, and cookies, sandwich, which are used as a dessert component in operational rations.

1.2 Classification. The cookies shall be of the following types and styles, as specified (see 6.1):

Type I - Oatmeal with chocolate chip

Type II - Sandwich

Style A - Vanilla-flavored filling

Style B - Chocolate-flavored filling

* 2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

C-M-350 - Milk Nonfat, Dry
N-C-195 - Cereal, Rolled Oats

FSC 8920

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:36Z
Check the source to verify that this is the current version before use.

TT-C-495 - Coatings, Exterior for Tinned Food Cans
JJJ-C-501 - Cocoa
PPP-C-29 - Canned Subsistence Items, Packaging and Packing Of
PPP-C-96 - Cans, Metal, 28 Gage and Lighter

MILITARY

MIL-L-1497 - Labeling of Metal Cans for Subsistence Items

STANDARDS

FEDERAL

FED-STD-101 - Preservation, Packaging, and Packing Materials: Test Procedures
FED-STD-595 - Colors

NOTE: These standards (3 by 5 inch color chips) may be obtained from General Services Administration, Business Service Center, Region #3, Washington, D. C. 20407

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-1105 - Sanitary Standards for Bakeries

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

PUBLICATIONS:

U.S. Department of Health, Education, and Welfare

Federal Food, Drug, and Cosmetic Act and Regulations Promulgated Thereunder

(Application for copies should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, D. C. 20402.)

U.S. Department of Agriculture

Regulations Governing the Grading and Inspection of Egg Products

(Application for copies should be addressed to the Information Division, Agricultural Marketing Service, U.S. Department of Agriculture, Washington, D. C. 20250.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:36Z
Check the source to verify that this is the current version before use.

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply:

Association of Official Analytical Chemists

Official Methods of Analysis of the Association of Official Analytical Chemists

(Application for copies should be addressed to the Association of Official Analytical Chemists, Box 540, Benjamin Franklin Station, Washington, D. C. 20044.)

Association of Vitamin Chemists, Inc.

Methods of Vitamin Assay

(Application for copies should be addressed to the Interscience Publishers, Inc., a Division of John Wiley and Sons, Inc., 605 Third Avenue, New York, N. Y. 10016.)

American Oil Chemists' Society

Official and Tenative Methods of the American Oil Chemists

(Application for copies should be addressed to the American Oil Chemists' Society, 508 South Sixth Street, Champaign, Ill. 61820.)

National Research Council

Food Chemicals Codex (F.C.C.)

(Application for copies should be addressed to the Office of Director, National Academy of Sciences, National Research Council, Washington, D.C. 20418.)

National Motor Freight Traffic Association, Inc., Agent

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Association, Inc., Tariff Order Section, 1616 P Street, N.W., Washington, D. C. 20036.)

Uniform Classification Committee, Agent

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, Illinois 60606.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:36Z
Check the source to verify that this is the current version before use.

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 Materials. All materials shall be clean, sound, wholesome, and free from evidence of insect infestation or other objectionable foreign matter.

* 3.1.1 Flour, enriched. The flour shall be wheat flour, bleached or unbleached, and shall be matured. The flour shall be enriched in accordance with the Definitions and Standards of Identity for Enriched flour under the Federal Food, Drug and Cosmetic Act and regulations promulgated thereunder.

3.1.2 Sugar. Sugar shall be white refined cane or beet sugar or a combination thereof, either powdered or granulated, as required for the specific product.

3.1.3 Shortening. The shortening shall be refined vegetable oil and shall have a stability of not less than 100 hours as determined by the active oxygen method (AOM).

3.1.4 Rolled oats. Rolled oats shall conform to quality requirements for type I of N-C-195.

3.1.5 Salt. Salt shall be white, refined, sodium chloride with or without anticaking agent. Iodized salt shall not be used.

3.1.6 Egg products. The egg product shall be fresh whole eggs, frozen whole eggs, dried whole eggs, or a combination thereof in the proper proportion so as to comply with the formulation requirements of 3.2. All egg products shall have been produced and handled in compliance with requirements set forth in the USDA publication entitled "Regulations Governing the Grading and Inspection of Egg Products". They shall be prepared under continuous inspection of the USDA and shall bear the inspection shield mark. Egg products shall have been tested and certified Salmonella negative by the USDA.

3.1.7 Milk, dry, nonfat. Nonfat dry milk shall be extra grade of high heat type and shall be spray processed (conventional), as specified in C-M-350.

* 3.1.8 Leavening agents. Leavening agents shall be sodium bicarbonate, ammonium bicarbonate and monocalcium phosphate or other appropriate leavening agents. The leavening agents shall conform to Food Chemical Codex.

Source: https://assist.dla.mil -- Downloaded: 20261O-16T12:36Z
Check the source to verify that this is the current version before use.

3.1.9 Vanilla flavoring. Vanilla flavoring shall be pure vanilla bean extract, vanillin or ethyl vanillin or a combination thereof.

3.1.10 Chocolate chips. Chocolate chips shall be made from semisweet chocolate which meets the requirements in the Definitions and Standards for Chocolate and Cocoa Products under the Federal Food, Drug and Cosmetic Act. The chocolate chips shall be in the form of chips or drops. The fat content shall be not less than 28.0 percent. The count per pound shall be not less than 3000 nor more than 4400.

* 3.1.11 Cocoa. Cocoa shall conform to the product requirements of medium fat cocoa as defined in JJJ-C-501.

* 3.1.12 Plastic fat. The plastic fat used in the filling shall conform to 3.1.3 except that hydrogenated cocumut oil may be used. In addition, when hydrogenated coconut oil is used the melting point shall be within the range of 100°F. to 110°F. It shall have a plasticity suitable for the production of sandwich cookie filling. It may contain added lecithin or other suitable plasticizing agents.

3.1.13 Vitamins. Ascorbic acid (vitamin C) and thiamine hydrochloride shall comply with Food Chemical Codex.

3.2 Formulas (types I and II cookies).

3.2.1 Type I. Oatmeal cookies with chocolate chips shall be prepared from the following ingredients in the proportions indicated:

TABLE I. Oatmeal cookies, chocolate chips

Material	Parts by weight
Flour	not more than 100
Sugar	not more than 105
Nonfat dry milk	not less than 6
Eggs (on a liquid basis)	not less than 20
Shortening	not less than 65
Rolled oats	not less than 45
Chocolate chips	not less than 62.5
Salt	not less than 1.5 or more than 1.20
Bicarbonate of soda	(as required)
Flavoring	(as required)
Water	(variable)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:36Z
Check the source to verify that this is the current version before use.

3.2.2 Type II. Sandwich, cookie, styles A and B, shall be prepared from the following ingredients in the proportions indicated:

TABLE II. Base cake (sandwich)

Material	Parts by weight
Flour	not more than 100
Sugar	not more than 35
Shortening	Not less than 25
Salt	not less than 1.10 or more than 1.25
Baking soda	(as required)
Ammonium bicarbonate	(as required)
Monocalcium phosphate	(as required)
Water	(as required)

TABLE III. Filling formula (vanilla)

Material	Parts by weight
Powdered sugar	not more than 100
Plastic fat	not less than 50 nor more than 60 1/
Vanilla	(as required)

1/ Exact amount between specified limits to be adjusted to yield proper consistency for stenciling.

TABLE IV. Filling formula (chocolate)

Material	Parts by weight
Powdered sugar	not more than 100
Plastic fat	not less than 50 nor more than 60 1/
Cocoa	not less than 10
Vanilla	(as required)

1/ See footnote 1/ of table III.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:36Z
Check the source to verify that this is the current version before use.

3.2.3 Vitamin content in fillings. The cookie fillings, styles A and B, shall be fortified with vitamins and shall contain the following minimum vitamin levels:

Thiamine hydrochloride (Vitamin B-1)	-	Not less than 0.8 milligrams per 14.18 grams of filling.
Ascorbic acid (Vitamin C)	-	Not less than 37.5 milligrams per 14.18 grams of filling.

3.3 Finished product.

3.3.1 Type I, oatmeal with chocolate chips. The cookies shall be well-baked. They shall be browned on the bottom surface and outer edges, but not appreciably browned on the top surface. They shall be wholly intact, free of checks or cracks. The weight of each cookie shall be not less than 13.7 grams. The diameter of each cookie at its greatest dimension shall be such as to enable easy placement of the cookie in the required lined can. However, the diameter at its greatest dimension shall be not less than 2-5/16 inches. The cookies shall be tender and crisp with an appetizing flavor, free of a burnt or scorched flavor. Moisture content shall be not greater than 5.0 percent.

3.3.2 Type II, sandwich. Each cookie shall consist of two round base cakes with a layer of filling between them. The weight of a cookie shall be not less than 21.5 grams with the filling weighing not less than 6.4 grams. The base cakes shall have been uniformly well-baked with a color ranging from not lighter than chip 27885 or darker than chip 13711 of FED-STD-595 for colors. The color comparisons shall be made under north sky daylight with the objects held in such a way as to avoid specular refractance (glossiness). The moisture content of the base cakes shall be not greater than 5.0 percent by weight. The filling shall be centered so that it does not protrude beyond the perimeter of the base cakes. The filling shall be fortified as specified in 3.2.3. The cookie shall be wholly intact, free of checks or cracks. The diameter of the cookie shall be such that the cookie can easily be placed in the required lined can. However, the diameter shall be not less than 2-6/16 inches. The cookie shall be tender and crisp and have an appetizing flavor, free of a burnt or scorched flavor.

3.3.3 Height of cookies. The cookies shall have an overall height which will preclude damage to them when packaged as specified in 5.1. The minimum height of the cookies in the can shall be 1-1/2 inches.

3.4 Federal Food, Drug, and Cosmetic Act. All deliveries shall conform in every respect to the provisions of the Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:36Z
Check the source to verify that this is the current version before use.

3.5 Workmanship. The product shall be processed in establishments meeting the requirements of MIL-STD-1105. It shall be prepared and processed with minimum delay between the various stages in production.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Preacceptance inspection (plant sanitation inspection). The product shall be rejected if produced in plants not meeting the requirements of 3.5.

4.3 Inspection. Sampling for inspection shall be performed in accordance with MIL-STD-105, except where otherwise indicated hereinafter.

4.3.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced specifications, drawings and standards unless otherwise excluded, amended, modified or qualified in this specification or applicable purchase documents.

4.3.1.1 Examinations.

4.3.1.1.1 Identity. Conformance of ingredients to identity (kind, count of chocolate chips, Chemical Codex quality, grade, U.S.D.A inspection and certification - as applicable) shall be ascertained by examination of pertinent labels, invoices and other valid documents, presence of U.S.D.A shield on egg products containers and certification for Salmonella negative egg product.

* 4.3.1.1.2 Condition. Each ingredient, except rolled oats, shall be examined organoleptically, as necessary, to determine conformance to 3.1. When examining shortening and plastic fat, odor and taste determinations shall be performed by heating the item to 350°F checking for off odors and then cooling item to approximately 100°F and checking for off flavors. The sample unit for examination shall be approximately 1 pound of ingredient (1 ounce for vitamins and vanilla flavoring) derived from each of 5 primary containers. In the event a lot consists of less than five containers, a sample unit shall be extracted from each container in the lot. One or more sample units not conforming to condition requirements shall indicate an unacceptable ingredient and use of such shall be cause for rejection of the involved finished product.

Source: https://assist.dla.mil -- Downloaded: 202610-16T12:36Z
Check the source to verify that this is the currentversion before use.

4.3.1.1.3 Rolled oats. Rolled oats shall be examined for product characteristics in accordance with the applicable quality assurance provisions of N-C-195, except that the criteria pertinent to the cooked product shall not apply.

4.3.2 Testing of components. Testing of components described in the specification and changes to the testing of components described in subsidiary specifications shall be as shown in table V. Results shall apply to the lot average for the characteristics listed in the table.

TABLE V. Testing of components (see 4.3.1)

Component	Sample unit	Lot size expressed in	Inspection level	Characteristics	Results reported	Test ref & req para
Shortening and plastic fat	1 pound composite	pounds	S-2	Stability	Pass or fail 1/	4.4 3.1.3 3.1.12
				Melting point (Coconut fat only)	Nearest degree	
Chocolate chips	8 ounce composite 2/	pounds	S-2	Fat	Nearest 0.1 percent	4.4 3.1.10
Cans 3/	1 can with lid	cans	S-1	Tin plate	Nearest 0.01 lb/ base box	4.4 5.1
Can liners	1 liner	liners	S-2	Basis weight	Nearest lb/ream	4.4 5.1.1
				Turpentine penetration	Nearest second	

1/ Whenever a test failure has occurred, the laboratory shall report the time and peroxide value from which the AOM stability (to the nearest hour) was determined.

2/ The composite shall be formed from the number of containers indicated by the inspection level.

3/ Testing of can coating and can label shall be performed on the same can submitted for tin plate test.

Source: https://assist.dla.mil -- Downloaded: 202610-16T12:36Z
Check the source to verify that this is the current version before use.

4.3.3 Examination of formulations. Examination shall be performed to determine conformance to 3.2, as concerns formulations. Records of formulations shall be maintained. Nonconformance shall be cause for rejection of the involved finished product.

4.3.4 Examination of end item. Examination shall be in accordance with tables VII through IX and 4.3.4.1 and 4.3.4.2. Sampling plans for the aforementioned tables shall be in accordance with table VI. The acceptable quality levels (AQLs) shall be expressed as defects per hundred units.

TABLE VI. Sampling plans

Table	Sample unit	Lot size expressed in	Inspection level	AQLs Major	AQLs Minor	AQLs Total
VII	1 filled can	cans	S-3	-	4.0	-
VIII	1 filled can	cans	S-3	2.5	-	10.0
IX	1 filled marked shipping container	shipping containers	S-3	2.5	-	6.5

TABLE VII. Examination for weight of cookies and weight of sandwich cookie filling 1/

Category	Defects
Minor	
201	Weight of a sandwich cookie less than 21.5 grams 2/
202	Weight of oatmeal chocolate chip cookie less than 13.7 grams
203	Weight of sandwich cookie filling less than 6.4 grams 2/ 3/

1/ Weighing device shall be calibrated in increments down to 0.1 gram.

2/ Weigh one sandwich cookie per sample unit.

3/ Subtract weight of two base cakes (based on the average weight of a base cake calculated from the weight of 20 base cakes).

Source: https://assist.dla.mil -- Downloaded: 202610-16T12:36Z
Check the source to verify that this is the current version before use.

TABLE VIII. Examination of can contents 1/

Category		Defects
Major	Minor	
		Liner
101		Missing
102		Not fabricated as specified
	201	Tear, hole or part missing
	202	Size not as specified 3/
	203	Tips of corrugations not in contact with walls of can
		Cookies
103		One or more missing
104		Crushed cookie 4/
	204	Broken or checked cookie 4/
105		Chocolate chip cookie not color specified
106		Base cakes not within color range specified 2/
107		Base cakes not uniformly well baked
	205	Diameter of each cookie less than specified minimum 3/
	206	Height of the three cookies less than 1-8/16 inches 3/
	207	Filling of sandwich cookie extends beyond the perimeter of base cakes
	208	Assortment of cookies not as specified
108		Cookie not tender and crisp
109		Not appetizing (e.g. raw, scorched, burnt, or other objectionable flavor or odor)

1/ Presence of foreign material (e.g. insects, filth, wood, metal, glass, paint, etc.) shall be cause for rejection of the lot.

2/ Examine one cookie per sample unit.

3/ Measuring device shall be calibrated in 1/16 inch increments.

4/ A checked cookie is a whole cookie that has fracture lines appearing on its surface. A broken cookie is one that is broken into not more than 3 distinct pieces or has 1/8 but not more than 1/4 of the area missing. A crushed cookie is one that is broken into more than 3 distinct pieces or has 1/4 or more of the area missing.

Source: https://assist.dla.mil -- Downloaded: 202610-16T12:36Z
Check the source to verify that this is the current version before use.

TABLE IX. Examination of shipping containers for marking and count

Category		Defects
Major	Minor	
101		Markings missing, incorrect or illegible.
	201	Number of cans less than quantity marked on shipping container.
	202	Markings on shipping container indicate a content of more than 96 cans.

* 4.3.4.1 Examination of cans for condition and labeling. Examination shall be in accordance with the criteria in the United States Standards for Condition of Food Containers.

4.3.4.2 Examination of can for internal coating, and seam leakage. Examinations shall be in accordance with the applicable quality assurance provisions of PPP-C-29.

4.3.5 Testing of base cakes. Base cakes shall be tested for moisture content in accordance with 4.4. The quantity for testing shall be a 1/2-pound representative sample. Testing shall be performed on a ground composite. The test result shall be reported to the nearest 0.1 percent. The lot shall be rejected if moisture exceeds 5.0 percent.

4.3.6 Testing of sandwich cookie filling. Cookie filling shall be tested for vitamin content in accordance with 4.4. The sample shall be a representative 1/4-pound composite of filling. Results shall be reported to the nearest 0.01 mg for thiamine hydrochloride and nearest 0.1 mg for Vitamin C. A test result less than 0.8 mg thiamine hydrochloride/14.18 grams filling, or 37.5 mg Vitamin C/14.18 grams filling shall be cause for rejection of the lot.

4.3.7 Testing oatmeal chocolate chip cookies. The cookies shall be tested for moisture content in accordance with 4.4. The sample for testing shall be a 1/2-pound representative sample. Testing shall be performed on a ground composite. Results shall be reported to the nearest 0.1 percent. A moisture content of more than 5.0 percent shall be cause for rejection of the lot.

4.4 Test methods. Examination and test procedures which differ from those specified herein, unless otherwise excepted, may be used by the supplier if they provide a quality assurance equivalent to that specified. If the Government contracting officer determines that such procedures and controls

Source: https://assist.dla.mil -- Downloaded: 202610-16T12:36Z
Check the source to verify that this is the current version before use.

do not provide, as a minimum such quality assurance, the supplier will use the procedures set forth herein. In case of dispute as to examination or test results, the procedures specified herein will govern.

4.4.1 Examination procedures.

4.4.1.1 Examination for leakage. The procedure for determining seam leakage of cans shall be in accordance with PPP-C-29.

4.4.2 Test procedures.

* 4.4.2.1 Chemical analysis. Chemical analysis, when required, shall be made in accordance with the following methods from Official Methods of Analysis of the Association of Official Analytical Chemists, except as specified below:

Test	Source	Method
Shortening and Plastic Fat Stability	Section C, Chapter: Commercial Fats and Oils 1/	Cd 12-57
Fat in Chocolate chips	Chapter: Cacao Beans and Its Products Section, Fat	Quantitative Determination
Moisture: Base cake and Oatmeal with chocolate chip	Chapter: Cereal Foods Section; Wheat Flour	Total solids (Moisture) Indirect Method Vacuum Oven Method
Melting point (WMP) Hydrogenized coconut oil	Section C, Chapter: Commercial Fats and Oils 1/	Cc 2-38

1/ Official and Tentative Methods of the American Oil Chemists' Society.

4.4.2.2 Vitamin determination. Vitamin contents shall be determined by the method described in Methods of Vitamin Assay of the Association of Vitamin Chemists, Chapter: Ascorbic acid; Modification of "Loeffler and Ponting" method and Chapter: Thiamine hydrochloride.

4.4.2.3 Tin coating weight. Tin coating weight shall be determined by any method specified in PPP-C-96.

5. PREPARATION FOR DELIVERY

5.1 Packaging, level A. Three cookies, one each of type I and one each of styles A and B, type II, shall be packaged in an open-top style, round, metal can, size 300 by 200, with soldered side seam and compound-lined double

Source: https://assist.dla.mil -- Downloaded: 202610-16T12:36Z
Check the source to verify that this is the current version before use.

seamed ends. The can shall be made throughout from not less than commercial 0.25-pound electrolytic tinplate per base box (see 4.4.2.3). The ends of the can shall be coated inside with an enamel furnished by the can manufacturer in accordance with best commercial practice for the product. The can shall be coated outside with a lacquer conforming to type III of TT-C-495. The can shall be lined as specified in 5.1.1. The can shall be hermetically sealed and shall not leak when examined for leakage in accordance with 4.4.1.1.

5.1.1 Can liner. The inside walls of the can shall be lined with a sheet of single-face corrugated material made from 2 sheets of glassine, parchment, or greaseproof paper having a minimum basis weight of 25 pounds ± 5 percent, per ream (24 by 36-500) when tested in accordance with method 5022 of FED-STD-101 and a nominal average turpentine test of not less than 300 seconds when tested in accordance with method 3017 of FED-STD-101. The liner shall be 8-3/16 inches in length by 1-9/16 inches in width, ± 1/16 inch in either dimension, with the corrugations parallel to the width. The liner shall be placed so that the tips of the corrugations are in contact with the walls of the can.

5.2 Packing, level C. Ninety six cans of cookie units, packaged as specified in 5.1, shall be packed in accordance with the Uniform Freight Classification Rules or National Motor Freight Classification Rules, as applicable.

5.3 Labeling and marking.

5.3.1 Cans. Cans shall be labeled in accordance with MIL-L-1497.

5.3.2 Shipping containers. Shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

(a) Title, number and date of this specification.
(b) Type and style of product required (see 1.2).

6.2 The margins of this specification are marked with an asterisk (*) to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and suppliers are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:36Z
Check the source to verify that this is the current version before use.

Custodians:

Army - GL
Navy - SA
Air Force - 45

Review activities:

Army - MD
Navy - MC, MS
DP - SS

Preparing activity:

Army - GL

Project No. 8920-0205

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:36Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:36Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS. The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

Cookies, Oatmeal With Chocolate Chips and Sandwich: Canned MIL-C-1029E

NAME OF ORGANIZATION AND ADDRESS	CONTRACT NUMBER
	MATERIAL PROCURED UNDER A ☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*	TELEPHONE NO.
	DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 202610-16T12:36Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
US ARMY NATICK LABORATORIES
NATICK, MA 01760

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

STSNLT-EQS

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314



Commander
US Army Natick Laboratories
ATTN: STSNLT-EQS
Natick, Massachusetts 01760

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:36Z
Check the source to verify that this is the current version before use.