MIL-C-1008C
20 January 1976
SUPERSEDING
MIL-C-1008F
14 April 1971

MILITARY SPECIFICATION

GLOVES, CLOTH, COTTON, WORK, MEN'S AND WOMEN'S

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirements for cotton work gloves.

1.2 Classification. The gloves shall be of one type and shall be procured in the following classes as specified (see 6.2).

Class 1 - Men's
Class 2 - Women's

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on [illegible] of invitation for bids or request for proposal, form a part of this [illegible]cification to the extent specified herein.

SPECIFICATIONS

FEDERAL

V-T-276 - Thread, Cotton
CCC-C-458 - Cloth, Flannel, Cotton
DDD-L-20 - Label; for Clothing, Equipage, and Tentage (General Use)

MILITARY

MIL-B-17757 - Boxes, Shipping, Fiberboard (Modular Sizes)

STANDARDS

FEDERAL

FED-STD-191 - Textile Test Methods
FED-STD-751 - Stitches, Seams, and Stitching

FSC 8415

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:35Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage

LAWS AND REGULATIONS

U.S. POSTAL SERVICE MANUAL

(Copies of the manual may be obtained from the Superintendent of Documents, U.S. Government Printing Office, Washington, D. C. 20402.)

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply:

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT
National Motor Freight Classification

(Application for copies shall be addressed to the American Trucking Association, Inc., Tariff Order Section, 1616 P Street, N.W., Washington, D. C. 20036.)

UNIFORM CLASSIFICATION COMMITTEE, AGENT
Uniform Freight Classification

(Application for copies shall be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, Illinois 60606.)

3. REQUIREMENTS

3.1 Guide sample. Samples, when furnished, are solely for guidance and information to the supplier (see 6.3). Variation from this specification may appear in the sample, in which case this specification shall govern.

3.2 First article approval. The requirements for first article will be as specified by the procuring activity (see 6.2).

3.3 Materials.

3.3.1 Basic materials.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:35Z
Check the source to verify that this is the current version before use.

3.3.1.1 Class 1 - men's gloves. The basic material for the class 1 gloves shall be of a canton flannel material, conforming to type IV, class 6, of CCC-C-458.

3.3.1.2 Class 2 - women's gloves. The basic material for the class 2 gloves shall be of a canton flannel material, conforming to type IV, class 3, of CCC-C-458.

3.3.2 Cuff fabric. The fabric for the cuffs shall be of a knitted 1 x 1 rib seamless unbleached cotton tubing, conforming to the requirements specified in Table I when tested as specified in 4.3.1.

Table I. Requirements for cuff tubing

Characteristic	Requirement	
	Minimum	Maximum
Yards per pound	12	14
Wales per inch	14	--
Courses per inch	20	--
Flat width, inches	2-1/4 (5.72 cm)	--

3.3.3 Thread. The thread for seaming and stitching the gloves shall be tural (unbleached) cotton, conforming to type IA1, ticket numbers 30 and 3-ply, of V-T-276.

3.4 Label. Each glove shall be marked with a combination identification and size label conforming to type III or IV, class 4, of DDD-L-20, except that the size is not applicable and shall bear the following inscription:

GLOVES, CLOTH, COTTON, WORK
CLASS 1 - MEN'S (Example)
CONTRACT NO.: DSA-000-000-0000 (Example)
STOCK NO.: 8415-00-000-0000 (Example)
NAME OF SUPPLIER:

The markings shall show fastness to accelerated laundering only.

3.5 Design. The gloves shall be a full inseam, clute-cut pattern, with an attached knitted cuff (see Figure 1).

3.5.1 Figure. Figure 1 is furnished for information purposes only. To the extent of any inconsistencies between the written specification and the figure, the written specification shall govern.

3.6 Dies and patterns. The dies or patterns for cutting all hand component parts of the gloves shall be furnished by the supplier, and shall be of the proper proportions to provide for good fitting gloves conforming to the finished measurements specified in 3.9.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:35Z
Check the source to verify that this is the current version before use.

3.6.1 Pattern parts. The hand component parts of the gloves shall be cut from the basic material specified in 3.3.1, and in accordance with the following pattern parts required for the manufacturing process:

Nomenclature of pattern parts	Cut parts per pair
No. 2 finger	2
No. 3 finger	2
No. 4 finger	2
Thumb	2
Palm	2

3.7 Construction.

3.7.1 Stitches, seams, and stitchings. Stitch, seam, and stitching types specified in Table II shall conform to FED-STD-751. Whenever two or more methods for seam or stitch types are given for the same part of the operation, any one may be used.

3.7.2 Stitches per inch. The minimum and maximum number of stitches per inch shall be as specified in Table II.

* 3.7.3 Type 301 stitching. Ends of 301 stitching shall be backstitched or backtacked not less than 3/8 inch (9.52 mm), except where ends are caught in other seams and stitching. Thread tension shall be maintained so there will be no loose stitching resulting in a loose bobbin or top thread, or no excessively tight stitching resulting in puckering of the materials sewn. The lock shall be embedded in the materials sewn.

* 3.7.3.1 Repairs of type 301 stitching. Repairs of type 301 stitching shall be as follows:

a. When thread breaks or bobbin run-outs occur during sewing, the stitching shall be repaired by restarting the stitching a minimum of 3/8 inch (9.52 mm) back of the end of the stitching. 1/

b. Thread breaks, or two or more consecutive skipped stitches or run-offs noted during inspection of the item (in-process or end item), shall be repaired. The stitching shall start a minimum of 3/8 inch (9.52 mm) in back of the defective area, continue over the defective area and continue a minimum of 3/8 inch (9.52 mm) beyond the defective area, onto the existing stitching. Loose or tight stitching shall be repaired by removing the defective stitching without damaging the material and restitching in the required manner. 1/

1/ When making the above repairs, the ends of stitching are not required to be backstitched.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:35Z
Check the source to verify that this is the current version before use.

3.7.4 Type 401 stitching. Thread tension shall be maintained so that there will be no loose stitching. Where stitch type 401 is used, the looper thread shall be on the inside of the gloves. Both ends of all seams or stitching produced with 401 stitch type, when not caught in other seams or stitching, shall have a 1/2 to 3/4 inch (12.70 to 19.05 mm) chain extending beyond each end. All repairs shall be in accordance with 3.7.3.1(a) and 3.7.3.1(b).

3.8 Manufacturing operations. The gloves shall be manufactured in accordance with operation requirements specified in Table II. The supplier is not required to follow the exact sequence of operations, provided the finished gloves are identical to those produced by following the exact sequence as shown.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:35Z
Check the source to verify that this is the current version before use.

Table II - Construction of gloves

No.	Description of Operation	Stitch Type	Seam and Stitching Type	Stitches Per Inch	Thread	
					Needle	Bobbin or Looper
1.	Cutting a. Cut the hand component parts of the gloves in the length (warp) direction from the base fabric specified in 3.3.1. b. Cut the knitted cuff tubing material specified in 3.3.2 to a sufficient length, which will permit half of the tubing to be turned inside other half so as to form a double thickness. c. The face side of the base fabric to be assembled, shall be the unmapped side.					
2.	Replacement of defective components During the spreading, cutting, and manufacturing process, components having material defects or damages that are classified as defects in Section 4, shall be removed from production and replaced with non-defective and properly matched components.					
3.	Assemble hand portion of gloves (thumb and fingers) a. Stitch the thumb piece to thumb section of palm face to face, 1/8 to 3/16 inch (3.17 to 4.76 mm) from the raw edge.	301 or 401	SSa-1	8-12	30/3 30/3	30/3 50/3
	b. Stitch the No. 2 finger to the No. 3 finger portion face to face from the wrist edge to the finger crotch, 1/8 to 3/16 inch (3.17 to 4.76 mm) from the raw edge.	301 or 401	SSa-1	8-12	30/3 30/3	30/3 50/3
	c. Stitch the No. 3 finger to the No. 4 finger portion face to face from the wrist edge to the finger crotch, 1/8 to 3/16 inch (3.17 to 4.76 mm) from the raw edge.	301 or 401	SSa-1	8-12	30/3 30/3	30/3 50/3

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:35Z
Check the source to verify that this is the current version before use.

Table II - Construction of gloves (cont'd)

No.	Description of Operation	Stitch Type	Seam and Stitching Type	Stitches Per Inch	Thread	
					Needle	Bobbin or Looper
3.	Assemble hand portion of gloves (thumb and fingers) (cont'd) d. Stitch the No. 2 finger to the first (index) finger face to face from the wrist edge to the finger crotch, 1/8 to 3/16 inch (3.17 to 4.76 mm) from the raw edge.	301 or 401	SSa-1	8-12	30/3 30/3	30/3 50/3
4.	Closing Close gloves by stitching face to face from the top edge of the first (index) finger and along the periphery of the fingers and side of glove to the wrist edge, 1/8 to 3/16 inch (3.17 to 4.76 mm) from the raw edge.	301 or 401	SSa-1	8-12	30/3 30/3	30/3 50/3
5.	Attach cuff Join cut ends of double thickness cuff tubing to hand portion of glove at wrist edge, and stitch 1/4 to 5/16 inch (6.35 to 7.93 mm) from cut edges completely around and continuing the stitching by at least 1 inch (2.54 cm) beyond the beginning. When 401 stitch type is used, a 1/2 to 3/4 inch (12.70 to 19.05 mm) chain shall be exposed at point of run-off.	301 or 401	SSa-1	8-12	30/3 30/3	30/3 50/3
6.	Finishing Turn gloves to its finished position, napped side of the base fabric on the inside, and form or lay-off gloves on proper heated laying-off boards.					
7.	Labeling Each glove shall have the identification marking (see 3.4) applied on the back hand portion of glove, centered and positioned so that the distance between					

NCTR Form 1, 15 Sep 1967

MIL-G-1005G

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:35Z
Check the source to verify that this is the current version before use.

Table II - Construction of gloves (cont'd)

No.	Description of Operation	Stitch Type	Seam and Stitching Type	Stitches Per Inch	Thread	
					Needle	Bobbin or Looper
7.	Labeling (cont'd) the top edge of the first line and the wrist seam is approximately 1/2 inch (12.70 mm). The legend shall face the opening.					
8.	Trimming and cleaning a. Trim thread ends and remove all loose threads. b. Remove all spots and stains.					
9.	Pairing The finished gloves shall be paired and tacked or stapled together with a non-corrosive staple in accordance with the best commercial practice, which will permit the gloves to be separated without tearing the fabric.					

NCTR Form 1, 15 Sep 1967

MIL-G-1008C

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:35Z
Check the source to verify that this is the current version before use.

3.9 Measurements. The finished gloves shall conform to the measurements pecified in Table III. All measurements and tolerances are expressed in nches and the metric equivalent, and shall be made with the glove laid flat nd under no tension.

Table III. Finished measurements

leasurement	Class 1	Class 2	Tolerance
)verall length (A)	10-1/2 (26.67 cm)	9-1/2 (24.13 cm)	+ 1/2, -0 (+12.70 mm, -0)
Width of palm (B)	5-1/4 (13.36 cm)	4-1/4 (10.79 cm)	+ 3/8, -0 (+9.52 mm, -0)
Length from tip of second finger to crotch of third finger (C)	3-1/4 (8.26 cm)	3-1/4 (8.26 cm)	+ 1/4, -0 (+6.35 mm, -0)
Length from tip of thumb to thumb crotch (D)	3 (7.62 cm)	2-1/2 (6.35 cm)	+ 1/4, -0 (+6.35 mm, -0)
Length from top edge of cuff to wrist seam (E)	2-1/2 (6.35 cm)	2 (5.08 cm)	+ 1/4, -0 (+6.35 mm, -0)

NOTE: A through E refer to Figure 1.

A. Measurement taken from tip of second finger to top edge of knitted cuff.

B. Measurement taken across palm at thumb crotch, seam to folded edge.

C. Measurement taken from tip of second finger to crotch of third finger.

D. Measurement taken from tip of thumb to thumb crotch.

E. Measurement taken from top edge of cuff to wrist seam.

3.10 Workmanship. The finished gloves shall conform to the quality established by this specification. The occurrence of defects shall not exceed the applicable acceptable quality levels.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:35Z
Check the source to verify that this is the current version before use.

for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to assure supplies and services conform to the prescribed requirements.

4.1.1 Certificate of compliance. Where certificates of compliance are submitted, the Government reserves the right to check test such items to determine the validity of the certification.

4.2 First article inspection. When required, the first article submitted in accordance with 3.2, shall be inspected as specified in 4.3.2.1 and 4.3.2.2 for compliance with design, construction, workmanship, appearance, and dimensional requirements.

4.3 Inspection. Inspection shall be performed in accordance with MIL-STD-105, except where otherwise indicated herein.

4.3.1 Component and material inspection. In accordance with 4.1, components and material shall be inspected in accordance with all the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document. In addition, the knitted cuff tubing material shall be tested for the characteristics specified in Table IV in accordance with the referenced test methods of FED-STD-191. Testing for all the requirements listed is applicable to the sample unit. The lot size shall be expressed in units of pounds and the sample unit shall be 1 yard (0.92 m) full width. The sample size shall be as follows:

Lot size	Sample size
800 or less	2
801 up to and including 22,000	3
22,001 and over	5

The lot shall be unacceptable if one or more sample units fail to meet any requirement specified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:35Z
Check the source to verify that this is the current version before use.

Table IV. Cuff tubing

Characteristic	Requirement paragraph	Test method
Material identification	3.3.2	1/
Type of knit	3.3.2	Visual 2/
Weight	3.3.2	5041
Wales per inch	3.3.2	5070
Courses per inch	3.3.2	5070
Flat width	3.3.2	5020 3/

1/ A certificate of compliance will be acceptable for this requirement.

2/ One determination shall be performed per sample unit, and the results reported as "pass" or "fail."

3/ Test results shall be reported to the nearest 1/4 inch (6.35 mm).

.3.2 Examination of the end item. The defects found during the examination of the end item shall be classified in accordance with 4.3.2.1 and 4.3.2.2. The applicable inspection levels and the acceptable quality levels (AQL's) shall be as indicated in 4.3.2.3. The lot size shall be expressed in units of one glove each. The sample unit shall be one glove and selection shall be by pairs. Defects for pairing shall be classified as a single defect.

4.3.2.1 Visual examination.

Defect	Classification Major	Minor
Material Defects and Damages		
a. Any hole, cut, tear or rip.	X	
b. Any visible mend, loose yarn, broken yarn, snagged thread, slubby yarn more than twice the size of the normal diameter of the yarn, or a thin place.		X
c. Ruptured fibers in the line of stitching (caused by a blunt or broken needle).	X	
d. Any run or dropped stitch in knitted cuff.	X	
e. Any knitted cuff spliced.	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:35Z
Check the source to verify that this is the current version before use.

Defect	Classification Major	Minor
Cleanness		
a. Any spot or stain.		X
b. Thread ends not trimmed or loose threads not removed throughout major portion of glove.		X
Cutting		
Any component part not cut in accordance with specification requirements, e.g., any hand component part not cut in the length (warp) direction from the base canton flannel material.	X	
Pairing		
a. Mispaired, i.e., two left or two right gloves submitted as a pair.	X	
b. Pair not tacked or stapled together.		X
c. Tacking or stapling too tight, i.e., not permitting the gloves to be separated without tearing the fabric.	X	
Components and Assembly		
a. Any component part or operation omitted.	X	
b. Any component not as specified, e.g., knitted cuff not tubular or seamless.	X	
c. Knitted cuff not constructed of double thickness.	X	
d. Any component part misplaced or not serving intended purpose.		X
e. Any component part not securely affixed, e.g., knitted cuff loosely attached to hand portion of glove.		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:35Z
Check the source to verify that this is the current version before use.

Defect	Classification Major	Minor
Seams and Stitching		
a. Any open seam.	X	
b. Open seam repaired, but not repaired as specified.		X
NOTE: The seam shall be classified open when one or more stitches joining a seam are broken or when two or more continuous skipped or run-off stitches occur.		
c. Not specified seam or stitch type.	X	
d. Any line of stitching omitted.	X	
e. Any line of stitching misplaced or not beginning or ending where specified.		X
f. Any part of glove caught in an unrelated operation.	X	
g. Loose tension resulting in a loose seam.	X	
. Tight tension (stitches break when normal strain is applied in the direction of the seam or stitching).	X	
i. End of 301 stitching, when not caught in other seams or stitching, not backstitched or backstitched less than 3/8 inch (9.52 mm).		X
j. End of seam or stitching produced with 401 stitch type, when not caught in other seams or stitching:		
1. Chain does not extend beyond each end.	X	
2. Chain extends less than 1/2 inch (12.70 mm), or more than 3/4 inch (19.05 mm) beyond each end.		X
k. Looper thread of 401 stitch type on outside.		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:35Z
Check the source to verify that this is the current version before use.

Defect	Classification	
	Major	Minor
Seams and Stitching (cont'd)		
l. Stitches per inch (to be scored only when the condition exists on the major portion of a seam):		
1. One or two stitches per inch less than the minimum.		X
2. Three or more stitches per inch less than the minimum.	X	
3. More than the maximum number of stitches per inch, damaging assembly.	X	
4. More than the maximum number of stitches per inch, but not damaging assembly.		X
m. Gage of stitching irregular or not as specified:		
1. Seriously affecting serviceability.	X	
2. Affecting serviceability, but not seriously.		X
Label (Marking)		
a. Omitted, incorrect, illegible, or incomplete:		
1. On one glove.		X
2. On both gloves.	X	
b. Misplaced.		X

4.3.2.2 Dimensional examination. The gloves shall be examined for dimensional defects. Any dimension deviating from dimensions and tolerances specified in 3.9, shall be scored as a defect.

4.3.2.3 Inspection levels and acceptable quality levels. The inspection levels and acceptable quality levels (AQL's), expressed in defects per one hundred units (DHU), shall be as follows:

	Inspection level	AQL's Major	AQL's Total
For defects applicable to 4.3.2.1	II	2.5	6.5
For defects applicable to 4.3.2.2	S-3	-	4.0

4.3.3 Examination of preparation for delivery requirements. An examination shall be made to determine that packaging, packing, and marking comply with Section 5 requirements of this specification. Defects shall be scored in accordance with the list below. The sample unit shall be one shipping container fully prepared for delivery with the exception that it need not be closed. Defects of closure listed below shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 and the AQL shall be 2.5 defects per 100 units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:35Z
Check the source to verify that this is the current version before use.

Examine	Defect
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence or method of application.
Materials	Any component missing, damaged, or not as specified.
Workmanship	Inadequate application of components such as incomplete closure of container flaps, loose strapping, or inadequate stapling, bulging or distortion of container.
Content	Number of pairs per bundle is more or less than specified. 1/ Number of bundles per container is more or less than specified.

1/ For this defect, two bundles from each shipping container in the sample shall be examined.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A or C as specified (see 6.2).

5.1.1 Level A. Five pairs of gloves, of one class only, shall be neatly packed in a bundle with every other pair reversed fingertip to cuff. The bundle shall be securely tied at each end with cotton tape or twine.

5.1.2 Level C (Commercial Packaging). Gloves shall be packaged to afford adequate protection against deterioration and physical damage during shipment from the supply source to the first receiving activity. The package and the quantity per package shall be the same as that normally used by the supplier for retail distribution.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 Level A. Forty-five (45) pairs of class 1 gloves or sixty (60) pairs of class 2 gloves, packaged as specified in 5.1, shall be packed in a fiberboard shipping container assembled, closed, and reinforced conforming to type CF, class weather-resistant, grade V2s, size 1A, of MIL-B-17757. The fiberboard for the box liner shall conform to type CF, class weather-resistant, variety DW, grade V15c, of MIL-B-17757. Each container shall have the contents completely covered on the top and bottom with a sheet of any suitable commercial grade kraft paper.

5.2.2 Level B. Forty-five (45) pairs of class 1 gloves or sixty (60) pairs of class 2 gloves, packaged as specified in 5.1, shall be packed in a fiberboard shipping container assembled and closed conforming to type CF, class domestic, grade 275, size 1A, of MIL-B-17757. The fiberboard for the box liner shall conform to type CF, class domestic, variety DW, grade 200, of MIL-B-17757. Each container shall have the contents completely covered on the top and bottom with a sheet of any suitable commercial grade kraft paper.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:35Z
Check the source to verify that this is the current version before use.

5.2.2.1 When specified (see 6.2), the shipping container shall be a grade V3c, V3s, or V4s fiberboard shipping container fabricated in accordance with MIL-B-17757, and closed in accordance with the appendix of the box specification.

5.2.3 Level C (Commercial Packing). Gloves, packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. The quantity per shipping container shall be the same as that normally used by the supplier for retail distribution. Containers shall comply with the U.S. Postal Service Manual, Uniform Freight Classification Rules, or National Motor Freight Classification Rules, as applicable.

5.3 Marking. In addition to any special marking required by the contract or order, shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The gloves covered by this specification are intended to be worn by male and female personnel of the Military Services as work gloves.

6.2 Ordering data. Procurement documents should specify the following:

a. Title, number, and date of this specification.
b. Class required (see 1.2).
c. Whether first article sample is required (see 3.2).
d. Selection of applicable levels of packaging and packing (see 5.1 and 5.2).
e. When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).

6.3 Samples. For access to samples, address the procuring office issuing the invitation for bids.

6.4 Marginal notations. The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:
Navy - SA
Army - GL
Air Force - 82

Review activity:
Army - MD

User activities:
Navy - OS, YD

Preparing activity:
Navy - SA

Project No. 8415-0903

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:35Z
Check the source to verify that this is the current version before use.

FIGURE 1 GLOVES, CLOTH, COTTON, WORK, MEN'S AND WOMEN'S

MIL-G-1508B

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:35Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:35Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

MIL-G-1008G; Gloves, Cloth, Cotton, Work, Men's and Women's

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

FORM 1426
1 JAN 72

REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

S/N 0102-014-1802

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:35Z
Check the source to verify that this is the current version before use.

FOLD

Officer in Charge
Navy Clothing and Textile Research Unit
21 Strathmore Road
Natick, MA 01760

POSTAGE AND FEES PAID

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Officer in Charge
Navy Clothing and Textile Research Unit
21 Strathmore Road
Natick, MA 01760

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T12:35Z
Check the source to verify that this is the current version before use.