MIL-C-51098E(EA)
AMENDMENT 5
24 August 1987
SUPERSEDING
AMENDMENT 4
14 May 1987

MILITARY SPECIFICATION

CYLINDER, NITROGEN-FILLED, PUNCTURABLE SEAL

This amendment forms a part of MIL-C-51098E(EA), dated 12 February 1981, and is approved for use within the Chemical Research, Development and Engineering Center, Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

2.1, After the list of drawings add the following:

"SPECIAL PACKAGING INSTRUCTIONS (SPI)

P5-51-376 - Cylinder, Nitrogen Filled, Puncturable Seal."

PAGE 4

4.4.1, Delete in its entirety and substitute the following:

"4.4.1 Lotting. Each lot shall be identified and controlled in accordance with MIL-STD-1168. A lot of cylinders shall consist of the filled cylinders produced by a manufacturer at one plant and under essentially the same manufacturing conditions. No more than one interfix of the following components shall be contained in any one lot of cylinders produced:

a. Body
b. Cap"

AMSC N/A

FSC 4230

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:50Z
Check the source to verify that this is the current version before use.

PAGE 5

4.4.3.3(a), Under Major defects of AQL 1.0 percent add:

"111 Spherical radius incorrect
112 Protective finish missing or incorrect"

Under Minor defects delete:

"201 Protective finish missing or incorrect"

PAGE 6

4.4.4.2, Sentence 1: Delete in its entirety and substitute the following:

"Submerge the filled cylinder in boiling water or air heated to 100° ± 5°C for at least 15 minutes."

4.4.4.3, Delete in its entirety and substitute the following:

"4.4.4.3 Rupture. The filled cylinder shall be tested in a heating device that provides an environment that is homogeneous within 25°F during the test period. The temperature of the environment shall be raised from a temperature not to exceed 150°F at a rate not to exceed 300°F per minute until cylinder rupture occurs. Examine the cylinder for conformance to 3.3.2 (see 6.3)."

PAGE 7

Section 5, Delete in its entirety and substitute the following:

"5. PACKAGING

5.1 Packaging requirements shall be as specified on SPI P5-51-376."

PAGE 9

6.3, Sentence 1: Delete "hot air oven" and substitute "heating device".

Custodian:

Army - EA

Preparing activity:

Army - EA

Project No. 4230-A077

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:50Z
Check the source to verify that this is the current version before use.