MILITARY SPECIFICATION

COMPUTER, BALLISTICS, MORTAR

This specification is approved for use by the US Army Armament, Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification establishes the requirements for manufacture and acceptance of the Computer, Ballistics, Mortar: 11785700. Throughout this specification this assembly is referenced as MBC.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specification and standards. Unless otherwise specified, the following specifications and standards of the issue listed in that issue of the Department of Defense index of Specifications and Standards (DoDISS) specified in the solicitation form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-F-13926	-	Fire Control Materiel; General Specification Governing the Manufacture and Inspection
MXL-I-45607	-	Inspection Equipment, Acquisition, Maintenance and Disposition of

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-109	-	Quality Assurance Terms and Definitions

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Center, Attn: AMSMC-QA, Dover, New Jersey 07801-5001 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-02-23T03:34Z
Check the source to verify that this is the current version before use.

MIL-STD-454	Electronic Equipment, General Requirements for
MIL-STD-1521	Technical Reviews and Audits for Systems, Equipments, and Computer Programs
MIL-STD-45662	Calibration System Requirements

(Copies of specifications and standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.1.2 Other Goverment documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal.

DRAWINGS

9379231	Program, Computer-MBC
9379241	Computer, Program Product Specification for Computer Set, Ballistics: Mortar M23
11785700	Computer, Ballistics, Mortar
11785850	Computer Set, Ballistics, Mortar: M23

PACKAGING DATA SHEETS

11785700-1	-	Packaging of Computer, Ballistics, Mortar

(Copies of drawings and packaging data sheets required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 Item definition. The Mortar Ballistics Computer (MBC) is a portable computing device which will allow an operator to quickly perform functions of the mortar fire direction center. The MBC shall consist of communication, keyboard, and display interfaces to enable the operator to do the following:

a. Receive and transmit digital data messages.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:34Z
Check the source to verify that this is the current version before use.

b. Communicate with DMD (AN/PSG-2B) and FIST (AN/PSG-5).

c. Enter fire direction center data.

d. Select mortar, location, weapon type, and ammunition.

e. Compute firing data.

3.2 Performance.

3.2.1 General. The performance of the MBC shall be in accordance with the following requirements.

3.2.1.1 External input power. The MBC shall be capable of accepting power from a 20 to 32 volt vehicular power supply. With input power applied to J2-A (Positive) and J2-B (Return) , the MBC power consumption shall be 2.5 watts maximum.

3.2.1.2 Internal input power. The MBC shall be capable of accepting power and operating from the batteries specified on 11785700, with the batteries suppling the input power (J2-A positive and J2-B negative).

3.2.1.3 Local push to talk. This signal line, XMTKY (J1-F), shall have a DC resistance less than 10 ohms with respect to XMTKYR (J1-H) during message transmissions from the AUDIO TO AM RADIO or AUDIO TO FM RADIO outputs. This signal line shall be 100 kilohms minimum resistance with respect to XMTKYR at other times.

3.2.1.4 FM Radio output. During transmissions, the output levels shall be 5 plus or minus 2 millivolts rms between AUDIO TO FM RADIO (J1-E) and RADIO COMMON (J1-D) when terminated a 150 ohm resistive load.

3.2.1.5 AM Radio output. During message transmissions, the output shall be 19.5 plus or minus 4 millivolts rms between AUDIO TO AM RADIO (J1-J) and RADIO COMMON (J1-D) when terminated in a 50 ohm resistive load.

3.2.1.6 Wireline output. The WIRELINE 1 signal line is the electrical complement of the WIRELINE 2 signal line. During message transmission on wireline, the signal voltage between WIRELINE 1 and WIRELINE 2 shall be 775 millivolts plus or minus 2dB when terminated in a 600 ohm resistive load. The wireline terminals shall receive audio signals at levels between 7.75 and 775 millivolts rms.

3.2.1.7 Radio input. The MBC shall receive audio signals between 8 millivolts and 2 volt rms with the signal applied between either AUDIO FROM AM RADIO (J1-A) and RADIO COMMOM (J1-D) or AUDIO FROM FM RADIO (J1-C) and RADIO COMMON (J1-D).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:34Z
Check the source to verify that this is the current version before use.

3.2.1.8 Computer pragram. The MBc firmware shall contain and execute the computer program in accordance with 9379231 and 9379241.

3.2.1.9 FSK Frequencies. The MBC shall transmit and receive messages using 1200 plus or minus 10 Hz to represent a "mark" and 2400 plus or minus 10 Hz to represent a "space".

3.2.1.10 Data rate. The MBC shall transmit and receive messages at 600 plus or minus 0.6 and 1200 plus or minus 1.2 bits per second with FSK frequencies of 1200 and 2400 Hz.

3.2.1.11 Built-in-Test (BIT). The MBC shall provide operator-selected self test capability.

3.2.2 Physical characteristics. The physical characteristics shall be as prescribed by the drawings, specifications, and QAP's.

3.2.3 Reliability. When specified in the contract, a special sample shall be subjected to reliability testing. The manufacturing and production techniques emloyed in the fabrication of the MBC shall not degrade the inherent reliability. The inherent reliability shall not be less than 16,585 hours Mean Tim Between Failures (MTBF).(See 4 and 6)

3.3 Environmental. The MBC shall meet the requirements specified herein unless otherwise specified.

3.3.1 Room ambient temperature. The requirements of this specification shall be met with the MBC stabilized at room ambient temperature of +16°C to +32°C (+60°F to +90°F), unless otherwise specified in the requirements paragraph.

3.3.2 Environmental stress screen (ESS) temperature. The MBC shall meet the requirements of 3.2.1.1 and 3.2.1.11 inclusive, after having been exposed to a minimum of eight temperature cycles at temperatures of -57°C and +71°C (-71°F and +160°F).

3.3.3 Operating temperature. The MBC shall meet the requirements of 3.2.1.1 and 3.2.1.11 inclusive, while exposed to a minimum of eight temperature cycles at temperatures of -40°C and +71°C (-40°F and +160°F).

3.3.4 Environmental stress screen (ESS) vibration. The MBC shall meet the requirements of 3.2.1.1 and 3.2.1.11 inclusive after having been subjected to a random or pseudorandom vibration which includes frequency content from 100 Hz to 1000 HZ and up to a 3g RMS in two axis for a period of 10 minutes plus or minus 15 seconds.

3.3.5 Immersion. The MBC shall show no signs of leakage when immersed under 36 inches plus or minus 5 inches for a period of not less than 15 minutes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:34Z
Check the source to verify that this is the current version before use.

3.4 Fabrication. The MBC shall be manufactured in accordance with drawing 11785700.

3.5 First article. When specified in the contract, a sample shall be subjected to first article inspection (See 4 and 6).

3.6 Workmanship. The workmanship requirements of MIL-F-13926 and MIL-STD-454 shall be met. All components shall be fitted properly and firmly in their respective positions. All electrical connections shall be mechanically secure and electrically sound. There shall be no evidence of corrosion, burrs, roughness, sharp edges or other defects which could adversely affect its use or suitability for the purpose intended.

3.7 Materials. Materials shall be in accordance with drawings, material specifications and general specifications forming a part of this specification.

4. QUALITY ASSURANCE PREVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 General provisions. The component and subassembly inspection requirements of MIL-F-13926 and MIL-STD-454 form a part of the Quality Assurance Provisions of this specification. Definitions of inspection terms shall be as listed in MIL-STD-109.

4.2 First article initial product) approval. The requirement for first article approval and the responsibility (Government or contractor) for irst article testing shall be as specified in the contract. The sample for first article approval test shall consist of three (3) MBC’S plus three (3) each of all items covered by QAP. The three MBC'S shall be tested as specified herein for all the requirements of this specification. The items covered by QAP shall be tested, as specified thereon, for all characteristics delineated on the QAP. The samples shall be manufactured in the same manner, using the same materials, equipment, processes, and procedures as will be used in the production of the balance of the contract quantity. All parts and materials, including packaging and packing, shall be obtained from the same source of supply as will be used in the production of the balance of the contract quantity.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:34Z
Check the source to verify that this is the current version before use.

4.2.1 Government testing. When the Government is responsible for conducting first article approval tests, the contractor prior to submitting-the sample to the-Government, shall inspect the sample to insure that it conforms to all requirements of the contract and submit a record of this inspection with the sample, including certificates of conformance for all materials.

4.2.2 Contractor testing. When the contractor is responsible for conducting first article approval tests, the sample shall be inspected by the contractor for all the requirements of the contract. The sample and a record of this inspection, including certificates of conformance for all materials, shall be submitted to the Government for approval. The Government reserves the right to witness any or all of the contractor's inspections.

4.3 Inspection provisions.

4.3.1 Submission of product. Unless otherwise specified by the contracting officer, inspection lot size, lot formation, and presentation of lots shall be in accordance with "Submission of Product" provision of MIL-STD-105.

4.3.2 Examination and tests.

4.3.2.1 Components and Subassemblies. All components and subassemblies shall be inspectedin accordance with the inspection provisions contained in Quality Assurance Provisions (QAP's) listed in the Technical Data Package (TDP). In the absence of QAP's, the applicable Quality Assurance Provisions of MIL-F-13926 shall apply.

4.4 Sampling.

4.4.1 Environmental/performance. The MBC shall be inspected to the requirements in Table II.

TABLE II. Classification of defects.

No.	Characteristics 100% Inspection	Requirement	Test Procedure
1.	External input power	3.2.1.1	4.6.3.1
2.	Internal input power	3.2.1.2	4.6.3.2
3.	Local push to talk	3.2.1.3	4.6.3.3
4.	FM Radio output	3.2.1.4	4.6.3.4
5.	AM Radio output	3.2.1.5	4.6.3.5
6.	Wireline output	3.2.1.6	4.6.3.6
7.	Radio input	3.2.1.7	4.6.3.7
8.	Computer program	3.2.1.8	4.6.3.8
9.	FSX Frequencies	3.2.1.9	4.6.3.9

Source: https://assist.dla.mil -- Downloaded: 202610-23T03:34Z
Check the source to verify that this is the current version before use.

10.	Data rate	3.2.1.10	4.6.3.10
11.	Built-in-Test (BIT)	3.2.1.11	4.6.3.11
12.	ESS and operating temperatures	3.3.2 & 3.3.3	4.6.1
13.	ESS vibration	3.3.4	4.6.2

MAJOR: AQL 1.0% Defective

101.	Workmanship	3.6	4.6.5

4.4.2 Special sampling.

4.4.2.1 Environmental special sample. Three MBC shall be selected at random, as a special sample, from each lot or each 50 produced which ever occurs first.The sample shall meet the requirements and tests in Table III.

TABLE III. Classification of defects.

No.	Characteristics	Requirement	Test Procedure
201.	Immersion	3.3.5	4.6.4

4.4.2.2 Other special sample. One MBC shall be selected at random, as a special sample, from each lot each 100 produced which ever occurs first. The sample shall meet the requirements and tests in Table IV.

TABLE IV. Classification of defects.

No.	Characteristics	Requirement	Test Procedure
301.	Fabrication	3.4	Applicable Drawing\ Visual
302.	Materials	3.7	Applicable Drawing\ Visual

NOTE: The tests in Table IV shall be conducted at room ambient temperature (as specified in 3.3.1).

4.4.3 Failure of sample. Should any one item of a special sampling fail to meet the specified test requirements, acceptance of the represented inspection lot will be suspended by the Government until necessary corrections have been made by the contractor and resubmitted items have been approved in accordance with “Acceptance and Rejection” as specified in MIL-STD-105.

4.5 Inspection equipment. Except as otherwise provided for by the contract, the contractor shall supply and maintain inspection equipment in accordance with the applicable requirements of MIL-I-45607.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:34Z
Check the source to verify that this is the current version before use.

4.5.1 Government furnished inspection equipment. Where the contract provides for Government furnished test equipment, supply and maintenance of test equipment shall be in accordance with the applicable requirements specified in MIL-I-45607.

4.5.2 Contractor furnished inspection equipment.

4.5.2.1 Government design. All inspection equipment specified by drawing number in specification or QAP forming a part of the contract shall be supplied by the contractor in accordance with technical data included in the Technical Data Package List (TDPL).

4.5.2.2 Contractor design. In the absence of Government inspection equipment design, the contractor shall design and supply inspection equipment compatible with the “Test Methods and Procedures" specified in 4.6 of this specification and with the component inspection procedures specified in “Examination” and "Test Facilities" requirements of MIL-F-13926. Since tolerance of test equipment is normally considered to be within 10% of the product tolerance for which it is intended, this inherent error in the test equipment design must be considered as part of the prescribed product tolerance limit. Thus. concept, construction, materials, demensions, and tolerance used in the design of test equipment shall be so selected and controlled as to insure that the test equipment will reliably indicate acceptability of a product which does not exceed 90% of the prescribed tolerance limit, and permit positive rejection when non-conforming. Construction shall be such as to facilitate routine calibration of test equipment.

4.5.2.3 Inspection equipment design requirements.

4.5.2.3.1 Temperature testing. The volume of the test chamber shall conform to the test facilities requirements of MIL-F-13926. The air temperature at the control sensor shall be in accordance with the specified requirements within plus or minus 2.5° (1.4°C). The temperature gradient across the cross-sectional area occupied by the test item shall not exceed 0.5° per foot in any direction. The heat source of the test chamber shall be so located that radient heat, if used, will not fall directly on the test item. Thermocouples or equivalent temperature sensors utilized to determine or control the specified chamber temperature shall be centrally located within the test chamber within the supply airstream, or in the return airstream, whichever provides the specified test condition at the item under test and shall be baffled or otherwise protected against radiation effects.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:34Z
Check the source to verify that this is the current version before use.

4.5.2.3.2 Fabrication, setup and calibration. Design and fabrication of test equipment Shall be Such that it incorporates the features of rigidity, stability, and ease of maintenance. Setup and calibration equipment necessary for Certification Of the testing equipment accuracy shall be furnished and will become a part of the testing equipment. Operating and calibration instruction shall be prepared and submitted to the procuring activity.

4.6 Test methods and procedures. Unless otherwise specified in the contract, the following procedures shall be utilized to conduct specified tests. If the contractor chooses to use alternate test procedures,a detailed description of the set-up and procedure shall be submitted to the government procuring agency for approval prior to use.

4.6.1 ESS and operating temperatures. Testing equipment utilized in this test shall conform to the requirements of 4.5.2.3.1. The MBC shall be placed in the test chamber and the temperature of the chamber shall be reduced 5°C (9°F) Per minute plus or minus 1°C (1.8°F) to -57°C (-71°F) , from room ambient temperature (as specified in 3.3.1). The MBC shall be maintained at this temperature for a minimun of 20 minutes. Upon completion of the 20 minute exposure, the temperature of the chamber shall be raised 5°C (9°F) per minute plus or minus 1°C (1.8°F) to -40°C (-40°F). The MBC shall be maintained at this temperature for a minimum of 2 hours. Upon completion of the 2 hour exposure, the MBC shall be powered up by either an external (as specified in 3.2.1.1) or internal power source (as specified in 3.2.1.2). With the MBC powered up, the temperature of the chamber shall be raised 5° (9°F) per minute plus or minus l°C (1.8°F) to +71°C (+160°F). The MBC shall be maintained at this temperature for a minimum of 2 hours. Upon completion of the 2 hour exposure and while at +71°C (+160°F, the MBC shall be subjected to all the tests in 4.6.3. It shall meet the requirements of 3.2.1.1 and 3.2.1.11 inclusive. After meeting the requirements the MBC shall be turned off and the temperature of the chamber shall be reduced 5°C (9°F) per minute plus or minus 1°C (1.8°F) to room ambient temperature (as specified in 3.3.1). The above procedure shall be conducted a minimum of eight times. Upon completion of the cycles the MBC shall be removed from the chamber and subjected to all the tests in 4.6.3. It shall meet the requirements of 3.2.1.1 and 3.2.1.11 inclusive.

4.6.2 ESS vibration. Conduct the vibration test with the MBC positioned on an appropriate adapter affixed to a vibrating machine that is capable of providing the amplitudes and frequencies specified in 3.3.4. Unless otherwise specified, the test equipment shall be in accordance with the “Test Facilities” requirements of MIL-F-13926. The applied motion shall be in two

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:34Z
Check the source to verify that this is the current version before use.

separate planes for the time period specified. Upon completion of the vibration sweep the MBC shall be removed from the vibration adapter and shall be subjected to all the tests in 4.6.3. It shall meet the requirements of 3.2.1.1 and 3.2.1.11 inclusive.

4.6.3 Functional. Tests contained in 4.6.3.1 and 4.6.3.11 inclusive are to be conducted utilizing appropriate calibrated meters, fixtures, adapters, and cables connected to the contacts specified in the tests respective requirement paragraph in 3.2.1.1 and 3.2.1.11 inclusive.

4.6.3.1 External input power. Attach the MBC to a vehicular power supply (20 to 30 VDC). Apply input power up the MBC, and measure the MBC'S power consumption. The MBC shall meet the requirements of 3.2.1.1.

4.6.3.2 Internal input power. Select one of the batteries specified on 11785700 for this test. Insert the batter, power up the MBC, and subject the MBC to the test contained in 4.6.3.11 with the exception that the 28 volt DC power is the selected battery. The MBC shall meet the requirements of 3.2.1.2.

4.6.3.3 Local push to talk. Attach the MBC to an ohm meter and measure the resistance during message transmissions from the AUDIO TO AM RADIO and AUDIO TO FM RADIO outputs. Stop message transmissions and measure the resistance. The MBC shall meet the requirements of 3.2.1.3.

4.6.3.4 FM Radio output. Attach the MBC to a voltmeter. Terminate the FM RADIO output in a 50 ohm resistive load. Measure the voltage between AUDIO TO FM RADIO and RADIO COMMON during transmissions. The MBC shall meet the requirements of 3.2.1.4.

4.6.3.5 AM Radio output. Attach the MBC to a voltmeter. Terminate the AM radio output in a 50 ohm resistive load. Measure the voltage between AUDIO t0 AM RADIO and RADIO COMMON during transmissions. The MBC shall meet the requirements of 3.2.1.5.

4.6.3.6 Wireline output. Attach the MBC to a voltmeter. Terminate WIRELINE signal lines in a 600 ohm resistive load. Measure the voltage between WIRELINE 1 and WIRELINE 2 during transmision. The MBC shall meet the requirements of 3.2.1.6. Input signals to the MBC as specified in 3.2.1.6 and Verify the MBC had received the input signals.

4.6.3.7 Radio input. Attach the MBC to a signal source between AUDIO FROM AM RADIO and RADIO COMMON. Also attach a signal source between AUDIO FROM FM RAD1O and RADIO COMMON. Input signals to the MBC as specified in 3.2.1.7. Verify the MBC had received the input signals.

Source: https://assist.dla.mil -- Downloaded: 2026l0-23T03:34Z
Check the source to verify that this is the currentversion before use.

4.6.3.8 Computer program. elect submit to the procuring activity, one complete fire missions for each mortar family (i.e., 60mm, 8hm/ etc.). Each fire mission shall include as a minimum, but is not limited to, forward observer locations, metrology data, fire zones, no-fire zones, and ammunition data. Enter all the fire missions into the MBC and run the missions. Verify that the computed fire data is correct.

4.6.3.9 FSK Frequencies. Attach the MBC to a signal source. Verify the MBC can receive the frequencies specified in 3.2.1.9. Measure the frequencies being output by the MBC when “marks” and "spaces" are being transmitted. The transmitted frequencies shall be as specified in 3.2.1.9.

4.6.3.10 Data rate. Attach the MBC toa signal source. Measure the rate at which the MBC receives and transmits messages. The MBC shall meet the requirements of 3.2.1.10.

4.6.3.11 Built-in-Test (BIT). Connect unit under test to plus 28 volt dc power. Pressing the ON\OFF then the TEST keys shall cause the MBC to display the current version of the software. Verify the software revision is in accordance with ordering data (See 6).After pressing the SEQ key, the MBC shall display 4 selectable tests that may be implemented by pressing the display select switch located directly below the desired test. Select the MCR test. The MCR test shall test the RAM EPROM on the memory and the display\processor circuit card assemblies. The MBC shall display TESTING MICR' during the test. Verify 'MICR:PASS' appears after MCR test. Depress the REVIEW key. The test menu will reappear. Select the SW test The SW test shall prompt the user to press the key displayed by the MBC. After all the keys have been tested, the MBC shall display ‘END OF TEST’ and then "READY". By pressing the SEQ key, the MBC shall sequence thru and display characters in each position of the display. The last display shall also blink the MSG and SEQ LED’s. Examine the display characters for defects. Depress the REVIEW key. Select the MOD test. The MOD test shall test both the modem and audio interface circuit card assemblies. The MBC shall display 'TESTING MODEM' during the test Verify "MODEM:PASS' appears after the test.

4.6.4 Immersion. Conduct the immersion test with the MBC positioned in an appropriate adapter affixed to the immersion tank. The temperature of the water shall be 18°c plus or minus 5°C (64°F plus or minus 9°F). Immediately prior to immersing the MBC, open and close the covers three times each. Immerse the MBC to a depth as specified in 3.3.5. The MBC shall remain immersed for a period as specified in 3.3.5. Upon completion of the immersion period, remove the MBC from the water and wipe the exterior surfaces of the MBC dry. Subject the MBC to all the tests in 4.6.3. It shall meet the requirements of 3.2.1.1 and 3.2.1.11 inclusive. Open the MBC and examine the interior and contents for evidence of leakage. It shall meet the requirements of 3.3.5.

Source: https://assist.dla.mil -- Downloaded: 202610-23T03:34Z
Check the source to verify that this is the current version before use.

4.6.5 Workmanship. The MBC shall be subjected to a visual and tactile examination for evidence of faulty workmanship. The assembly shall conform to the requirements of 3.6.

4.7 Reliability testing. The requirement for reliability test approval and the responsibility (Government or contractor) for reliability testing shall be as specified in the contract. The sample for reliability test shall consist of 3 MBC'S. The samples shall be manufactured in the same manner, using the same materials, equipment, processes, and procedures as will be used in the production of the balance of the contract quantity. All parts and materials, including packaging and packing, shall be obtained from the same source of supply as will be used in the production of the balance of the contract quantity.

4.7.1 Government testing. When the Government is responsible for conducting reliability tests, the contractor prior to submitting the sample to the Government, shall inspect the sample to assure that it conforms to all requirements of the contract and submit a record of this inspection with the sample, including certificates of conformance for all materials.

4.7.2 Contractor testing. When the contractor is responsible for conducting reliability tests, the sample shall be inspected and tested by the contractor for all the requirements of the contract. The sample and a record of these inspections and tests, including certificates of conformance for all materials, shall be submitted to the Government for approval. The Government reserves the right to witness any or all of the contractors reliability tests and inspections.

5. PREPARATION FOR DELIVERY

5.1 Delivery requirements. Handling, packaging, packing, shipping, and marking of the Mortar Ballistic Computer: 11785700 shall be in accordance with Packaging Data Sheet 11785700. The level of protection shall be as specified in the procurement document.

6. NOTES

6.1 Intended use. The MBC described herein, along with the following parts, forms the Mortar Ballistic Computer Set: 11785850:

9355747	Case, Field
80063-SM-C-456359 -	Bag Assy CW-598/GRA-39
80063-SM-D-875498 -	Cable Assy - Primary Radio Interface
80063-SM-D-955457 -	Cable Assy - AN\GRC-106 Interface
80063-SM-D-917637 -	Cable Assy - Vehicular Receptacle
80063-SM-C-875489 -	Cable Assy - Vehicular Battery

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:34Z
Check the source to verify that this is the current version before use.

6.2 Ordering data. Procurement documents shall specify the following:

a. Title, number and date of this specification.

b. Provisions for first article testing.

c. provisions for reliability testing.

d. Applicable Packaging Data Sheet.

Applicable levels of preservation, packing, and marking (see 5.1).

f. Applicable stock numbers.

g. Applicable software revision.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1220-A297]

Source: https://assist.dla.mil -- Downloaded: 2023-10-23T03:34Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Armament Munitions &
Chemical Command
ATTN: AMSMC-QA
Dover, NJ 07801-5001

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:34Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-C-70489 (AR)	

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:34Z
Check the source to verify that this is the current version before use.