MILITARY SPECIFICATION

CONTAINER, SKIPPING AND STORAGE

MK 309 MOD 0

This specification has been approved by the Bureau of Naval Weapons, Department of the Navy

1. SCOPE

1.1 Scope - This specification establishes the requirements for the procurement of one type of reusable shipping and storage container for the AQM-37A Target Wings, Fins, Canards, and Pitot Tube.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of the specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

QQ-S-781	Steel Strapping, Flat

STANDARDS

MIL-STD-105	Sampling Procedure and Tables for Inspection by Attributes
MIL-STD-129	Marking for Shipment and Storage

DRAWINGS AND LISTS (LD's)

BUREAU OF NAVAL WEAPONS

LD 477259	Container, Shipping and Storage Mk 309 Mod 0

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:09Z
Check the source to verify that this is the current version before use.

PUBLICATIONS

BUREAU OF NAVAL WEAPONS

CLASSIFICATION OF DEFECTS (NAVWEPS CD's}

CD 1448386 Container, Shipping and Storage, MK 309 Mod 0 (for AQM-37A Target Wings, Fins, Canards, and Pitot Tube)

(And all NAVWEPS CD's listed thereon)

(Copies of specifications, standards, and drawings required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REUIREMENTS

3.1 General requirements

3.1.1 Construction - The Mk 309 Mod 0 Container shall be manufactured in strict accordance with Bureau of Naval Weapons List of Drawings (LD) 477259 and all documents referenced thereon.

3.1.2 Precedence - In the event of any conflict between applicable documents, the following order of precedence shall be observed:

(a) Contract or Purchase Order.
(b) This specification.
(c) Applicable drawings of LD 477259.
(d) Referenced documents of LD 477259.
(e) Other applicable documents as referenced in paragraph 2.1 of this specification.

3.1.3 Preproduction samples - Unless otherwise specified in the contract or order (see 6.2), the preproduction samples of the Container shall be manufactured using the methods and procedures proposed for production. The samples will be tested as specified in Section 4 herein for the purpose of determining that, prior to starting production, the contractor's production methods are capable of yielding items that comply with the technical requirements of the documents noted in 3.1.2.

3.2 Performance requirements and product characteristics Containers covered by this specification shall be capable of meeting the following performance requirements and product characteristics:

Source: https://assist.dla.mil -- Downloaded: 202610-23T05:09Z
Check the source to verify that this is the current version before use.

3.2.1 Rough handling requirements

3.2.1.1 Rotational drop - There shall be no evidence of structural failure, visible damage, or permanent deformation when each corner of the loaded Container is allowed to fall freely onto a rigid steel or concrete surface from a height of 24 inches as described in 4.4.1.

3.3 Government-loaned property - The Government will furnish the contractor on a loan basis, dynamically-simulated Wings, Fins, Canards, and Pitot Tube. This equipment will be utilized in testing Containers supplied under this specification (see 6.2).

3.4 No data is required by this specification, or by documents referenced in Section 2.1, unless specified in the contract or order (see 6.2).

3.5 Workmanship - Workmanship in the fabrication and assembly of Containers shall be of sufficiently high quality to assure that completed equipment will comply with all requirements of this specification. Particular attention shall be paid to plating, painting, welding, bonding, marking and freedom of parts from burrs and sharp edges. The assembled Containers shall be thoroughly clean of all dirt, chips, and other foreign matter. The standards of workmanship exhibited in any approved preproduction sample, subject to any qualification stated in the Government's notice of approval, shall be determinative of the requirements of the contract relative to workmanship insofar as not specifically covered by applicable specifications.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection - Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, this supplier may utilize his own facilities or any commercial labratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and service conform to prescribed requirements.

4.2 Classification of inspections - Inspection of the Container shall be classified as follows:

(a) Preproduction inspection (see 4.4).
(b) Quality conformance Inspection (see 4.5).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:09Z
Check the source to verify that this is the current version before use.

4.3 Sampling

4.3.1 Preproduction sample - A preproduction sample of one (1) Container, manufactured in accordance with 3.1.1 and 3.1.3, shall be subjected to the preproduction tests-detailed in 4.4. Acceptance of the preproduction sample shall be based on no defects in the sample. Further production of the Container by the supplier, prior to the approval of the preproduction sample shall be at the supplier's risk.

4.3.2 Quality conformance inspection sampling - The sampling plans and procedures set forth in Standard MIL-STD-105 shall be used in the determination of acceptability of the Containers inspected as specified in 4.5.

4.3.3 Inspection lot - The number of units in an inspection lot shall be, where practicable, 30 Containers. In no event will an inspection lot exceed 30 units.

4.4 Preproduction inspection - The preproduction sample, after satisfactorily passing the examinations of 4.5.2, shall be subjected to the Rotational Drop Test of 4.4.1. Certified inspection data covering the results of preproduction inspections shall be forwarded to the Bureau of Naval Weapons, if required (see 6.2).

4.4.1 Rotational drop test - Each preproduction sample shall be subjected to the following test: The loaded Container shall be supported at one corner of its base on a block six inches in height. A 12 inch high block shall be placed under the other corner of the same end of the Container. The lowest point of the opposite end of the Container shall then be raised to a height of 24 inches and allowed to fall freely onto a steel or concrete surface of sufficient mass to absorb the shock without deflection. This test shall be applied to all four corners of the Container. Any evidence of structural failure, visible damage, or permanent deformation to the Container shall be cause for rejection of the preproduction sample. Minor dents, scratches, or paint flaking are not cause for rejection.

4.5 Quality conformance inspection

4.5.1 Samples shall be selected using the plans and procedures set forth in Standard MIL-STD-105, Inspection Level II. Each Container in the sample shall be examined as required by 4.5.2. An AQL of 2.5 percent for MAJOR Defects and 6.5 percent for MINOR Defects shall be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:09Z
Check the source to verify that this is the current version before use.

4.5.2 Examination - The minimum of examinations to be performed by the supplier for acceptance shall be those set forth in CD 1448386, Container, Shipping and Storage Mk 309 Mod 0.

5. PREPARATION FOR DELIVERY

5.1 Preservation - Preservation shall be as follows:

5.1.1 Level A - Not applicable.

5.1.2 Level C - Cleaning, drying and preservation shall be in accordance with the manufacturer's commercial practice.

5.2 Packing

5.2.1 Level C - All interior pieces and cover latches shall be tightly secured. Two (2) Containers shall be strapped to a pallet for shipment, using steel strrapping QQ-S-781, Type I, Class B.

5.3 Marking - In addition to any special marking required by the contract or order, Containers shall be marked in accordance with drawing 1878306 of LD 477259 and Standard MIL-STD-129.

6. NOTES

6.1 Intended use - A Container supplied under this specification is intended for use in the shipment, storage, and stowage of one (1) set of Wings, Fins, Canards and Pitot Tube for the AQM-37A Target.

6.2 Ordering data - Procurement documents shall specify:

(a) Title, number, and date of this specification.

(b) Preproduction sample size, if different (see 4.3.1).

(c) Activity designated to perform preproduction testing (see 4.1).

(d) Name and address of activity which will furnish Government-loaned property (see 3.3).

(e) Preproduction inspection data, if required (see 3.4 and 4.4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:09Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specstion in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obing information on the use of this specification which will insure that suitable products can be procured with a mum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on s on reverse side, staple in corner, and send to preparing activity *(as indicated on reverse hereof)*.

IFICATION

L-C-91239(MP) Container, Shipping and Storage MK 309 MOD 0

NIZATION *(Of submitter)*	CITY AND STATE

RACT NO.	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT
		$

RIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

AS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES.

MENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

S THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

EMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

ITTED BY *(Printed or typed name and activity)*	DATE

1426

APR 63

C-9279

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:09Z
Check the source to verify that this is the current version before use.