INCH-POUND

MIL-D-51256B
INT. AMENDMENT 2 (EA)
27 February 1989
SUPERSEDING
INT AMENDMENT 1
22 May 1987

MILITARY SPECIFICATION

DETECTOR KIT, CHEMICAL AGENT, ABC-M18A2

This interim amendment is approved for use within U.S. Army Chemical Research, Development and Engineering Center, Department of the Army, with MIL-D-51256, dated 8 November 1984.

PAGE 1

2 1.1: Delete "SPECIFICATIONS" and all documents listed thereunder in their entirety.

PAGE 2

2.1.1.

Under "STANDARD". Add the following·

"FEDERAL

FED TEST METHOD STD. NO. 101 - Test Procedures for Packaging Materials."

Under "STANDARDS", "MILITARY": Delete "MIL-STD-129 - Marking for Shipment and Storage" and "MIL-STD-147 - Palletized Unit Loads"

AMSC N/A FSC 6665

DISTRIBUTION STATEMENT A Approved for public release, distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:55Z
Check the source to verify that this is the current version before use.

Under "DRAWINGS". Add the following:

"SPECIAL PACKAGING INSTRUCTIONS (SPI)

P5-77-2092 - Detector Kit, Chemical Agent, ABC-M18A2".

2.2, line 10. Delete "D 3951 - Commercial Packaging".

PAGE 3

3.3.1.1, line 2: Delete "4 4.4.3.1" and substitute "4.3.3.1".

3.3.1.2, line 2: Delete "4.4 4 3.2" and substitute "4.3.3.2".

PAGE 4

4.3.1: Add the following sentence to the end of the paragraph: "Sampling for the packaging inspection shall be conducted in accordance with MIL-STD-105 "

4.3.2.1 Delete in its entirety and substitute the following:

"**4.3.2.1 For examination and non-destructive tests.** Each kit and its packaging shall be examined for the defects listed in 4.4.3.3(a) and 4.4.3.3(b) (the AQL's do not apply). If any sample kit or its packaging has a defect, the preproduction sample shall be rejected. Each packaged kit shall be tested for leakage in accordance with 4 4.4 3, the acceptance number is zero."

4.3 2.2: Delete in its entirety and substitute the following:

"**4.3.2.2 For destructive tests.** The first test conducted shall be 4.3.3.1, using three kits from the preproduction sample. The remaining five kits shall be tested in accordance with 4.4 4 4, 4 3.3.2, 4.4 4.1, and 4.4.4.2, in that order "

4.3.3.2, line 1: Delete "Sample kits packed in" and substitute "Sample kits assembled in".

4.4.2.1, line 1: Delete "**For examination.**" and substitute "**For examination and non-destructive tests.**"

4.4.2.2, line 1: Delete "**For test.**" and substitute "**For destructive tests.**", and add the following sentence to the end of the paragraph: "Sampling for 4 4.4 4 shall be conducted in accordance with MIL-STD-105 using level S-3."

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:55Z
Check the source to verify that this is the current version before use.

4.4.3.1, line 1· Delete "**For examination.**" and substitute "**For examination and non-destructive tests.**", and add the following to the end of the paragraph: "After the preproduction sample is packaged for shipment and storage, each item in the preproduction sample shall be tested in accordance with 4.4.4.3, the acceptance number is zero "

4.4.3.2, line 1: Delete "**For test.**" and substitute "**For destructive tests**"and add the following sentence to the end of the paragraph· "Heat seal seam strength of packaged detector kits shall be tested in accordance with 4 4 4 4 "

PAGE 6

4.4.3.3(b) Delete Major defects 102 through 107 and substitute the following·

"102 Unit pack barrier and closure not as specified
103 Supplemental container and closure not as specified
104 Fiberboard pads missing or not as specified (when specified)
105 Cushioning missing or not as specified
106 Packing container and closure not as specified
107 Supplemental container and closure missing or not as specified
108 Marking missing, incorrect or illegible"

4.4 4: Add the following paragraphs in sequence:

"**4.4.4.3 Unit pack bag leakage.** The leakage of the unit pack bag containing the M18A2 kit shall be determined by subjecting the sample to the hot water technique, Method 5009.2 of FED. TEST METHOD STD NO. 101.

4.4.4.4 Heat seal seam. The heat seal seam strength of the unit pack bag shall be determined by subjecting the sample to FED. TEST METHOD STD NO 101, Method 2024, except that the static load shall be 45 (+5,-0) ounces, and a 5 percent reduction shall be permitted when room temperature in test area exceeds 90°F."

PAGE 6 and 7

Section 5. Delete in its entirety and substitute the following:

"**5. PACKAGING**

5.1 Packaging. Packaging shall be in accordance with SPI P5-77-2092."

6.2, line 3. Delete "(see 5.2)" and substitute "(see 5 1)" and add "(d) Shelf life code " in sequence

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:55Z
Check the source to verify that this is the current version before use.

6.4: Add the following new paragraph in sequence:

"**6.4 Material safety data sheets.** The Contracting Officers will identify those activities requiring copies of completed Material Safety Data Sheets prepared in accordance with FED-STD-313. The pertinent Government mailing addresses for submission of data are listed in FED-STD-313

Custodian:

Army - EA

Preparing activity.

Army - EA

Project No. 6665-A577

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:55Z
Check the source to verify that this is the current version before use.