MIL-F-52652A(ME)
14 April 1975
SUPERSEDING
MIL-F-52652(ME)
23 June 1969

MILITARY SPECIFICATION

FIRE FIGHTING EQUIPMENT SET: TRUCK MOUNTED; PUMPER, CLASS 530-SERIES, ARMY AIRCRAFT CRASH, PACKAGING OF

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers requirements for the preservation, packaging, packing, and marking of a Fire Fighting Equipment Set, Truck Mounted, Pumper, Class 530-Series Army Aircraft Crash (SC 4210-97-CL-E09) (NSN 4210-00-202-8076).

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein:

SPECIFICATIONS

Federal

QQ-S-781	- Strapping, Steel, and Seals.
PPP-B-566	- Boxes, Folding, Paperboard.

FSC 4210

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:28Z
Check the source to verify that this is the current version before use.

PPP-B-601	- Boxes, Wood, Cleated-Plywood.
PPP-B-636	- Boxes, Shipping, Fiberboard.
PPP-C-650	- Crates, Wood, Open and Covered.
PPP-F-320	- Fiberboard; Corrugated and Solid, Sheet Stock (Container Grade), and Cut Shapes.
PPP-P-40	- Packaging and Packing of Hand Tools.
PPP-T-60	- Tape: Packaging, Waterproof.

Military

MIL-P-116	- Preservation-Packaging, Methods of.
MIL-P-775	- Packaging of Hose, Hose Assemblies; Rubber, Plastic, Fabric, or Metal (Including Tubing); and Fittings, Nozzles and Strainers.
MIL-E-10062	- Engines: Preparation for Shipment and Storage of.
MIL-T-11407	- Truck, Firefighting, Pumper, Tactical-Type, Midship-Mounted-Pump, 500 Gallon-Per-Minute (Class 530-C).

STANDARDS

Military

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	- Marking for Shipment and Storage.

(Copies of specifications and standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

UNIFORM CLASSIFICATION COMMITTEE, AGENT

Uniform Freight Classification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:28Z
Check the source to verify that this is the current version before use.

(Application for copies should be addressed to the Uniform Classification Committee, ATTN: Tariff Publishing Officer, Room 1106, 222 South Riverside Plaza, Chicago IL 60606.)

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT

National Motor Freight Classification.

(Application for copies should be addressed to the American Trucking Associations, Inc., ATTN: Tariff Order Section, 1616 P Street, NW, Washington, DC 20036.)

3. REQUIREMENTS

3.1 Materials. Materials shall be as specified herein. Materials not specified shall be selected by the supplier and shall be subject to all provisions of this specification. Materials shall be free of defects.

3.2 Preproduction pack. The supplier shall furnish a preproduction pack for examination within the time frame specified (see 6.2), to prove prior to starting production packaging, that the applied preservation, packaging, packing, and marking comply with the requirements of this specification. Examination shall be as specified in Section 4 and shall be subject to surveillance and approval by the Government (see 6.3). The preproduction pack may be accomplished utilizing either the preproduction set or a production set. If the preproduction model set is utilized, any preservation, packaging, and packing shall be removed by the supplier at no expense to the Government, when requested by the Government, to facilitate comparison between the preproduction set and the production set.

3.3 Preservation and packaging. Preservation and packaging shall be Level A, B, or C, as specified.

3.3.1 Level A.

3.3.1.1 Preservative. Preservative specified herein shall conform to the applicable specification listed in, and shall be applied in accordance with, MIL-P-116.

3.3.1.2 Methods. Methods of preservation, indicated by symbols herein, shall conform to the corresponding symbols in MIL-P-116.

3.3.1.3 Unprotected surfaces. Unpainted exterior metal surfaces of components requiring the application of a contact preservative in accordance with MIL-P-116 shall be coated with Type P-1 preservative.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:28Z
Check the source to verify that this is the current version before use.

3.3.1.4 Axes, pinch bars, wrecking bars, bolt cutter, hacksaw frame and blades, chisels, hammers, pliers, hand shovels, knives, hand saw, shears, and spanner wrenches. Each item shall be preserved and packaged in accordance with the Level A requirements of PPP-P-40.

3.3.1.5 Hoses, elbows, nipples, nozzles, coupling, reducers, strainer and siamese connection. Each item shall be preserved and packaged in accordance with the Level A requirements of MIL-P-775.

3.3.1.6 Fire extinguishers.

3.3.1.6.1 Hand type. Each extinguisher shall be packaged in a close-fitting box conforming to PPP-B-636, W5c. The contents shall be cushioned and secured to prevent damage by free movement within the box. The box shall be closed and sealed as specified for Method V in the box specification.

3.3.1.6.2 Wheeled type. The wheeled type fire extinguishers shall not require packaging but shall be packed as specified in 3.4.1.

3.3.1.7 Grapnel. The points of grapnel hooks shall be protected with fiberboard conforming to PPP-F-320, Class Weather Resistant, Variety SW, Grade W6c. The fiberboard shall be secured in place with tape conforming to PPP-T-60, Type IV.

3.3.1.8 First aid kit. The components of the first aid kit shall be placed in the case and the case packaged in a close-fitting box conforming to PPP-B-636, W5c. The box shall be closed and sealed as specified in 3.3.1.6.1.

3.3.1.9 Lanterns. Each lantern, contained in a vendor's carton or a box conforming to PPP-B-566, variety plain, type and style optional, shall be preserved Method IC-2.

3.3.1.10 Foam liquid. The foam liquid in 5-gallon pails shall not require packaging.

3.3.1.11 Gaskets. Gaskets of like description shall be preserved together, Method IC-1 or IC-3.

3.3.1.12 Scissors. Scissors shall be individually preserved, Method IC-1; means shall be provided to prevent the scissors from damaging the bag.

3.3.1.13 Ladder. The ladder shall not require preservation and packaging but shall be secured in the retracted position.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:28Z
Check the source to verify that this is the current version before use.

3.3.1.14 Rope. The rope shall be coiled, the coil secured with cotton tape or twine, and the coil packaged in a close-fitting box conforming to PPP-B-636, W5c. The box shall be closed and sealed as specified for Method V in the appendix to the box specification.

3.3.1.15 Portable saw. The engine shall be preserved in accordance with the Level A requirements of MIL-E-10062 as specified for Type II, Method I. All components shall then be placed and secured in the metal carrying case, and the case lid secured.

3.3.1.16 Chest, blacksmiths tool kit. The chest shall not require preservation and packaging but shall be utilized for consolidated packaging of components as specified in 3.3.1.19.

3.3.1.17 Firefighting truck. The firefighting truck shall be preserved and packaged in accordance with the Level A requirements of MIL-T-11407.

3.3.1.18 Other components. Other components not specifically specified herein shall be preserved and packaged as specified for components of similar design and characteristics.

3.3.1.19 Consolidated packaging. Packaged and unpackaged components of the set, except the ladders and the wheel-mounted fire extinguisher, shall be condolidated packaged as follows: The space within the blacksmiths tool chest shall be utilized to the maximum extent possible for consolidation of the items. The chest containing the components, and the other items that will not fit into the chest, shall be packaged in a minimum number of close-fitting boxes conforming to PPP-B-601, Overseas Type, Grade B, Style I. When a firefighting truck is furnished, the size and configuration of the boxes shall be determined by the available space for placing and securing the boxes on the fire truck. When the boxes are to be secured to the truck, strapping of the boxes shall not be required. When a truck is not furnished, the components of the set, except the ladders and wheel-mounted fire extinguishers, preserved and packaged as specified herein, shall be consolidated packaged in boxes specified herein. The boxes shall be strapped in accordance with the appendix to the box specification.

3.3.2 Level B. Preservation and packaging shall be as specified in 3.3.1 for Level A, except boxes for consolidated packaging shall be Domestic Type.

3.3.3 Level C. The components of the set, other than the firefighting truck, shall be preserved and packaged to afford protection against deterioration and damage from the supplier to the initial destination. The supplier's standard commercial practice is acceptable provided it fulfills

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:28Z
Check the source to verify that this is the current version before use.

these requirements. The firefighting truck shall be preserved and packaged in accordance with the Level C requirements of MIL-T-11407.

3.4 Packing. Packing shall be Level A, B, or C, as specified (see 6.2).

3.4.1 Level A. When a firefighting truck is furnished, the ladders shall be placed in the racks provided on the truck and shall be secured in place. The wheel-mounted fire extinguisher shall be packed in a close-fitting box conforming to PPP-B-601, Overseas Type, Grade B, Style A or B. The extinguisher shall be blocked, braced, and anchored within the box to prevent free movement. The consolidated containers shall be secured to the truck in any available space that will not increase cubage, or in any way interfere with lifting, steering, or towing of the truck. If space permits, the box containing the wheeled fire extinguisher shall be secured to the truck. Securing shall be with straps conforming to QQ-S-781, Type I, regular duty, Finish B, Size 3/4 inch, or by bolting. When space does permit securing of the box containing the wheeled fire extinguisher to the truck, the box shall be strapped in accordance with the appendix to the box specification. The box shall be shipped separately from but at the same time as the truck. The truck, with the ladders and consolidated containers attached, shall be shipped unboxed (mobile). When a truck is not furnished, the set components, except the ladders, preserved and packaged as specified in 3.3, and the boxed wheel-mounted fire extinguisher shall be packed in a crate conforming to PPP-C-650, Type V, Style A, Class 1. The ladders shall be packed in a crate conforming to PPP-C-650, Type II, Style A. Blocking, bracing, and anchoring of the contents, and closure and strapping of the crates shall be in accordance with the appendix to the crate specification.

3.4.2 Level B. Packing shall be as specified in 3.4.1 for Level A, except the box shall be Domestic Type and the Type V crate shall be a Style B, Class 1, open crate.

3.4.3 Level C. The components of the set, except the ladders, preserved and packaged as specified in 3.3, shall be packed in containers that will assure carrier acceptance and safe delivery to the initial destination at the lowest ratings of the carrier. Containers as a minimum shall comply with Uniform Freight Classification rules or with National Motor Freight Classification rules. Ladders shall be secured in the retracted position and shall not require packing. When a truck is furnished, the ladders shall be secured in the racks provided on the truck. The containers containing the other components of the set shall be secured in any

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:28Z
Check the source to verify that this is the current version before use.

space on the truck in a manner not to increase cubage or interfere when the truck is lifted with slings, or interfere with steering or towing the truck. The truck shall be shipped unboxed (mobile). Any containers that cannot be secured to the truck shall be shipped separately from but at the same time as the truck.

3.5 Marking. In addition to any special marking required by the contract or purchase order, packages, shipping containers, and unboxed (mobile) trucks shall be marked in accordance with MIL-STD-129.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Material inspection. The supplier is responsible for insuring that supplies and materials used are manufactured, examined, and tested in accordance with referenced specifications and standards.

4.2 Classification of inspections. Inspections shall be classified as follows:

(a) Preproduction pack inspection (see 4.3).
(b) Quality conformance inspection (see 4.4).

4.3 Preproduction pack inspection.

4.3.1 Examination. The preproduction pack shall be examined for the defects specified in 4.5. Presence of one or more defects shall be cause for rejection.

4.4 Quality conformance inspection.

4.4.1 Inspection stages. Inspection shall be in three stages as follows:

(a) The first stage shall include inspection of procedures, methods, materials, containers, and packaging marking prior to placing the packages into consolidated containers.
(b) The second stage shall include inspection of closure and marking of consolidated containers, and the arrangement and blocking and bracing of consolidated containers in the shipping containers.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:28Z
Check the source to verify that this is the current version before use.

(c) The third stage shall include inspection of the closed, strapped, and marked shipping containers prepared for shipment, and securing of the consolidated containers to the truck, when a truck is furnished.

4.4.2 Unit of product. For the purpose of inspection, all packages or packs prepared for any applicable inspection stage that will comprise a complete pack, shall be considered a unit of product.

4.4.3 Sampling. Sampling for examination shall be in accordance with MIL-STD-105.

4.4.4 Examination. Samples selected in accordance with 4.4.3 shall be examined for the defects marked "X" for the applicable level in Table I. Acceptable Quality Level (AQL) shall be 2.5 percent defective.

4.5 Inspection procedure.

4.5.1 Examination.

Table I. Classification of Defects

No.	Defect	Level		
		A	B	C
101.	Materials, methods, and containers not as specified. Each incorrect material, method, and container shall constitute one defect (3.1, 3.3, 3.4).	X	X	X
102.	Unpainted exterior surfaces of components not coated with preservative as specified (3.3.1.3, 3.3.2).	X	X	-
103.	Tools not preserved and packaged in accordance with the referenced document as specified (3.3.1.4, 3.3.2).	X	X	-
104.	Hose and fittings not preserved and packaged in accordance with the referenced document as specified (3.3.1.5, 3.3.2).	X	X	-
105.	Fire extinguishers not packaged and boxes closed and sealed as specified (3.3.1.6.1, 3.3.2).	X	X	-
106.	Points of grapnel not protected as specified (3.3.1.7, 3.3.2).	X	X	-
107.	First aid kit components not placed in their case and the case not packaged as specified (3.3.1.8, 3.3.2).	X	X	-
108.	Lanterns not preserved as specified (3.3.1.9, 3.3.2).	X	X	-
109.	Gaskets of unlike description packaged together (3.3.1.11, 3.3.2).	X	X	-
110.	Scissors not preserved and means provided to prevent damage to the bag (3.3.1.12, 3.3.2).	X	X	-

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:28Z
Check the source to verify that this is the current version before use.

Table I. Classification of Defects (Cont'd)

No.	Defect	Level A	Level B	Level C
111.	Rope not coiled, coil not secured, and not packaged as specified (3.3.1.14, 3.3.2).	X	X	-
112.	Engine of portable saw not preserved in accordance with the referenced document as specified (3.3.1.15, 3.3.2).	X	X	-
113.	Case lid for portable saw not secured (3.3.1.15, 3.3.2).	X	X	-
114.	Blacksmiths tool chest not utilized as specified (3.3.1.16, 3.3.1.19, 3.3.2).	X	X	-
115.	Firefighting truck not preserved in accordance with the referenced document as specified (3.3.1.17, 3.3.2, 3.3.3).	X	X	X
116.	Other components not specifically specified not preserved and packaged as specified (3.3.1.18, 3.3.2).	X	X	-
117.	Consolidated packaging not as specified (3.3.1.19, 3.3.2).	X	X	-
118.	Boxes not secured to the truck when a truck is furnished (3.4.1, 3.4.2, 3.4.3).	X	X	X
119.	Marking illegible, incomplete, or incorrect (3.5).	X	X	X

5. PREPARATION FOR DELIVERY

(This section not applicable to this specification).

6. NOTES

6.1 Intended use. This specification is intended to be used for direct reference in contracts or purchase orders for the preservation, packaging, packing, and marking of a Fire Fighting Equipment Set: Truck Mounted; Pumper, Class 530-Series, Army Aircraft Crash, (SC 4210-97-CL-E09) (NSN 4210-00-202-8076).

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:28Z
Check the source to verify that this is the current version before use.

(b) Time frame required for submission of the preproduction pack (see 3.2).
(c) Level of preservation and packaging and level of packing required (see 3.3 and 3.4). Level B preservation and packaging is intended to provide economical but limited protection and should be specified only when it has been determined the set components will be held in covered storage.

6.3 Preproduction pack. Any changes or deviations of production packs from the approved preproduction pack will be subject to the approval of the contracting officer. Approval of the preproduction pack will not relieve the supplier of his obligation to preserve, package, pack, and mark the set components in accordance with this specification.

Custodian:

Army - ME

Review activity:

Army - SM

Preparing activity:

Army - ME

Project No. 4210-A071

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:28Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE MIL-F-52652A(ME) Fire Fighting Equipment Set: Truck Mounted; Pumper, Class 530-Series, Army Aircraft Crash, Pkg Of

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426

REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:28Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commander
US Army Mobility Equipment Research
and Development Center
ATTN: AMXFB-DS.
Ft. Belvoir, Va. 22060

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:28Z
Check the source to verify that this is the current version before use.