MILITARY SPECIFICATION

SQUIB, ELECTRIC, SINGLE BRIDGEWIRE

This amendment forms a part of Military Specification MIL-S-85309(AS) Dated 3 January 1980, and is approved for use within the Naval Air Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1: Below SPECIFICATIONS, MILITARY, delete title "Initiator, Electric, Design and Evaluation of" and substitute "Initiators, Electric, General Design Specification for." Delete "MIL-C-45662" and associated title.

PAGE 2

2.1: Below STANDARDS, MILITARY, delete "MIL-STD-331" and associated title, and under MIL-STD-831, add "MIL-STD-45662 Calibration Systems Requirements."

PAGE 3

3.2.1.1.3: Delete "through the leads for 5 minutes over a temperature range from -80 to +200 degrees Fahrenheit (^{o}F)." and substitute "through the leads for 30 milliseconds (ms) minimum."

3.2.1.4.1.1: Delete in its entirety and substitute: "3.2.1.4.1.1. All-fire, 4.5 amperes (A). The squib shall function with the application of 4.5 $\pm$ 0.1 A to the leads, and shall produce a pressure output of 250 pounds per square inch (lb/in^2) in a 5 cubic centimeter (cm^3) pressure vessel within 5 ms maximum after application of firing current."

FSC 1336

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-23T10:39Z
Check the source to verify that this is the current version before use.

PAGE 4

3.2.2.1: Delete "meet the requirements of MIL-STD-331, Test 103, Procedures 1 and 2, and shall" and substitute "meet the forty-foot drop requirements of MIL-I-23659, and shall".

3.3.4: Delete "MIL-S-45662." and substitute "MIL-STD-45662."

PAGE 6

4.2.1: Delete "500 squibs" and substitute: "1000 squibs."

Table I, Group II, column 1: Delete "3 A" and substitute "4.5 A".

Table I, Group VII, column I: Delete "3 A" and substitute "4.5 A".

PAGE 7

Table II, Group A, column 1: Delete "(in-process)" and substitute "(in-process, 100 percent)".

Table II, Group C, column 1: Delete "3 A" and substitute "4.5 A".

Table II, Group E, column 1: Delete "500 squibs" and substitute "1000 squibs."

PAGE 9

4.4.2.3: Delete "through both leads for 5 minutes minimum." and substitute "through the leads for 30 ms minimum."

4.4.2.4: Delete "10 milliamperes (mA)" and substitute "100 milliamperes (mA)".

4.4.4: Delete "Using radiographic equipment that will provide" and substitute "Using radiographic equipment and procedures in accordance with MIL-STD-202, Method 209, and that will provide".

4.4.5: Delete "Group B through Group E in Table II, will be fired and shall" and substitute "Group B through Group D in Table II, shall be fired or destroyed and shall".

PAGE 10

4.4.5.1.1: Delete "4.4.5.1.1 All-fire, 3 A, Connect a 3.0 ± 0.1 A power source" and substitute "4.4.5.1.1 All-fire, 4.5 A. Connect a 4.5 ± 0.1 A constant current power source".

4.4.5.2.2: Delte "34" and substitute "35".

4.4.6.1: Delete "in accordance with MIL-STD-331, Test 103, Procedures 1 and 2." and substitute "in accordance with MIL-I-23659."

PAGE 13

Figure I, lower right corner, output box description: Delete "3A".

Preparing activity
Navy - AS
(Project 1336-N543)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T10:39Z
Check the source to verify that this is the current version before use.