# MILITARY SPECIFICATION

## WARHEAD, 2.75 INCH ROCKET, TEST, PXR6369, WITH SMOKE FOR TEST: FUZE, ROCKET, M433

This specification is approved for use within the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Qgencies of the Department of Defense.

## 1. SCOPE

1.1 Scope. This specification covers the quality assurance provisions and special requirements not covered by the drawings for parts and assembly of the PXR6369 Test Warhead.

## 2. APPLICABLE DOCUMENTS

2.1.1 Government documents.

2.1.1 Specificaitons and standards. Unless otherwise specified (see 6.2), the following specifications and stand ards of the issue listed in that issue of the Department of Defense Index of Specificaitons and Standards (DoDISS] specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

| | |
|---|---|
| MIL-A-48078 | Ammunition, Standard Quality Assurance Provisions, General Specification for |

STANDARDS

MILITARY

| | |
|---|---|
| MIL-STD-105 | Sampling Procedures and Tables for Inspection by Attributes |

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to Commande; U.S. Army Armament Munitions and Chemical Command ATTN: AMSMC-QA Picatinny Arsenal, New Jersey 07806-5000 using the self addressed Standardization Document Improvemetnt Proposal (DD Form 1426) appearing at the end of this document or by letter.

**AMSC N/A** **FSC 1340**

**DISTRIBUTION STATEMENT A. Approved for public release; distributuion is unlimited.**

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:49Z
Check the source to verify that this is the current version before use.

2. 1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publ ications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be thoise in effect on the date of the solicitation.

DRAWINGS

US ARMY ARMAMENT, RESEARCH, DEVELOPMENT AND ENGINEERING CENTER (ARDEC)

PRODUCT AND PACKAGE DRAWINGS

| | |
|---|---|
| 8886811 | Container, Ammo, Fiber, M523, For Warhead, 2.75 Inch Rocket HE: M151, Smoke WP M156 |
| 8886810 | Box, Packing, Ammunition, for Warhead, 2.75 Inch Rocket, HE M151 and Smoke WP M156 |
| 9209570 | Box, Packing, Ammunition for Rocket Motor: 2.75 2.75 Inch MK40 Mod 1, MK4, MK40 Mod O and Warheads M151, M156, M230 |
| 12561319 | Warhead, 2.75 Inch Rocket, Test, PXR6369 with Smoke for Test: Fuze, Rocket, M433 |

INSPECTION DRAWINGS

| | |
|---|---|
| 9260701 | Fuze, Rocket, M433 |

(Copies of specificaitons, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.1.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets or MS standards) , the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained .

3.1 Materials. Materials shall be in accordance with applicable drawings and specifications.

3.2 Components and assemblies. The components and assemblies shall comply with all requirements specified on Drawing 12561319 and associated drawings (except for P/N 889406-2, see below) and with



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:49Z
Check the source to verify that this is the current version before use.

all requirements specified in applicable specifications and standards. The Warhead, 2.75 Inch Rocket, M151, Metal Parts Assembly, shall comply with all requirements specified on drawing 8889406-2 except the Hydrostate Pressure and Air Leakage requirements do not apply.

3.3 Function. A static function test shall be performed on the smoke cartridge assembly at -50° ± 5° and at +150° ± 5°F.

3.4 Data requirements. The contractor shall generate data in accordance with the requirements of the data item descriptions cited in 4.5.2.

3.5 First article inspection. This specification makes provisions for first article inspection. Requirements for submission of first article samples by the contractor shall be as specified in the contract.

3.6 Workmanship. Unless otherwise specified on the drawing, all parts and assemblies shall be free from burrs, chips, sharp edges, cracks, unblended radii, surface defects, dirt, grease, rust porosity, warpage, burn marks, checks, blisters, excess flash, corrosion products, and other foreign matter. The cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agents. Surface coating shall be continuous except for a few slight scratches not exposing base material. The loading and assembly operations shall be performed in a thorough, workmanlike manner consistent with the best practices of the industry. All required markings shall be neat and sharply defined.

4. QUALITY ASSURANCE PROVISIONS

4.1 Respossibilities for inspections. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the government. The government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are made a part of this specification.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:49Z
Check the source to verify that this is the current version before use.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor;s overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibiliuty of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Classificaiton of inspections. Unless otherwise specified herein or in the contract, the following types of inspeciton shall be conducted on this item.

a. First Article Inspection
b. Quality Conformance Inspection

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the contracting officer for evaluation in accordance with the provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated:

| Part Description | Drawing | Quantity |
|---|---|---|
| Warhead, 2.75 Inch Rocket, M151, Metal Parts Assembly | 8889406-2 | 2 5 |
| Warhead, Modified, 2.75 Inch Rocket, Test, PAR6369 | 12561318 | 2 5 |
| Smoke Cartridge Assembly | 12561317 | 2 5 |
| Warhead, 2.75 Inch Rocket, Test, PXR6369 With Smoke, for Test | 12576607 | 2 5 |

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection. See MIL-A-4 8078.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:49Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

## CLASSIFICATION OF DEFECTS & TESTS



| PARAGRAPH | TITLE | | SHEET 1 OF 1 | | DRAWING NUMBER |
|---|---|---|---|---|---|
| | Warhead, 2.75 Inch Rocket: Test, PXR6369, With Smoke, For Test: Fuze, Rocket: M433 | | | | Listed Below |
| | | | | | NEXT HIGHER ASSEMBLY |
| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| | Warhead, 2.75 Inch Rocket, M151, Metal Parts Assembly (Dwg. 8889406-2) | | | | |
| | Examination for defects | 25 | | 3.2 | 4.4.2.1 |
| | Warhead, Modified, 2.75 Inch Rocket, Test, PXR6369 (Dwg. 12561318) | | | | |
| | Examination for defects | 25 | | 3.2 | 4.4.2.2 |
| | Smoke Cartridge Assembly (Dwg. 12561317) | | | | |
| | Examination for defects | 25 | | 3.2 | 4.4.2.3 |
| | Function test | 25 | | 3.3 | 4.5.1 |
| | Warhead, 2.75 Inch Rocket: Test, PXR6369, With Smoke, For Test (Dwg. 12576607) | | | | |
| | Examination for defects | 25 | | 3.2 | 4.4.2.4 |

NOTES:





Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:49Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspeciton lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078.

4.4.2 Examinatin. See MIL-A-48078.

a. Sampling Plans. Unless otherwise specified in the Classification of Defects and test tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:49Z
Check the source to verify that this is the current version before use.

## CLASSIFICATION OF DEFECTS & TESTS



| PARAGRAPH | TITLE | | SHEET 1 OF 2 | | DRAWING NUMBER 8889406-2 |
|---|---|---|---|---|---|
| 4.4.2.1 | Warhead, 2.75 Inch Rocket, M151, Metal Parts Assembly | | | | NEXT HIGHER ASSEMBLY 12561318 |
| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| CRITICAL | None defined | | | | |
| MAJOR | | | | | |
| 101 | Concentricity of pitch diameter of fuze thread | | 0.40% | 3.2 | Gage |
| 102 | Concentricity of counterbore at front of fuze thread | | 0.40% | 3.2 | Gage |
| 103 | Concentricity of diameter at rear of fuze thread | | 0.40% | 3.2 | Gage |
| 104 | Concentricity of ogive | | 0.40% | 3.2 | Gage |
| 105 | Concentricity of base at rear of threads with pitch diameter | | 0.40% | 3.2 | Gage |
| 106 | Concentricity of base at rear of threads with outside diameter | | 0.40% | 3.2 | Gage |
| 107 | Concentricity of bourrelet | | 0.40% | 3.2 | Gage |
| 108 | Perpendicularity of motor body seat | | 0.40% | 3.2 | Gage |
| 109 | Length of fuze thread | | 0.40% | 3.2 | Gage |
| 110 | Diameter of counterbore at front fuze thread | | 0.40% | 3.2 | Gage |
| 111 | Diameter of rear of fuze thread | | 0.40% | 3.2 | Gage |
| 112 | Diameter of nose between bourrelet and ogive | | 0.40% | 3.2 | Gage |
| 113 | Diameter of base at rear of threads | | 0.40% | 3.2 | Gage |

NOTES:

AMSMC Form 1570, 1 Feb 85 — Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.





Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:49Z
Check the source to verify that this is the current version before use.

## CLASSIFICATION OF DEFECTS & TESTS



| PARAGRAPH | TITLE | | SHEET 2 OF 2 | | DRAWING NUMBER |
|---|---|---|---|---|---|
| 4.4.2.1 | Warhead, 2.75 Inch Rocket, M151, Metal Parts Assembly | | | | 8889406-2 |
| | | | | | NEXT HIGHER ASSEMBLY 12561318 |
| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| 114 | Length from front face to motor housing seat | | 0.40% | 3.2 | Gage |
| 115 | Length from motor housing seat to rear of base | | 0.40% | 3.2 | Gage |
| 116 | Profile ogive | | 0.40% | 3.2 | Gage |
| 117 | Pitch diameter of fuze thread (a) | | 0.40% | 3.2 | Gage |
| 118 | Minor diameter of fuze thread, max. (a) | | 0.40% | 3.2 | Gage |
| 119 | Pitch diameter of rear thread (a) | | 0.40% | 3.2 | Gage |
| 120 | Major diameter of rear thread, min. (a) | | 0.40% | 3.2 | Gage |
| 121 | Thread damages or not full (a) | | 0.40% | 3.2 | Visual |
| MINOR | | | | | |
| 201 | Evidence of poor workmanship | | 0.65% | | Visual |

NOTES:
(a) These characteristics apply after painting. All other characteristics apply before painting.

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.





Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:49Z
Check the source to verify that this is the current version before use.

## CLASSIFICATION OF DEFECTS & TESTS



| PARAGRAPH | TITLE | | SHEET 1 OF 1 | | DRAWING NUMBER 12561318 |
|---|---|---|---|---|---|
| 4.4.2.2 | Warhead, Modified, 2.75 Inch Rocket, Test, PXR6369 | | | | NEXT HIGHER ASSEMBLY 12561319 |
| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| CRITICAL | None defined | | | | |
| MAJOR | | | | | |
| 101 | Weight of inert filler improper | | 0.40% | 3.2 | Scale |
| 102 | Evidence of inert filler in fuze cavity area | | 0.40% | 3.2 | Visual |
| MINOR | | | | | |
| 201 | Evidence of poor workmanship | | 0.65% | 3.8 | Visual |

NOTES:







Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:49Z
Check the source to verify that this is the current version before use.

## CLASSIFICATION OF DEFECTS & TESTS



| PARAGRAPH | TITLE | | SHEET 1 OF 1 | | DRAWING NUMBER 12561317 |
|---|---|---|---|---|---|
| 4.4.2.3 | Smoke Cartridge Assembly | | | | NEXT HIGHER ASSEMBLY 12561319 |
| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| CRITICAL | None defined | | | | |
| MAJOR | | | | | |
| 101 | Weight of smoke mixture improper | | 0.40% | 3.2 | Scale |
| 102 | Maximum length | | 0.40% | 3.2 | Gage |
| 103 | Improper bonding of felt pad | | 0.40% | 3.2 | Visual |
| 104 | Function test | 22 | | 3.3 | 4.5.1 |
| MINOR | | | | | |
| 201 | Improper markings | | 0.65% | 3.2 | Visual |
| 202 | Evidence of poor workmanship | | 0.65% | 3.6 | Visual |

NOTES:



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:49Z
Check the source to verify that this is the current version before use.

## CLASSIFICATION OF DEFECTS & TESTS



| PARAGRAPH | TITLE | | SHEET 1 OF 1 | | DRAWING NUMBER 12576607 |
|---|---|---|---|---|---|
| 4.4.2.4 | Warhead, 2.75 Inch Rocket Test, PXR6369, With Smoke, for Test | | | | NEXT HIGHER ASSEMBLY 12561319 |
| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| CRITICAL | None defined | | | | |
| MAJOR | | | | | |
| 101 | Improper bonding of smoke cartridge assembly | | 0.40% | 3.2 | Visual |
| 102 | Maximum outside diameter | | 0.40% | 3.2 | Gage |
| 103 | Maximum length | | 0.40% | 3.2 | Gage |
| MINOR | | | | | |
| 201 | Excessive adhesive | | 0.65% | 3.2 | Visual |
| 202 | Improper markings | | 0.65% | 3.2 | Visual |
| 203 | Missing plastic plug | | 0.65% | 3.2 | Visual |
| 204 | Evidence of poor workmanship | | 0.65% | 3.6 | Visual |

NOTES:







Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:49Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the Quality Conformance Inspection tables.

4.4.4 Inspection equipment. The inspection equipment required to perorm the examinations and tests prescribed herein is described in the in the "Paragraph Reference/Inspection Method" col umn in tables starting wiht 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.3 herein. The contractor shall submit all inspection equipment designs to the government for evaluation and approval prior to fabrication of such equipment.

4.5 Methods of inspection.

PRECAUTION: This specification covers sampling and testing of chemical, toxic, or explosive materials which are potentially hazardous to personnel. Accordingly, it is emphasized that all applicable safety rules, regulations, and procedures must be followed in handling and processing these materials.

4.5.1 Function test. The smoke cartridges shall be subjected to a static acceptance test using a Government approved fixture. The fixture shall simulate the interface between M433 Fuze booster assembly and smoke cartridge assembly on test warhead, PXR6369, P/N 12561319. The Government will furnish the M84 electric detonator, explosive lead in, and explosive booster and the contractor shall furnish all other necessary materials. The smoke cartridge assembly shall function after functioning of the booster assembly. The booster assembly shall be initiated using a M84 detonator or approved substiture. Half of the sample shall be conditioned at a temperature of -50° ± 5°F and the other half shall be conditioned at 150°F ± 5°F for a minimum of 4 hours prior to testing. Testing shall be accomplished within 2 minutes after removal of sample from temperature conditioning chamber. The lot shall be rejected if one or more smoke cartridge assemblies fail to function when tested.

4.5.2 Data requirements. The contractor shall submit a quality inspection test demonstration and evaluation report in accordance with Data Item Descriptions DI-R-1721 and DI-R-1724 giving the detailed test results.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:49Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Packaging, level A.The Warheads shall be packaged in accordance with drawing 8886811.

5.2 Packing and marking, level A. The packaged warheads, when shipped without motors, shall be packed and marked in accordance with drawing 8886810. When shipped with motors, the packaged warheads shall be packed and marked in accordance with drawing 9209570. The DOT marking shall be: Special Firework - Handle Carefully - Keep Fire Away.

6. NOTES

6.1 Intended use. The Warheads covered by this specification are intended for testing the M433 Fuze

6.2 Ordering data. See MIL-A-4 8078.

6.3 Submission of inspection equipment for design approval. See 6.2 of MIL-S-48078. Submit designs as required to Commander, U.S. Army Armament Research, Development and Engineering Center, US Army Armament, Munitions and Chemical Command, ATTN: AMXMC-QAR-1 (D), Picatinny Arsenal, NJ 07806-5000.

6.4 Government furnished materials. The procuring agency will provide the following for smoke cartridge assembly function test:

a. E84 Electric Detonator, P/N 8838107

b. Explosive Lead In, P/N 8883684

c. Explosive Booster, P/N 8883685

6.5 Data requirements. When this specification is used in an acquisition which incorporates a DD Form 1423, Contract Data Requirements List 9CDRL), the data requirements identified below shall be developed as specified by an approved Data Item Description (DD Form 1664) and delivered in accordance with the approved CDRL incorporated into the contrace. When the provisions of DAR 7-104.9 (n) (2) are invoked and the DD Form 1423 is not used, the data specified below shall be delivered by the contractor in accordance with the contract or purchase order requirements. Deliverable data required by this specification is cited in the following paragraphs.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:49Z
Check the source to verify that this is the current version before use.

| Paragraph No. | Data Requirement Title | Applicable DID No. |
|---|---|---|
| 4.5.3 | Quality Inspection Defect Report | DI-R-1721 |
| 4.5.3 | Quality Inspection Test Demonstration and Evaluation Report | DI-R-1724 |

(Data item descriptions related to this specif icat ion, and identified in Section 6 will be approved and listed as such in DoD 5000. 19L, Vol II, AMSDL. Copies of data item descriptions requi red by the contractors in connection with specific acquisition functions should be obtained from the Naval Publications and Forms Center or as directed by the contracting officer.)

6.6 First article. When a first article is required for inspection and approval, see 3.7 and 4.3.

6.7 Source control and spacification control drawings. Certificates of conformance from the supplier certifying that the item complies with the drawing requirements shall be provided to the government representative.

6.8 Subject term (key word) listing.

Military Specification
Warhead (Test)
Fuze
Pyrotechnics (Smoke)
Rocket (Hydra 70)

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1340 -A716)



Source: https://assist.dla.mil -- Downloaded: 202610-23T03:49Z
Check the source to verify that this is the current version before use.

**INSTRUCTIONS:** In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

*NOTE:* This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

---

*(Fold along this line)*

---

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

**OFFICIAL BUSINESS**
PENALTY FOR PRIVATE USE $300

**BUSINESS REPLY MAIL**
FIRST CLASS PERMIT NO 12062 WASHINGTON D C

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

COMMANDER
US ARMY ARDEC
ATTN: AMSMC-QA
PICATINNY ARSENAL, NJ 07801-5000

Source: https://assist.dla.mil -- Downloaded: 202640-23T03:49Z
Check the source to verify that this is the current version before use.

# STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

*(See Instructions – Reverse Side)*

| 1. DOCUMENT NUMBER | 2. DOCUMENT TITLE |
|---|---|
| MIL-W-70622 | WARHEAD, 2.75 INCH ROCKET, TEST, PXR6369 |

| 3a. NAME OF SUBMITTING ORGANIZATION | 4. TYPE OF ORGANIZATION *(Mark one)* |
|---|---|
| | ☐ VENDOR |
| b. ADDRESS *(Street, City, State, ZIP Code)* | ☐ USER |
| | ☐ MANUFACTURER |
| | ☐ OTHER *(Specify)*. _____ |

5 PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6 REMARKS

| 7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional | b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional |
|---|---|
| c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional | 8. DATE OF SUBMISSION *(YYMMDD)* |

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:49Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:49Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:49Z
Check the source to verify that this is the current version before use.