INCH-POUND

MIL-G-63386(AR)
AMENDMENT 3
04 APRIL 1990
SUPERSEEDING
AMENDMENT 2
31 AUGUST 1982

MILITARY SPECIFICATION

GAS GENERATOR ASSEMBLY

This amendment forms a part of Military Specification MIL-G-63386(AR), dated 28 October 1980, and is approved for use by the U.S. Army Armament Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 4

4.3.1: Under Drawings, delete “9298522” and substitute “9298532”.

Under Part Description, delete "Charge Assembly" and substitute ‘Charge Holder".

TABLE 1: Under Header, Bridged Assembly. Delete "dwg. 9298522” and substitute "dwg. . 9298532”.

PAGE 6

TABLE 1: Under Gas Generator Assembly. Delete “All fire voltage function, 125, 3.2, 4.5.7”.

* Gas Generator Assembly
(Dwg 9298530)

		Number of Sample Units
Change From:	Assembly Functioning Output (+70°F)	80
	Assembly Functioning output (-20°F)	20
Change TO:	Assembly Functioning Output (+70°F)	50
	Assembly Functioning output (-25°F)	50

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:45Z
Check the source to verify that this is the current version before use.

4.4.2.3: Major 103, Delete in its entirety.

4.4.2.7: Major 107, delete “125”
Major 108, delete defect in its entirety
Major 109 Change no. of sample units from 80(a) 50(a)
Major 110 Change no. of sample units from 20(a) 50(a)

Change notes to read:

Notes: (a) All units must fire on first attempt, and meet the minimum P_S pressure requirement. No failure-to-function allowed; three(3) pressure time failures permitted.

4.5.4: First line, "of gas generator assembly”. Fifth line, add “(9298532)” after ". .. applicable drawing".

4.5.6: Environmental conditioning and functioning. Delete paragraph in its entirety and Substitute:

‘4.5.6: Environmental conditioning and functioning. The Gas Generator Assemblies shall be tested as following, in sequence specified, using approved equipment:

a. Measure resistance of the bridgewire in accordance with 4.5.4.

b. Measure insulation resistance in accordance with 4.5.5.

c. Condition for two (2) hours minimum at -65 + 5°F.

d Remove from cold chamebr and wtihin 20 sec. transfer to a hot chamber at 165 ± 5°F.

e. Condition for two (2) hours minimum at 165 ± 5°F and 20% maximum relative humidity.

f. Remove from hot chamber.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:45Z
Check the source to verify that this is the current version before use.

g. Vibrate for 15 minutes, minimum in a sweep covering a frequency range of 25-500-25 cycles per second, parallel to the transverse orthogonal axis, with base charge down and a 2 + 0.2 G's peak.

h. Measure resistance of bridgewire in accordance with 4.5.4.

i. Measure insulation resistance in accordance with 4.5.5,

j. The Gas Generator assemblies shall be functioned as specified in 4.5,8."

* Change 4.5.6: Item j read:

j. The gas generator assemblies shall be functioned as specified in 4.5.8 except that this test is to be conducted for function only. No pressure time measurement required.

PAGE 19

4.5.7: Delete the paragraph in its entirety.

* 4.5.8: Delete first paragraph in its entirety and substitute the following:

4.5.8: Gas generator output functioning. This test shall be performed for each gas generator assembly lot. The assemblies shall be assembled in a fixture in accordance with Dwg . 9298530 which is instrumented to provide a record of pressure versus time. The assemblies and fixture whall be conditioned at the required test temperature for two (2) hours minimum prior to test. The Gas Generator Assembly shall be initiated with all fire voltage specified on the applicable drawing and the pressure/time resuflts evaluated against the applicable requirements. All units must fire on first attempt, and meet the minimum Ps pressure requirement. No failure-to function allowed; three (3) pressure time failures permitted.

PAGE 21

5.3.1: Change "ELECTRIC BLASTING CAPS --HANDLE CAREFULLY" to 'DETONATING FUZE, CLASS C EXPLOSIVE".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:45Z
Check the source to verify that this is the current version before use.

MIL-G-63386(AR)
AMENDMENT 3

Change note at end of paragraph from “Insert number of blasting caps . ...” to “Insert number of gas generator. . ..”

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions? modification, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1345-A573)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:45Z
Check the source to verify that this is the current version before use.