MILITARY SPECIFICATION SHEET

CAPACITORS, FIXED, METALLIZED PLASTIC DIELECTRIC, DC, IN NONMETAL CASES, ESTABLISHED RELIABILITY STYLE CFR29

This amendment forms a part of MIL-C-55514/12(ER), dated 2 June 1987, and is approved for use within the Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

FIGURE 1: Delete dimension "H" and substitute "L".

PAGE 2

TABLE I, column 3: Delete F G J K and substitute "J, K, M".

TABLE I, column 10: Delete "H $^{+.093}_{-.062}$" and substitute "L 3/."

Footnote 2, delete and substitute:

2/ Tolerances: Thickness and width $^{+.062}_{-.156}$ on .437 through .500 and $^{+.093}_{-.187}$ on .562 and greater.

Following footnote 2, add footnote 3.

"3/ Tolerances: Length $^{+.093}_{-.062}$."

Preparing activity:
Army - ER

Agent:
DLA - ES

(Project 5910-A419-2)

AMSC N/A FSC 5910

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:30Z
Check the source to verify that this is the current version before use.