MILITARY SPECIFICATION

REACTOR: 10525925

This amendment forms a part of Military Specification MIL-R-60191(MU), dated 23 February 1965.

Paragraph 1.1: Delete "TF5RX0422" and substitute "TF5RX04ZZ".

Paragraph 3.1: Delete "TF5RX0422" and substitute "TF5RX04ZZ".

Paragraph 3.3.4.1: Delete "135°F." and substitute "135°F, except that it shall meet the requirements of 3.4.3 after being thoroughly dried."

Following paragraph 4.1.1 add:

"4.1.2 First article (initial production) submission.- When required by the contract, an initial production sample shall be submitted in accordance with the contract schedule to a Government approved facility for test and evaluation. The sample shall consist of three reactors. The sample shall be manufactured in the same manner, using the same materials, equipment, processes and procedures as used in regular production. All parts and materials, including packaging and packing, shall be the same as used for regular production and shall be obtained from the same source of supply. After inspection and provisional acceptance at source, the initial production sample shall be inspected at a Government approved facility for all requirements of the drawings, and specifications. The Government reserves the right to require new initial production samples until such time as an acceptable sample is submitted."

Paragraph 4.5.1.3.2: Delete "95 ± 5 percent" and substitute "92 to 97 percent"; delete "specified requirements of 3.3.4.1" and substitute "requirements of 3.3.4.1, except the unit shall be tested as specified in 4.5.2.3 after being thoroughly dried".

Paragraph 4.5.1.5, line 1: Delete "Fungus" and substitute "Fungus resistance".

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1220-A066

FSC 1220

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:15Z
Check the source to verify that this is the current version before use.