MILITARY SPECIFICATION

WARHEAD, GUIDED MISSILE, HE, M207E1
BODY AND BOATTAIL BUSHING FOR

This Amendment forms a part of Military Specification MIL-W-63388 (AR) dated 7 January 1980.

PAGE 6

4.4.2.1-Majors 101, 103, 111, & 113 change, "0.40%" to "0.25%" under "AQL or 100%" column.

Major 113- Delete in its entirety and substitute:
"Wall thickness, shroud (See Note 1)"

Add: Majors and Note 1 as follows:

"118.	Length next to large basic dimension at aft end	0.40%, 3.2, Gage
119.	Length to large basic dimension at aft end	0.40%, 3.2, Gage
120.	Length to small basic dimension at aft end	0.40%, 3.2, Gage
121.	Runout between two basic dimensions with datum	0.40%, 3.2, Gage
122.	Perpendicularity of front face with datum	0.40%, 3.2, Gage
123.	Runout of O.D with datums	0.40%, 3.2, Gage

Note 1: Wall thickness of shroud shall be measured by longitudinal, traverse and rotation all around point at bottom."

PAGE 7

4.4.2.1, Minor 201- Delete and substitute:

"Distance from front face to missile mounting diameter face."
Delete minors 204 and 205 in their entirety
Change minors 206 to 205, 207 to 206, & 208 to 209.

Add minors:

204-	"Overall length	0.65%, 3.2, Gage
207-	Protective finish, inadequate	0.65%, 3.2, Visual
208-	Identification missing or illegible	0.65%, 3.2, Visual"

FSC: 1336

Custodian
Army-AR

Preparing Activity
Army-AR

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:46Z
Check the source to verify that this is the current version before use.

Project No. 1336-A354