MIL-C-51407A(EA)
10 March 1983
SUPERSEDING
MIL-C-51407(EA)
9 November 1979

MILITARY SPECIFICATION

CHLORINATED LIME, TECHNICAL

This specification is approved for use by US Army Armament Research and Development Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers one technical grade of chlorinated lime.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. Unless otherwise specified, the following specifications, standards, and handbooks of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

NN-P-71	-	Pallets, Material Handling, Wood, Stringer Construction, 2-Way and 4-Way (Partial)
NNN-P-1475	-	Paper, Filter, Analytical
PPP-P-704	-	Pails, Metal: (Shipping, Steel, 1 Through 12 Gallons)

: Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed: to: Commander, US Army Armament Research and Development Command, ATTN: DRDAR-TSC-S, Aberdeen Proving Ground, MD 21010 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:06Z
Check the source to verify that this is the current version before use.

STANDARDS

FEDERAL

Fed. Test Method Std. No. 536 - Soap and Soap-Products (Including Synthetic Detergents); Sampling and Testing

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-147 - Palletized Unit Loads

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein.

CODE OF FEDERAL REGULATIONS (CFR)

16 CFR 1500 - Consumer Product Safety Commission, Hazardous Substances and Articles: Administration and Enforcement Regulations
40 CFR 162 - Regulations for the Enforcement of the Federal Insecticide, Fungicide, and Rodenticide Act
49 CFR 171 to 179 - Department of Transportation Hazardous Materials Regulations

(The Code of Federal Regulations is available from the Superintendent of Documents, US Government Printing Office, Washington, DC 20402. Orders for the above publications should cite "16 CFR 1500, 40 CFR 162," or "49 CFR 171 to 179.")

(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. The issues of the documents which are indicated as DoD adopted shall be the issue listed in the current DoDISS and the supplement thereto, if applicable.

ASTM STANDARDS

D1193 - Reagent Water

(Application for copies should be addressed to ASTM, 1916 Race Street, Philadelphia, PA 19103.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:06Z
Check the source to verify that this is the current version before use.

(Industry association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 Chemical and physical characteristics. Chlorinated lime shall conform to the requirements of table I when tested as specified therein.

TABLE I. Chemical and physical characteristics

Characteristic	Requirement	Test paragraph
Available chlorine, percent by weight	30.0 to 39.0	4.2.4.1
Loss of available chlorine on heating, percent by weight, maximum	25.0	4.2.4.2
Moisture, percent by weight, maximum	3.0	4.2.4.3
Total mixed oxides of heavy metals plus aluminum oxide, percent by weight, maximum	0.50	4.2.4.4
Iron, percent by weight, maximum	0.25	4.2.4.5
Particle size:		4.2.4.6
Percent passing 1400 micrometer sieve, minimum	98.0	
Percent passing 600 micrometer sieve, minimum	60.0	
Bulk density, grams per milliliter, minimum	0.80	4.2.4.7

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Quality conformance inspection.

4.2.1 Lotting. A lot shall consist of the chlorinated lime produced by one manufacturer, at one plant, from the same materials, and under essentially the same manufacturing conditions provided the operation is continuous. In the event the process is a batch operation, each batch shall constitute a lot (see 6.3).

Source: https://assist.dla.mil -- Downloaded: 20261O-26T04:06Z
Check the source to verify that this is the current version before use.

4.2.2 Sampling.

4.2.2.1 For examination of packaging. Sampling shall be conducted in accordance with MIL-STD-105.

4.2.2.2 For chlorinated lime test. See 6.5 for sampling and testing precautions. Sampling shall be conducted in accordance with table II. A representative specimen of approximately 500 grams (g) shall be removed from each sample container and placed in a suitable clean, dry container labeled to identify the lot and container from which it was taken.

TABLE II. Sampling for chlorinated lime test

Number of containers in batch or lot	Number of sample containers
3 to 150	3
151 to 1,200	5
1,201 to 7,000	8
7,001 to 20,000	10
Over 20,000	20

4.2.2.3 For container leakage test. Sampling shall be conducted in accordance with MIL-STD-105.

4.2.3 Inspection procedure.

4.2.3.1 For examination of packaging. The sample unit shall be one filled unit container, ready for shipment. Sample unit containers shall be examined for the following defects using an AQL of 1.0 percent defective:

(a) Contents per container not as specified
(b) Container not as specified
(c) Container closure not as specified
(d) Container damaged or leaking
(e) Unitization not as specified
(f) Marking incorrect, missing, or illegible

4.2.3.2 For chlorinated lime test. Each sample specimen taken in 4.2.2.2 shall be tested as specified in 4.2.4. Failure of any test by any specimen shall be cause for rejection of the lot represented.

4.2.3.3 For container leakage test. The sample unit shall be one container. The sample containers selected in 4.2.3.3 shall be tested as specified in 4.2.5 using an AQL of 1.0 percent defective.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:06Z
Check the source to verify that this is the current version before use.

4.2.4 Chlorinated lime tests. See 6.5 for sampling and testing precautions. Water in accordance with ASTM D1193 and reagent grade chemicals shall be used throughout the tests. Where applicable, blank determinations shall be run and corrections applied where significant. Tests shall be conducted as follows:

4.2.4.1 Available chlorine.

4.2.4.1.1 Reagents.

(a) Sodium arsenite solution (0.1N). Dissolve exactly 4.948 g of arsenous oxide in 150 milliliters (mL) of warm water containing approximately 3 g of sodium hydroxide. Cool, neutralize the excess alkali with dilute sulfuric acid (1 to 3), using phenolphthalein as the indicator, until the solution is just decolorized. Add 300 mL of water containing about 25 g of sodium bicarbonate. If a pink color develops, add a few drops of the dilute sulfuric acid to decolorize the solution. Transfer quantitatively to a 1-liter (L) volumetric flask, dilute to volume, and mix.

(b) Starch solution. Mix approximately 2 g of soluble starch with sufficient cold water to form a thin slurry. Add the slurry to approximately 1 L of boiling water. Add 1 g of salicylic acid and boil until the solution is clear. Cool and store in a glass stoppered bottle.

(c) Standard 0.1N iodine solution. Mix 12.70 $\pm$ 0.05 g of iodine with twice its weight of potassium iodide. Dissolve in a small quantity of water, filter into a 1-L volumetric flask, dilute to the mark, and mix well. Pipet 50 mL of the sodium arsenite solution into an Erlenmeyer flask. Dilute with 100 mL water and add approximately 5 g of sodium bicarbonate. Add 5 mL of starch solution and titrate with iodine solution from a buret until a permanent blue color is obtained (Note 1: iodine solution should be added cautiously and dropwise near the endpoint). Calculate normality of the iodine solution as follows:

$$\text{Normality of iodine solution} = \frac{5}{V}$$

where: V = Milliliters of iodine solution used.

4.2.4.1.2 Procedure. Weigh to the nearest 0.01 g, 5.0 g of specimen and quantitatively transfer to a porcelain mortar. Add 30 to 40 mL of water and grind and mix until a smooth paste is obtained. Add more water, stir well with the pestle, allow the insolubles to settle for a few seconds, and decant the supernatant liquid into a 1-L volumetric flask. Add more water to the insolubles in the mortar; grind, mix, and decant as before. Repeat the operation until all of the material has been transferred to the volumetric flask. Rinse the mortar and pestle and add the rinsings to the volumetric flask. Dilute to the mark with water. Mix thoroughly. Without allowing the material to settle, pipet a 50-mL aliquot into a 250-mL Erlenmeyer flask containing 50 mL of water. From a buret or pipet, add 50 mL of 0.1N sodium arsenite solution. Add an

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:06Z
Check the source to verify that this is the current version before use.

excess of sodium bicarbonate (5 to 10 g) and 5 mL of starch solution. Titrate the excess sodium arsenite solution with standard 0.1N iodine solution from a buret until a permanent blue color is obtained (Note 1, above, is applicable). Calculate percent by weight available chlorine as follows:

$$\text{Percent available chlorine} = \frac{3.546\ (AC - BD)}{W}$$

where: A = Milliliters of sodium arsenite solution used,
B = Milliliters of iodine solution used,
C = Normality of sodium arsenite solution,
D = Normality of iodine solution, and
W = Weight, in grams, of specimen in aliquot.

4.2.4.2 Loss of available chlorine on heating. Place 15.00 g of specimen in a test tube (6 inches long and 1 inch in diameter), and insert a rubber stopper carrying an air condenser (glass tube) 15 inches long and 1/4 inch in internal diameter. The tube must extend exactly 1/2 inch beyond the stopper into the test tube. Place the test tube in a steam bath at 100° ± 2°C for 2 hours; a water bath shall not be used. At the end of the heating period remove the tube, substitute a solid rubber stopper for the air condenser stopper, and allow to cool to room temperature. Transfer the material to a porcelain mortar and proceed from this point with the determination of available chlorine as described in 4.2.4.1, except that instead of a 50-mL aliquot, use a 40-mL aliquot. Calculate the percent available chlorine of the heated specimen. Calculate the percent by weight loss of available chlorine as follows:

$$\text{Percent loss of available chlorine} = \frac{100(A - B)}{A}$$

where: A = Percent available chlorine (4.2.4.1) and
B = Percent available chlorine after heating.

4.2.4.3 Moisture.

4.2.4.3.1 Apparatus. Fit a round-bottom flask of 500 mL capacity with a reflux column of approximately 1 inch in diameter and from 12 to 16 inches in length, containing projections to prevent drops from falling from the top of the column into the flask, with a connecting tube at the top of the reflux column. Use ground-glass joints without a lubricant. Insulate, if necessary, so that all water is driven over in about 20 minutes. Drawn down the connecting tube, and fuze on 12 inches of 5 millimeter (mm) glass tubing. Bend the tube at an angle of about 20° from the horizontal with 2 inches at the outlet and bend directly downward with a ground-glass connection fitted to a water-cooled condenser with straight inner tube about 12 inches long. During the determination, place the outlet of the condenser 1/2 inch above the surface of the liquid and insert for at least 1 inch into a receiver of either 100 mL Goetz centrifuge tubing with a 1-mL graduated stem at the bottom in 0.05 mL divisions, or a 100-mL oil tube with a 3-mL graduated stem in 0.1 mL divisions, depending upon the amount of moisture in the sample.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:06Z
Check the source to verify that this is the current version before use.

4.2.4.3.2 Procedure. Add 25 g of specimen to 100 mL of orthodichlorobenzene contained in a 500 mL flask. Shake contents and connect flask to reflux column. Place 75 mL of petroleum ether in the receiver and add 1 to 2 drops of wetting agent solution in petroleum ether, then heat the flask. The orthodichlorobenzene will drive the water up the column and into the condenser. After the orthodichlorobenzene condensation has reached the receiver, allow 25 mL of the liquid to accumulate in the receiver, which will remove most of the water from the condenser coil. If high precision is desired, or if there is any noticeable amount of water in the condenser coil, disconnect the connecting tube from the top of the condenser and wash out the condenser with a little of the above petroleum ether containing a drop of wetting agent. Regulate the size of the sample and type of receiver so that the water obtained will come within the calibrated stem readings. Calculate percent by weight moisture as follows:

$$\text{Percent moisture} = \frac{100\ V}{W}$$

where: V = Milliliters of water collected and
W = Weight, in grams, of sample.

4.2.4.4 Total mixed oxides of heavy metals plus aluminum oxide. Weigh to the nearest 0.01 g, 10.0 g of specimen into a porcelain casserole. Add 50 mL of water and stir the mixture. Use a watch glass to prevent splattering. Cautiously add 60 mL of 10-percent hydrogen peroxide, in small increments. Allow the reaction to subside and slowly add hydrochloric acid until the solution is distinctly acid (approximately 30 mL will be required). After the reaction subsides, rinse the watch glass into the casserole. Evaporate the solution to near dryness on a steam bath and dry in an oven at 120°C for 1 hour. Remove the casserole from the oven and cool. Using a watch glass to prevent splattering, carefully cover the residue with 30 mL of hydrochloric acid, dilute with hot water to approximately 150 mL, and digest on a steam bath for 10 minutes. Rinse the watch glass into the casserole. Filter the contents of the casserole through a filter paper conforming to type II, class 6 of NNN-P-1475. Wash the contents of the filter paper thoroughly with a hot solution of dilute (1 to 99) hydrochloric acid. Complete the washing with hot water. Discard the filter paper and residue. Add 10 mL of dilute nitric acid (1 to 4) to the filtrate in a beaker and boil for a few minutes. Nearly neutralize with ammonium hydroxide; then, using methyl red as the indicator, complete the neutralization with ammonium hydroxide and add 1 drop in excess. Boil for 1 to 2 minutes and filter through 9-centimeter filter paper conforming to type II, class 5 of NNN-P-1475. Wash the filter paper and its contents six times with hot 2-percent ammonium chloride solution to which has been added sufficient ammonium hydroxide to make it just alkaline to methyl red. Retain the filtrate. Place the filter paper and its contents in the original beaker and macerate in 10 mL of hydrochloric acid. Dilute with hot water to 150 mL. Add 3 drops of methyl red indicator, neutralize with ammonium hydroxide, and add 1 or 2 drops in excess. Boil for 1 or 2 minutes and filter through an 11-centimeter filter paper conforming to type II, class 5 of NNN-P-1475. Wash the

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:06Z
Check the source to verify that this is the current version before use.

filter paper and its contents 10 times with the hot 2-percent ammonium chloride solution (as specified above). Combine this filtrate with that retained above. Retain the precipitate. Adjust the combined filtrate to about 200 mL and transfer to a 300-mL Erlenmeyer flask. Add 2 mL of ammonium hydroxide, heat to boiling, remove heat source, and pass hydrogen sulfide through the solution for 15 minutes. Cover the flask and allow it to stand for 1 hour. If a precipitate forms, filter, wash the collected precipitate with the 2-percent ammonium chloride solution (as specified above), and combine this precipitate with the precipitate retained above. Ignite the combined precipitate in a crucible at 1000°C to constant weight, cool, and record weight as iron oxide, aluminum oxide, and the oxides of heavy metals. (Retain the ignited precipitate for the determination of iron.) Calculate the percent by weight mixed oxides of heavy metals plus aluminum oxide as follows:

$$\text{Percent mixed oxides plus aluminum oxide} = \frac{100\ A}{W}$$

where: A = Weight, in grams, of the ignited precipitate and
W = Weight, in grams, of specimen.

4.2.4.5 Iron.

4.2.4.5.1 Reagents.

(a) Stannous chloride. Dissolve 5 g of the crystallized stannous chloride in 10 mL of hot hydrochloric acid and dilute to 100 mL with water. Keep the solution in a closed dropping bottle containing metallic tin.

(b) Phosphoric acid mixture. Add slowly, while stirring, 150 mL of orthophosphoric acid and 150 mL of sulfuric acid to 500 mL of water. Dilute to 1 L with water and mix.

(c) Indicator. Make up a 0.3 percent aqueous solution of either the barium or sodium salt of diphenylamine sulfonate.

(d) Standard potassium dichromate. Dissolve 2.452 g of potassium dichromate in water and dilute to 1 L. Standardize against National Bureau of Standards standard sample No. 27b (Sibley Iron Ore).

(e) Mercuric chloride. Prepare a saturated solution of mercuric chloride in water.

4.2.4.5.2 Procedure. Add 2 g of fused potassium bisulfate to the retained ignited precipitate from 4.2.4.4. Slowly heat over a low flame and gradually increase the heat until the melt is cherry red and the oxides have dissolved. Allow the melt to cool and transfer it to a 250-mL beaker. Wash the crucible with hot water, receiving the water in the same beaker. Dilute to 50 mL, add 10 mL hydrochloric acid, and heat to boiling. Next add a solution of stannous chloride, drop by drop, while stirring, until the solution is decolorized and

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:06Z
Check the source to verify that this is the current version before use.

then add 1 drop more. Cool in an ice water bath, wash down the inside of the beaker with water, and add rapidly 10 mL of a cool, saturated solution of mercuric chloride. Stir the solution vigorously for 1 minute, add 15 mL of the phosphoric acid mixture and 3 drops of the indicator. Dilute to 150 mL with cold water and titrate with standard potassium dichromate solution. Take as the end point the stage at which a drop causes an intense deep-blue coloration that remains unchanged on the further addition of dichromate. Calculate percent by weight iron based on original sample.

$$\text{Percentage of iron} = \frac{AN\ 5.584}{W}$$

where: A = Milliliters of potassium dichromate,
N = Normality of potassium dichromate, and
W = Weight, in grams, of specimen (see 4.2.4.4).

4.2.4.6 Particle size. Determine particle size in accordance with method 2101 of Fed. Test Method Std. No. 536.

4.2.4.7 Bulk density. Weigh approximately 40.0 g of specimen, previously passed through a 1400 micrometer sieve, into a 100-mL graduated cylinder from which the lip has been removed. Stopper the graduate and pass a closely fitting glass sleeve, about 3 inches long, over it. Clamp the sleeve to a ringstand. Place a large rubber stopper under the cylinder and adjust the sleeve so that the graduate will be 10 centimeters above the rubber stopper when the base of the graduate touches the lower edge of the sleeve. Raise the graduate until it touches the sleeve, then release. Continue raising and dropping the graduate until 100 cycles are completed. Read the volume of the sample and calculate the bulk density in grams per milliliter.

4.2.5 Container leakage test. Place the container in each of the following positions, and leave it in each for a period of 15 minutes:

(a) Upright
(b) Upside down
(c) On one side (or one quadrant)
(d) On one end (or second quadrant)
(e) On other side (or fourth quadrant)

Examine the container after each period for any evidence of leakage.

4.2.6 Container venting. The contractor shall certify that the container venting requirements specified in 5.1.1 have been met.

5. PACKAGING

5.1 Unit packing. Unit packing shall be level A, B, or C as specified (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:06Z
Check the source to verify that this is the current version before use.

5.1.1 Level A. A quantity of 20.0 (+0.2 or -0) pounds (lb) of chlorinated lime shall be unit packed in a nominal 3-1/2-gallon (gal) capacity, removable head steel drum conforming to type III, class 6 of PPP-P-704, except that the drum shall conform to Department of Transportation (DOT) Specification 37A instead of 5B. In addition, the drum shall be designed to vent internal pressures in excess of 3 pounds per square inch (see 6.6), and yet prevent entry of the exterior atmosphere (see 4.2.6). The filled drum shall show no evidence of leakage when tested as specified in 4.2.5.

5.1.2 Level B. Chlorinated lime shall be packed as specified in 5.1.1, except that the exterior coating shall be a baked phenolic coating.

5.1.3 Level C. A quantity of 20.0 (+0.2 or -0) lb of chlorinated lime shall be packed in a 3-1/2-gal fiber drum conforming to DOT Specification 21C. The innermost ply of the fiber drum shall be a minimum 10-mil thick aluminum foil. Top and bottom chimes of the drum shall be galvanized. Bottom head shall have an innermost ply of minimum 2-mil thick aluminum foil and shall be waterproof when immersed in 8 inches of water for 24 hours. All inner and outer surfaces of the drum shall be free of dirt, oil, or grease.

5.2 Packing. Chlorinated lime, unit packed as specified in 5.1, shall require no further protection for shipment other than unitization.

5.3 Unitization. A uniform quantity of packs of chlorinated lime shall be palletized in accordance with type IV of MIL-STD-147, using storage aids 5 and 7, tie-down and load strap bonding means, and a softwood pallet conforming to type IV of NN-P-71.

5.4 Marking. Containers and pallet loads shall be marked in accordance with MIL-STD-129 and DOT regulations. Each container shall be marked to show the lot or batch number and date of manufacture of the chlorinated lime, a type II shelf life of two years, and the following "Directions for Use" and "Precautionary labeling."

5.4.1 Directions for use. Each drum shall be marked as follows:

DIRECTIONS FOR USE

Use only as directed by medical officer or sanitary engineer.

5.4.2 Precautionary labeling. Each shipping container shall be labeled to comply with the requirements of 16 CFR 1500 and 40 CFR 162. Precautionary labeling shall be as follows:

Source: https://assist.dla.mil -- Downloaded: 20261O-26T04:06Z
Check the source to verify that this is the currentversion before use.

DANGER! MAY BE FATAL IF SWALLOWED
MAY CAUSE BURNS
HARMFUL IF INHALED
STRONG OXIDANT

Use extreme caution when opening - contents may spray!
Avoid contact with eyes, skin, and clothing.
Avoid breathing dust.
Use with adequate ventilation.
Wash thoroughly after handling.
Avoid contamination of chlorinated lime with acids and oxidizable materials such as fuels, oils, paint products, disinfectants, and ammonia. Such contamination can cause release of hazardous gases.
Poisonous gases may be produced when heated.
Keep container closed and stored in a cool dry place.
Mix only in accordance with directions for use.

FIRST AID:

In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. For eyes get medical attention. Wash clothing before reuse.

POISON
Call a physician.

If swallowed: Immediately give milk, egg white, starch paste, or milk of magnesia by mouth. Do not induce vomiting.

Note to physician: Do not give acidic antidotes.

6. NOTES

6.1 Intended use. Chlorinated lime covered by this specification is intended for bleaching and as a general disinfectant.

6.2 Ordering data. Acquisition documents should specify the title, number, and date of this specification, and the level of unit packing required (see 5.1).

6.3 Batch. A batch is defined as that quantity of material which has been manufactured by some unit chemical process or subjected to some physical mixing operation intended to make the final product substantially uniform.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:06Z
Check the source to verify that this is the current version before use.

6.4 Significant places. For the purpose of determining conformance with this specification, an observed or calculated value should be rounded off "to the nearest unit" in the last right-hand place of figures used in expressing the limiting value, in accordance with the rounding-off method of ASTM E29.

6.5 Sampling and testing precautions. This specification covers inspection of chemical material which is potentially hazardous to personnel. It is important that sampling be done as rapidly and thoroughly as possible because of the chemical changes which the material undergoes upon exposure to the air. When opening containers of bleaching materials, personnel must be protected against the caustic effect of bleach in the eyes or on the skin, as well as the effect of chlorine gas on the lungs. All applicable safety rules, regulations, and procedures must be followed in the handling and processing of this material.

6.6 Vent seal cap liners. Vent seal cap liners may be utilized in the design of drums as specified in 5.1.1. Vent liners, if used, should be resistant to the chlorinated lime and should remain inert when in contact with the chlorinated lime. The use of vent seal cap liners should not be construed as relieving the contractor of his responsibilities to furnish the Government with items fully in conformance with the requirements of this specification.

Custodian:

Army - EA

Preparing activity:

Army - EA

Project No. 6810-AB31

☆U.S. GOVERNMENT PRINTING OFFICE: 1983-605-034/2470

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:06Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426

PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:06Z
Check the source to verify that this is the current version before use.