INCH-POUND

MIL-D-51468C(EA)
10 July 1992
SUPERSEDING
MIL-D-51468B(EA)
7 April 1988

MILITARY SPECIFICATION

DECONTAMINATION KIT, PERSONAL, M258A1

This specification is approved for use by the U.S. Army Chemical Research, Development and Engineering Center, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers one type of personal decontamination kit.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, U.S. Army Chemical Research, Development and Engineering Center, ATTN: SMCCR-PET-S, Aberdeen Proving Ground, MD 21010-5423 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 4230

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:06Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-1168 - Ammunition Lot Numbering

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

U.S. ARMY CHEMICAL RESEARCH, DEVELOPMENT AND ENGINEERING CENTER

DRAWINGS

5-77-2366 - Decontamination Kit, Personal, M258A1

SPECIAL PACKAGING INSTRUCTIONS (SPI)

P5-77-2366 - Decontamination Kit, Personal, M258A1

(Copies are available from Commander, U.S. Army Information Systems Command, ATTN: ASQNC-ARI-IOT, Rock Island, IL 61299-7210.)

2.2 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Materials and components.

3.1.1 Materials. All materials cited on Drawing 5-77-2366 or on the subsidiary drawings shall conform to the specifications listed thereon or to the specific characteristics set forth on the drawings.

3.1.2 Components. All components of the decontamination kit shall conform to the specifications and drawings listed on Drawing 5-77-2366 and subsidiary drawings.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:06Z
Check the source to verify that this is the currentversion before use.

3.2 Manufacture and assembly. The kit shall be manufactured and assembled in accordance with Drawing 5-77-2366 and subsidiary drawings.

3.3 Ampoule leakage. The ampoules shall not leak when tested as specified in 4.4.6.1.

3.4 Ampoule fill. Each ampoule shall be filled with decontaminating solution to a height of 43 millimeters (mm) to 51 mm, when tested as specified in 4.4.6.2.

3.5 Ampoule tip. The sealed end of the ampoule shall be rounded and smooth to the touch when tested as specified in 4.4.6.3.

3.6 Decon 1 and 2 packet leakage. The decon 1 packet and the decon 2 packet shall not leak when tested as specified in 4.4.6.4.

3.7 Decon 1 packet decontaminating solution content. The pad in the decon 1 packet shall contain 3.5 to 4.9 grams (g) of decontaminating solution when tested as specified in 4.4.6.5.

3.8 Decon 2 packet active chlorine content. The pad in the decon 2 packet shall have an active chlorine content of no less than 0.156 g when tested as specified in 4.4.6.6.

3.9 Decon 2 packet moisture content. The decon 2 packet shall have a total moisture content of no more than 8.5 percent by weight when tested as specified in 4.4.6.7.

3.10 Pad sticking. During removal, the pad shall not stick to the packet when tested as specified in 4.4.6.8.

3.11 Ampoule screen. The screen shall show no evidence of damage or separation in the heat seal area when tested as specified in 4.4.6.9.

3.12 Packet components. There shall be no missing or damaged decon 1 and decon 2 packet components when tested as specified in 4.4.6.10.

3.13 Strap tension. The welded area of the strap shall withstand a dead load of 18.0 ± 1.0 kilograms (kg) for 5 ± 1 seconds when tested as specified in 4.4.6.11.

3.14 First packet withdrawal. No other packets shall be pulled completely out of the kit when the first decon 1 packet is withdrawn from a filled kit when tested as specified in 4.4.6.12.

3.15 Pull. The assembled kit shall require 12 ± 6 pounds to open when tested in accordance with 4.4.6.13.

3.16 First article. When specified (see 6.2), a sample of kits shall be subjected to the first article inspection in accordance with 4.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:06Z
Check the source to verify that this is the current version before use.

3.16.1 Accelerated aging. The decontamination kit shall meet all the test requirements in this specification after accelerated aging as specified in 4.3.4.1.

3.16.2 Cold storage stability. The decontamination kit shall meet all the test requirements in this specification after cold storage as specified in 4.3.4.2.

3.17 Workmanship. The decontamination kit and all components and subassemblies thereof shall be free from defects and contamination by foreign matter such as dirt, grease, and oil.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.1.2 Contractor assurance of compliance. The contractor's quality program or detailed inspection system shall provide assurance of compliance of all characteristics with the applicable drawing, special packaging instruction, and specification requirements using, as a minimum, the conformance criteria specified herein.

4.1.3 Alternative inspection provisions. Alternative inspection procedures, methods, or equipment, such as statistical process control, tool control, and other types of sampling procedures may be used by the contractor when they provide, as a minimum, the level of quality assurance required by the inspection provisions specified herein. Prior to applying such alternative procedures, methods, or equipment, the contractor shall describe them in a written proposal submitted to the Government for evaluation and approval. (See 6.5.) When required, the contractor shall demonstrate that the effectiveness of each proposed alternative is equal to or better than the quality assurance provisions specified herein. In

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:06Z
Check the source to verify that this is the current version before use.

cases of dispute as to whether the contractor's proposed alternative provides equal quality assurance, the provisions of this specification shall apply. All approved alternative inspection provisions shall be specifically incorporated into the contractor's quality program or detailed inspection system, as applicable.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

(a) First article inspection (see 4.3)
(b) Quality conformance inspection (see 4.4)

4.3 First article inspection.

4.3.1 Inspections to be performed. As determined by the Government, the first article sample items shall be examined and tested in accordance with this specification using either the first article procedures in this specification or other first article procedures which will be provided by the Government. As determined by the Government, the sample first article items may be subjected to any or all of the examinations and tests specified in this specification and be inspected for compliance with any or all of the requirements of the applicable drawings and special packaging instructions.

4.3.2 Lotting. A first article lot of not less than 1000 kits shall be manufactured and packaged using the same methods, materials, equipment, and processes as will be used during regular production. The first article sample shall be submitted for inspection and approval in accordance with the terms of the contract.

4.3.3 Sampling and inspection procedure.

4.3.3.1 For examination. Sampling and inspection procedure for examination shall be as specified in 4.4.2.1 and 4.4.3.1.

4.3.3.2 For test. Sampling and inspection procedure for test shall be as specified in table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:06Z
Check the source to verify that this is the current version before use.

Table I. First article tests

Requirement	Sample size	Accept/reject criteria	Test paragraph
Accelerated aging (3.16.1)	12 complete kits	———	4.3.4.1
Cold storage stability (3.16.2)	12 complete kits	———	4.3.4.2
Test after accelerated aging or cold storage:	———	———	———
Ampoule leakage (3.3)	90 ampoules	Acc 0, rej 1	4.4.6.1
Ampoule fill (3.4)	30 ampoules	Acc 0, rej 1	4.4.6.2
Ampoule tip (3.5)	90 ampoules*	Acc 0, rej 1	4.4.6.3
Decon 1 packet leakage (3.6)	30 packets	Acc 0, rej 1	4.4.6.4
Decon 2 packet leakage (3.6)	30 packets	Acc 0, rej 1	4.4.6.4
Decon 1 packet decontaminating solution content (3.7)	10 packets (no more than 1 per kit)	Acc 0, rej 1	4.4.6.5
Decon 2 packet active chlorine content (3.8)	10 packets (no more than 1 per kit)	Acc 0, rej 1	4.4.6.6
Decon 2 packet moisture content (3.9)	10 packets (no more than 1 per kit)	Acc 0, rej 1	4.4.6.7
Pad sticking (3.10)	30** Decon I packets 30*** Decon II packets	Acc 0, rej 1	4.4.6.8
Ampoule screen (3.11)	30*** Decon II packets	Acc 0, rej 1	4.4.6.9
Packet components (3.12)	30** Decon I packets 30*** Decon II packets	Acc 0, rej 1	4.4.6.10
Strap tension (3.13)	10 kits	Acc 0, rej 1	4.4.6.11
First packet withdrawal (3.14)	10 kits	Acc 0, rej 1	4.4.6.12
Pull (3.15)	10 kits	Acc 0, rej 1	4.4.6.13

* Same sample ampoules used for ampoule leakage test may be used.
** Same sample packets used for decon I leakage test may be used.
*** Same sample packets used for decon II leakage test may be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:06Z
Check the source to verify that this is the current version before use.

4.3.4 Tests. Tests shall be conducted as follows:

4.3.4.1 Accelerated aging. Place the decontamination kits in an oven at 43° ± 1°C for 24 hours. Remove the kits from the oven and allow to reach ambient temperature.

4.3.4.2 Cold storage stability. Store the decontamination kits at -54° ± 1°C for 24 hours. Remove the kits from cold storage and allow to reach ambient temperature.

4.3.5 Acceptance criteria. If any first article sample item fails to comply with any of the applicable requirements, the first article lot shall be rejected. The Government reserves the right to terminate inspection upon any failure to comply with any of the requirements. The contractor shall obtain written approval from the contracting activity prior to proceeding with regular production.

4.4 Quality conformance inspection.

4.4.1 Lotting. A lot shall consist of the items produced by one manufacturer, at one plant and under essentially the same manufacturing conditions. However, no more than one interfix number of decon 1 packets or decon 2 packets shall be represented in any one lot of kits. Each lot shall be identified and controlled in accordance with MIL-STD-1168.

4.4.2 Sampling.

4.4.2.1 For examination. Sampling shall be conducted in accordance with the classification of characteristics in 4.4.5 and, when specified, table II. Samples shall be selected at random.

4.4.2.2 For test. Sampling shall be conducted as specified in table III (see 6.4 for sampling and testing precautions).

4.4.3 Inspection procedure.

4.4.3.1 For examination. Every item in the lot shall be inspected for critical characteristics. The lot represented shall be rejected when nonconformance to a critical characteristic is found. Sample items and the packaging thereof shall be examined in accordance with the classification of characteristics in 4.4.5. Failure of any sample item to conform to any characteristic in the classification of characteristics based on the sampling and acceptance criteria specified therein shall be cause for rejection of the lot represented.

4.4.3.2 For test. Sample kits shall be tested as specified in table III.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:06Z
Check the source to verify that this is the current version before use.

TABLE II. Sampling

Lot size	Inspection levels and sample sizes										
	I	II	III	IV	V	VI	VII	VIII	IX	X	XI
2 to 8	*	*	*	*	*	*	*	*	5	3	2
9 to 15	*	*	*	*	*	*	13	8	5	3	2
16 to 25	*	*	*	*	*	20	13	8	5	3	3
26 to 50	*	*	*	*	32	20	13	8	5	5	5
51 to 90	*	*	*	50	32	20	13	8	7	6	5
91 to 150	*	*	125	50	32	20	13	12	11	7	6
151 to 280	*	*	125	50	32	20	20	19	13	10	7
281 to 500	*	315	125	50	48	47	29	21	16	11	9
501 to 1200	*	315	125	75	73	47	34	27	19	15	11
1201 to 3200	1250	315	125	116	73	53	42	35	23	18	13
3201 to 10000	1250	315	192	116	86	68	50	38	29	22	15
10001 to 35000	1250	315	294	135	108	77	60	46	35	29	15
35001 to 150000	1250	490	294	170	123	96	74	56	40	29	15
150001 to 500000	1250	715	345	200	156	119	90	64	40	29	15
500001 and over	1250	715	435	244	189	143	102	64	40	29	15

*Indicates one hundred percent inspection. If sample size exceeds lot size, perform one hundred percent inspection.

Accept the lot represented on zero nonconforming characteristics and reject the lot represented on one or more nonconforming characteristics for all inspection levels.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:06Z
Check the source to verify that this is the current version before use.

Table III. Quality conformance tests

Requirement	Sample size and accept/reject criteria	Test paragraph
Ampoule leakage (3.3)	Table II, Level VII; prior to assembly in packets	4.4.6.1
Ampoule fill (3.4)	Table II, Level X; prior to assembly in packets	4.4.6.2
Ampoule tip (3.5)	Table II, Level IX; prior to assembly in packets*	4.4.6.3
Decon 1 packet leakage (3.6)	Table II, Level X; prior to assembly in kits	4.4.6.4
Decon 2 packet leakage (3.6)	Table II, Level X; prior to assembly in kits	4.4.6.4
Decon 1 packet decontaminating solution content (3.7)	20, prior to assembly in kits; Acc 0, rej 1	4.4.6.5
Decon 2 packet active chlorine content (3.8)	20, prior to assembly in kits; Acc 0, rej 1	4.4.6.6
Decon 2 packet moisture content (3.9)	Table II, Level XI; prior to assembly in kits	4.4.6.7
Pad sticking (3.10)		
Decon I packet	Table II, Level XI; prior to assembly in kits**	4.4.6.8
Decon II packet	Table II, Level XI; prior to assembly in kits***	4.4.6.8
Ampoule screen (3.11)	Table II, Level XI; prior to assembly in kits***	4.4.6.9
Decon 1 packet components (3.12)	Table II, Level XI; prior to assembly in kits**	4.4.6.10
Decon 2 packet components (3.12)	Table II, Level XI; prior to assembly in kits***	4.4.6.10
Strap tension (3.13)	Table II, Level XI	4.4.6.11
First packet withdrawal (3.14)	Table II, Level X	4.4.6.12
Pull (3.15)	Table II, Level X	4.4.6.13

* Same sample ampoules used for ampoule leakage test may be used.
** Same sample packets used for decon I leakage test may be used.
*** Same sample packets used for decon II leakage test may be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:06Z
Check the source to verify that this is the current version before use.

4.4.4 Inspection characteristics. Critical characteristics are characteristics whose nonconformance to specified requirements is likely to result in hazardous or unsafe conditions for individuals using, maintaining, or depending upon the product or whose nonconformance to specified requirements is likely to prevent performance of the tactical function of a major end item. Major characteristics are characteristics whose nonconformance to specified requirements is likely to result in failure or to reduce materially the usability of the item for its intended purpose. Minor characteristics are characteristics whose nonconformance to specified requirements is not likely to reduce materially the operation or usability of the item for its intended purpose.

4.4.5 Classification of characteristics. Quality conformance examinations shall be as specified in the following classification of characteristics paragraphs. When specified herein, accept on 0 and reject on 1 attributes sampling inspection shall be performed on the designated characteristics using the stated levels in table II for selection of sample sizes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:06Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.5(a)	Decontamination kit, personal, M258A1	1 OF 1	5-77-2366
			NEXT HIGHER ASSY

CATEGORY	CHARACTERISTIC	SAMPLING AND ACCEPTANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD
Critical	None defined			
Major				
101	Case and components undamaged	Table II, Level VII	3.2	VI
102	Lot number evident, correct, and legible	Table II, Level VII	3.2	VI and CE
103	Case marking evident, correct, and legible	Table II, Level VII	3.2	VI and CE
104	Specified components correctly assembled	Table II, Level VII	3.2	VI
Minor				
201	Packets placed correctly inside kit	Table II, Level IX	3.2	VI
202	Cut edges of strap free of loose threads	Table II, Level IX	3.2	VI
203	Weld dimensions on strap	Table II, Level IX	3.2	CE
204	Workmanship (foreign matter in or on case)	Table II, Level IX	3.17	VI

NOTES:
CE - Commercial inspection equipment
VI - Visual inspection

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:06Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.5(b)	Ampoule filled		5-77-2372
			NEXT HIGHER ASSY 5-77-2374

CATEGORY	CHARACTERISTIC	SAMPLING AND ACCEPTANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD
Critical	None defined			
Major	None defined			
Minor				
201	Workmanship	Table II, Level IX	3.17	VI

NOTES:

CE - Commercial inspection equipment
VI - Visual inspection

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:06Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.5(c)	Decon 1 packet		5-77-2375
			NEXT HIGHER ASSY 5-77-2366

CATEGORY	CHARACTERISTIC	SAMPLING AND ACCEPTANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD
Critical	None defined			
Major				
101	Packet heat seal width	Table II, Level VII	3.2	CE
102	Packet notch dimensions	Table II, Level VII	3.2	CE
103	Packet notch locations correct	Table II, Level VII	3.2	CE
104	Packet notches cleanly cut	Table II, Level VII	3.2	VI
105	Packet marking evident, correct, and legible	Table II, Level VII	3.2	VI and CE
Minor				
201	Workmanship	Table II, Level IX	3.17	VI

NOTES:
CE - Commercial inspection equipment
VI - Visual inspection

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:06Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.5(d)	Decon 2 packet		5-77-2376
			NEXT HIGHER ASSY 5-77-2366

CATEGORY	CHARACTERISTIC	SAMPLING AND ACCEPTANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD
Critical	None defined			
Major				
101	Packet heat seal width	Table II, Level VII	3.2	CE
102	Packet notch dimensions	Table II, Level VII	3.2	CE
103	Packet notch locations correct	Table II, Level VII	3.2	CE
104	Packet notches cleanly cut	Table II, Level VII	3.2	VI
105	Packet marking evident, correct, and legible	Table II, Level VII	3.2	VI and CE
Minor				
201	Workmanship	Table II, Level IX	3.17	VI

NOTES:
CE - Commercial inspection equipment
VI - Visual inspection

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:06Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.5(e)	Packaging		P5-77-2366
			NEXT HIGHER ASSY

CATEGORY	CHARACTERISTIC	SAMPLING AND ACCEPTANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD
Critical	None defined			
Major				
101	Intermediate packing and packing container as specified	Table II, Level X	5.1	VI and CE
102	Contents of intermediate packing and packing container as specified	Table II, Level X	5.1	VI
103	Intermediate packing and packing container closure as specified	Table II, Level X	5.1	VI and CE
104	Intermediate packing and packing container undamaged	Table II, Level X	5.1	VI
105	Marking evident, correct, and legible	Table II, Level X	5.1	VI and CE
106	Fiberboard packing aids evident (where required) and as specified	Table II, Level X	5.1	VI and CE
107	Shelf life marking evident, correct, and legible	Table II, Level X	5.1	VI and CE

NOTES:
CE - Commercial inspection equipment
VI - Visual inspection

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:06Z
Check the source to verify that this is the current version before use.

4.4.6 Tests. Tests shall be conducted as follows (see 6.4 for sampling and testing precautions):

4.4.6.1 Ampoule leakage. Place the ampoules in a vacuum tank and weight with a suitable cover to ensure complete submersion when the tank is filled with water. Place sufficient water soluble dye in the water to impart visible color to a drop of solution. Reduce the pressure in the tank to 127 mm of mercury or less absolute, maintain at that pressure for at least 25 minutes, and then pressurize to ambient. After no less than 20 minutes at ambient pressure, remove the ampoules from the tank, rinse thoroughly in clean water, and spread on a drying screen. Colored solution in an ampoule shall be considered evidence of leakage.

4.4.6.2 Ampoule fill. With the ampoule held vertically on a flat surface, measure the height of the meniscus above the surface to the nearest millimeter.

4.4.6.3 Ampoule tip. Hold the ampoule and touch the sealed end. Inspect for evidence of a pointed tip.

4.4.6.4 Packet leakage. Submerge the packets for at least 30 seconds in ambient temperature water in a transparent vacuum tank under a vacuum of 7 ± 1 pounds per square inch. Keep the packet submerged in a vertical position with the uppermost surface covered by no more than 25 mm of water. Continuously examine the packet during the time it is submerged for evidence of bubbles. The presence of bubbles shall be considered evidence of leakage.

4.4.6.5 Decon 1 packet decontaminating solution content. Weigh the packet to the nearest 0.01 g. Open the packet and remove the pad. Wash the pad thoroughly with water. Place the pad and opened packet in an air circulation oven and dry at 105° ± 2°C for 60 ± 5 minutes. Weigh the entire packet and pad to the nearest 0.01 g. Calculate the weight of the solution on the pad as follows:

$$\text{Weight of solution} = 1.07(A - B)$$

where: A = Weight of pad and packet before drying, in grams, and
B = Weight of pad and packet after washing and drying, in grams.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:06Z
Check the source to verify that this is the current version before use.

4.4.6.6 Decon 2 packet active chlorine content. Remove the pad from the packet and place in a 250-milliliter (mL) flask. Add about 50 mL of water to the flask and mix thoroughly. Add 20 mL of a 10-percent aqueous solution of potassium iodide and 3 mL of glacial acetic acid, and allow to stand for 2 to 5 minutes. Titrate the liberated iodine with 0.1*N* sodium thiosulfate solution using starch indicator. Calculate the active chlorine content as follows:

$$\text{Active chlorine content in grams} = 0.0176AB$$

where: A = Milliliters of sodium thiosulfate solution used in titration, and
B = Normality of the sodium thiosulfate solution.

4.4.6.7 Decon 2 packet moisture content. Open packet and remove pad. Place pad in tared weighing dish and weigh to the nearest 0.01 g. Place weighed pad and weighing dish in oven and dry at 105° ± 5°C for 60 ± 5 minutes. Remove from oven and cool in desiccator for not less than 3 minutes. Remove from desiccator and reweigh to the nearest 0.01 g. Calculate the percent moisture as follows:

$$\text{Percent moisture} = \frac{100(A-B)}{A}$$

where: A = Initial weight of pad in grams, and
B = Final weight of pad in grams.

4.4.6.8 Pad sticking. Open the packet and remove the pad.

4.4.6.9 Ampoule screen. Open the packet and remove screen and ampoule assembly. Visually inspect the screen for compliance to the specified requirement.

4.4.6.10 Packet components. Empty the packets and visually inspect the components.

4.4.6.11 Strap tension. Cut the strap off the kit so that the welded area is approximately in the center of the strap sample. Attach each end of the strap to a suitable device and apply a load of 18.0 ± 1.0 kg for 5 ± 1 seconds. The test may be performed without cutting the strap from the kit provided that the specified load is applied to the welded area.

4.4.6.12 First packet withdrawal. Hold the kit in an upright position and withdraw the first decon 1 packet nearest the front of the kit. Observe if any of the remaining packets have been pulled completely out of the kit.

4.4.6.13 Pull. Using a test fixture to hold the cover and case in place and a pull tester operated at 70° ± 20°F and 50 ± 20 percent relative humidity, pull the cover from the case at a rate of 12 ± 2 inches/minute. Do not use a lubricant on the parts to facilitate this test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:06Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Packaging. Packaging shall be as specified in P5-77-2366.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The M258A1 kit is intended for use in the decontamination of chemical agents on skin and personal equipment.

6.2 Acquisition requirements. Acquisition documents must specify the following:

(a) Title, number, and date of this specification
(b) Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1)
(c) Level of preservation and packing required (see 5.1)
(d) Shelf life code
(e) Palletization
(f) First article:

(1) Time allowed for contractor submission of samples for Government test and evaluation after award of contract when testing is performed by the Government.
(2) Name and address of test facility and shipping instructions when testing is performed by the Government.
(3) Time required for the Government to notify the contractor whether or not to proceed with production.

6.3 Component specifications.

DOD-C-51464 - Chloramine B (Metric)
DOD-D-51467 - Decontaminating Solutions (Metric)

6.4 Sampling and testing precautions. This specification covers inspection of chemical material which is potentially hazardous to personnel (toxic by ingestion, eye irritant). All applicable safety rules, regulations, and procedures must be followed in the handling and processing of this material. Refer to appropriate material safety data sheets for any safety precautions.

6.5 Submission of alternative inspection provisions. Proposed alternative inspection provisions should be submitted by the contractor to the procuring contracting officer for evaluation and approval by the technical activity responsible for preparation of this specification.

Source: https://assist.dla.mil -- Downloaded: 2026l0-26T04:06Z
Check the source to verify that this is the currentversion before use.

6.6 Changes from previous issues. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

6.7 Subject term (key word) listing.

Ampoule
Decontaminating
Decontaminating solutions
Packets
Pads

Custodian:

Army - EA

Preparing activity:

Army - EA

Project No. 4230-A098

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:06Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of this form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-D-51468C(EA)	920710

3. DOCUMENT TITLE
DECONTAMINATION KIT, PERSONAL, M258A1

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME *(Last, First, Middle Initial)*	b. ORGANIZATION	
c. ADDRESS *(Include Zip Code)*	d. TELEPHONE *(Include Area Code)* (1) Commercial (2) AUTOVON *(If Applicable)*	7. DATE SUBMITTED *(YYMMDD)*

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE *(Include Area Code)*	
U.S. Army Chemical Research, Development and Engineering Center	(1) Commercial (301) 671-3259	(2) AUTOVON DSN 584-3259
c. ADDRESS *(Include Zip Code)* Commander U.S. Army CRDEC ATTN: SMCCR-PET-S Aberdeen Proving Ground, MD 21010-5423	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

DD Form 1426, OCT 89 *Previous editions are obsolete.*

Source: https://assist.dla.mil -- Downloaded: 2026-02-26T04:06Z
Check the source to verify that this is the current version before use.