MILITARY SPECIFICATION

FUEL AND PRESSURE UNIT, PORTABLE FLAME THROWER, M9

1. SCOPE

1.1 This specification covers the M9 fuel and pressure unit for use with the M9-7 flame thrower.

2. APPLICABLE DOCUMENTS

2.1 Government documents. The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

PPP-B-601	-	Boxes, Wood, Cleated-Plywood.
PPP-B-621	-	Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636	-	Box, Fiberboard.

MILITARY

MIL-P-116	-	Preservation, Methods of.
MIL-B-121	-	Barrier Material, Greaseproofed, Waterproofed, Flexible.
MIL-W-8604	-	Welding of Aluminum Alloys: Process For.
MIL-L-21260	-	Lubricating Oil, Internal-Combustion Engine, Preservative.

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	-	Marking for Shipment and Storage.
MIL-STD-810	-	Environmental Test Methods for Aerospace and Ground Equipment.

FSC 1040

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

DRAWINGS

US ARMY MUNITIONS COMMAND

DL81-1-6839 - Fuel and Pressure Unit, Portable Flame Thrower, M9.

(All drawings referenced in this specification are listed on the above Edgewood Arsenal drawing.)

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

UNIFORM CLASSIFICATION COMMITTEE

Uniform Freight Classification

(Application for copies of these ratings, rules and regulations should be addressed to Uniform Classification Committee, 202 Union Station, 516 West Jackson Boulevard, Chicago, Illinois 60606.)

3. REQUIREMENTS

3.1 Materials and components.

3.1.1 Materials. All materials cited on Drawing DL81-1-6839 or on the subsidiary drawings shall conform to the specification listed thereon, or to the specific characteristics set forth on the drawings.

3.1.2 Components. All components shall conform to the specifications and drawings listed on Drawing DL81-1-6839 and subsidiary drawings.

3.2 Assembly. The fuel and pressure unit shall be assembled as shown on Drawing E81-1-6839.

Source: https://assist.dla.mil -- Downloaded: 20261O-26T04:05Z
Check the source to verify that this is the current version before use.

3.3 High pressure sphere (Dwg D81-1-6863).

3.3.1 Permanent volumetric expansion. The permanent volumetric expansion of the sphere shall not exceed 2-percent of the volumetric expansion at a pressure of 3,350 ± 50 pounds per square inch gage (psig) when tested in accordance with 4.3.4.1.

3.3.2 Burst. The sphere shall not burst at a minimum pressure of 5,000 psig when tested in accordance with 4.2.4.4.

3.4 Fuel tank assembly (Dwg D81-1-6900).

3.4.1 Permanent volumetric expansion. The permanent volumetric expansion of the tank assembly shall not exceed 12-percent of the total volumetric expansion at a pressure of 450 ± 10 psig when tested in accordance with 4.3.4.1.

3.4.2 Leakage. The tank assembly shall not leak air at a pressure of 330 to 340 psig, when tested in accordance with 4.3.4.2.

3.4.3 Burst. The tank assembly shall not burst at a minimum pressure of 700 psig when tested in accordance with 4.2.4.4.

3.4.4 Welding procedure (fuel tank).

(a) Approval. Prior to the start of production, the supplier shall establish an approved welding procedure in accordance with MIL-W-8604, except that the paragraph describing maintenance sampling shall not be applicable. The welding procedure shall include provisions for repair and rework of weldment. The supplier shall submit with his proposed welding procedure, the quality control procedure to be used during production, to assure that the welding procedure is maintained and controlled, and is producing welds conforming to MIL-W-8604. The supplier shall requalify his procedure whenever it varies from the accepted welding procedure. Compliance with this requirements shall be in accordance with 4.2.2 and Edgewood Arsenal Radiographic Standard R6-2.

(b) Production. During production, the supplier shall utilize, maintain, and control the approved welding procedure. Compliance with this requirement shall be in accordance with Edgewood Arsenal Radiographic Standard R6-2 and 4.3.3.3.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:05Z
Check the source to verify that this is the currentversion before use.

3.5 High pressure valve (Dwg D81-1-6848).

3.5.1 Leakage (Dwg D81-1-6848). The valve assembly shall not leak air at a pressure of 3,350 ± 50 psig (see 6.4), when tested in accordance with 4.3.4.3.

3.5.2 Safety disk plug (Dwg D81-1-6859).

3.5.2.1 Leakage. The safety disk plug shall not leak at a pressure of 2,000 to 2100 psig (see 6.4), when tested in accordance with 4.3.4.3(a).

3.5.2.2 Burst. The safety disk shall burst between 2300 and 2700 psig (see 6.4), when tested in accordance with 4.3.4.3(b).

3.6 Check valve assembly (Dwg C81-1-6892).

3.6.1 Porosity. The valve shall not leak air when tested in accordance with 4.3.4.4(a).

3.6.2 Valve seat. The valve seat shall not leak air at a rate greater than 1.5 liters per minute when tested in accordance with 4.3.4.4(b).

3.6.3 Safety disk plug (Dwg B81-1-6893).

3.6.3.1 Leakage. The safety disk plug shall not leak air at a pressure of 330 to 340 psig, when tested in accordance with 4.3.4.4(c).

3.6.3.2 Burst. The safety disk shall burst between 400 and 430 psig with temperature at 70° ± 10° F, when tested in accordance with 4.3.4.4(d).

3.7 Pneumatic hose (Dwg C81-1-6925). The hose shall not leak air at a pressure of 3,350 ± 50 psig when tested in accordance with 4.3.4.5.

3.8 Fuel and pressure assembly (Dwg E81-1-6839). The fuel and pressure assembly shall meet the following requirements when tested in accordance with 4.3.4.6.

(a) The assembly shall not leak air when the high pressure sphere is charged to a pressure of 2,000 to 2,100 psig.

(b) The fuel tank pressure shall be 285 ± 45 psig during the 5 minute leak test period.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:05Z
Check the source to verify that this is the currentversion before use.

(c) During and after the 3-second burst, the fuel tank pressure shall be 285 ± 45 psig.

(d) The bleeder valve in the fuel filler cap shall bleed off the remaining pressure.

3.9 Filler cap assembly. The filler cap assembly shall not leak air at a pressure of 330 -340 psig, when tested in accordance with 4.3.4.7.

3.10 Preproduction.

3.10.1 Fuel and pressure assembly.

3.10.1.1 Vibration. The fuel and pressure assembly shall conform to 3.8 when tested in accordance with 4.2.4.1(a).

3.10.1.2 Mechanical shock. The fuel and pressure assembly shall conform to 3.8 when tested in accordance with 4.2.4.1(b).

3.10.2 High pressure safety disk.

3.10.2.1 High temperature. The high pressure safety disk shall burst between 2200 and 3000 psig at a temperature of 155° F when tested in accordance with 4.2.4.2(a).

3.10.2.2 Low temperature. The high pressure safety disk shall burst between 2200 and 3000 psig at a temperature of -40°F when tested in accordance with 4.2.4.2(b).

3.10.3 Low pressure safety disk.

3.10.3.1 High temperature. The low pressure safety disk shall burst between 375 and 425 psig at a temperature of 155°F when tested in accordance with 4.2.4.3(a).

3.10.3.2 Low temperature. The low pressure safety disk shall burst between 425 and 475 psig at a temperature of -40°F when tested in accordance with 4.2.4.3(b).

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:05Z
Check the source to verify that this is the currentversion before use.

3.11 Workmanship. The fuel and pressure unit shall be free from damage such as dents, kinks, and scores and foreign matter (dirt, metal chips, grease, oil) which could affect its intended use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.

4.1.1 Supplier's responsibility. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specifications where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.2 Objective evidence. The supplier shall provide objective evidence acceptable to the contracting officer that the requirements of 3.1 and section 5 for which specific inspection has not been provided in this specification have been satisfied.

4.2 Preproduction.

4.2.1 Sample. Prior to the start of regular production, a preproduction lot of 37 fuel and pressure assemblies and 33 each additional low and high pressure safety disks shall be produced using the same methods, materials, and equipment that will be used in regular production.

4.2.2 Welding procedure qualification. The supplier shall produce tanks using the proposed welding procedure to demonstrate the quality of the weld produced. Evaluation of the proposed welding procedure shall be based upon the following:

(a) Review of the written procedure.
(b) Radiograph evaluation of the welds.
(c) Metallographic examination.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:05Z
Check the source to verify that this is the currentversion before use.

4.2.3 Inspection.

4.2.3.1 For examination. Each fuel and pressure assembly shall be examined and tested in accordance with the classification of defects and MIL-STD-105. The AQL is not applicable and the acceptance number is zero.

4.2.3.2 Test. The fuel and pressure assemblies and components shall be tested in accordance with table I, in the sequence listed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

Table I. Preproduction sampling and inspection acceptance/rejection criteria

Item	Quantity	Requirement	Test	Accept	Reject
Fuel and pressure unit	37	R6-2, MIL-W-8604	Radiographic	0	1
	37	3.8	4.3.4.6	0	1
	5	3.10.1.1	4.2.4.1(a)	0	1
	5	3.10.1.2	4.2.4.1(b)	0	1
	The components of the assemblies which have been subject to vibration and shock shall be identified with the letter "V" and "S" as applicable. If all 37 units are accepted, all the units shall be disassembled and tested as follows:				
High Pressure Sphere	37	3.3.1	4.3.4.1	0	1
	5	3.4.4	4.2.2	0	1
	5"V"	3.4.4	4.2.2	0	1
	5"S"	3.4.4	4.2.2	0	1
	22 excluding those subjected to vibration and shock	3.3.2	4.2.4.4	0	*
Fuel Tank Assembly	37	3.4.1 3.4.2	4.3.4.1 4.3.4.2	0 0	1 1
	5	3.4.4	4.2.2	0	1
	5"V"	3.4.4	4.2.2	0	1
	5"S"	3.4.4	4.2.2	0	1
	22 excluding those subjected to vibration and shock	3.4.3	4.2.4.4	0	*
High Pressure Valve	37	3.5.1	4.3.4.3	0	1
High Pressure Safety Disk	58 including those subjected to vibration and shock	3.5.2.1 3.5.2.2	4.3.4.3(a) 4.3.4.3(b)	0 0	1 **
	6	3.10.2.1	4.2.4.2(a)	0	1
	6	3.10.2.2	4.2.4.2(b)	0	1
Check Valve	37	3.6.1, 3.6.2	4.3.4.4(a)(b)	0	1

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:05Z
Check the source to verify that this is the current version before use.

Table 1. Preproduction sampling and inspection acceptance/rejection criteria cont'd

Item	Quantity	Requirement	Test	Accept	Reject
Low Pressure Safety Disk	58 including those subjected to vibration and shock	3.6.3.1 3.6.3.2	4.3.4.4(c) 4.3.4.4(d)	0 0	1 **
	6	3.10.3.1	4.2.4.3(a)	0	1
	6	3.10.3.2	4.2.4.3(b)	0	1
Pneumatic Hose	37	3.7	4.3.4.5	0	1
Filler Cap	37	3.9	4.3.4.7	0	1

* Retest. If 2 or more fail, the lot shall be rejected. If a single failure occurs, a second sample of 16 more shall be tested. If in the first and second sample combined 2 or more failures occur, the lot shall be rejected.

**Retest. If 2 or more fail, the lot shall be rejected. If a single failure occurs, a second sample of 34 shall be tested. If in the first and second sample combined 2 or more failures occur, the lot shall be rejected.

4.2.4 Tests.

4.2.4.1 Fuel and pressure assembly.

(a) Vibration. The fuel and pressure assembly in a vertical position shall be securely fastened to a vibration table and vibrated in accordance with figure 514-2, curve A, and table 514-11, schedule I of MIL-STD-810, method 514-1.

(b) Mechanical shock. The fuel and pressure assembly shall be mounted on the test plate and subjected to three shocks in each direction applied along three mutually perpendicular axes for a total of 18 shocks. The shock pulse shape shall be in accordance with figure 516.1, of MIL-STD-810 with a peak value (A) of 15g and nominal duration (D) of 11 milliseconds.

4.2.4.2 High pressure safety disk.

(a) High temperature. The high pressure safety disk shall be conditioned and tested in accordance with MIL-STD-810, method 501.1. (See 6.4).

o

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:05Z
Check the source to verify that this is the currentversion before use.

(b) Low temperature. The high pressure safety disk shall be conditioned and tested in accordance with MIL-STD-810, method 502-1, except that conditioning and test shall be at -40°F. (See 6.4).

4.2.4.3 Low pressure safety disk.

(a) High temperature. The low pressure safety disk shall be conditioned and tested in accordance with MIL-STD-810, method 501-1. (See 6.4).

(b) Low temperature. The low pressure safety disk shall be conditioned and tested in accordance with MIL-STD-810, method 502.1, except that conditioning and test shall be at -40°F. (See 6.4).

4.2.4.4 Burst. Subject the high pressure sphere or fuel tank assembly to the specified hydrostatic pressure for 60 to 70 seconds (see 6.4). After 60 to 70 seconds increase the pressure until destruction of the test item. Record the pressure at destruction.

4.3 Regular production.

4.3.1 Lot. A lot shall consist of the fuel and pressure units produced by one manufacturer, at one plant, from the same materials, and under essentially the same manufacturing conditions. However, no more than one lot of regulators, high pressure valve, check valves, or safety disk plugs shall be represented in any one lot of finished fuel and pressure assemblies.

4.3.1.1 Safety disk plugs. A lot shall consist of the safety disk plugs produced by one manufacturer using safety disks from one sheet of material measuring approximately 1 square foot.

4.3.1.2 Radiographic examination. The fuel tank assemblies shall be consecutively numbered in the order welded. For radiographic examination only, a lot shall be ten consecutively numbered fuel tank assemblies.

4.3.2 Sampling.

4.3.2.1 For nondestructive examination. Sampling shall be conducted in accordance with MIL-STD-105.

4.3.2.2 For destructive test (safety disk plugs) Sampling shall be conducted in accordance with MIL-STD-105, level S-2.

4.3.2.3 For radiographic examination. One fuel tank assembly shall be randomly selected from each lot.

4.3.3 Inspection provisions.

4.3.3.1 For nondestructive examination. Sample items shall be examined in accordance with the classification of defects and MIL-STD-105.

4.3.3.2 Destructive test (safety disk plugs). Sample safety disk plugs shall be tested in accordance with 4.3.4.2(a)(b) and 4.3.4.3(c)(d), as applicable.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:05Z
Check the source to verify that this is the current version before use.

4.3.3.3 For Radiographic examination. Sample items shall be examined in accordance with Edgewood Arsenal Radiographic Standard R6-2. If one or more defects exist, the entire lot shall be examined in accordance with Standard R6-2.

4.3.3.4 Critical defects. Each item in the lot shall be tested for the critical defects listed in the classification of defects.

4.3.3.5 Classification of defects.

(a) Fuel and pressure unit, portable flame thrower, M9 assembly (Dwg E81-1-6839).

Categories	Defects	Acceptance standards
Critical:		
1	Functioning	4.3.4.6
Major:	AQL 1.0 percent defective	
101	Components missing or incorrectly assembled	
102	Marking incorrect	
103	Belt buckle assembly nonfunctioning	
104	Workmanship (3.11)	
Minor:	AQL 2.5 percent defective	
201	Protective finish missing or incorrect	
202	Marking illegible	

(b) Sphere, high pressure, assembly (Dwg D81-1-6863).

Categories	Defects	Acceptance standards
Critical:		
1	Permanent volumetric expansion	4.3.4.1
Major:	AQL 1.0 percent defective	
101	Component missing or incorrectly assembled	
102	Thread incorrect	
103	Retaining ring incorrect or incorrectly located	
104	Marking incorrect	

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:05Z
Check the source to verify that this is the current version before use.

(b) Sphere, high pressure, assembly (Dwg D81-1-6863) (Continued)

Categories	Defects
Minor:	AQL 2.5 percent defective
201	Protective finish missing or incorrect

(c) Tank, fuel assembly (Dwg D81-1-6900).

Categories	Defects	Acceptance standards
Critical:		
1	Permanent volumetric expansion	4.3.4.1
2	Leakage	4.3.4.2
Major:	AQL 1.0 percent defective	
101	Components missing or incorrectly assembled	
102	Filling hole thread incorrect	
103	Fuel outlet thread incorrect	
104	Mounting bracket location incorrect	
105	Sphere retaining ring incorrect or incorrectly located	
Minor:	AQL 2.5 percent defective	
201	Marking incorrect or missing	
202	Protective finish missing or incorrect	

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:05Z
Check the source to verify that this is the currentversion before use.

(d) Valve, high-pressure, assembly (Dwg D81-1-6848).

Categories	Defects	Acceptance standards
Critical:		
1	Leakage	4.3.4.3
Major:	AQL 1.0 percent defective	
101	Component missing or incorrectly assembled	
102	Thread incorrect	
103	Protective finish missing or incorrect	

(e) Valve, check, (low pressure) assembly (Dwg C81-1-6892).

Categories	Defects	Acceptance standards
Critical:		
1	Leakage	4.3.4.4(a)(b)
Major:	AQL 1.0 percent defective	
101	Threads incorrect	
102	Component missing or incorrectly assembled	
103	Torque incorrect	

(f) Pneumatic hose assembly (Dwg C81-1-6925).

Categories	Defects	Acceptance standards
Critical:		
1	Leakage	4.3.4.5
Major:	AQL 1.0 percent defective	
101	Component missing or incorrect	

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

(g) Cap, filler, assembly (Dwg C81-1-6879).

Categories	Defects	Acceptance standard
Critical:	Leakage	4.3.4.7
Major:	AQL 1.0 percent defective	
101	Thread incorrect	
102	Component missing or incorrectly assembled	
103	Protective finish missing or incorrect	

(h) Frame, assembly (Dwg D81-1-6885).

Categories	Defects
Critical:	None defined
Major:	AQL 1.0 percent defective
101	Welding incorrect
102	Tank mounting brackets location incorrect
103	Component missing or incorrectly assembled
Minor:	AQL 2.5 percent defective
201	Protective finish missing or incorrect

4.3.4 Tests. Tests shall be conducted as follows: Unless otherwise specified, all tests shall be conducted at ambient temperature.

4.3.4.1 Permanent volumetric expansion.

High pressure sphere and fuel tank assembly. Test the sphere and fuel tank assembly by water-jacket or other method suitable to obtain accurate data. Subject the sphere to the specified hydrostatic pressurefor 60 to 70 seconds. The gage shall be of such precision as to permit reading to an accuracy of 1 percent. The expansion gage shall be of such precision to permit reading to an accuracy of 1 percent or 0.1 cubic centimerer. (see 6.3 and 6.4).

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:05Z
Check the source to verify that this is the currentversion before use.

4.3.4.2 Leckage.

Fuel tank assembly. Install the filler caps, seal the outlet opening, and apply the required internal air pressure through the check valve adapter. Submerge in water to a depth of 3 to 4 inches for 15 to 20 minutes. (See 6.4).

4.3.4.3 High pressure valve assembly leakage. Prior to installation of the safety disk plug, Dwg 581-1-6859, turn the valve to the open position and cap the outlet and safety plug openings. Subject the valve to the specified pressure and submerge in water for 60 to 70 seconds. (See 6.4). Assemble the safety disk plug.

(a) Safety disk plug leakage. Attach the male threaded end to a source of air pressure and submerge the assembly in water at ambient temperature; increase the pressure at the rate of 100 to 150 psig per second until the specified pressure is obtained and hold for 30 to 40 seconds. (See 6.4).

(b) Safety disk plug burst. If the safety disk does not leak, place the assembly behind a suitable barricade and increase the pressure to that specified for burst. (See 6.4).

4.3.4.4 Cneck valve assembly.

(a) Prior to the installation of the safety disk plug, cap the outlet and safety plug openings. Subject the valve to 500 ± 30 psig through the inlet opening and submerge in water at ambient temperature for 60 to 70 seconds. (See 6.4).

(b) Remove the cap from the outlet end and connect the inlet end to a calibrated rotameter. Subject the valve to 300 ± 30 psig through the outlet opening for 60 to 70 seconds. Record the rotameter reading. (See 6.4).

(c) Safety disk plug leakage. Attach the male threaded end to a source of air pressure and submerge the assembly in water at ambient temperature; increase the pressure at the rate of 100 to 150 psig per seoond until the specified pressure is obtained and hold for 30 to 40 seconds. (See 6.4).

(d) Safety disk plug burst. If the safety disk does not leak, place the assembly behind a suitable barricade and increase the pressure to that specified for burst. (See 6.4).

4.3.4.5 Pneumatic hose. Subject the hose to the specified pressure and submerge in water for 60 to 70 seconds. (See 6.4).

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:05Z
Check the source to verify that this is the current version before use.

4.3.4.6 Fuel and pressure assembly.

(a) Connect the M8 hose and M7 gun (see 6.1) to the assembly. Fill the fuel tanks with preservative oil conforming to grade 2 or 3 of MIL-L-21260 to within 2-inches of the filler hole. Connect a pressure gage to one of the fuel tanks.

(b) Pressurize the high pressure sphere to the required pressure and open the high pressure valve to charge the complete assembly. (See 6.4).

(c) After 60 to 70 seconds record the reading of the pressure gage on the fuel tank. Check the assembly for leakage during the 5 to 6 minute period and record the fuel tank pressure gage reading.

(d) Fire a 3-second unignited burst, check and record pressure. After 5 to 6 minutes record the fuel tank pressure gage reading.

(e) At the completion of the test, operate the gun until all air and oil are expelled. Open the bleeder valve in the filler cap to empty any air still in the fuel and pressure assembly, then close the high pressure valve on the sphere.

Note: The interior of the fuel tanks has been coated with preservative oil during this test. (See 5.2.1).

4.3.4.7 Filler cap assembly. Assemble the cap to a suitable fixture having a pressure gage. Connect the assembly to a source of air and subject the cap to the specified pressure for 30 to 40 seconds. (See 6.4).

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:05Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Cleaning and drying. The interior and exterior surfaces of the fuel and pressure unit assembly shall be cleaned, in conformance with method C-1, MIL-P-116, and dried by any applicable method listed therein.

5.2 Packaging. Preservation and packaging level shall be as specified (see 6.1).

5.2.1 Level A. The fuel and pressure unit, cleaned in accordance with 5.1, shall have the interior of the tanks, lines and valves completely coated by flushing, fogging, filling or slushing with preservative oil, conforming to grade 2 or 3 of MIL-L-21260 (see 4.3.4.5). Excess oil shall be drained and the filling openings closed by their respective closures. All threads and unpainted exterior surfaces shall be coated with the same preservative. The unit shall be inclosed in a wrap of barrier material, conforming to type I, MIL-B-121, and packaged in a fiberboard box conforming to W5c, PPP-B-636. Blocking, bracing or cushioning shall be provided as necessary to protect the item from damage when tested in accordance with the rough handling tests prescribed in MIL-P-116. Blocking, bracing or cushioning material used shall be of weather-resistant type. The box shall be closed and all seams and joints sealed with tape in accordance with the appendix to PPP-B-636.

5.2.2 Level C. Packaging shall be in accordance with 5.2.1 except the box and interior blocking, bracing or cushioning may be of domestic class material and sealing of the seams and joints is not required.

5.3 Packing. Packing level shall be as specified (see 6.1).

5.3.1 Level A. The fuel and pressure unit, packaged in accordance with 5.2.1, shall be packed, one each, in a snug-fitting box conforming to either class 2, style 4, PPP-B-621 or overseas type, PPP-B-601. The box shall be closed and strapped in accordance with the appendix to the respective box specification.

5.3.2 Level C. The fuel and pressure unit, packaged in accordance with 5.2.2, shall be packed in an exterior fiberboard box conforming to the requirements of Uniform Freight Classification rules and regulations of other carriers applicable to the mode of transportation.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:05Z
Check the source to verify that this is the currentversion before use.

assembled

5.4 Marking. In addition to any special marking specified in the contract or order, or other applicable documents, marking shall be in accordance with MIL-STD-129.

5.5 Repair parts. When this item is being procured for stockage and issue as a repair parts, preservation, packaging, packing and marking shall be as specified on the repair parts packaging data sheet (see 6.5).

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

(a) Title, number and date of this specification.
(b) The M8 hose and M7 gun will be Government furnished only when this item is procured as a spare part.
(c) Level of packaging and packing required.
(d) When packaging data sheet is required.
(e) Preproduction:

(1) Time allowed for supplier submission of samples for Government test and evaluation after award of contract.
(2) Name and address of test facility and shipping instructions when testing is performed by the Government.
(3) Time required for the Government to notify the supplier whether or not to proceed with production.

6.2 Pretesting for stress. Any internal pressure applied after heat treatment and prior to the official test should not exceed 90-percent of the test pressure.

6.3 Test apparatus failure. If the test pressure cannot be maintained for a sufficient period of time to determine the permanent volumetric expansion due to failure of the test apparatus, the test may be repeated at a pressure increased by 100 psig when testing the high pressure sphere and increased by 20 psig when testing the fuel tank.

6.4 Caution. Due to the hazards inherent in testing with high pressures, manufacturers are hereby notified that every precaution possible should be taken for the safety and protection of the personnel engaged in testing the items.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

6.5 Packaging data sheet. The packaging data sheet is identified by the Federal stock number for this item and should be ordered from the Commanding Officer, Edgewood Arsenal, ATTN: SMUEA-TSE-DD, Edgewood Arsenal, Maryland 21010.

6.6 Supersession data. This specification supersedes Chemical Corps Purchase Description 196-131-753A, dated 25 June 1962.

Custodian:

Army - MU

Preparing activity:

Army - MU (EA)

Project No. 1040-A058

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:05Z
Check the source to verify that this is the currentversion before use.

SPECIFICATION ANALYSIS SHEET

Form Approved Budget Bureau N · 119 R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side; staple in corner, and send to preparing activity.

SPECIFICATION		
ORGANIZATION	CITY AND STATE	
CONTRACT NO	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT $

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*	DATE

DD, FORM, APR 63 1426

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS

Commanding Officer
US Army Edgewood Arsenal
ATTN: SMUEA-QAWS
Edgewood Arsenal, Maryland 21010

FOLD

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:05Z
Check the source to verify that this is the current version before use.