MILITARY SPECIFICATION

HAMMERS, ELECTRIC, PORTABLE, HAND

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers two types of one size of portable, hand-held, electric hammers.

1.2 Classification. Portable, hand-held, electric hammers shall be of the following types, as specified (see 6.2):

Type I - Electric motor driven.
Type II - Magnetically operated.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein:

SPECIFICATIONS

Federal

J-C-580	- Cord, Flexible, and Wire, Fixture (Electrical, 0- to 600-Volt Service).
W-C-596	- Connector, Plug, Electrical; Connector, Receptacle, Electrical.
QQ-T-580	- Tool Steel, Carbon and Carbon-Vanadium.
SS-A-281	- Aggregate, (For) Portland-Cement-Concrete.
SS-C-192	- Cement, Portland.
PPP-B-601	- Boxes, Wood, Cleated-Plywood.
PPP-B-621	- Boxes, Wood, Nailed and Lock-Corner.
PPP-P-40	- Packaging and Packing of Hand Tools.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:08Z
Check the source to verify that this is the current version before use.

Military

MIL-V-173	- Varnish, Moisture-and-Fungus-Resistant, (for Treatment of Communications, Electronic, and Associated Equipment).
MIL-P-514	- Plates, Identification, Instruction and Marking, Blank.

STANDARDS

Military

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	- Marking for Shipment and Storage.
MIL-STD-130	- Identification Marking of US Military Property.
MIL-STD-1474	- Noise Limits for Army Materiel.

(Copies of specifications and standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION ACT OF 1970 (OSHA)

Title 29, Code of Federal Regulations, Chapter XVII, Part 1926.

(Application for copies should be addressed to the Superintendent of of Documents, Government Printing Office, Washington, DC 20402.)

NATIONAL BUREAU OF STANDARDS

Handbook H28 - Screw-Thread Standards for Federal Services.

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington, DC 20402.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:08Z
Check the source to verify that this is the current version before use.

UNIFORM CLASSIFICATION COMMITTEE, AGENT

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, ATTN: Tariff Publishing Officer, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., ATTN: Tariff Order Section, 1616 P Street, NW Washington, DC 20036.)

AIR POLLUTION CONTROL DISTRICT

Rule 66

(Application for copies should be addressed to the Air Polution Control District, County of Los Angeles, CA 90001.)

UNDERWRITERS LABORATORIES, INC.

UL-45 - Electric Tools.

(Application for copies should be addressed to the Underwriters Laboratories, Inc., 207 Each Ohio Street, Chicago, IL, 60611; 161 Avenue of the Americas, New York, NY 10013; or Sansome Street, San Francisco, CA 94111.)

AMERICAN NATIONAL STANDARDS INSTITUTE, INC.

ANS B3.5 - Tolerances for Ball and Roller Bearings.
ANS B3.6 - Boundary Dimensions for Ball and Roller Bearings.
ANS B3.8 - Mounting Ball and Roller Bearings, Specifications for.

(Application for copies should be addressed to the American National Standards Institute, Inc., 1430 Broadway, New York, NY 10018.)

3. REQUIREMENTS

3.1 Description. Each hammer shall be a self-contained single unit with carrying case and shall be the type as specified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:08Z
Check the source to verify that this is the current version before use.

3.2 First article (preproduction model). When specified (see 6.2), the supplier shall furnish one or more hammers for examination and testing within the time frame specified (see 6.2), to prove prior to starting production, that his production methods will produce hammers that comply with the requirements of this specification. Examination and tests shall be as specified in Section 4 and unless otherwise specified herein, all examinations and tests shall be conducted by the supplier subject to surveillance and approval by the Government (see 6.3).

3.3 Material. Material shall be as specified herein. Material not specified shall be new and of a quality necessary to produce hammers to meet the requirements specified herein.

3.4 Safety. Hammers shall be safe to use both mechanically and electrically. All moving parts which are hazardous to the operator shall be guarded against accidental contact. Protective devices shall not impair the operating functions. The enclosures, except for ventilation openings, shall totally enclose all stationary and rotating electrical parts. Ventilation openings shall be within the acceptable minimum safety requirements of UL-45. Hammers and accompanying accessories shall satisfy the requirements of the Occupational Safety and Health Act of 1970, Title 29, Chapter XVII, Part 1926, Subparts I and K.

3.4.1 Sound level requirement. The sound level of the hammer shall be in accordance with MIL-STD-1474, Category D for steady-state noise when tested in accordance with 4.5.2.9. Hearing protectors need not be supplied with the hammer. Hazard signs, if required, shall state: "CAUTION, HEARING PROTECTION REQUIRED WHEN THIS HAMMER IS OPERATED."

3.5 Interchangeability. All parts shall be manufactured to such standards that will permit replacement or adjustment without modification of the hammer or its parts.

3.6 Weight. The weight of the hammer shall be not more than 35 pounds excluding the power-cable assembly.

3.7 Tool retainer. The hammer shall be equipped with a tool retainer mechanically fastened to it. The tool retainer shall hold the operating tools while operating and while the hammer is being retracted from the work surface.

3.8 Carrying case. A metal, composition, or metal-reinforced composition carrying case shall be furnished with each hammer. The case shall be provided with a handle, hinged cover, and latch(es). The case, handle, cover, and latch(es) shall be of such size and strength to contain and support the hammer and tool retainer. When specified (see 6.2), a separate carrying case shall be furnished to contain and support all the accessories specified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:08Z
Check the source to verify that this is the current version before use.

3.9 Performance.

3.9.1 Drilling. The hammer shall drill concrete at a rate of 1 inch per minute with a 2-inch-diameter star drill and shall drill 3 inches per minute with a 1-inch-diameter star drill.

3.9.2 Concrete breaking. The hammer shall break up a concrete slab, 2 feet wide by 4 feet long by 1 foot thick, at a rate of 2.5 cubic feet per hour, leaving pieces no larger than 1/2 cubic foot in size.

3.9.3 Penetration. The hammer shall drive a 1-inch-diameter tool blank into a lead block at a rate of 2.5 inches per minute.

3.9.4 Endurance. The hammer shall withstand 100 hours of cyclic endurance operation of 15 seconds on and 15 seconds off.

3.10 Accessories and operating tools. When specified (see 6.2), accessories and operating tools as listed in Table I shall be furnished.

Table I. Accessories.

Accessories and operating tools	Nominal length under collar (inches)	Width or diameter (inches)	Quantity
Cold chisel	12	7/8	2
4-point star drill	18	1	1
4-point star drill	18	2	1
Bull (moil) point	12	point	2
Digger spade	18	4-1/2	1
Nail driver	6	1-1/8	1
Nail driver	6	5/8	1
Tamper	12	4	1
Adapter, taper-shank, with knock-out key (when taper-shank star drills are furnished (see 3.10.2)).	-	-	1
Handle, star-drill-turning	-	-	1

3.10.1 Cutting tools. The cutting tools (chisels, star drills, and bull points) shall be of forged steel conforming to QQ-T-580, grade and class optional. After forging, the cutting tools shall be normalized, hardened, and tempered to a hardness of 56 to 60 Rockwell C on the cutting point or edge.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:08Z
Check the source to verify that this is the current version before use.

The remaining portion shall be hardened to 38 to 43 Rockwell C throughout the entire cross section of the tool. When taper shank star drills are furnished, the taper shank adapter shall be hardened to 45 to 50 Rockwell C.

3.10.2 Shanks. The shanks of the accessories shall be provided with a collar to engage in the tool retainer (see 3.7). The shanks of the chisels, bull points, digger spades, nail drivers, and tampers shall be provided with a hexagon shape to prevent rotation in the hammer nose. Taper shanks for star drills may be utilized.

3.10.3 Nail driver. The nail driver shall consist of a driving head and a spring-loaded centering sleeve. The spring shall keep the centering sleeve extended not less than 3/4 inch beyond the driving head and shall allow the sleeve to retract sufficiently to permit the driving head to fully seat the nail. No special heat treatment or hardening is required for the nail-driving, centering sleeve. The 5/8-inch-diameter nail driver shall be capable of driving 60d nails in seasoned oak. The 1-1/8-inch-diameter nail driver shall be capable of driving 8-inch spikes (3/8-inch diameter) in seasoned oak.

3.10.4 Digger spade. The blade of the digger spade shall be forged integral with the shank.

3.11 Handle. The hammer shall be equipped with an end handle with a closed grip and switch. The closed grip opening shall be large enough to accommodate the hand of a man wearing arctic mittens.

3.12 Cable assembly. The cable shall be 12 feet plus or minus 1/2 foot in length and shall conform to J-C-580, Type SO or SJO. The cable shall be fitted with a two-pole, 15-ampere molded plug in accordance with W-C-596, Style D24. The cable shall be reinforced or armored at its junction with the hammer for protection against sharp bends and mechanical strains on the conductors.

3.13 Switch. Hammers shall be provided with a switch mounted in the end handle. The switch shall be guarded to prevent accidental actuation. The switch shall be plainly and permanently marked to show the "ON" and "OFF" positions, unless it is of the automatic release type. Switches shall be capable of interrupting the stalled motor current at full rated voltage for 50 consecutive times at intervals of 10 seconds without flashing to the case, sticking, or burning of the contacts.

3.14 Dielectric strength. The circuit elements and windings shall withstand 900 volts for 1 minute without breakdown of insulation or current grounding to the frame.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:08Z
Check the source to verify that this is the current version before use.

3.15 Type I, electric motor driven. The motor shall be of the universal type, intermittent duty, conforming to the requirements of UL-45. All motor components shall be protected against vibration and chafing of insulation.

3.15.1 Voltage and current. The motor shall operate on either 115-volt, single-phase, 25- to 60-cycle alternating current or 115-volt direct current with a maximum of 20 amperes.

3.15.2 Commutators. Commutators shall be of the metal V-ring and sheet-mica construction. Molded insulation in the commutator shall not be used. A removable cover or covers shall be fitted over the commutator so that the brushes and connections may be inspected and the commutator may be cleaned while the motor is in operation.

3.15.3 Brushes. The brushes shall be of the heavy-duty rectangular type fitted in brush holders provided with spiral or helical springs and flexible copper shunts. The brushes shall be self adjusting and accessible for service and replacement. Moving parts of the brush mechanism shall be completely covered. When used, insulated screwcaps shall be protected by the motor housing and locked to prevent loosening in operation.

3.15.4 Motor shaft. When the pinion gear or spline is cut on the shaft, the shaft shall be made of heat-treated alloy steel.

3.15.5 Bearings. Armature shaft bearings shall be either ball or roller. Intermediate shaft bearings shall be either ball, roller, or needle. Ball and roller bearings shall conform to and be installed in accordance with ANS B3.5, B3.6, and B3.8. Needle bearings shall conform to ANS B3.5.

3.16 Type II, magnetically operated. Magnetically operated hammers shall be actuated by electromagnets imposing a reciprocating motion to the plunger or piston.

3.16.1 Voltage and current. Magnetically operated hammers shall operate on 115-volt, 60-cycle, single-phase alternating current with a maximum of 20 amperes.

3.16.2 Temperature rise. The temperature rise at 50° C. ambient temperature shall not exceed 55° C. within the solenoid enclosure after 30 minutes of operation at rated voltage.

3.16.3 Cooling-fan motor. When an integral, motor-driven cooling fan is used to cool the solenoid windings, the motor shall conform to 3.15 through 3.15.5.

3.17 Fungus and moisture resistance. The electrical circuitry, including all components and connections except as specified below, shall be protected

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:08Z
Check the source to verify that this is the current version before use.

from the effects of fungus growth and moisture by an overall treatment with a varnish conforming to MIL-V-173, composition as specified in 3.17.1, with 1 percent copper 8-quinolinolate (by weight) based on the nonvolatile content of the varnish:

(a) Components or circuit elements that are inherently fungus and moisture resistant or which are hermetically sealed need not be treated.
(b) Components or circuit elements whose functions will be adversely affected by the varnish coating shall not be treated.

When used, the varnish shall be applied by spray, brush, or a combination of both to give a dry-film thickness of not less than 1 mil to component or element surfaces previously cleaned and prepared so that the surfaces are free from all foreign matter which would interfere with the adherence or function of the varnish.

3.17.1 Composition. Composition I shall be used unless Composition II must be used in order to comply with local air pollution regulations in the application of the varnish. When Composition II is used, the supplier shall provide evidence to the Government that the use of Composition II is required, and shall certify that the Composition II material complies with Rule 66 - Air Pollution Control District, County of Los Angeles, CA.

3.18 Identification marking. The hammer shall be identified in accordance with MIL-STD-130. Unless otherwise specified, identification plates shall conform to MIL-P-514, Type I, Style 1, Composition C of Type I, Grade A, Class 1 material.

3.19 Items to be furnished with the hammer. No shipment of hammers shall be made unless operating tools and accessories are included with the shipment or unless approval for shipment of the hammers without such items has been received from the contracting officer.

3.20 Workmanship. Hammers shall be free from defects such as incomplete welds, rust, cracks, and other defects that could impair their operation or serviceability. All parts, components, and assemblies (including castings, forgings, molded parts, stampings, bearings, seals, machined surfaces, and welded parts) shall be clean and free from sand, fins, pits, sprues, scale, flux and other harmful extraneous materials. All edges shall be rounded or beveled. The exterior surface of each hammer shall have a painted or a buffed finish and shall be free of all machine grinding and filing marks.

3.20.1 Threaded parts. All threaded parts shall be threaded with unified threads in accordance with Handbook H28.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:08Z
Check the source to verify that this is the current version before use.

3.20.2 Fastening devices. All screws, pins, bolts, and other fastening devices shall be provided with a means to prevent loosening or loss of adjustment. Peening, staking, or other means that will cause permanent deformation shall not be allowed.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Component and material inspection. The supplier is responsible for insuring that components and materials used are manufactured, examined, and tested in accordance with referenced specifications and standards.

4.2 Classification of inspections. Inspections shall be classified as follows:

(a) Preproduction inspection (see 4.3).
(b) Quality conformance inspection (see 4.4).
(c) Inspection of preparation for delivery (see 4.6).

4.3 Preproduction inspection.

4.3.1 Examination. The hammers shall be examined as specified in 4.5.1. Presence of one or more defects shall be cause for rejection.

4.3.2 Tests. The hammers shall be tested as specified in 4.5.2.1 through 4.5.2.9. Failure of any test shall be cause for rejection.

4.4 Quality conformance inspection.

4.4.1 Sampling. Sampling for test shall be in accordance with MIL-STD-105.

4.4.2 Examination. Each hammer shall be examined as specified in 4.5.1. Presence of one or more defects shall be cause for rejection.

4.4.3 Test. Samples selected in accordance with 4.4.1 shall be tested as specified in 4.5.2.7. AQL shall be 2.5 percent defective.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:08Z
Check the source to verify that this is the currentversion before use.

4.5 Inspection procedure.

4.5.1 Examination. The hammers shall be examined as specified herein for the following defects:

101. Parts or components missing.
102. Defective casting or forging affecting operation.
103. Fastening devices not as specified.
104. Cable assembly not as specified.
105. Switch not as specified.
106. Weight not as specified.
107. Accessories missing or incomplete.
108. Tool retainer does not hold the tools.
109. Lubrication points not accessible.
110. Handle not as specified.
111. Hammer carrying case not as specified.
112. Threads not as specified.
113. Rough surfaces or burred edges.
114. Data requirements and provisioning not as specified (see 6.4 and 6.5).
115. Identification marking not as specified.
116. Workmanship not as specified.

4.5.2 Tests.

4.5.2.1 Test conditions. Perform the concrete drilling and breaking tests on a test slab 4 feet long, 2 feet wide, and 1 foot thick. The test slab shall consist of one part cement conforming to SS-C-192; two parts fine aggregate conforming to SS-A-281; and four parts coarse aggregate conforming to SS-A-281, size No. 57. Allow the test block to set for 28 days prior to testing.

4.5.2.2 Concrete drilling. Using a 2-inch-diameter star drill of the type and material conforming to 3.10.1, drill three holes in the test slab, limiting the drilling time to 2 minutes per hole. Do not change or sharpen the star drill during this test. Measure the depth of the three holes, total, and divide by the total drilling time (6 minutes) to obtain the drilling rate per minute. Repeat, except using a 1-inch star drill conforming to 3.10.1 and limiting the drilling time per hole to 1 minute. Inability to drill 1 inch per minute with the 2-inch drill or 3 inches per minute with the 1-inch drill shall constitute failure of this test.

4.5.2.3 Concrete breaking. After completion of the drilling test, fit the hammer with a bull point of the type and material conforming to 3.10.1, and demolish the test slab. The bull point may be sharpened or replaced as

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:08Z
Check the source to verify that this is the current version before use.

required. Inability of the hammer to break 2.5 cubic feet of concrete per hour leaving pieces no larger than 1/2 cubic foot in size shall constitute failure of this test.

4.5.2.4 Switch. With the hammer connected to full rated voltage, operate the switch to open and close the contacts 50 consecutive times at intervals of 10 seconds. Flashing to the case, sticking, or burning of the contacts shall constitute failure of this test.

4.5.2.5 Temperature rise. Operate the hammer continuously for 30 minutes at full load amperage, voltage, and frequency rating and determine the temperature rise. Temperatures of the field winding shall be determined by the thermocouple method. Temperature rises in excess of those specified in UL-45 shall constitute failure of this test.

4.5.2.6 Endurance. Set the hammer in a test rack in the upright position. Arrange tension springs or weights to exert 60 pounds downward on the hammer handle. Disconnect and bypass the switch. Operate the hammer against an opposing force, such as concrete, for 100 hours of cyclic operation of 15 seconds on and 15 seconds off. The brushes may be replaced as required. At the completion of these cycles, test the hammer as specified in 4.5.2.2. Any breakage, permanent deformation, or malfunction except for the switch, shall constitute failure of this test criteria.

4.5.2.7 Penetration. Pour commercially pure lead into a steel container 6 inches deep and 6 inches in diameter. Allow the lead to set for 5 minutes. Keep the lead block in this container during the test. Use a tool blank 1 inch in diameter and flat across the end. Allow the hammer to impact in the lead for 30 seconds. Inability of the tool blank to penetrate 1-1/4 inches into the lead block shall constitute failure of this test.

4.5.2.8 Nail driving. Using the 5/8-inch-diameter nail driver, drive a quantity of 100-60d nails in seasoned oak. Using the 1-1/8-inch-diameter nail, drive a quantity of 15-8-inch spikes (3/8-inch diameter) in seasoned oak. Inability of the hammer to drive the required nails and spikes until they are sealed shall constitute failure of this test.

4.5.2.9 Noise. The hammer shall be placed in a test area which is free of any large reflecting surfaces, such as signs or walls within 50 feet of the hammer or sound-level measuring equipment. With the hammer in operation, sound level measurements shall be made adjacent to the hammer in accordance with MIL-STD-1474 and with the recording microphones located to simulate the ear position of an operator using the hammer. Conformance to the noise level criteria specified in 3.4.1, shall constitute successful completion of this test. If the criteria are not met, the minimum distance from the hammer at which the noise levels are acceptable shall be determined, and that distance shall be used on the warning plates specified in 3.4.1. The sound level of each accessory furnished with the hammer shall be determined and included in the test report.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:08Z
Check the source to verify that this is the current version before use.

4.6 Inspection of preparation for delivery.

4.6.1 Quality conformance inspection of pack.

4.6.1.1 Examination. Each completed pack prepared for shipment shall be examined for the following defects. Presence of one or more defects shall be cause for rejection.

117. Materials, methods, and containers not as specified for Level A or B. Each incorrect material, method or container shall constitute one defect.
118. Preservation and packaging not in accordance with referenced document.
119. Unlike quantities of hammers and accessories packed together.
120. Strapping not in accordance with appendix of applicable box specification.
121. Marking missing, illegible, incorrect, or incomplete.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. The hammer, accessories, and tools shall be preserved and packaged in accordance with PPP-P-40 utilizing the carrying cases provided. When a carrying case is not provided for the accessories and tools, they shall be consolidated packaged together in boxes as specified in PPP-P-40 for intermediate containers. The preservation and packaging shall be Level A, B, or C as specified (see 6.2).

5.2 Packing. Packing shall be Level A, B, or C as specified (see 6.2).

5.2.1 Level A. Like quantities of hammers and accessories, preserved and packaged as specified in 5.1, shall be packed together in a close-fitting box conforming to PPP-B-601, overseas type, Grade B; or PPP-B-621, Class 2. The box shall be closed and strapped in accordance with the appendix to the box specification.

5.2.2 Level B. Hammers and accessories shall be packed together as specified in 5.2.1 for Level A, except the box shall be domestic type.

5.2.3 Level C. Like quantities of hammers and accessories, preserved and packaged as specified in 5.1, shall be packed together in a manner to assure carrier acceptance and safe delivery to destination at lowest rating in wooden or fiberboard containers, as applicable to the quantity packed together. Containers and packing shall comply with Uniform Freight Classification rules or National Motor Freight Classification rules.

5.3 Marking. Packages and shipping containers shall be marked in accordance with MIL-STD-129.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:08Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. The hammers are intended for use in light demolition, concrete drilling, and heavy spike driving.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Type of hammer required (see 1.2).
(c) When a preproduction model is required (see 3.2).
(d) Time frame required for submission of the preproduction model and number of hammers to be furnished (see 3.2).
(e) When a separate carrying case is required for the accessories (see 3.8).
(f) When accessories and operating tools are required (see 3.10).
(g) Level of preservation and packaging and level of packing required (see 5.1 and 5.2). Level B preservation and packaging is intended to provide economical but limited protection and should be specified only when it is determined that the hammers will be held in covered storage.

6.3 Preproduction model. Any changes or deviations of production hammers from the approved preproduction model during production will be subject to the approval of the contracting officer. Approval of the preproduction model will not relieve the supplier of his obligation to furnish hammers conforming to this specification.

6.4 Data requirements. The contracting officer should include requirements for such data as technical publications, instructional materials, illustrated parts lists, and suppliers maintenance and operation manuals to be furnished with each hammer.

6.5 Provisioning. The contracting officer should include provisioning requirements for repair parts and maintenance tools as necessary (including any special tools), and instructions on shipment of hammers.

6.6 Ear protection. When the noise level exceeds Category D of MIL-STD-1474, the operator's manual for the hammer should include appropriate instructions for: Use of hearing protection, accessories that produce noise above 85 dB(A), and distance from the hammer at which 85 dB(A) will be met.

Custodian:

Army - ME

User activities:

Army - GL, EL

Preparing activity:

Army - ME

Project No. 5130-A218

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:08Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:08Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side staple in corner, and send to preparing activity Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION MIL-H-52364B(ME) Hammers, Electric, Portable, Hand

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1426
11 Oct 72 (Rev)

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:08Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
U. S. ARMY MOBILITY EQUIPMENT
RESEARCH, DEVELOPMENT
CENTER
FORT BELVOIR, VIRGINIA 22060

OFFICIAL BUSINESS

AMSME-RZD-S

POSTAGE AND FEES PAID
DOD-314

COMMANDER
U. S. ARMY MOBILITY EQUIPMENT
RESEARCH, DEVELOPMENT CENTER
ATTN: AMSME-RZD-S
FORT BELVOIR, VIRGINIA 22060

FOLD

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:08Z
Check the source to verify that this is the current version before use.