INCH - POUND

MIL-L-51343B(MI)
16 November 1990
SUPERSEDING
MIL-L-51343A(MU)
6 October 1972

MILITARY SPECIFICATION

LAUNCHER, ROCKET, 66MM, FOUR TUBE, M202

This specification is approved for use by the U.S. Army Missile Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers one type of rocket launcher, designated as the 66mm, four tube M202.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards and handbooks. The following specifications, standards and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, U.S. Army Missile Command, ATTN: AMSMI-RD-SE-TD-ST, Redstone Arsenal, AL 35898-5270 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 1055
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

PPP-B-26 - Bag, Plastic (General Purpose)

MILITARY

MIL-A-2550 - Ammunition, General Specification for

STANDARDS

MILITARY

MIL-STD-129 - Marking for Shipment and Storage

MIL-STD-1168 - Ammunition Lot Numbering

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWING

ARMY

DL147-1-100 - Launcher, Rocket, 66mm, Four Tube, M202

(Application for copies of DL147-1-100 should be addressed to Commander, U.S. Army Missile Command, ATTN: ASQNC-MIC-OS-ED-DT-WS, Redstone Arsenal, AL 35898-7340. Copies of drawings required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Order of precedence. In the event of conflict between the text of this document and the references cited herein the text of this document shall take precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), a sample of launchers shall be subjected to first article inspection (see 6.3) in accordance with 4.3.

3.2 Materials and components.

3.2.1 Materials. All materials cited on drawing DL147-1-100, or on detail drawings, shall conform to the specifications listed thereon, or to the

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

specific characteristics set forth on the drawings. When applicable, Government-furnished equipment (GFE) shall include the inert M74 rocket and clip (see 4.3.7.11).

3.2.2 Components. All components of the launcher shall conform to the specifications and drawings listed on drawing DL147-1-100 and detail drawings.

3.3 Assembly. The launcher shall be assembled in accordance with drawing E147-1-100, showing a detail of drawing DL147-1-100.

3.4 Nonfunctioning requirements.

3.4.1 Front cover assembly and handle interlock. When the front cover is closed, or open and swinging free, the handle assembly shall be incapable of unlatching. When the front cover is opened and latched, the handle assembly shall be free to open and latch when tested as specified in 4.3.7.1. When the handle release button is depressed, the handle shall be disengaged and may be returned to the stowed position. When the handle assembly is in its stowed position, and latched, the front cover assembly shall be disengaged from its fully opened and latched position.

3.4.2 Trigger safety. When the safety button on the handle is positioned so that the "S" shows, the trigger shall be incapable of functioning. The trigger safety button shall require a 1 to 4 pound force to slide from safe to fire position and from fire to safe position and from fire to safe position when tested as specified in 4.3.7.2.

3.4.3 Safety guide tube and firing pin cam. The trigger shall not function when the trigger safety is in the fire position and firing mechanism is collapsed to any position beyond 1 inch from fully extended position. The points of three firing pins shall extend outward from the firing mechanism housing a maximum of 0.075 inch and one firing pin shall be retracted in the housing when tested as specified 4.3.7.3.

3.5 Functioning requirements.

3.5.1 Extension shaft engagement into safety guide tube. The extension shaft shall enter the safety guide tube smoothly without excessive drag or binding when tested as specified in 4.3.7.4.

3.5.2 Trigger function. The trigger shall function at not less than 8 pounds nor more than 18 pounds pull when tested as specified in 4.3.7.5.

3.5.3 Springs. Springs shall not break or take a permanent set when tested as specified in 4.3.5.2.

3.5.4 Firing pins. Each assembled firing pin (see drawing C147-1-73 covering a detail of drawing DL147-1-100) shall free fall through a gage having a hole diameter of 0.374 $\pm$ 0.0005 inch when tested as specified in

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

4.3.7.6. Gage height shall be 1.125 inches minimum. The gage shall include a minimum width slot for the cam follower to fall through.

3.5.5. Firing pin tension. The force required to collapse each firing pin into the housing shall be between 7.50 and 11.0 pounds when tested as specified 4.3.7.7.

3.5.6 Sight. The sight shall operate smoothly and freely without binding when tested as specified in 4.3.7.8.

3.5.7 Outer tube.

3.5.7.1 Destructive testing. There shall be no cracks or leaks when the tube is subjected to an external hydrostatic pressure of 20 to 25 pounds per square inch gage (psig) and then no cracks when subjected to an internal hydrostatic pressure of 1500 ± 50 psig for a minimum period of 5 seconds when tested as specified in 4.3.6.9(a). Pressure shall then be increased until the tube bursts.

3.5.7.2 Nondestructive testing. There shall be no cracks or permanent deformation in excess of that permitted by the drawing dimensions when the tube is subjected to an internal pressure of 700 ± 20 psig applied for a minimum of 5 seconds when tested as specified in 4.3.7.9(b).

3.5.8 Clip latch. The clip and round assembly shall be incapable of being inserted or extracted from the launcher without depressing the clip latch when tested as specified in 4.3.7.10.

3.5.9 Functioning of inert M47 clip. Four primers shall function when tested as specified in 4.3.7.11.

3.5.10 Trigger cycle. The launcher trigger shall activate the firing pins and conform to 3.5.2 when tested as specified in 4.3.6.2.

3.5.11 Cable assembly.

3.5.11.1 Destructive testing. The swaged balls on the cable shall not move or separate from the cable nor shall any wire strand break when subjected to a tension load of 225 pounds (minimum) as specified in 4.3.7.12(a).

3.5.11.2 Nondestructive testing. The swaged balls on the cable shall not move or separate from the cable nor shall any wire strand break when subjected to a tension load of 150 ± 5 pounds as specified in 4.3.7.12(b). No assembly subjected to this test shall be used in production.

3.5.12 Pawl assembly. The spring swaged into the pin shall not slip or separate when subjected to a tension load of 2 to 3 pounds when tested as specified in 4.3.7.13.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

r oil lamp. There ... There shall be no external signs of leakage from the lubricating

3.5.13 Retraction of firing mechanism. The return spring shall partially retract the firing mechanism a minimum of 0.375 inch into the launcher when the extension shaft and keys are lined up with the shaft ratchet and safety guide slots, when tested as specified in 4.3.7.14.

3.5.14 Rear cover. When the rear cover latch is opened, the cover shall move freely to a fully opened position and return to a closed, latched position when tested as specified in 4.3.7.15.

3.5.15 Lever detent. The welded detent rivet shall not separate or slip, or the weld crack when a 1000 ± 25 pound load is applied as specified in 4.3.7.16. No assembly subjected to this test shall be used in production.

3.5.16 Handle support. The brazed pin shall not separate or slip when a 750 ± 20 pound load is applied as specified in 4.3.7.17. No assembly subjected to this test shall be used in production.

3.6 Workmanship. The launcher shall be free from foreign matter (oil, grease, or dirt) and damage such as cracks, burrs, dents, excess epoxy, excess paint, voids in painted surfaces, excessive gaps in epoxy joints or deformation which could affect its intended use, and shall comply with the workmanship requirements of MIL-A-2550.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

D) Delete the entire paragraph. Paragraph 4.4.1.1

4.1.2 Inspection conditions. Unless otherwise specified (see 6.2), all inspections shall be performed in accordance with the test conditions specified in 4.3.7.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3)

b. Quality conformance inspection (see 4.3.2)

4.3 First article inspection.

4.3.1 First article sample. The contractor shall submit a first article sample as designated by the contracting officer for evaluation in accordance with the provisions of 4.3.2. The first article sample shall consist of the following:

a) 10 launchers
b) 10 of each spring

c) 5 outer tubes

d) 2 launcher tube assemblies

The first article sample shall consist of parts which have been produced by the contractor or furnished by a supplier and which have been manufactured using the same production processes, procedures and equipment which will be used in fulfilling the contract. All parts and materials, including packaging and packing, shall be obtained from the same source of supply as will be used in regular production. Prior to submission, the contractor shall inspect the sample to the degree necessary to assure that it conforms to the requirements of the contract and submit a record of this inspection with the sample, including statements of findings/certificates of conformance for materials. A sample containing known defects will not be submitted unless specifically authorized by the contracting officer. A first article sample, or portion thereof, as directed by the contracting officer, shall also be submitted whenever there is a lapse in production for a period in excess of 90 days or whenever a change occurs in manufacturing process, material used, drawing or specification such as to significantly affect product uniformity as determined by the Government.

4.3.2 Quality conformance inspection. Quality conformance inspection shall be specified in table 1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

TABLE I. Quality conformance inspection.

Examinations and tests	Requirement paragraph	Test paragraph
Materials and components	3.2	(Examination)
Non-functioning requirements	3.4	4.3.7.1, 4.3.7.2, 4.3.7.3
Extension shaft engagement into tube	3.5.1	4.3.7.4
Trigger function	3.5.2	4.3.7.5
Springs	3.5.3	4.3.5.2(b)
Firing pins	3.5.4	4.3.7.6
Firing pin tension	3.5.5	4.3.7.7
Sight	3.5.6	4.3.7.8
Outer tube testing	3.5.7.1, 3.5.7.2	4.3.7.9(a), (b)
Clip latch	3.5.8	4.3.7.10
Functioning of inert M47 clip	3.5.9	4.3.7.11
Trigger cycle	3.5.10	4.3.6.2
Cable assembly testing	3.5.11.1, 3.5.11.2	4.3.7.12(a), (b)
Pawl assembly	3.5.12	4.3.7.13
Retraction of firing mechanism	3.5.13	4.3.7.14
Rear cover	3.5.14	4.3.7.15
Lever detent	3.5.15	4.3.7.16
Handle support	3.5.16	4.3.7.17
Workmanship	3.6	(Examination)

4.3.3 Lot size and sampling.

4.3.3.1 Lot size. Each lot shall be identified and controlled in accordance with MIL-STD-1168. No more than one interfix number from one outer tube manufacturer shall be permitted in any one interfix launcher number.

4.3.3.2 Sampling.

4.3.3.2.1 Examination and nondestructive tests. Sampling for conformance shall be conducted in accordance with tables II and III.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

TABLE II. Sampling plan A.

Lot Size	Sample Size
2 to 20	100%
21 to 280	20
281 to 1200	47
1201 to 3200	53
3201 to 10,000	68
10,001 to 35,000	77
35,001 to 150,000	96
150,001 to 500,000	119
500,001 and over	143
In all cases: Acceptance number is ZERO Rejection number is ONE	

TABLE III. Sampling plan B.

Lot Size	Sample Size
2 to 13	100%
14 to 150	13
151 to 280	20
281 to 500	29
501 to 1200	34
1201 to 3200	42
3201 to 10,000	50
10,001 to 35,000	60
35,001 to 150,000	74
150,001 to 500,000	90
500,001 and over	102
In all cases: Acceptance number is ZERO Rejection number is ONE	

4.3.3.2.2. Destructive tests.

a) Outer tube. Fifteen outer tubes shall be randomly selected from each lot.

b) Cable assembly. Sampling shall be conducted in accordance with tables II and III.

4.3.5 Inspection procedure.

4.3.5.1 Examination and nondestructive tests.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

a) Launcher components. The sample launchers and components shall be examined and tested in accordance with the classification of defects (see 4.3.6) and list of defects (see 4.3.6.2). Sample launchers shall be sequentially tested in accordance with 4.3.6.1, 4.3.6.2, 4.3.7.1, 4.3.7.2, and 4.3.7.11.

b) Bonding compliance. Evidence of compliance with the required bonding techniques shown on detail drawings E147-1-99 and E147-1-100 shall be determined by visual examination of the squeeze-out of epoxy bonding agent from bonded joints. Gaps in the squeeze-out of no longer than 0.250 inch are acceptable as long as any two gaps are separated by at least 0.750 inch of continuous epoxy squeeze-out, except that no gaps are acceptable along closure strip bonded joints. Cleaning or removal of excess epoxy from the tube and bulkhead joint is permitted before or after curing at the option of the contractor, provided the assembly is Government inspected before and after epoxy removal. Cleaning or removal of excess epoxy from the closure strip and tube interface is permitted to obtain a smooth, flush joint.

c) The sample detent levers and handle supports shall be tested in accordance with 4.3.7.16 and 4.3.7.17, using sampling plans in accordance with tables II or III.

4.3.5.2 Destructive tests.

a) Outer tubes. Sample outer tubes shall be tested in accordance with 4.3.7.9(a). The acceptance number is zero.

b) Springs. The springs shall be extended or flexed in a manner representative of actual functioning for 100 cycles. If a spring breaks or fails to return to its original condition before breaking, the spring is defective.

c) Cable assembly. Sample cable assemblies shall be tested in accordance with 4.3.7.12(a). The acceptance number is zero.

4.3.6 Test procedures.

4.3.6.1 Trigger cycling. The extension and retraction of the firing pins shall be measured before and after completion of this test. An empty clip shall be inserted into the launcher, fully extended, and the trigger pulled four times. Then the clip shall be collapsed into the launcher. This constitutes a single cycle. Repeat the cycle until the trigger has been pulled 4,000 times (1,000 cycles). Measure the extended firing pins after each 250 cycles (see 3.4.3). Every 250 cycles, inspect the ends of the clip for burrs or cracks that could damage the launcher tubes. Replace clip as required and continue testing.

4.3.6.2 List of defects. Each launcher and each component noted in the list of defects below shall be inspected for those defects. If any launcher

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

or component contains any listed defect, that launcher or component shall be rejected.

4.3.6.2.1 Launcher, rocket, M202 (see drawing E147-1-100, showing detail of drawing DL147-1-100).

1) Firing pin protrusion incorrect (0.075 inch maximum) (see 4.3.7.3)

2) Clip latch incorrect (see 4.3.7.10)

3) Rear cover fails to latch (see 4.3.7.15)

4.3.6.2.2 Tube assembly, launcher (see drawing E147-1-99, showing a detail of drawing DL147-1-100).

1) Tube location incorrect (both ends)

2) Perpendicularity

3) Parallelism

4) Detent pin location

5) Rear bulkhead location (4.441 dimension)

4.3.6.2.3 Firing pin mechanism assembly (see drawing C147-1-71, showing a detail of drawing DL147-1-100)

1) Alignment pin protrusion incorrect (0.310 $\pm$ 0.040 inch maximum)

2) Pins require lubrication or do not roll freely.

4.3.6.3 Critical defects. 100% of the items in a lot shall be tested for critical defects shown in 4.3.6.4.

4.3.6.4 Classification of defects. Critical defects are numbered 1 through 99. Major defects are numbered 101 through 199. Minor defects are numbered 201 through 299.

4.3.6.4.1 Launcher, rocket, 66mm, multishot, M202 (see drawing E147-1-100, showing a detail of drawing DL147-1-100).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

Categories	Defects	Inspection Method	Sampling Plan
Critical:			
1	Functioning	4.3.7.11	
2	Front cover assembly and handle interlock functioning incorrect	4.3.7.1	
3	Trigger safety functioning incorrect	4.3.7.2	
4	Extension shaft engagement into safety guide tube incorrect	4.3.7.4	100%
5	Trigger function incorrect	4.3.7.5	
6	Sight assembly operation incorrect	4.3.7.8	
7	Firing pin tension incorrect	4.3.7.8	
8	Retraction of firing mechanism incorrect	4.3.7.14	

4.3.6.4.2 Firing pin (see drawing C147-1-73, showing a detail of drawing DL147-1-100).

Categories	Defects	Inspection Method	Sampling Plan
Critical:			
1	Free fall through gage	4.3.7.6	100%

4.3.6.4.3 Ratchet assembly (see drawing D147-1-43, showing a detail of drawing DL147-1-100).

Categories	Defects	Inspection Method	Sampling Plan
Critical:	(None defined)		:
Major:			
101	Failure of pawl assembly pull test	4.3.7.13	Table III

4.3.6.4.4 Tube, outer (see drawing C147-1-92, showing a detail of drawing DL147-1-100).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

Categories	Defects	Inspection Method	Sampling Plan
Critical:			
1	Cracks or permanent deformation	4.3.7.9(b)	100%

4.3.6.4.5 Cable (see drawing B147-1-127, showing a detail of drawing DL147-1-100).

Categories	Defects	Inspection Method	Sampling Plan
Critical:	(None defined)		
Major:			
101	Movement of separation	4.3.7.12(b)	Table II

4.3.6.4.6 Packaging (see Section 5).

Categories	Defects	Inspection Method	Sampling Plan
Critical:	(None defined)		
Major:			Table III
101	Bag not sealed	Visual	
102	Loose pack	Visual	
103	Seams or joints not sealed	Visual	
104	Container incorrect	Visual	
105	Strapping loose or missing	Visual	
106	Marking illegible or incorrect	Visual	
107	Glue or adhesive in area of front cover handle toggle key	Visual	
108	Accessories missing	Visual	
109	Spare clip retainer missing	Visual	

4.3.7 Methods of inspection.

4.3.7.1. Front cover assembly and handle interlock. After final paint touch-up, perform the following tests.

(a) When the front cover is closed and again when open and swinging free, attempt to open the handle assembly from its stowed and locked position.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

(b) When the front cover is opened and latched, open and latch the handle assembly.

(c) Repeat (a) and (b) a total of 10 times.

(d) The trigger handle must be fully collapsed, the interlock tripped, and the handle latched into place before the front cover is released and can be closed. The front cover must be unlatched, the interlock tripped and the handle cover locked into position before the trigger handle is automatically released from its stowed position.

4.3.7.2 Trigger safety. After final paint touch-up, perform the following test. Insert an empty clip into the launcher and extend to firing position. With the safety button on the handle as specified, attempt to squeeze trigger by hand. Use a spring gage tester to determine force required to slide the safety button from safe to fire position 10 times, and squeeze trigger each time.

4.3.7.3 Safety guide tube and firing pin cam. After final paint touch-up, perform the following test. With the trigger safety button in the "F" position, insert and extend an inert clip, and attempt to function the trigger with the clip in two positions: three quarters extended, and fully extended. Firing pin extension shall be measured at the fully extended position. Measurement shall be taken after functioning trigger one time.

4.3.7.4 Extension shaft engagement into safety guide tube.

(a) Insert and extend inert clip.

(b) Pull trigger.

(c) Push detent and collapse clip 2 to 3 inches.

(d) Extend clip.

(e) Repeat steps (b), (c) and (d), three additional times.

4.3.7.5 Trigger function. After final paint touch-up, perform the following test.

(a) Insert and extend inert clip.

(b) Move trigger safety to "S" position.

(c) Attach spring gage tester to trigger approximately 0.5 inch above lower tip of trigger handle and pull down at an angle of approximately 20 degrees to the longitudinal axis of launcher. This action rotates the "just fired" firing pin onto the safing ramp. Record force required.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

(d) Move trigger safety to "F" position.

(e) Attach spring gage tester as in (c) above. Pull trigger and record force needed to fire pin.

(f) Repeat steps (b), (c), (d), and (e) three additional times.

4.3.7.6 Firing pin. Place each assembled firing pin into gage and allow it to free fall completely through the gage.

4.3.7.7 Firing pin tension. After final paint touch-up, push each firing pin into housing, which has been assembled into the firing mechanism, and record the force required to compress the spring to just above the fully retracted position. Firing pins shall move freely throughout their full travel with no binding, dragging, or hang-up.

4.3.7.8 Sight. After final paint touch-up, perform the following test.

(a) Raise sight to operating position and check detent for engagement.

(b) With sight lock fully depressed, assure that lock will not override adjustment plate end tabs.

(c) Depress sight adjustment plate lock and rotate to operating position.

(d) Open and close lens cover. Check for detent engagement.

(e) Depress sight adjustment plate lock and rotate sight to closed position.

(f) Lower sight to closed position and check for detent engagement.

4.3.7.9 Outer tube.

(a) Destructive. The tube shall be placed in a suitable fixture and subjected to the specified pressures for the required time and then the tube shall be burst. Record burst pressure.

(b) Nondestructive. The tube shall be placed in a suitable fixture and subjected to the specified pressure for the required time.

4.3.7.10 Clip latch. Slowly insert an empty clip assembly into the launcher without depressing the clip latch. The clip shall enter the launcher approximately 0.5 inch before the clip latch restricts movement. Depress the clip latch, and fully insert the clip. From the fully collapsed position, apply a steady slow pull at an approximate rate of 6 inches per second on the bail handle at the end of the clip; the clip shall extend from the launcher and lock into firing position. To remove the clip assembly, collapse into the

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

launcher, remove clip retainer, extend clip assembly by the bail handle, push the clip latch, and extract the clip.

4.3.7.11 Functioning. Insert an inert M74 clip (provided as GFE when applicable [see 6.2]), with four primers installed, into the launcher. When the launcher is ready to fire, pull trigger four times. The mechanism shall operate and initiate the four primers.

4.3.7.12 Cable assembly.

(a) Destructive. Secure one end of the swaged balls in a stationary fixture, grip the other ball at end of the cable and apply specified load for 5 seconds, then increase tension until destruction. Record load required to destroy cable.

(b) Nondestructive. Secure on of the swaged balls in a stationary fixture, grip the other ball at end of cable and apply specified load for 5 seconds.

4.3.7.13 Pawl assembly. Attach a spring gage tester into loop of spring and secure pin in a stationary fixture. Apply specified load along longitudinal axis.

4.3.7.14 Retraction of firing mechanism. After final paint touch-up, insert and extend inert M74 clip and place the launcher in a horizontal position. Remove the clip retainer and observe to see that the firing mechanism retracts the specified distance from the primer manifold.

4.3.7.15 Rear cover. After final paint touch-up, insert inert M74 clip, close and latch rear cover, open cover latch, move cover to the full open position, then close and latch cover. Repeat opening and latching five times.

4.3.7.16 Lever detent. After welding, use a suitable fixture with a 0.375 inch diameter hole. Apply the specified load to the end of the 0.125 inch diameter rivet and hold for 5 seconds.

4.3.7.17 Handle support. After brazing, apply specified load to the exposed end of pin and hold for 5 seconds.

4.3.8 Inspection of packaging. The sampling and inspection of the preservation, packaging, and container marking shall be in accordance with MIL-STD-129 and Drawings D147-1-189, D147-1-164 and D147-1-163..

5. PACKAGING

5.1 Packaging, level A.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:05Z
Check the source to verify that this is the currentversion before use.

5.1.1 Cleaning. The launcher shall be free of dirt and other foreign matter when packaged.

5.1.2 Launcher (drawing E147-1-100). The launcher shall be packaged in accordance with drawing D147-1-189, showing a detail of drawing DL147-1-100.

5.1.3 Sling (drawing D147-1-181). The sling shall be packaged in accordance with drawing D147-1-189, showing a detail of drawing DL147-1-100.

5.1.4 Special tools. The special tools, consisting of one Boresighting Disk Set (see drawing C147-1-177, showing a detail of drawing DL147-1-100) and one wrench-screwdriver combination (see drawing (C147-1-190, showing a detail of drawing DL147-1-100) shall be packaged together by sealing within a bag conforming to type II, style 1, PPP-B-26, having inside dimensions of 4 inches wide by 8 inches long. Included air volume in the bag shall be kept to a practical minimum. The special tools, packaged, shall be secured to the launcher in accordance with drawing D147-1-189, showing a detail of drawing DL147-1-100.

5.1.5 Technical publications. Applicable technical publications shall be sealed within a bag conforming to type II, style I, PPP-B-26, having inside dimensions of 10 inches wide by 12 inches long. Included air volume shall be kept to a practical minimum.

5.2 Packing, level A. The launcher, packaged as specified in 5.1.2, shall be packed in accordance with drawing D17-1-189, showing a detail of drawing Dl147-1-100.

5.3 Marking. In addition to any special marking required in the contract or order, interior packages shall be marked in accordance with MIL-STD-129 and shipping containers shall be marked in accordance with drawing D147-1-164, showing a detail of drawing DL147-1-100.

5.4 Palletization. When specified in the contract or order, the launcher, packed in accordance with 5.2, shall be palletized in accordance with drawing D147-1-163, showing a detail of drawing DL147-1-100.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The launcher described in this specification is intended to launch rockets to neutralize hard, soft, or jungle-type targets and is man-portable for field use.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of the specification

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.1.2)

c. Whether a first article sample is required (see 3.1 and 4.3)

d. That the M74 rocket and clip will be GFE when applicable (see 3.2.1)

e. Whether inspection conditions will vary from those stated in 4.3.7 (see 4.1.2)

f. Whether palletization is required (see 5.4).

6.3 First article. When first article inspection is required, the contracting officer should provide specific guidance to offerers whether the item(s) should be a first article sample, a first production item, or a number of items to be tested as specified in 4.3. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examinations, approval of first article test results and disposition of first articles. Invitations for bids should provide that the Government reserves the right to waive the requirement for samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the Government, and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract.

6.4 Caution. Due to the hazards attending primer firing, contractors are advised to take all necessary precautions to protect personnel during testing.

6.5 Metrication. Metric equivalents in accordance with FED-STD-376 are acceptable for use in this specification.

6.6 Subject term (keyword) listing.

Artillery
Explosives
Missile, shoulder-fired
Projectile

6.7 Government-furnished property. The contracting officer should arrange to furnish the property listed in 3.2.1.

6.8 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

Custodian:
Army - MI

Preparing Activity:
Army - MI

Project No. 1055-A074

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER MIL-L-51343B(MI)	2. DOCUMENT DATE (YYMMDD) 16 November 1990

3. DOCUMENT TITLE
Launcher, Rocket, 66MM, Four Tube, M202

4. NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON	e. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME Commander, U.S. Army Missile Command Attn: AMSMI-RD-SE-TD-ST	b. TELEPHONE (Include Area Code) (1) Commercial: (205) 876-6980 (2) AUTOVON: 746-6980
c. ADDRESS (Include Zip Code) Redstone Arsenal, AL 35898-5270	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340

DD FORM 1426 89 OCT

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.