MIL-S-51261A(MU)
28 January 1970
SUPERSEDING
MIL-S-51261(MU)
31 January 1967

MILITARY SPECIFICATION

SERVICE UNIT, FLAME THROWER, TRACK VEHICLE MOUNTED, XM45E1

1. SCOPE

1.1 This specification covers one type of service unit.

2. APPLICABLE DOCUMENTS

2.1 Government documents. The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

L-P-378	-	Plastic Film (Polyethylene Thin Gage).
NN-P-530	-	Plywood, Flat-Panel.
QQ-S-781	-	Steel Strapping, Flat.
UU-T-106	-	Tape, Pressure-Sensitive Adhesive, Masking, Paper.
UU-C-282	-	Chipboard.
VV-F-800	-	Fuel Oil, Diesel.
VV-L-800	-	Lubricating Oil, General Purpose, Preservative (Water-Displacing, Low Temperature).
PPP-B-566	-	Box, Folding, Paperboard.
PPP-B-601	-	Boxes, Wood, Cleated-Plywood.
PPP-B-621	-	Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636	-	Box, Fiberboard.
PPP-F-320	-	Fiberboard; Corrugated and Solid, Sheet Stock (Container Grade), and Cut Shapes.
PPP-P-291	-	Paperboard, Wrapping, Cushioning.
PPP-T-60	-	Tape; Pressure Sensitive Adhesive, Waterproof-For Packaging.
PPP-T-76	-	Tape, Pressure-Sensitive Adhesive Paper, Water Resistant, (For Carton Sealing).
PPP-T-97	-	Tape, Pressure-Sensitive Adhesive, Filament Reinforced.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-C-104 - Crate, Wood, Lumber and Plywood Sheathed, Nailed and Bolted.
MIL-P-116 - Preservation, Methods of.
MIL-B-117 - Bag and Sleeve, Interior Packaging.
MIL-B-121 - Barrier Material, Greaseproofed, Waterproofed, Flexible.
MIL-P-130 - Paper, Wrapping, Laminated and Creped.
MIL-T-704 - Treatment and Painting of Material.
MIL-H-775 - Hose, Rubber or Fabric (Including Tubing) and Fittings, Nozzles and Strainers, Packaging of.
MIL-P-3542 - Primer: Pressure-Sensitive Tape.
MIL-H-5606 - Hydraulic Fluid, Petroleum Base; Aircraft, Missile and Ordnance.
MIL-G-10924 - Grease, Automotive and Artillery.
MIL-B-13239 - Barrier Material, Waterproofed, Flexible All Temperature.
MIL-V-13811 - Varnish, Waterproofing, Electrical, Ignition.
MIL-L-15017 - Lubricating Oil, Hydraulic.
MIL-H-15424 - Hand Tools: Packaging of.
MIL-C-16173 - Corrosion Preventive Compound, Solvent Cutback, Cold Application.
MIL-C-17504 - Coating Compound, Acrylic, Clear.
MIL-P-17667 - Paper, Wrapping, Chemical Neutral (Non-Corrosive).
MIL-C-51172 - Compressor, Reciprocating, 50 CFM, 3000 psi.
MIL-C-52078 - Cap-Plug, Cap and Plug, Protective, Plastic, Dust and Moisture Seal.
MIL-C-62015 - Carrier, Cargo, Full-Tracked M548, Processing for Storage and Shipment of.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-1168 - Lot Numbering of Ammunition.

DRAWINGS

US ARMY MUNITIONS COMMAND

EDGEWOOD ARSENAL

DL381-8-1063 - Service Unit, Flame Thrower, Track Vehicle Mounted, XM45E1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

PUBLICATIONS

DEPARTMENT OF THE ARMY TECHNICAL MANUAL

TM3-366 - Flame Fuels.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials and components.

3.1.1 Materials. All materials cited on Drawing DL381-8-1063 or on subsidiary drawings shall conform to the specifications listed thereon or to the specific characteristics set forth in the drawings.

3.1.2 Components. All components of the service unit shall conform to the specifications and drawings listed on Drawing DL381-8-1063 and subsidiary drawings.

3.2 Full-tracked cargo carrier modification. Modifications to the M548 full-tracked cargo carrier shall conform to Drawings E81-8-2020, E381-8-2714 and associated drawings.

3.3 Assembly. The service unit shall be assembled in accordance with Drawing E81-8-1127. The hydraulic installation (Drawing K381-8-2725) shall be filled with one of the following.

(a) For service between 32° and 125° F, hydraulic oil conforming to Military Symbol 2135H of MIL-L-15017.

(b) For service below 32° F, hydraulic oil conforming to MIL-H-5606.

3.4 Performance.

3.4.1 Compressor preheating. The engine coolant shall heat the compressor preheating system when tested as specified in 4.4.4.1(a).

3.4.2 Fuel heating. The engine coolant shall heat the heater jacket and mixing tank heating system when tested as specified in 4.4.4.1(g).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

3.4.3 Hydraulic pump.

3.4.3.1 Fan motor. The hydraulic pump shall drive the fan motor, for compressor preheating, at a speed of no less than 1750 revolutions per minute (rpm) when tested as specified in 4.4.4.1(b).

3.4.3.2 Fuel pump.

(a) Intake. The fuel pump shall pump a minimum of 190 gallons of diesel fuel conforming to VV-F-800 into the fuel storage tanks in a maximum time of 8 minutes against a suction head of 10 feet. The diesel fuel shall be at a maximum temperature of 80° F. Under the same test conditions, the fuel pump shall pump a minimum of 190 gallons of diesel fuel into the mixing tank in a maximum time of 11 minutes when tested as specified in 4.4.4.1(c).

(b) Discharge. The fuel pump shall pump a minimum of 190 gallons of diesel fuel out of the mixing tank in a maximum time of 13 minutes against 125 pounds per square inch gage (psig) minimum back pressure when tested as specified in 4.4.4.1(d).

(c) Mixing tank. The pump shall pump a minimum of 190 gallons of diesel fuel from the storage tanks to the mixing tank in a maximum of 8 minutes when tested as specified in 4.4.4.1(e).

3.4.3.3 Agitator motor. The hydraulic pump shall drive the agitator motor when tested as specified in 4.4.4.1(f).

3.4.4 Compressor air system.

3.4.4.1 Compressor shaft speed. The cargo carrier engine hand throttle shall control the engine speed at 1800 ± 50 rpm so that, with the cargo carrier power takeoff engaged, the transmission in fourth gear, and the transfer case in neutral, the compressor shall be driven at its rated speed when tested as specified in 4.4.4.1(i).

3.4.4.2 Performance.

(a) Three thousand psig air system. The 3000 psig air system shall furnish air to its hose connection at a pressure of 3000 ± 200 psig and at a minimum rate of 50 cubic feet per minute (cfm). The compressor shall be capable of pressurizing a five cubic foot minimum pressure vessel from 0 psig to a minimum of 2800 psig in a maximum time of 20 minutes when tested as specified in 4.4.4.1(j).

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:05Z
Check the source to verify that this is the current version before use.

(b) Two thousand psig air system. The 2000 psig air system ıall furnish air to its hose connection at a pressure of 2000 ± 100 psig ıen tested as specified in 4.4.4.1(j).

3.4.5 Leakage.

3.4.5.1 Components. The fuel mixing, hydraulic, coolant and air 'stems shall not leak when tested as specified in 4.4.4.3.

3.4.5.2 Hull unit. Leakage of the hull shall not exceed the capacity the bilge pumps when tested as specified in 4.4.4.1(k).

3.5 Storage tanks. The storage tanks, Drawing E381-8-2689 and Drawing 381-8-2674, shall not leak when subjected to an air pressure of 2 to 3 ig for a minimum period of 20 minutes when tested as specified in 4.4.4.2.

3.6 Identification marking. Each service unit shall be serially numbered.

3.7 Mixing. The service unit (see 4.3.1) shall blend gasoline and ickner and transfer the thickened fuel mix in a maximum of 15 minutes en tested as specified in 4.3.3.

3.8 Roadability. The service unit shall not leak and shall be capable of rforming in accordance with 3.4 after being driven over unimproved roads d hilly terrain at speeds between 15 and 30 miles per hour for a minimum 1000 miles (see 6.2) and tested for a minimum period of 15 minutes after ch 100 miles as specified in 4.4.4.3 when tested as specified in 4.3.3.2. e storage tanks shall have 200 gallons of diesel fuel in them for this st.

3.9 Preproduction. Prior to the start of regular production, a prepro- ction sample service unit shall be produced in accordance with this ecification for examination and tests (see 4.3).

3.10 Workmanship. The service unit shall be free from contamination ıst, dirt, oil or excessive grease) and damage such as dents, cracks or formation which could affect its intended use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.

4.1.1 Supplier's responsibility. Unless otherwise specified in the tract or purchase order, the supplier is responsible for the perform- e of all inspection requirements as specified herein. Except as erwise specified in the contract or order, the supplier may use his

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:05Z
Check the source to verify that this is the current version before use.

ports provided. The fuel dures as will be used in regular production the outlet and relief

own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to specified requirements.

4.1.2 Objective evidence. The supplier shall provide objective evidence acceptable to the contracting officer that the requirements of 3.1, 3.2, 3.3 and section 5 for which specific inspection has not been provided in this specification have been satisfied.

4.2 Classification of inspections.

(a) Preproduction inspection (see 4.3).
(b) Quality conformance inspection (see 4.4).

4.3 Preproduction inspection.

4.3.1 Sample. A preproduction sample of one service unit shall be manufactured using the same methods, materials, equipment and processes as will be used during regular production.

4.3.2 Inspection procedure.

4.3.2.1 For examination and tests. The sample service unit shall be examined and tested in accordance with 4.4.4.

4.3.2.2 For nondestructive test. The sample service unit shall be tested in accordance with 4.3.3.

4.3.3 Tests.

4.3.3.1 Mixing. Prior to and after road test, pump 190 ± 1 gallons of gasoline into the mixing tank. Add 49 ± 1 pounds of M4 thickner (see 6.2) to the gasoline and agitate until desired consistency is obtained in accordance with TM3-366. Transfer the thickened fuel to a suitable container. For safety precautions use TM3-366.

4.3.3.2 Roadability. The service unit shall be driven the required distance at the specified speed. The unit shall be stopped and functioned as specified. During functioning all piping, valves, hoses, connections and gages shall be visually checked for leakage.

4.3.4 Acceptance/rejection criteria. The preproduction sample shall comply with the examinations and tests specified in 4.3.2 to be acceptable. The acceptance number is zero. The supplier shall obtain written approval from the contracting officer prior to proceeding with regular production.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:05Z
Check the source to verify that this is the currentversion before use.

4.4 Quality conformance inspection.

4.4.1 Lotting. A lot shall consist of the like components identified and controlled in accordance with MIL-STD-1168.

4.4.2 Sampling.

4.4.2.1 Storage tank. Each storage tank shall be tested for leakage.

4.4.2.2 Service unit. Each service unit shall be tested for performance and leakage.

4.4.3 Inspection procedure.

4.4.3.1 Storage tank. Each storage tank shall be tested in accordance with 4.4.4.2. Defective tanks shall be rejected.

4.4.3.2 Service unit. Each service unit shall be tested in accordance with 4.4.4.1 and 4.4.4.3. Defective units shall be rejected.

4.4.3.3 Classification of defects.

(a) Preparation for delivery (section 5).

Categories		Defects
Critical:		None defined
Major:		AQL 4.0 percent defective
101		Tags not processed as specified
102		Preservatives or coatings missing
103		Openings, covers, and doors not processed as specified
104		Equipment not lubricated as specified
105		Item improperly secured to prevent movement
106		Strapping loose or missing
107		Marking missing, illegible, or incorrect

4.4.4 Tests. Tests shall be conducted as follows:

4.4.4.1 Performance. In the following specified order, the service unit shall be tested at any ambient temperature:

(a) Start the cargo carrier engine and allow to warm up. Circulate coolant through the compressor preheating system. Feel the compressor preheating system to assure that it is warm to the touch.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:05Z
Check the source to verify that this is the currentversion before use.

(b) Close both valves (compressor preheat and heat exchanger) and operate the fan motor for compressor preheating. Record the fan shaft speed using stroboscope or other acceptable method. Then stop the fan.

(c) With the service unit inlet a minimum of 10 feet above the surface of diesel fuel supply, pump diesel fuel into the storage tanks. Then pump diesel fuel into the mixing tank. In each case, record the number of gallons pumped, pumping time and temperature of the diesel fuel.

(d) Connect a pressure gage and valve to the outlet of the mixing tank. While discharging the diesel fuel from the mixing tank, adjust the valve to maintain a minimum reading of 125 psig on the gage. Record the time required to empty the mixing tank.

(e) Transfer the diesel fuel from the storage tanks to the mixing tank. Record the time required.

(f) After the mixing tank is filled, start the agitator motor and look into the tank to ascertain the agitator is functioning. Stop the agitator.

(g) Operate the fuel heating system. Record the temperature of the diesel oil. Shut off the fuel heating system.

(h) Empty the mixing tank.

(i) Connect the 3,000 psig outlet of the compressor to a five cubic foot pressure vessel and operate the compressor at its rated speed and power.

(j) Attach a calibrated pressure gage to the 2000 psig hose connection and record the pressure.

(k) Each vehicle shall be operated a minimum of five minutes in water deep enough to float the vehicle. During this time both bilge pumps shall be operating.

4.4.4.2 Storage tank. Subject the tank to the specified pressure and use a suitable leak-detecting solution to check all joints for leakage.

4.4.4.3 Leakage.

(a) Fuel system. With the service unit operating, check all piping, joints, and fittings of the fuel system for visible signs of leakage with the controls set at the following operating positions:

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:05Z
Check the source to verify that this is the currentversion before use.

(1) Filling mixing tank from oil supply.
(2) Heating test fluid.
(3) Discharging test fluid from mixing tank.

(b) Hydraulic piping. With the service unit operating, check the hydraulic lines, joints, and fittings of the hydraulic power system for visible signs of leakage during the following operations:

(1) Compressor preheating.
(2) Agitation.
(3) Discharging test fluid from the mixing tank.

(c) Coolant system. With the service unit operating and coolant control valves open, check all piping, joints, and fittings of the coolant system for visible signs of leakage.

(d) Air piping. Close both air service outlet valves, and operate the compressor to pressurize the 3000 psig air lines to 3000 + 200 psig. Check all pressurized air line joints for leakage with a suitable leak-detecting solution.

5. PREPARATION FOR DELIVERY

5.1 Cleaning and drying. After test runs, if any, have been completed and before the application of any preservatives or coatings, all surfaces shall be cleaned and dried in conformance with MIL-P-116. Cleaning process C-1, and the most applicable of the drying procedures listed therein, shall be used. In addition, special cleaning and drying methods covering certain areas on the equipment are indicated herein, and these methods whenever specified shall be used. Adequate precautions shall be taken to protect adjacent critical areas.

5.2 Repainting. Damaged portions of painted surfaces shall be treated and repainted in accordance with the applicable requirements of type A finishing system of MIL-T-704. The same quality and color of paint, as specified on the applicable drawings, shall be used.

5.3 Lubrication. After cleaning and repainting have been completed, all grease fittings shall be wiped clean. Joints, bearings, and similar moving parts shall be thoroughly lubricated with the equipment manufacturer's approved lubricants. Change of crankcase oil and servicing of enclosed gears is not included in this lubrication procedure. After lubrication, all grease fittings shall be wiped clean and a red circle shall be painted around the base of each fitting. Grease fittings shall be covered with red plastic snap-on caps or with class 1 pressure-sensitive tape conforming to PPP-T-60.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:05Z
Check the source to verify that this is the current version before use.

5.4 Preservation and packaging.

5.4.1 Level A.

5.4.1.1 Preservatives and packaging methods. Unless otherwise specified, preservatives cited herein, and the application thereof, shall conform to the applicable requirements of MIL-P-116. Preservatives shall not be applied to painted surfaces, and provisions shall be made to prevent such surfaces from coming in contact with preservatives on adjacent metal parts. Packaging methods cited herein shall also conform to MIL-P-116.

5.4.1.2 Tags and tag waterproofing. Unless otherwise specified, tags shall be waterproofed by coating both sides of the tags with a clear acrylic coating compound conforming to MIL-C-17504.

5.4.1.3 Pressure-sensitive tape application. Painted surfaces, to which tape is to be applied, shall be cleaned to remove dirt, grease and other foreign matter, and then shall be coated with primer, pressure-sensitive tape, conforming to MIL-P-3542 to increase adhesiveness of the tape and durability of seals formed by the tape.

5.4.1.4 Exposed unpainted metal surfaces.

5.4.1.4.1 Machines surfaces. Machines surfaces shall be coated with either type P-6 or P-11 preservative. Where it is necessary to protect the preservative from being prematurely removed, such preserved areas shall be covered with grade A, greaseproofed barrier material, conforming to MIL-B-121, and secured in place with class 1 pressure-sensitive tape, conforming to PPP-T-60. The tape and barrier material shall be overcoated with electrical ignition waterproofing varnish, conforming to MIL-V-13811.

5.4.1.4.2 Other unpainted metal surfaces. All unpainted surfaces, other than those specified in 5.4.1.4.1, such as steering assemblies, tie rods, springs, pintle assemblies, threaded surfaces and surfaces exposed by disassembly, shall be coated with type P-1 preservative.

5.4.1.4.3 Fire extinguishers. All openings into the interior of the fire extinguishers shall be sealed with class 1, pressure-sensitive tape conforming to PPP-T-60. All exterior surfaces, including the taped areas, shall be overcoated with a clear acrylic coating compound conforming to MIL-C-17504. The extinguishers shall then be packaged in accordance with the method III and packed with other OVE. (On Vehicle Equipment)

5.4.1.5 Carrier, cargo. Except as otherwise specified therein, the carrier and components shall be preserved and packaged in accordance with the applicable level A requirements of MIL-C-62015.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

5.4.1.6 Service unit.

(a) Hydraulic system. The supply tank of the hydraulic system on the service unit shall be filled to operating level with an approved hydraulic fluid as recommended in TM3-1040-256-12.

(b) Controls. Controls shall be positioned as follows:

(1) Fuel valves - closed position.
(2) Fan motor and fuel pump - off position.
(3) Agitator - off position.
(4) Compressor clutch control handle - disengaged position.
(5) All air valve controls slightly open, except safety air valve, which shall be completely open.
(6) Coolant preheater valves - closed position.
(7) Hydraulic tank drain valves - closed position.
(8) Compressor oil drain valves - closed position. No processing required.
(9) Cooler drain valve - open position.
(10) Hydraulic pump clutch control lever - disengaged position.

(c) Control panel. The glass or plastic dials on the control panel shall be covered with a fitted piece of plywood conforming to group A of NN-P-530 (type 1, grade 3 or 4 of CS35) provided the plywood does not have continuous holes or openings extending through the piece from face to back and secured in place with class 1 pressure-sensitive tape conforming to PPP-T-60. A cover fabricated from barrier material, class 1 conforming to MIL-B-121, shall be secured over the entire control panel using pressure-sensitive tape, class 1 conforming to PPP-T-60.

(d) Grounding reel. The openings into the reel drum shall be sealed off with pressure-sensitive tape, class 1 conforming to PPP-T-60. The exposed portions of the grounding cable and clips shall be covered with the above tape. The loose end of the taped grounding cable shall be secured to the reel with the same tape as above.

(e) High pressure air valves, bleed valves and high pressure air connections. These valves and connections located on the delivery panel shall be capped with capplugs conforming to MIL-C-52078 and taped using pressure-sensitive tape conforming to class 1 of PPP-T-60.

(f) Fuel mixing system. The entire fuel mixing system shall be flushed out with P-10, grades 2 and 3 preservative oil, allowing excess preservative oil to drain off. The interior surfaces of the mixing tank and cover shall be coated with the same type of preservative oil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

(g) Fuel service outlet and inlet. Each fuel service inlet and outlet shall be closed with the cap or plug provided and wrapped with type 1 laminated and creped wrapping paper, conforming to MIL-P-130, or with grade A greaseproofed barrier material, conforming to MIL-B-121. The wraps shall be secured in place by tying or taping.

(h) Suction pipe and stowage tube. The suction pipe shall be coated with type P-9 preservative and placed in the stowage tube. The stowage tube cover shall be closed and the seams around cover taped with class 1, pressure-sensitive tape, conforming to PPP-T-60. The tape shall be overcoated with electrical ignition waterproofing varnish conforming to MIL-V-13811.

(i) Air compressor. Air compressor shall be preserved and packaged in accordance with level A requirements of MIL-C-51172.

5.4.1.7 Nameplates, data and instruction plates. These items shall be thoroughly cleaned, dried and then coated with a clear acrylic coating compound conforming to MIL-C-17504.

5.4.1.8 Component parts. Preservation and packaging, level A.

(a) Kit, machine gun mount. Preserve and package in accordance with level A requirements of packaging data sheet 10949672.

Group A

a. The following items shall be packaged together in a fiberboard box conforming to style RSC, grade W5c of PPP-B-636. Inside dimensions of the box shall be approximately 17-1/4 by 8-1/4 by 5-7/8 inches (length, width and depth respectively). The box shall be closed in accordance with the appendix to PPP-B-636, using PPP-T-76 tape (see 5.6.2).

(1) Lubrication order, 1-09-2300-224-12/2/7 and strapping diagram, ORD. No. 11588973. Package both items together in accordance with method IC-1 of MIL-P-116 in a 10 by 14 inch bag.

(2) Lamp, M535478-1683. The lamp shall be wrapped in chipboard conforming to UU-C-282 and placed in a paperboard box conforming to variety 1, style 2, type A, class A of PPP-B-566. Inside dimensions of the box shall be approximately 1-1/4 by 1-1/4 by 2-1/4 inches (length, width, and depth). The box shall be closed with a 1 by 2 inch piece of tape conforming to UU-T-106. The closed box shall be sealed in a plastic bag conforming to type II, class C of MIL-B-117.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

(3) Extension light 17C-35079-33, padlock MS35647-7, adapter FSN 5120-240-8701, adapter FSN 5120-240-8702. Coil light wire to smallest practical size and wrap each of the specified items in barrier material conforming to type II, grade A, class 2 of MIL-B-121. Package items in accordance with method IC-2 of MIL-P-116, in a variety 1, style II, type A, class A box of PPP-B-566. Inside dimensions of the box shall be approximately 6 by 2-1/2 by 9-3/4 inches (length, width and depth). The box shall be closed with 2 pieces of 2 by 5 inch tape conforming to UU-T-106. The closed box shall be sealed in a plastic bag measuring 10 by 15 inches, conforming to type II, class C of MIL-B-117.

(4) Bag 7961712. Fold to smallest practical size.

(5) Grease gun 10915142. The gun shall be wrapped in barrier material conforming to type II, grade A, class 2 of MIL-B-121. The wrapped gun shall be packaged in accordance with method IC-2 of MIL-P-116, using a box conforming to variety 1, style II, class A of PPP-B-566. Inside dimensions of the box shall be approximately 5 by 3 by 16-1/2 inches (length, width and depth). The box shall be closed using 2 pieces of 2 by 5 inch tape conforming to UU-T-106. The closed container shall be sealed in a 9 by 23 inch plastic bag conforming to type II, class C of MIL-B-117.

(6) Tape 17-T-805.

b. The following items, unless otherwise specified, shall be packaged, individually, as indicated.

(1) Cover (air intake) 11588991 and cover (radiator) 11588982. Fold covers together and place in style RSC, grade W5c fiberboard box conforming to PPP-B-636. Inside dimensions of the box shall be approximately 17-1/4 by 8 by 5 inches (length, width and depth). The box shall be closed in accordance with the appendix to PPP-B-636 using PPP-T-76 tape.

(2) Fixture, track 10932359. Package two track fixtures separately in accordance with method I of MIL-P-116, using preservative grade 4 of MIL-C-16173, as required, and wrap in type II, grade A, class 2 barrier material conforming to MIL-B-121. The preserved and wrapped items shall then be packaged together in a fiberboard box conforming to style RSC, grade W5c of PPP-B-636. Inside dimensions of the box shall be approximately 19 by 5-1/4 by 4-1/2 inches (length, width and depth). Closure of the box shall be in accordance with the appendix to PPP-B-636, using PPP-T-76 tape.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

(3) Punch, drive pin 10861180. The punch shall be packaged in a fiberboard box conforming to grade W5c, style RSC of PPP-B-636. Inside dimensions of the box shall be approximately 20 by 6-1/2 by 2-1/2 inches (length, width and depth). The box shall be closed in accordance with the appendix to PPP-B-636, using PPP-T-76 tape.

(4) Block, snatch 8383241. Package in accordance with method I of MIL-P-116. Use preservative conforming to MIL-C-10924 applied through grease fittings as required. Filler pads, type CF, class NR of PPP-F-320 shall be used for cushioning and to make a tight pack. The preserved and cushioned item shall be placed in a fiberboard box conforming to style RSC, grade W5c of PPP-B-636. Inside dimensions of the box shall be approximately 17 by 15 by 6-1/4 inches (length, width and depth respectively). The box shall be closed in accordance with the appendix to PPP-B-636, using PPP-T-76 tape.

(5) Tow cable 10861718. The cable shall be coiled to approximately 20 by 20 inches and packaged method III of MIL-P-116 in a fiberboard box conforming to style FOL, grade W5c of PPP-B-636. Inside dimensions of the box shall be approximately 20 by 5 by 20 (length, width and depth). The box shall be closed in accordance with the appendix to PPP-B-636, using PPP-T-76 tape.

(6) Fire extinguisher 7714780. Package in accordance with method III of MIL-P-116, using cushioning conforming to type CF, grade V3c of PPP-F-320. The cushioned item shall be packaged in a fiberboard box conforming to style RSC, grade V3c of PPP-B-636. The fiberboard box and cushioning shall be as specified on drawing D381-8-2772. Closure of the box shall be in accordance with the appendix to PPP-B-636, using PPP-T-76 tape.

(7) Chain, utility 7077063. The chain shall be packaged method III of MIL-P-116, using a fiberboard box conforming to style RSC, grade V3c of PPP-B-636. Inside dimensions of the box shall be approximately 17 by 10 by 6-1/8 inches (length, width, and depth). The box shall be closed in accordance with the appendix to PPP-B-636, using PPP-T-76 tape.

(8) Cover assembly 10950020. Fold the cover as applicable and package in a style RSC, grade W5c fiberboard box conforming to PPP-B-636. Inside dimensions of the box shall be approximately 25 by 25 by 8 inches (length, width and depth). The box shall be closed in accordance with the appendix to PPP-B-636, using PPP-T-76 tape.

(9) Hardware. Package the following items together in a barrier bag conforming to MIL-B-121. The bag dimensions shall be approximately 10 by 12 inches. The bag shall be heat sealed in accordance with the manufacturers standard procedure.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

(a) Washer 11589321, eight (8) each.
(b) Washer 11589319-4, eight (8) each.
(c) Pad 11589318-4, four (4) each.
(d) Pad 11589149, fourteen (14) each.
(e) Screw MS90716-115, eight (8) each.

(10) Fire extinguisher 874542. Two each, fire extinguishers shall have all openings sealed with class 1 of PPP-T-60 tape. Each extinguisher shall be externally overcoated including the tape, with acrylic coating conforming to MIL-C-17504. Package both extinguishers together in a fiberboard box conforming to grade V3c, style FOL of PPP-B-636, and cushion as applicable with material conforming to PPP-P-291. The box shall be closed in accordance with the appendix to PPP-B-636, using PPP-T-76 tape. Inside dimensions of the box shall be approximately 29-1/2 by 15 by 13-3/4 inches, (length, width and depth).

(11) Cab cover assembly. Fold cover to approximately 32-1/2 by 31 by 2 inches and package method III of MIL-P-116 in a fiberboard box conforming to style RSC, grade W5c of PPP-B-636. Closure of the box shall be in accordance with the appendix to PPP-B-636, using PPP-T-76 tape.

(12) Mount assembly 10949948. Wrap mount in barrier material conforming to type II, grade A, class 2 of MIL-B-121. Secure the wrap in place with tape conforming to PPP-T-76.

(13) Hose assembly, service line, 1-1/4 inch, FSN 1040-953-0000. Package method III of MIL-P-116 in a fiberboard box conforming to style RSC, grade W5c of PPP-B-636. Inside dimensions of the box shall be approximately 23 by 23 by 4-1/2 inches (length, width and depth). The box shall be closed in accordance with the appendix to PPP-B-636, using PPP-T-76 tape.

(14) Inlet fuel hose assembly FSN 1040-326-5659. Package in accordance with MIL-H-775 in a fiberboard box conforming to style RSC, grade W5c of PPP-B-636. Inside dimesnions of the box shall be approximately 43 by 6 by 4 inches (length, width and depth). The box shall be closed in accordance with the appendix to PPP-B-636, using PPP-T-76 tape.

(15) Hose assembly, service line, 3/4 inch, FSN 4720-955-5319. Package method III of MIL-P-116 in a fiberboard box conforming to style RSC, grade W5c of PPP-B-636. Inside dimensions of the box shall be approximately 22-1/2 by 22-1/2 by 4 inches (length, width and depth). The box shall be closed in accordance with the appendix to PPP-B-636, using PPP-T-76 tape.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

(16) Hose, air, assembly FSN 1040-992-6343. Package same as item 15 except the inside box dimensions shall be approximately 17-1/2 by 17-1/2 by 3-1/2 inches (length, width and depth).

(17) Hose assembly, charging FSN 1040-859-2267. Package method IC-1 of MIL-P-116 in a type II 7 by 7 inch plastic bag conforming to MIL-B-117. The sealed bag with hose, shall be placed in a fiberboard box conforming to style RSC, grade W5c, of PPP-B-636. Inside dimensions of the box shall be approximately 17 by 6 by 2 inches (length, width and depth). The box shall be closed in accordance with the appendix to PPP-B-636, using PPP-T-76 tape.

(18) Hose assembly, rubber FSN 1040-384-0494. Package method III of MIL-P-116, in a fiberboard box conforming to grade W5c, style RSC of PPP-B-636. Inside dimensions of the box shall be approximately 7 by 7 by 4-1/2 (length, width and depth). The box shall be closed in accordance with the appendix to PPP-B-636, using PPP-T-76 tape.

(19) Adapter assembly, quick disconnect FSN 1040-897-2296. Package method IC-1 of MIL-P-116 and wrap in paper conforming to MIL-P-17567. Cap the open ends with plastic caps conforming to MIL-C-52078, and place in a 5 by 2 inch plastic bag conforming to MIL-B-117. The sealed bag shall then be placed in a grade W5c, style RSC fiberboard box conforming to PPP-B-636. The box shall be closed in accordance with the appendix to PPP-B-636, using PPP-T-76 tape.

(20) Funnel, metal, type V, class A-2, 1 quart, FSN 7240-824-2082. Package method III of MIL-P-116 in a fiberboard box conforming to style RSC, grade W5c of PPP-B-636. Inside dimensions of the box shall be approximately 13 by 8-1/2 by 6-1/2 inches (length, width and depth). The box shall be closed in accordance with the appendix to PPP-B-636, using PPP-T-76 tape.

(21) Stake, static, ground, FSN 5975-989-5891. Package method III of MIL-P-116 in a fiberboard box conforming to style FOL, grade W5c of PPP-B-636. Inside dimensions of the box shall be approximately 10-3/4 by 2 by 37 inches (length, width and depth). The box shall be closed in accordance with the appendix to PPP-B-636, using PPP-T-76 tape.

(22) Waste receptacle, FSN 7240-764-5269. Package method III of MIL-P-116 in a fiberboard box conforming to style RSC, grade W5c of PPP-B-636. Inside dimensions of the box shall be approximately 20 by 20 by 35 inches (length, width and depth). The box shall be closed in accordance with the appendix to PPP-B-636, using PPP-T-76 tape.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

(23) Wrench, open end, FSN 5120-080-0983. Package ethod III of MIL-P-116 in a fiberboard box conforming to style RSC, rade W5c of PPP-B-636. Inside dimensions of the box shall be pproximately 16 by 6 by 2 inches (length, width and depth). The box iall be closed in accordance with the appendix to PPP-B-636, using PP-T-76 tape.

(24) Wrench, pipe, 14 inch, FSN 5120-154-8420. Pack- ge same as item (23) except box dimensions shall be 14 by 5 by 3-1/2 iches.

(25) Safety can, FSN 7240-248-9620. Package same ; item (22), except box dimensions shall be 12 by 12 by 15 inches.

(26) Cushions. Package the following cushions idividually as specified, and then package together in a fiberboard ox conforming to grade W5c, style RSC of PPP-B-636. Inside dimensions the box shall be approximately 28-1/2 by 18-1/2 by 15 inches (length, dth, depth). The box shall be closed in accordance with the appendix) PPP-B-636, using PPP-T-76 tape.

(a) Cushion 10949733, 3 each. Package each ishion method IC-1 of MIL-P-116, in a plastic bag conforming to type 1 L-P-378. The bag shall measure approximately 26 by 32 inches.

(b) Cushion 10949726, 3 each. Package same as) above, except bag shall measure 26 by 35 inches.

(c) Cushion 10949962, 1 each. Package same as) above.

(d) Cushion 11598769, 1 each. Package same as) above.

(27) Straps, web. The following straps shall be taped gether with PPP-T-76 tape and placed in a fiberboard box conforming to ade W5c, style RSC of PPP-B-636. Inside dimensions of the box shall approximately 6 by 6 by 6 inches (length, width and depth). The box all be closed in accordance with the appendix to PPP-B-636, using P-T-76 tape.

(a) Strap, web, crowbar and matlock, 8690466 0"), 2 each.

(b) Strap, web, tack fixture, 8690470 (28"), each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

(c) Strap, web, axe, shovel and sledge, 8690473 (36"), 2 each.
(d) Strap, web, matlock head, 8690462 (12"), 1 each
(e) Strap, web, tow cable, 8690468 (24"), 1 each.
(f) Strap, web, cargo door retaining, 8690465 (18") 2 each.

(28) Exhaust extension. Coat with P-19 preservative of MIL-P-116, and wrap in barrier material conforming to grade A, type II, class 2 of MIL-B-121. Secure the wrap with tape conforming to PPP-T-76. Place the wrapped item in a fiberboard box conforming to style RSC, grade W5c of PPP-B-636. Inside dimensions of the box shall be approximately 17-1/2 by 4-1/2 by 5 inches (length, width and depth). The box shall be closed in accordance with the appendix to PPP-B-636, using PPP-T-76 tape.

(29) Clips. Package the following items method III of MIL-P-116 by wrapping together in barrier material conforming to grade A, type II, class 2 of MIL-B-121, and placing in a style RSC, grade W5c fiberboard box conforming to PPP-B-636. The box shall be closed in accordance with the appendix to PPP-B-636, using PPP-T-76 tape. Inside dimensions of the box shall be approximately 7 by 5 by 4 inches (length, width, depth)

(a) Clip 7752865, 4 each.
(b) Clip 87632222, 2 each.
(c) Clip 8763447, 4 each.
(d) Pin 10390023, 4 each.

Group B

a. Machine gun, .50, M2, FSN 1005-726-5636. Preserve and package in accordance with packaging data sheet 1005-726-5636. Pack in a style 2 wood box conforming to PPP-B-621. Inside dimensions of the box shall be approximately 47-3/4 by 8 by 9-5/8 inches (length, width and depth The box shall be closed and strapped in accordance with the appendix to PPP-B-621, using galvanized strapping.

b. The following items, preserved and packaged as indicated, shall be strapped together with two 3/4 x 0.030 galvanized steel straps conforming to QQ-S-781, or tape conforming to PPP-T-97. The strapped item shall be packed in a fiberboard box conforming to style FOL, grade W5c of PPP-B-636. The box shall be closed in accordance with the appendix to PPP-B-636, using PPP-T-76 tape (see 5.6.2).

(1) Axe, FSN 5110-293-2336. Protect bit by covering with fiberboard CF, SW, 200 grade, doemstic class of PPP-F-320, and secure in place with tape conforming to class 1 of PPP-T-60.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

(2) Crowbar FSN 5120-240-6040.

(3) Hammer FSN 5120-265-7462.

(4) Handle FSN 5120-254-6618.

(5) Mattock FSN 5120-243-2395.

(6) Shovel FSN 5120-293-3936.

c. The following items, preserved and unit packaged, in accordance with MIL-H-15424 and MIL-P-116, shall be packaged in a fiberboard box conforming to grade W5c, style RSC of PPP-B-636. Inside dimensions of the box shall be approximately 11-3/4 by 6 by 12 inches (length, width, depth). The box shall be closed in accordance with the appendix to PPP-B-636, using PPP-T-76 tape (see 5.6.2).

(1) Cutters, wire FSN 5110-595-8229.
(2) Carrier FSN 8465-261-4994.
(3) Flashlight FSN 6230-264-8261.
(4) Panel, marker FSN 8345-174-6865.
(5) Extension, grease gun FSN 4930-288-1511.
(6) Extension, socket wrench FSN 5120-227-8674.
(7) Pliers, slip joint FSN 5120-223-7397.
(8) Pliers, linemans FSN 5120-239-8251.
(9) Punch FSN 5120-273-001.
(10) Screwdriver FSN 5120-293-3169.
(11) Screwdriver FSN 5120-234-8913.
(12) Socket FSN 5120-189-7932.
(13) Socket FSN 5120-189-7946.
(14) Socket FSN 5120-235-5870.
(15) Socket FSN 5120-189-7985.
(16) Socket FSN 5120-189-7934.
(17) Socket FSN 5120-189-7935.
(18) Socket FSN 5120-189-7927.
(19) Socket FSN 5120-189-7913.
(20) Socket FSN 5120-189-7917.
(21) Socket FSN 5120-189-7914.
(22) Wrench FSN 5120-224-3154.
(23) Wrench FSN 5120-224-3141.
(24) Wrench FSN 5120-277-2342.
(25) Wrench FSN 5120-187-7126.
(26) Wrench FSN 5120-277-8300.
(27) Wrench FSN 5120-277-7025.
(28) Wrench FSN 5120-240-5609.
(29) Wrench FSN 5120-264-3796.
(30) Handle, socket wrench, FSN 5120-336-7590.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

d. The following items preserved and packaged level A in accordance with MIL-H-15424 and MIL-P-116, shall be placed together in a fiberboard box conforming to grade W5c, style RSC of PPP-B-636. Inside dimensions of the box shall be approximately 13 by 8 by 6 inches (length, width and depth). The box shall be closed in accordance with the appendix to PPP-B-636, using PPP-T-76 tape (see 5.6.2).

(1) Brush, FSN 1005-508-2589.
(2) Brush FSN 1005-716-2701.
(3) Brush FSN 1005-550-4037.
(4) Rod FSN 1005-556-4102.
(5) Hider FSN 1005-716-2072.
(6) Case FSN 1005-981-1257.
(7) Extractor FSN 4933-716-0041.
(8) Gate FSN 4933-535-1217.
(9) Rod FSN 1005-653-5441.
(10) Swab holder FSN 1005-716-2704.
(11) Bolt FSN 1005-614-7463.
(12) Box FSN 1005-714-8550.
(13) Extension FSN 1005-600-8976.
(14) Extractor FSN 1005-600-8959.
(15) Lever FSN 1005-600-9718.
(16) Lock FSN 1005-716-1300.
(17) Pin FSN 1005-731-2078.
(18) Pin FSN 1005-731-0080.
(19) Gear FSN 1005-550-4067.
(20) Slide, FSN 1005-535-1220.
(21) Spring, FSN 1005-309-8720.
(22) Stop, FSN 1005-716-1301.
(23) Switch, FSN 1005-550-4062.

e. Can, water, FSN 7240-242-6153. Package method III of MIL-P-116 and wrap in barrier material conforming to MIL-B-13239. Secure the wrap with tape conforming to PPP-T-76. The wrapped item shall be placed in a fiberboard box conforming to style RSC, grade W5c of PPP-B-636. The inside dimensions of the box shall be approximately 19 by 14-1/2 by 7 inches (length, width, depth). The box shall be closed in accordance with the appendix to PPP-B-636, using PPP-T-76 tape.

f. Hammer, hand, FSN 5120-224-4047. Preserve and package in accordance with MIL-H-15424 in a fiberboard box conforming to style RSC, grade W5c of PPP-B-636. Inside dimensions of the box shall be approximately 17 by 5-1/2 by 2-1/2 inches (length, width and depth). The box shall be closed in accordance with the appendix to PPP-B-636, using PPP-T-76 tape.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

g. Spout, flexible, FSN 7240-177-6154. Preserve and package in accordance with MIL-H-15424 in a fiberboard box conforming to style RSC, grade W5c, of PPP-B-636. Inside dimensions of the box shall be approximately 17-1/4 by 4-1/2 by 3-1/2 (length, width, depth). The box shall be closed in accordance with the appendix to PPP-B-636, using PPP-T-76 tape.

h. Case, ammunition, FSN 8465-705-2438. Package two cases, individually in accordance with method III of MIL-P-116, in a plastic bag measuring 8 by 10 inches and conforming to type 1, class C, style 1 conforming to MIL-B-117. The two individually packaged items shall be packed together in a fiberboard box conforming to style RSC, grade W5c of PPP-B-636. Inside dimensions of the box shall be approximately 14-1/4 by 11-1/2 by 4 (length, width, depth). The box shall be closed in accordance with the appendix to PPP-B-636, using PPP-T-76 tape.

i. Kit, first aid, FSN 6545-922-1200. Package method IC-2 of MIL-P-116 in a style RSC, grade W5c fiberboard box conforming to PPP-B-636. Seal the barrier material in accordance with the manufacturers standard procedures. The inside dimensions of the box shall be approximately 9-3/4 by 6-1/2 by 4 inches (length, width and depth). The box shall be closed in accordance with the appendix to PPP-B-636, using PPP-T-76 tape.

j. Oiler, FSN 4930-262-8868. Package method III of MIL-P-116, using a fiberboard box conforming to grade W5c, style RSC of PPP-B-636. Inside dimensions of the box shall be approximately 6 by 6 by 4-3/8 inches (length, width, depth). The box shall be closed in accordance with the appendix to PPP-B-636, using PPP-T-76 tape.

k. Bag, FSN 5140-473-6256. Package method III of MIL-P-116, in a plastic bag measuring 12 by 14 inches and conforming to MIL-B-117. The bagged item shall then be placed in a fiberboard box conforming to PPP-B-636. Inside dimensions of the box shall be approximately 12-1/2 by 8-1/2 by 3-3/4 inches (length, width and depth). The box shall be closed in accordance with the appendix to PPP-B-636, using PPP-T-76 tape.

l. Mittens, FSN 8415-266-8843. Package method IC-1 of MIL-P-116, in a plastic bag measuring approximately 8 by 15 inches and conforming to MIL-B-117. The bagged item shall be placed in a fiberboard box conforming to style RSC, grade W5c of PPP-B-636. Inside dimensions of the box shall be approximately 14-1/4 by 8 by 3. The box shall be closed in accordance with the appendix to PPP-B-636, using PPP-T-76 tape.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

m. Machine gun barrel, FSN 1005-726-6131. Depot pack.

n. Cover, machine gun, FSN 1005-735-7116. Fold and package method III of MIL-P-116 in a fiberboard box conforming to style RSC, grade W5c of PPP-B-636. Inside dimensions of the box shall be approximate 12 by 8 by 6 inches (length, width and depth). The box shall be closed in accordance with the appendix to PPP-B-636, using PPP-T-76 tape.

GROUP C

Kit, machine gun mount. Wrap the mount in barrier material conforming to type II, grade A, class 2 of MIL-B-121, and secure in place with tape conforming to PPP-T-76.

5.5 Packing, level A.

5.5.1 Service unit. Unless otherwise specified in the contract or order, the unit shall be shipped in accordance with the applicable level A requirements of MIL-C-62015.

5.5.2 Component parts.

5.5.2.1 Kit, machine gun mount. The kit preserved and packaged as specified in 5.4.1.8(a), shall be packed in accordance with the level A requirements of packaging data sheet 10949672, except that the top shall have its cleats mounted internally.

5.5.2.2 Group A items. Items designated in group A and preserved and packaged as specified therein, shall be packed together in a class 2, style 2 nailed wood box conforming to PPP-B-621. Inside dimensions of the box shall be approximately 59-3/4 by 54-1/4 by 33-1/4 inches (length, width and depth). The box shall be closed and strapped in accordance with the appendix to PPP-B-621, using galvanized strapping. Blocking and bracing shall be as required, and filler pads constructed from material conforming to type CF, grade W5c of PPP-F-320 shall be used as required to form a tight pack (see 5.6.3).

5.5.2.3 Group B items. Items designated in group B and preserved and packaged as specified therein, shall be packed together in a class 2, style 2 nailed wood box conforming to PPP-B-621. Inside dimensions of the box shall be approximately 50-1/2 by 26 by 17-1/4 inches (length, width and depth). The box shall be closed and strapped in accordance with the appendix to PPP-B-621, using galvanized strapping. Blocking and bracing shall be as required, and filler pads constructed from material conforming to type CF, grade W5c of PPP-F-320, shall be used as required to form a tight pack (see 5.6.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

5.5.3 Crate. The shipping containers specified in 5.5.2.1, 5.5.2.2 ınd 5.5.2.3, shall be placed and secured with galvanized strapping in ı skid crate conforming to type II, class 2, style A of MIL-C-104, ıs shown on Drawing C81-8-2871. Galvanized steel strapping (1-1/4 by 035) conforming to QQ-S-781, shall be used to secure the boxes to one ınother within the crate. Inside dimensions of the crate shall be pproximately 123 by 65-1/2 by 50-1/4 inches (length, width and depth). he load shall be secured to the pallet base and sufficiently blocked nd braced in accordance with the appendix to MIL-C-104.

5.6 Marking.

5.6.1 Unit packages. In addition to any special marking required by he contract or order, unit packages shall be marked in accordance with IL-STD-129.

5.6.2 Consolidated and intermediate packages. In addition to any pecial marking required by the contract or order, consolidated and ntermediate packages shall be marked in accordance with MIL-STD-129, ncluding part numbers, nomenclature and quantity of items.

5.6.3 Shipping containers. In addition to any special marking required y the contract or order, shipping containers shall be marked in accord- ıce with Drawing D150-1-16 and MIL-STD-129 for packing lists, etc. as equired.

5.6.4 Crate. In addition to any special marking required by the ontract or order, the crate shall be marked in accordance with Drawing 150-1-16 and MIL-STD-129 for packing lists, etc. as required.

5.7 Repair parts. When items are procured for storage and issue as repair part, preservation, packaging, packing and marking shall be ; specified on the repair part packaging data sheet which is identified ' the Federal stock number for the repair part.

6. NOTES

6.1 Intended use. The service unit is intended for use in servicing ıth portable and mechanized flame throwers with thickened fuel and mpressed air.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number and date of this specification.
(b) Serial number of each compressor and each service unit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

(c) Preproduction.

(1) Time allowed for supplier submission of samples for Government test and evaluation after award of contract.
(2) Name and address of test facility and shipping instructions when testing is performed by the Government.
(3) Time required for the Government to notify the supplier whether or not to proceed with production.

(d) The M4 thickner will be Government furnished.
(e) Road test plan shall be submitted by contractor for Government approval.

6.3 Caution. Because of the hazards inherent in testing with high pressure, manufacturers are hereby notified that every precaution possible should be taken for the safety and protection of personnel engaged in testing the items.

6.4 Supplementary quality assurance provisions (SQAP).

SQAP 81-3-66	-	Hose Assembly, Rubber.
SQAP 81-6-376	-	Hose Assembly, Charging.
SQAP 81-8-831	-	Tank, Hydraulic.
SQAP 81-8-847	-	Heat Exchanger.
SQAP 81-8-893	-	Receiver, Air.
SQAP 81-8-897-1	-	Valve, Safety Relief.
SQAP 81-8-897-2	-	Valve, Safety Relief.
SQAP 81-8-898	-	Valve, Check.
SQAP 81-8-936	-	Stake, Static Ground.
SQAP 81-8-981	-	Hose, Fuel.
SQAP 81-8-982	-	3/4 inch Service Line Fuel Hose Assembly.
SQAP 81-8-1028	-	Radiator, Compressor Heat.

Custodian:

Army - MU

Preparing activity:

Army - MU(EA)

Project No. 1040-A106

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

ORGANIZATION

CITY AND STATE | CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)* | DATE

DD FORM 1 JAN 66 1426 REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:05Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID

OFFICIAL BUSINESS

Commanding Officer
Edgewood Arsenal
ATTN: SMUEA-QAES
Edgewood Arsenal, Maryland 21010

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.