MILITARY SPECIFICATION

SURVIVAL KIT, AIRMAN'S, SEEK-1

1. SCOPE

1.1 This specification covers one type of airman's individual survival, escape, and evasion kit designated as SEEK-1. The components of the kit are packed in two similar containers marked, Container Number 1 and Container Number 2.

2. APPLICABLE DOCUMENTS

2.1 Government documents. The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

C-C-91	-	Candle, Illuminating.
L-P-378	-	Plastic Film (Polyethylene Thin Gage).
P-S-615	-	Soap, Surgical, Cake and Liquid.
U-P-401	-	Plaster, Adhesive, Surgical.
U-S-00560	-	Sodium Chloride Tablets.
V-T-295	-	Thread, Nylon.
GG-R-60	-	Razors, Safety; and Blades, Razor.
KK-C-300	-	Chamois, Leather, Sheepskin, Oil-Tanned.
NN-P-530	-	Plywood, Flat-Panel.
QQ-W-423	-	Wire, Steel, Corrosion-Resisting.
CCC-G-101	-	Gauze, Absorbent.
GGG-P-471	-	Pliers.
JJJ-C-561	-	Cotton, Sterile (Purified) and Nonsterile.
PPP-B-566	-	Boxes, Folding, Paperboard.
PPP-B-601	-	Boxes, Wood, Cleated-Plywood.
PPP-B-636	-	Box, Fiberboard.
PPP-F-320	-	Fiberboard; Corrugated and Solid, Sheet Stock (Container Grade), and Cut Shapes.
PPP-T-60	-	Tape: Pressure-Sensitive Adhesive, Waterproof, for Packaging.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-L-655	-	Lipstick, Antichap and Sunburn Protective.
MIL-M-18371	-	Mirrors, Emergency Signaling, Mark 3.
MIL-L-25142	-	Luminescent Material, Fluorescent.
MIL-B-36021	-	Benzalkonium Chloride Tincture, Tinted.

STANDARDS

FEDERAL

FED-STD-101	-	Preservation, Packaging, and Packing Materials: Test Procedures.
FED-STD-151	-	Metals; Test Methods.

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	-	Marking for Shipment and Storage.

DRAWINGS

US ARMY MUNITIONS COMMAND

DL5-87-1	-	Survival, Escape, and Evasion Kit Container.

PUBLICATIONS

DEFENSE PERSONNEL SUPPORT CENTER

MILITARY MEDICAL PURCHASE DESCRIPTION

FSN 6505-299-8276	-	Oxytetracycline Tablets, 0.25 gm, 100's
FSN 6850-985-7166	-	Water Purification Tablets, Iodine, 8 mg, 50's

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

US PHARMACOPEIAL CONVENTION INCORPORATED

Pharmacopeia of the United States of America XVII

(Copies of the Pharmacopeia of the United States of America may be obtained from the Mack Printing Company, Easton, Pennsylvania 18042.)

AMERICAN PHARMACEUTICAL ASSOCIATION

National Formulary

(Copies of the National Formulary may be obtained from the American Pharmaceutical Association, Washington, D. C. 20037.)

DEPARTMENT OF HEALTH, EDUCATION AND WELFARE

Federal Food, Drug, and Cosmetic Act and General Regulations for its Enforcement

(Application for copies should be addressed to the Superintendent of Documents, U. S. Government Printing Office, Washington 25, D. C.)

UNIFORM CLASSIFICATION COMMITTEE

Uniform Freight Classification

(Application for copies of these ratings, rules and regulations should be addressed to the Uniform Classification Committee, 202 Union Station, 516 West Jackson Boulevard, Chicago, Illinois 60606.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Materials and components. Materials and components shall conform to the applicable specifications and drawings as listed or required herein. Materials and components which are not covered by applicable specifications or drawings or are not specifically described herein shall be of the best quality and of the lightest practicable weight. All the medicinal products included in the kits shall be manufactured in accordance with the Pharmacopeia of the United States of America (U.S.P. XVII), or National Formulary (NF), and shall comply with the Food and Drug Administration (FDA) regulations.

3.1.1 Survival, escape and evasion kit container. The plastic containers shall conform to Drawing DL5-87-1. The lid clamps shall be capable of being easily removed and installed.

3.1.1.1 Instruction and direction card. An instruction and direction card listing the contents, quantity and usage of each component in each container shall be placed under the lid of each plastic container. In addition, the card shall contain information for the medicinal components listing the name of the drug, strength, quantity, usage, dosage, and any other pertinent information. Table I is a list of all the components of the survival kit and the minimum information required on the card. The size of the printing on the card shall be such that it shall be easily read through the top of the container. The card shall be folded in such a manner so that when placed in the container the item name of each component in the container is visible on the card through the lid of the container. The cards shall be waterproofed by laminating between clear plastic sheets or coated with a clear waterproofing compound.

3.1.2 Plastic envelope. The candle, matches, sewing kit, adhesive plaster, boric acid ointment, gauze, sparking kit, wire saw, pliers, fishing line, sun and bug repellent ointment, absorbent cotton, chamois, and snare wire shall be individually heat sealed within a plastic envelope fabricated from 0.0015 inch gage polyethylene material conforming to L-P-378, type I or II, grade A, B, or C, finish 1 or 2. Except for the envelopes enclosing the individual matches, one seam of the envelope shall contain an opening, 1/4 ± 1/16 inch in length. The contents of the envelope shall not be damaged by the sealing or the manner of enclosing. The size of the sealed envelope shall conform to table II.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:05Z
Check the source to verify that this is the current version before use.

TABLE I. Instruction and direction card information.

Item identification	Quantity	Use for	Dosage
Absorbent cotton	1	With sparking kit	
Adhesive plaster	1	Minor cuts and clothing repair	As required
Aluminum dish	1	Heating and cooking	As needed
Aspirin tablet	12	Headaches and minor pain	1 or 2 tablets every 4 hours as required. No more than 8 tablets in 24 hours.
Band aids	3	Minor cuts	As required
Boric acid ointment, 5%	1	Minor irritation of the eye	Squeeze a small amount of ointment in the eye.
Candle, illuminating	1	Light	As required
Chamois	1	Cleaning and polishing	As required
Fishing kit	1	Plastic container, 2 wet flies with snells, 15 fish hooks, nickel demon with double hook, and 3 lead strip sinkers.	As required
Fishing line	1	20 pound test nylon squidding line	
Gauze	1	Bandaging injuries	As required
Lipstick, anti-chap & sunburn protective, cold climate	1	Prevention of chapped or parched lips	Apply lightly on exposed areas as necessary.
Matches	6	Lighting fires, etc.	As required
Methamphetamine tablets	6	Alertness, stay awake	Take 1 tablet every 4 to 6 hours as needed.
Mirror	1	Signalling	As required

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

TABLE I. Instruction and direction card information (continued)

Item identification	Quantity	Use for	Dosage
Oxytetracycline tablets, 0.25 grams (4 grains)	16	Fever, infection, and diarrhea	Take 1 tablet every 4 to 6 hours as needed
Pliers	1	Repairs, cutting wire, etc.	As required
Razor blade	1	Shaving, cutting	As required
Sewing kit	1	Clothing repair	As required
Snare wire	1		As required
Soap	1	Wash wounds, cuts, etc	As required
Sodium chloride (Salt tablets)	6	Excess sweating, heat exhaustion	Take 1 or 2 tablets with approximately 12 ounces of water 2 or 3 times daily as required. Do not chew.
Spare sinkers	2		As required
Sparking kit	1	Making fires	Strike the flint with steel striker so as to create sparks and ignite cotton
Sun N Bug repellent	1	Repel insects. Prevent sun and wind burn.	Apply lightly to all exposed skin areas. Keep out of eyes.
Tincture of benzalkonium chloride	1	Superficial cuts, scratches and insect bites	Remove cap and lightly touch mouth end of applicator bottle to injury. If larger flow is required, gently tap bottom of inverted bottle.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

TABLE I. Instruction and direction card information (continued)

Item identification	Quantity	Use for	Dosage
Water purification tablets	50	Purifying water. Not for salt water.	1 tablet for canteen of clear water. 2 tablets if not clear. Replace canteen cap loosely, wait 5 minutes. Shake well allowing leakage, then tighten cap. Wait 10 minutes before using for any purpose. For very cold water wait 20 minutes.
Waterproof receptacle	1	Storing water	As required
Wire saw	1	Sawing and cutting	As required
Wrist compass	1	Directional findings	As required

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

Table II. Sealed plastic envelope dimensions.

Item	Applicable paragraph	Size of the sealed plastic envelope
Candle	3.1.8	Snug fitting
Matches	3.1.10	Snug fitting for each individual match
Sewing kit	3.1.13	3 by 1-1/4 inches maximum
Adhesive plaster	3.1.14	Snug fitting
Boric acid ointment	3.1.15	Snug fitting
Gauze	3.1.16	Snug fitting
Sparking kit	3.1.18	Snug fitting
Wire saw	3.1.19	4-5/8 by 3-3/4 inches maximum
Pliers	3.1.20	5-1/4 by 2-1/4 by 5/8 inch maximum
Fishing line	3.1.24	2-5/8 by 2-1/4 by 1/8 inch maximum
Sun and bug repellent ointment	3.1.26	Snug fitting
Absorbent cotton	3.1.27	3 by 2-3/8 by 1 inch maximum
Chamois	3.1.28	3-1/2 by 6 inches maximum
Snare wire	3.1.29	4-5/8 by 3-3/4 inches maximum

3.1.3 Aluminum foil packaging. Each aspirin, sodium chloride, methamphetamine hydrochloride, and oxytetracycline tablet shall be individually hermetically heat sealed within a laminated aluminum foil package. The aluminum foil shall be not less than 0.7 mil (0.0007 inch) thick. The specified number of tablets, each sealed within its individual pocket (cell) shall be joined together in a continuous, single line strip with perforations between each pocket (cell) for the easy separation of the individual pockets. Each pocket shall be of the minimum size necessary to protect the tablet and no pocket, including the heat-sealed area, shall be over 1-1/4 inches by 1-1/4 inches. Each pocket shall be capable of passing the leakage test using either the vacuum chamber or the submersion technique when tested as specified in 4.3.4.2. The separation of the individual pockets (cells) shall not

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

disturb or break the hermetic seal of the adjoining pocket (cell). There shall be no difficulty in the removal of the tablet from the aluminum foil pocket (cell). The aluminum foil shall not react with the tablet enclosed and the tablet shall not be affected or damaged by the heat sealing.

3.1.3.1 Marking. Labeling of each individual pocket (cell) shall be permanently and legibly marked in black in accordance with Federal Food, Drug, and Cosmetic Act. As a minimum, the following information shall appear on each pocket (cell):

Name of tablet
Purpose
Concentration
Expiration date (Oxytetracycline tablets only)
Manufacturer's lot number
Manufacturer's name
Manufacturer's address

3.1.4 Aluminum dish. The kit shall contain one dish fabricated from 0.005 ± 0.001 inch sheet aluminum and shall be of the same size and shape as the lower inner portion of the container. The dish shall fit snugly in the lower portion of one of the containers and shall not interfere with the closing. All components in the container shall be placed in the dish.

3.1.5 Lipstick. The kit shall contain one lipstick and dispenser conforming to MIL-L-655, type I, except the outer side of the dispenser shall contain, in white letters, the following information:

LIPSTICK, ANTICHAP AND SUNBURN-PROTECTIVE,
COLD CLIMATE, FOR USE ON, OR PREVENTION
OF CHAPPED OR PARCHED LIPS

3.1.6 Tablets.

3.1.6.1 Water purification. Each iodine water purification tablet shall conform to Military Medical Purchase Description for FSN 6850-985-7166. The kit shall contain 50 iodine water purification tablets packaged in an immediate container in accordance with the level A requirements of Military Medical Purchase Description for FSN 6850-985-7166. Marking shall be as specified in Military Medical Purchase Description for FSN 6850-985-7166 except on the directions for use panel add "4. NOT FOR USE WITH SALT WATER."

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:05Z
Check the source to verify that this is the current version before use.

3.1.6.2 Aspirin. Each aspirin tablet shall be a 5 grain tablet conforming to the requirements of U.S.P. The kit shall contain 12 aspirin tablets, which shall be packed in aluminum foil packaging, 3.1.3. Each aspirin tablet aluminum foil pocket (cell) shall contain the marking as specified in 3.1.3.1.

3.1.6.3 Sodium chloride. Each sodium chloride (salt) tablet shall conform to U-S-00560, type II. The kit shall contain 6 sodium chloride tablets which shall be packaged in aluminum foil packaging, 3.1.3. Each sodium chloride tablet aluminum foil pocket (cell) shall contain the marking as specified in 3.1.3.1.

3.1.6.4 Methamphetamine hydrochloride. Each methamphetamine hydrochloride tablet shall conform to the requirements of U.S.P. XVII and shall contain 5 milligrams (mg) of methamphetamine hydrochloride. The kit shall contain 6 methamphetamine hydrochloride tablets which shall be packaged in aluminum foil packaging, 3.1.3. Each methamphetamine hydrochloride tablet aluminum foil pocket (cell) shall contain the marking as specified in 3.1.3.1.

3.1.6.5 Oxytetracycline. Each oxytetracycline tablet shall conform to Military Medical Purchase Description for FSN 6505-299-8276. The kit shall contain 16 oxytetracycline tablets which shall be packaged in aluminum foil packaging, 3.1.3. Each oxytetracycline tablet aluminum foil pocket (cell) shall contain the marking as specified in 3.1.3.1.

3.1.7 Tincture of benzalkonium chloride. The tincture of benzalkonium chloride shall conform to MIL-B-36021, size 2. The kit shall contain 2 cubic centimeters of the tincture of benzalkonium chloride which shall be packaged, in an applicator bottle (immediate container), as specified in MIL-B-36021. The overall dimensions of the bottle plus the cardboard tube shall be approximately 1-7/8 inches in length and 5/8 inch in diameter. The cardboard tube shall contain the following information:

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:05Z
Check the source to verify that this is the currentversion before use.

BENZALKONIUM CHLORIDE TINCTURE, TINTED

1:1000, 2 cc

FOR EXTERNAL USE ONLY

USAGE

APPLY A SMALL AMOUNT TO SUPERFICIAL CUTS, SCRATCHES, AND INSECT BITES.

DIRECTIONS FOR USE

REMOVE CAP AND LIGHTLY TOUCH MOUTH END OF APPLICATOR BOTTLE TO INJURY. IF LARGER FLOW OF ANTISEPTIC IS REQUIRED GENTLY TAP BOTTOM OF INVERTED BOTTLE.

3.1.8 Candle. The kit shall contain one candle conforming to C-C-91, except that the burning time is not applicable. The candle shall be 3-1/2 inches in length, 1/2 to 9/16 inch in diameter, and shall weigh 9-1/4 to 9-3/4 grams. The candle shall be heat sealed within the plastic envelope, 3.1.2.

3.1.9 Waterproof receptacles. The waterproof receptacles shall be regular weight latex rubber prophylactic, Youngs Rubber Company, Trenton, New Jersey, "Trojans" or equivalent. Each rubber prophylactic shall be packaged individually and each package shall be hermetically sealed. The overall dimensions of each sealed package shall be 2-5/8 ± 1/8 inch long and 1 ± 1/8 inch wide. Each package shall be marked with the name of the contents. Commercial wrapping and marking shall be acceptable. One rubber prophylactic shall be placed in each container of the kit.

3.1.10 Matches. The matches shall be a good commercial quality, strike-anywhere, wooden type approximately 2-3/8 inches in length. Each match shall be heat sealed in the plastic envelope, 3.1.2. Six individually sealed matches shall be bundled together with a rubber band and shall be placed in each container of the kit.

3.1.11 Razor blades. The single edge razor blades shall conform to GG-R-60, style 1, grade C. The razor blades shall be packaged so that no portion of the cutting edge shall come in contact with any of the components in the container or the outer wrapper of the blade. Each blade shall be sheathed in a paperboard sleeve and then individually and completely wrapped in a snug-fitting paper wrapper. Each package shall be marked with the name of the contents. One razor blade shall be placed in each container of the kit.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:05Z
Check the source to verify that this is the currentversion before use.

3.1.12 Band-aids. The band-aids shall be Johnson and Johnson, New Brunswick, New Jersey, "Super Stick" flesh colored plastic strip with plain pad or equivalent. Each band-aid shall be approximately 3 inches long and 3/4 inch wide and shall be individually securely wrapped and sealed in accordance with the best commercial practice. Each individually wrapped band-aid shall have a strip opening and shall be approximately 3-1/4 inches in length and 7/8 inch in width. Each band-aid wrapper shall be marked with the name of the contents. Commercial markings shall be acceptable. Three band-aids shall be placed in each container of the kit.

3.1.13 Sewing kit. The kit shall contain one sewing kit which shall consist of two hand sewing needles and nylon thread conforming to V-T-295, type II, class 1 or 2, size E, color natural (white). The hand sewing needles shall be made of steel and nickel plated in accordance with good commercial practice. The needles shall be size 4 or 5 with an embroidery needle type eye. The point of the needle shall be ground to a sharp point blending in shape with the body of the needle directly above the point. The eye shall be suitably designed to prevent cutting of the thread. The needles shall be hardened and tempered in accordance with the best commercial practice. The needles shall be attached to a felt strip, which shall be folded in half lengthwise, to prevent contact of the needle points with the other survival kit components. A minimum of 15 yards of the thread shall be wound on a paperboard or plastic bobbin approximately 3/4 inch in diameter and 1/4 inch thick. The bobbin and the needles attached to the felt strip shall be heat sealed within the plastic envelope, 3.1.2.

3.1.14 Adhesive plaster. The adhesive plaster shall conform to U-P-401, type II, color white or flesh. The kit shall contain one yard in length by 1/2 inch wide of the adhesive plaster which shall be folded or rolled flat to provide a package not exceeding 3 inches in length, 1-1/4 inches wide, and 1/4 inch thick. A piece of wax impregnated paper shall be placed at the center of the package to prevent contact between the two adhesive surfaces. The folded or rolled flat adhesive plaster package shall be heat sealed within the plastic envelope, 3.1.2.

3.1.15 Boric acid ointment, ophthalmic. The ointment, when assayed as specified in 4.3.4.3, shall contain 4 to 6 percent of boric acid. The kit shall contain one-eighth ounce of boric acid ointment which shall be packaged in an ophthalmic tip metal squeeze tube. Closure of the tube shall be effected by a hand tightened, plastic, threaded cap. The tube shall be heat sealed in the plastic envelope, 3.1.2. The boric acid ointment tube shall contain the following information:

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:05Z
Check the source to verify that this is the currentversion before use.

BORIC ACID OINTMENT 5%

USAGE

FOR MINOR IRRITATION OF THE EYE

DIRECTIONS FOR USE

SQUEEZE A SMALL AMOUNT OF OINTMENT IN THE EYE

3.1.16 Gauze. The gauze shall conform to CCC-G-101, type I or VII, class 2. The kit shall contain one yard in length by 12 inches wide of the gauze which shall be folded to a size of 4 inches by 4 inches by 1/8 inch in height and shall be packaged in the best commercial practice to insure the sterility of the contents. The packaged gauze shall be heat sealed in the plastic envelope, 3.1.2. The commercial wrapper shall be marked with the name of the content. A certificate of sterility, as specified in CCC-G-101, shall be submitted to the procuring activity.

3.1.17 Signalling mirror. The kit shall contain one signalling mirror conforming to MIL-M-18371, type I. The mirror shall be placed within the container in such a manner to assure that the mirror shall not be damaged in transit or when carried by personnel. The mirror shall contain the markings as required by MIL-M-18371, except delete the word "INSTRUCTIONS", the identification markings, and the marking on the edge of the mirror.

3.1.18 Sparking kit. The kit shall contain one sparking kit which shall consist of one synthetic flint stone and one steel striker. The sparking metal (flint) shall be of a pyrophoric alloy substance of adequate strength to withstand chipping or breaking. The sparking metal shall be semi-circular in shape and shall be approximately 1-1/4 inches in diameter and 7/16 inch thick. The sparking metal shall be covered with a waterproof paint or otherwise treated to minimize deterioration in storage. The steel striker shall be a 1/8 inch round rod approximately 1-3/4 inches long with one end tapered for 1/2 inch to a 1/16 inch diameter. The steel striker shall be case hardened to 55 - 60 Rockwell C Scale. When the sparking metal is struck with the steel striker, the sparking metal shall produce sparks of sufficient intensity to ignite a piece of absorbent cotton when tested as specified in 4.3.4.4. The steel striker shall be securely taped to the sparking metal with a strip of pressure sensitive tape conforming to PPP-T-60. The sparking kit shall be heat sealed within the plastic envelope, 3.1.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

3.1.19 Wire saw. The kit shall contain one wire saw consisting of a wire assembly and two nylon loops. The flexible steel wire saw shall be fabricated from three thin narrow steel strips, each greater in width than thickness, containing inclined teeth. The strips shall be laid flat and twisted together with a pitch 2 to 4 times their width. The inclined teeth shall project in opposite cutting directions to provide cutting in any direction and shall also project radially around the periphery of the saw. The inner narrower strip shall have at least one untoothed edge. The two outer strips shall be of equal width and wider than the inner strip. The height of the teeth shall be 1/4 to 1/2 the width of the strip. The saw blade shall be 16 ± 1/2 inch long, with brass eyelets securely attached to each end. The outside diameter of the loops shall be 1-1/2 inches. The overall length of the saw assembly shall be 20 to 21 inches. The saw assembly shall be dichromate treated and shall show no evidence of corrosion when exposed to 100 hours of salt spray as specified in 4.2.3. The saw assembly shall not break and the loops shall not separate when subjected to a pull of 110 pounds as specified in 4.3.4.5. The nylon cord shall be no less than 7 inches long with the ends sealed to form a loop of no less than 1-1/2 inches in diameter. The wire saw shall be coiled and heat sealed within the plastic envelope, 3.1.2.

3.1.20 Pliers. The pair of pliers shall conform to GGG-P-471, type IX, class 1, except that the "A" dimension shall be 5 ± 1/16 inch. The kit shall contain one pair of pliers which shall be heat sealed within the plastic envelope, 3.1.2.

3.1.21 Soap. The cake of soap shall contain hexachlorophene and shall conform to P-S-615, type I. The cake of soap shall be approximately 2 inches long, 1/4 inch thick, and 1-1/4 inches wide and shall have an approximate net weight of 3/8 ounce. The cake of soap shall be covered with an inner wrapper of waxed paper and an outer wrapper of paper. The outer wrapper shall contain the word "SOAP." Commercial wrapping and marking shall be acceptable.

3.1.22 Wrist compass and strap. The wrist compass and strap shall conform to Waltham Compass Company, Waltham, Massachusetts, Drawing 91576, or equivalent, except that radium paint shall not be used. The 30 degree graduation marks, arrow, and letters E, S, and W shall be filled by fluorescent luminescent material conforming to MIL-L-25142, type I, II, or III. The wrist compass and strap shall be placed within the container in such a manner to insure that the compass shall not be damaged.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

[illegible] packet item shall contain the marking as specified in 3.4.2.2.

3.1.23 Fishing kit. The survival kit shall contain one fishing kit which shall consist of a plastic container, abrasive cloth, sinkers, and various fish hooks. The fishing kit container shall be fabricated from clear plastic and shall be Diamond Plastic Incorporated, Roanoke, Virginia, No. 410, or equivalent. The container shall be approximately 3-1/2 inches in length, 3/4 inch in width, and 1/4 inch in height. The abrasive cloth shall have a pressure sensitive adhesive on one side and coarse abrasive material on the other side. The abrasive cloth shall be cut to fit the lid of the container and the pressure sensitive side of the cloth shall be attached to the outerside of the lid. The wet flies, fish hooks, and sinkers shall be placed in the fishing kit container so that none of the contents shall be damaged and shall be as follows:

Quantity	Description
1	Wet fly, size 6 with 3 inch snell
1	Wet fly, size 14 with 3 inch snell
3	Size 1/0 O'Shaughnessy hooks
3	Size 3/0 O'Shaughnessy hooks
3	Size 2 O'Shaughnessy hooks
3	Size 10 Carlisle hooks
3	Size 8 Sproat hooks
1	Nickel demon with No. 6 double hook
3	Lead strip sinkers, approximately 3 by 1/6 by 1/32 inch

3.1.24 Fishing line. The fishing line shall be a 20 pound test nylon squidding line. Fifty feet of the fishing line shall be coiled and heat sealed in the plastic envelope, 3.1.2.

3.1.25 Spare sinkers. The kit shall contain two spare sinkers fabricated from lead. Each lead sinker shall weigh 12 ± 1 grams. The lead sinkers shall be placed in the container in a manner that none of the other components shall be damaged.

3.1.26 Sun and bug repellent ointment. The sun and bug repellent ointment shall be Silicote Corporation, Oshkosh, Wisconsin, "Silicote Sun N Bug Insect Repellent and Sun Screen, "Day-Baldwin, Incorporated, Hillside, New Jersey "Sun Screen and Insect Repellent," or equivalent. One ounce of the sun and bug repellent ointment shall be packaged in a metal squeeze tube. Closure of the tube

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:05Z
Check the source to verify that this is the currentversion before use.

shall be effected by a hand tightened, plastic, threaded cap. The capped tube shall be approximately 4-3/4 inches in length and one inch in diameter. The tube shall be heat sealed within the plastic envelope, 3.1.2. The tube shall contain the following information:

SUN N BUG INSECT REPELLENT AND SUNSCREEN OR

SUN SCREEN AND INSECT REPELLENT

USAGE

TO REPEL INSECTS AND TO PREVENT SUN AND WINDBURN

DIRECTIONS FOR USE

APPLY OINTMENT LIGHTLY TO ALL EXPOSED SKIN AREAS. KEEP OUT OF EYES.

3.1.27 Absorbent cotton. The absorbent cotton shall conform to JJJ-C-561, grade B. The kit shall contain 2 ± 1/4 gram of the absorbent cotton, which shall be heat sealed within the plastic envelope, 3.1.2.

3.1.28 Chamois. The chamois shall conform to KK-C-300, grade B, class 1 or 2. The kit shall contain a piece of the chamois, approximately 3 by 5 inches, which shall be heat sealed in the plastic envelope, 3.1.2.

3.1.29 Snare wire. The snare wire shall conform to QQ-W-423, form I, composition 302, 304, or 316, condition A, and shall be 30 inches in length and 0.013 inch in diameter. The ends of the wire shall be smooth and round and the snare wire shall not contain any sharp edges or burrs. The wire shall be coiled and heat sealed within the plastic envelope, 3.1.2.

3.2 Survival, escape and evasion kit assembly. The components shall be neatly placed within two individual containers in a manner that shall prevent movement and afford adequate protection against damage to themselves, to the other components in the container, or to the container. The containers shall be arbitrarily marked "Container No. 1" and "Container No. 2." The processing plant, grounds, equipment, personal practices, and sanitary procedures used in the production of the survival, escape, and evasion kits shall minimize the possibility of contamination of the containers and the components through microbial growth, dust, pests, rodents, condensate, or other unsanitary sources. The products shall be prepared,

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

processed, and handled in a manner that shall minimize deterioration or damage.

3.3 Expansion due to altitude and waterproofness. The containers shall not increase in height, the lid or clamps shall not separate from the containers, nor shall the containers open, burst, or distort when the surrounding atmospheric pressure is reduced to an absolute pressure of 100 ± 5 millimeters of mercury during a period of not less than 12 minutes, maintained at this pressure for 30 ± 5 minutes, and then returned to normal atmospheric pressure within one minute when tested as specified in 4.3.4.1. Upon completion of test and examination for above requirement, and without making any adjustment to the lid or clamps, the containers shall show no evidence of leakage when submerged in water having a temperature of 75° ± 5°F, under a static head of 12 inches of water for a period of 2 hours ± 5 minutes when tested as specified in 4.3.4.1.

3.4 Markings. Unless otherwise specified, the markings shall be legible and durable black letters and numerals, or other contrasting color, and shall be thoroughly dry prior to packaging. The marking shall be accomplished by using such methods and materials as shall be resistant to erasure of fading under the condition of usage. The marking medium shall not contain any materials which are deleterious to the substance being marked. The size of all the letters and numerals shall be such that they are easily readable. Unless otherwise specified, the markings shall be legible from the outerside of the bottles, or wrappings.

3.4.1 Identification of the product. The bottom of each container shall be marked on the inner side by means of a decal or by another durable and legible method. The following information shall be visible through the underside of each container:

SURVIVAL KIT, AIRMAN'S, SEEK-1
CONTAINER NO. 1 OR CONTAINER NO. 2 (AS APPLICABLE)
SPECIFICATION MIL-S-51296(MU)
DATE OF ASSEMBLY (MONTH AND YEAR)
CONTRACTOR'S NAME OR TRADEMARK
CONTRACT NO.

3.4.2 Medicinal components (excluding tablets). In addition to the markings specified herein, all medicinal components shall be labeled in accordance with the requirements of the Federal Food, Drug, and Cosmetic Act.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:05Z
Check the source to verify that this is the current version before use.

3.5 Preproduction. Prior to the start of regular production, a preproduction sample of SEEK-1 survival kits shall be produced in accordance with this specification for examination and test (see 4.2).

3.6 Workmanship. The survival, escape, and evasion kit shall be free of spots and stains. Because of the emergency and life support use of this equipment, the importance of providing a product of uniform excellent quality cannot be overemphasized. The kit shall be uniform in quality and shall be free from irregularities or defects which could adversely affect performance, reliability, or durability. The kit shall conform to the quality and grade of product established by this specification. The occurrence of defects shall not exceed the acceptance criteria established herein.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.

4.1.1 Supplier's responsibility. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to specified requirements.

4.1.2 Objective evidence. The supplier shall provide objective evidence acceptable to the contracting officer that the requirements of 3.1 and section 5 for which specific inspection has not been provided in this specification have been satisfied.

4.2 Preproduction.

4.2.1 Sample. A preproduction sample of 5 SEEK-1 survival kits shall be manufactured using the same methods, materials, equipment and processes as will be used during regular production.

4.2.2 Inspection.

4.2.2.1 For examination. The preproduction sample shall be examined in accordance with the classification of defects (4.3.3.3).

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:05Z
Check the source to verify that this is the current version before use.

4.2.2.2 For tests. The preproduction sample shall be tested as specified in 4.2.3 and 4.3.4.

4.2.3 Wire saw assembly corrosion resistance test. Determine the corrosion resistance of the wire saw assembly in accordance with method 811 of Fed Test Method Standard No. 151. There shall be no evidence of corrosion after being exposed to the salt spray for the specified period of time.

4.2.4 Acceptance/rejection criteria. The preproduction sample shall comply with the examinations and tests specified in 4.2.2 to be acceptable. The supplier shall obtain written approval from the contracting officer prior to proceeding with regular production.

4.3 Regular production.

4.3.1 Lotting. A lot shall consist of the SEEK-1 survival kits (container No. 1 and container No. 2) produced by one manufacturer, at one plant, from the same materials, under essentially the same manufacturing conditions.

4.3.1.1 Component lots. For the purpose of inspection, a component lot shall consist of all like components offered for acceptance at one time.

4.3.2 Sampling.

4.3.2.1 For examination. Sampling shall be conducted in accordance with MIL-STD-105.

4.3.2.2 For tests.

(a) Expansion due to altitude and waterproofness. Sampling shall be conducted in accordance with MIL-STD-105, Inspection Level S-4 using an AQL of 1.0.

(b) Aluminum foil packaging leakage. Sampling shall be conducted in accordance with MIL-STD-105, Inspection Level S-4 using an AQL of 1.0.

(c) Boric acid ointment assay. Sampling shall be conducted in accordance with MIL-STD-105, Inspection Level S-1 using an AQL of 1.0.

(d) Sparking kit and wire saw assembly strength. Sampling shall be conducted in accordance with MIL-STD-105, Inspection Level S-1 using an AQL of 1.0.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:05Z
Check the source to verify that this is the current version before use.

4.3.3 Inspection.

4.3.3.1 For examination. Sample survival kits and the level A preparation for delivery shall be examined in accordance with the classification of defects 4.3.3.3, 4.3.3.4 and MIL-STD-105 using an AQL of 2.5 and 4.0 defects per 100 units for Major and Minor defects respectively.

4.3.3.2 For tests. Sample survival kit components shall be tested in accordance with 4.3.4 and MIL-STD-105 using an AQL of 1.0 percent defective.

4.3.3.3 Classification of defects. The plastic containers and the contents of the sample survival kits (container No. 1 plus container No. 2), taken at random from the lot, shall be visually examined to determine conformance to this specification. Table III contains a list of defects which shall be used to classify and numerate the defects found. When applicable, inspection of components shall be performed prior to sealing in the plastic envelope.

Table III. Classification of defects for survival kit.

Defects	Major	Minor
Survival kit		
a. Any evidence of foreign matter, spots, stains, rust, or dirt	X	
b. Any component or any part of the component missing, damaged, deformed, broken, cracked, fogged, bent, crushed, chipped, kinked, torn, tangled, twisted, defective, or not as specified	X	
c. Any hole, tear, mend, burn, or any weakening defect such as deep scratches, abrasion marks, or dents	X	
d. Any surface rough, misaligned, or contains nicks, cracks, burrs, sharp edges (except for the cutting edges of the wire saw and razor blades), or other flaws	X	
e. Any component not packaged as specified or any container broken, cracked, damaged, or otherwise defective	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

Table III. Classification of defects for survival kit (continued)

Defects	Major	Minor
Survival kit (cont'd)		
f. Both waterproof receptacles or razor blades in one container. Both bundles of matches in one container	X	
g. Any component contains mends or splices	X	
h. Container does not close properly, misshapen, bent, or out of alignment	X	
i. Lid clamps of the kit container difficult to remove or install 1/	X	
j. Container dimensions incorrect (Dwg D5-87-1)	X	
Tablets		
a. Any pocket (cell) not uniform in size or shape	X	
b. Any crushed, broken, chipped, or crumbly (not firm)	X	
c. Number of pocket (cells) not as specified	X	
d. Perforations between the pocket (cells) missing or incomplete	X	
Plastic envelope		
a. One seam does not contain an opening (except matches)	X	
b. Contents in the envelope damaged by the sealing or by the method of enclosing	X	
c. Length of the opening:		
1. More than 5/16 inch	X	
2. Less than 3/16 inch	X	
d. Any specified component not sealed in the plastic envelope	X	

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:05Z
Check the source to verify that this is the currentversion before use.

Table III. Classification of defects for survival kit (continued)

Defects	Major	Minor
Aluminum dish		
a. Not fabricated from aluminum or does not fit snugly in the lower half of the container	X	
b. Contents of the container not placed in the dish	X	
Candle		
a. Not cylindrical in shape, or contains cracks, holes, or voids	X	
b. Wick does not extend beyond the taper tip, not visible at the bottom, or visible along the shaft	X	
Matches		
a. Not strike anywhere type, any head or wooden stick missing; any stick broken	X	
b. Not individually sealed or any opening in the plastic envelope	X	
c. Not bundled together		X
Sewing kit		
a. Any needle marred, bent, distorted, point blunted, eye blocked or broken, or otherwise defective	X	
b. Needles not attached to the felt strip or do not contain embroidery type eye	X	
Sparking kit		
a. Sparking metal broken, cracked, crumbly or otherwise defective	X	
b. Missing component	X	
c. Sparking metal protective treatment missing	X	
d. Not enclosed in plastic envelope	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

Table III. Classification of defects for survival kit (continued)

Defects	Major	Minor
Wrist compass		
a. Face obliterated, not clear, or otherwise defective	X	
b. Wrist strap cut, broken, or otherwise defective	X	
c. Any 30 degree graduation mark, arrow or letters E, S, and W not filled with the fluorescent luminescent paint	X	
Fishing kit		
a. Fish hooks:		
1. Hook end not sharp; eye blocked, or does not permit the fishing line to be attached	X	
2. Any not specified type	X	
b. Any not specified type wet flies	X	
c. Not specified type sinkers or difficult to attach to the fishing line	X	
d. Abrasive cloth not as specified or not attached to the outerside of the fishing kit container	X	
e. Container does not close properly, misshapen, bent, or out of alignment	X	
Markings		
a. Instruction and direction card:		
1. Missing, illegible, incorrect, or incomplete	X	
2. Item names of components on cards cannot be seen through the top of the container		X
b. For medicinal products:		
1. Lot control number, specified expiration date for the antibiotics, or other required FDA medicinal markings missing, illegible, incomplete, incorrect, improperly located, or not easily discernible	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

Table III. Classification of defects for survival kit (continued)

Defects	Major	Minor
Markings (Continued)		
c. All other markings:		
1. Missing, illegible, incomplete, incorrect, or improperly located		X

1/ One of the locking clamps on each container of the kit shall be completely removed and then fully reinstalled at least three times to assure that there is no difficulty in the removal or installing of the clamp.

4.3.3.4 Preparation for delivery. Each of the fully prepared shipping containers, containing survival, escape, and evasion kits (container number 1 plus container number 2 for each kit), selected as a sample unit from the lot, shall be visually examined to determine that the packaging, packing, and marking conform to this specification. The classification of defects, table IV, shall be used to enumerate the defects found.

Table IV. Classification of defects for preparation for delivery

Defects	Major
Exterior and interior marking:	
Missing, incorrect, incomplete, illegible; of improper size, location, sequence, or method of application; markings not the same on the interior and exterior containers.	X
Packaging and packing materials:	
Any non-conforming component; any component missing, damaged, or otherwise defective.	X
Workmanship:	
Inadequate application of the components such as incomplete closure of the unit package, container flaps, loose strappings, etc; bulging or distortion of the containers.	X

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

Table IV. Classification of defects for preparation for delivery (Cont'd)

Defects	Major
Content:	
Number per container is more or less than required; not composed of container number 1 plus container number 2.	X

4.3.4 Tests. Unless otherwise specified, all tests required herein shall be made at an atmospheric pressure of 28 to 32 inches of mercury, a temperature of 77° ± 18°F, and a maximum relative humidity of 80 percent. Tests shall be conducted as follows:

4.3.4.1 Expansion due to altitude and waterproofness. Place the closed containers in a suitable air chamber. Reduce the pressure in the chamber to the specified absolute pressure during a period of no less than 12 minutes and maintain this pressure for the required period of time. Return the pressure in the chamber to normal atmospheric pressure within one minute. Visually examine the containers for any evidence of damage specified in 3.3 but do not make any adjustment to the lid or clamps. Upon completion of the examination, submerge the containers in clean fresh water, having a temperature of 75° ± 5°F, to the specified depth for the required period of time. Remove the containers from the water and wipe the outside of the containers dry. Examine the inside of the containers for moisture. Any evidence of moisture on the inside of the containers is an indication that the container leaks and is not waterproof.

4.3.4.2 Aluminum foil packaging leakage. The aluminum foil packaging shall be tested for leakage using either the vacuum chamber technique or the submersion technique in accordance with method 241 of Fed Test Method Standard No. 101.

4.3.4.3 Boric acid ointment, ophthalmic. The boric acid ointment shall be assayed in accordance with the applicable method contained in the National Formulary, Eleventh edition.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

4.3.4.4 Sparking kit. Strike the sparking metal with the steel striker in such a manner as to create sparks to fall upon a 2 gm piece of absorbent cotton conforming to JJJ-C-561, grade B. The sparks from the sparking metal shall cause the cotton to burst into flames and the sparking metal shall not break, crumble, or fall apart.

4.3.4.5 Wire saw assembly strength. Determine the strength of the wire saw assembly using a suitable tensile testing apparatus capable of applying the required tension to the wire saw assembly and employing a means for determining the applied tension. The rate of travel shall be 1 ± 1/16 inch per minute under no load and shall be uniform at all times. Insert a metal rod through the loop at each end of the wire saw assembly and connect the rods to the tensile testing apparatus. Pull the wire saw assembly to the specified tension. The wire saw shall not break and the loops shall not separate.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A or C as specified (see 6.2).

5.1.1 Level A. The SEEK-1 survival kit (container number 1 and container number 2) shall be packaged in a fiberboard box conforming to style RSC and grade W5c of PPP-B-636. Inside dimensions of the box shall be 5-1/2 inches in length, 4-1/2 inches in width, and 4-1/4 inches in depth. A separator made from fiberboard conforming to grade W5c of PPP-F-320 shall be placed between the two containers. The size of the separator shall be 5-1/4 inches by 4-1/4 inches. The box shall be closed in accordance with the requirements for weather-resistant boxes in the appendix of PPP-B-636.

5.1.2 Level C. The SEEK-1 survival kit (container number 1 and container number 2) shall be packaged in the same manner as in 5.1.1 except that the kit shall be placed in a box conforming to variety 1, style X of PPP-B-566 and the separator shall be made of the same material and thickness as the folding paperboard box. The box shall be closed in conformance with the appendix of PPP-B-566.

5.2 Packing. Packing shall be in conformance with type I or II of level A or level C as specified (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:05Z
Check the source to verify that this is the current version before use.

5.2.1 Level A.

5.2.1.1 Type I - plywood packing. Thirty-six SEEK-1 survival kits, packaged as specified in 5.1.1, shall be packed, four in length, three in width and three in depth, in an overseas type, style A, cleated plywood box conforming to PPP-B-601 and fabricated from plywood complying with group A of NN-P-530 in accordance with type I, grade 3 or 4 of CS35, provided the plywood does not have continuous holes or openings extending through the entire panel from face to back. The box shall be closed and strapped, using zinc-coated strapping, in accordance with the appendix of PPP-B-601. (See 6.3.1).

5.2.1.2 Type II - fiberboard packing. Thirty-six SEEK-1 survival kits, packaged as specified in 5.1.1, shall be packed as specified in 5.2.1.1 except as follows: The packaged kits shall be packed in a box conforming to style RSC, grade V3c of PPP-B-636. The box shall be closed and strapped, using flat steel zinc-coated strapping or tape in accordance with the appendix of PPP-B-636. (See 6.3.2).

5.2.2 Level C. A uniform number of SEEK-1 survival kits, packaged as specified in 5.1.2, shall be packed to insure carrier acceptance and safe delivery to the first domestic destination. Shipping containers shall be in compliance with the Uniform Freight Classification rules or the regulations of other common carriers acceptable to the mode of transportation.

5.3 Marking. In addition to any special marking required by the contract or order, unit packages and shipping containers shall be marked in accordance with MIL-STD-129. The marking shall include the date of assembly (month and year).

6. NOTES

6.1 Intended use. The SEEK-1 survival kit is intended to be used by aircrewmen in emergency situations.

6.2 Ordering data. Procurement document should specify the following:

(a) Title, number and date of this specification.

(b) Level of packaging, and level and type of packing required (see section 5 and 6.3).

(c) Preproduction:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:05Z
Check the source to verify that this is the current version before use.

(1) Time allowed for supplier submission of samples for Government test and evaluation after award of contract.

(2) Name and address of test facility and shipping instructions when testing is performed by the Government.

(3) Time required for the Government to notify the supplier whether or not to proceed with production.

6.3 Conditions for use of Type I or Type II packing.

6.3.1 Type I. The type I plywood packing is intended for shipment to areas where there are known extremes of temperature, humidity and rainfall, where severe rough handling is anticipated and where there may be prolonged outdoor exposure to the weather.

6.3.2 Type II. The type II fiberboard packing is intended for worldwide shipment, handling and open storage in areas where it is anticipated that hazards will be less extreme than in areas for which type I packing is intended.

Custodian:

Army - MU

Preparing activity:

Army - MU (EA)

Project No. 4240-A335

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:05Z
Check the source to verify that this is the current version before use.