INCH-POUND

MIL-T-52332B
25 September 1991
SUPERSEDING
MIL-T-52332A(ME)
4 January 1974

MILITARY SPECIFICATION

TOOL, HORIZONTAL CONNECTING:

ERECTION EQUIPMENT FOR BRIDGE,

FLOATING, PNEUMATIC FLOAT, CLASS 60

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a horizontal connecting tool to be used as an erection aid in the construction of the class 60 floating bridge.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards, form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: USA Belvoir Research, Development, and Engineering Center, ATTN: STRBE-TSE, Fort Belvoir, VA 22060-5606 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 5420

DISTRIBUTION STATEMENT A. Approved for public release, distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:07Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

FF-P-386	-	Pins, Cotter (Split).
FF-S-200	-	Setscrews: Hexagon Socket and Spline Socket, Headless.
RR-C-271	-	Chains and Attachments, Welded, Weldless, and Roller Chain.
PPP-B-601	-	Boxes, Wood, Cleated-Plywood.
PPP-B-636	-	Boxes, Shipping, Fiberboard.
PPP-B-640	-	Boxes, Fiberboard, Corrugated, Triple Wall.
PPP-T-60	-	Tape: Packaging, Waterproof.

MILITARY

MIL-T-704	-	Treatment and Painting of Materiel.
MIL-H-5606	-	Hydraulic Fluid, Petroleum Base; Aircraft, Missile, and Ordnance.
MIL-H-6083	-	Hydraulic Fluid, Petroleum Base, for Preservation and Testing.
MIL-C-16173	-	Corrosion Preventive Compound, Solvent Cutback, Cold-Application.

STANDARDS

FEDERAL

FED-STD-595	-	Colors.

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	-	Marking for Shipment and Storage.
MIL-STD-889	-	Dissimilar Metals.

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Document Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Government drawings. The following Government drawings, form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those in effect on the date of the solicitation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:07Z
Check the source to verify that this is the current version before use.

DRAWINGS

ME

D7944-1 and -2 - Tool, Horizontal Connecting: Erection Equipment for Bridge, Floating Pneumatic Float, Class 60.

(Copies of drawings, publications, and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Non-Government publications. The following document(s) form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN SOCIETY OF MECHANICAL ENGINEERS (ASME)

Boiler and Pressure Vessel Code, Section IX, Qualification Standard for Welding and Brazing Procedures, Welders, Brazers and Welding and Brazing Operators.

(Application for copies should be addressed to the American Society of Mechanical Engineers, 345 East 47th Street, New York, NY 10017.)

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

A36 - Structural Steel.
A304 - Alloy Steel Bars to End-Quench Hardenability Requirements.
A502 - Steel Structural Rivets.
A519 - Seamless Carbon and Alloy Steel Mechanical Tubing.
A572 - High Strength Low-Alloy Columbium-Vanadium Steels of Structural Quality.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

AMERICAN WELDING SOCIETY (AWS)

A5.1 - Covered Carbon Steel Arc Welding Electrodes.
A5.18 - Carbon Steel Filler Metals for Gas Shielded Arc Welding - Steel.
D1.1 - Structural Welding Code - Steel.

(Application for copies should be addressed to the American Welding Society, 550 N.W LeJeune Road, P.O. Box 351040, Miami, FL 33135.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:07Z
Check the source to verify that this is the current version before use.

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., (NMFTA)

National Motor Freight Classification Rules.

(Application for copies should be addressed to the American Trucking Associations, Inc., ATTN: Traffic Order Section, 2200 Mill Road, Alexandria, VA 22314.)

UNIFORM CLASSIFICATION COMMITTEE, (UCC)

Uniform Freight Classification Rules.

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

(Non-Government standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Description. The horizontal connecting tool shall be as shown on drawings D7944-1 and -2 and as specified herein.

3.1.1 Drawings. The drawings forming a part of this specification are end product drawings. No deviation from the prescribed dimensions or tolerances is permissible without prior approval of the contracting officer. Any data (e.g. shop drawings, layouts, flow sheets, processing procedures, etc.) prepared by the supplier or obtained from a vendor to support fabrication and manufacture of the production item shall be made available, upon request, for inspection by the contracting officer or his designated representative.

3.2 First article. When specified (see 6.2), a sample shall be subjected to first article inspection (see 6.3) in accordance with 4.3.

3.3 Material. Material shall be as specified herein and as shown on the applicable drawing. Materials not specified shall be selected by the supplier and shall be subject to all provisions of this specification.

3.3.1 Material deterioration prevention and control. The horizontal connecting tool shall be fabricated from compatible materials, inherently corrosion resistant or treated to provide protection against the various forms of corrosion and deterioration that may be encountered in any of the applicable operating and storage environments to which the horizontal connecting tool may be exposed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:07Z
Check the source to verify that this is the current version before use.

3.3.1.1 Dissimilar metals. Dissimilar metals shall not be used in intimate contact with each other unless protected against galvanic corrosion. Dissimilar metals and methods of protection are defined and detailed in MIL-STD-889.

3.3.1.2 Identification of materials and finishes. The contractor shall identify the specific material, material finish or treatment for use with component and subcomponent, and shall make information available upon request to the contracting officer or designated representative.

3.3.2 Recovered Materials. For the purpose of this requirement, recovered materials are those materials which have been collected from solid waste and reprocessed to become a source of raw materials, as distinguished from virgin raw materials. The components, pieces and parts incorporated in the horizontal connecting tool may be newly fabricated from recovered materials to the maximum extent practicable, provided the horizontal connecting tool produced meets all other requirements of this specification. Used, rebuilt or remanufactured components, pieces and parts shall not be incorporated in the horizontal connecting tool.

3.3.3 Structural steel. Structural steel shall conform to ASTM A36.

3.3.4 Low-alloy structural steel. Low-alloy structural steel shall conform to ASTM A572, grade 50.

3.4 Inserts. Inserts shall be made of steel conforming to ASTM A304, grade designation UNS H41400, with a Rockwell hardness of C45 to C50. The inserts shall not be case hardened. The teeth shall be machined and shaped.

3.5 Pins. Pins shall be fabricated of steel conforming to ASTM A304, grade designation UNS H41400, and shall be heat treated to a tensile strength of 125,000 psi.

3.6 Hydraulic ram. The hydraulic ram shall have a capacity of 10 tons with an internal pressure between 8000 and 9000 psi. The materials used in the hydraulic ram shall be compatible with fluid conforming to MIL-H-6083 or MIL-H-5606. When shipped, the hydraulic ram shall not be filled with hydraulic fluid, except as specified in 5.1.1 and 5.1.2.

3.7 Hydraulic couplings. A set of hydraulic couplings shall consist of a female section for attachment to the ram; male section for attachment to a hydraulic hose; swivel of female section; and dust caps attached to the male and female sections with steel chain conforming to RR-C-271, type II, class 3, weldless, sash chain, zinc-coated. The coupling components shall be capable of withstanding a minimum of 10,000 psi internal working pressure without any evidence of leakage or failure. All coupling parts shall be of corrosion-resistant material or shall be rendered corrosion resistant by chromium or cadmium plating. The coupling shall be of such design that breaking the connection at the swivel will cause spring-loaded devices to seal the fluid passage in each half coupling. The spring-loaded devices shall open to permit

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:07Z
Check the source to verify that this is the current version before use.

the fluid flow when a connection is made. The exterior of the coupling shall be shaped to provide a wrench grip. The swivel shall turn freely by hand.

3.8 Rivets. Rivets shall conform to ASTM A502, grade 1.

3.9 Chain. Chain shall conform to RR-C-271, type I, grade C, class 1.

3.10 Steel tubing. Steel tubing shall conform to ASTM A519, hot finished, round, grade 1025.

3.11 Set screws. Set screws shall conform to FF-S-200, type I, style 1.

3.12 Cotter pins. Cotter pins shall conform to FF-P-386, type B.

3.13 Welding electrodes. Welding electrodes shall conform to AWS A5.1 or A5.18, classification and size as required.

3.14 Identification marking. The horizontal connecting tool shall be metal-die stamped as shown on the applicable drawing. Die stamping shall be legible after painting.

3.15 Treatment and painting. The horizontal connecting tool, except for the couplings, pins, screws, and threads, shall be treated and painted in accordance with MIL-T-704, type F except that the color number designation shall be 34094 in accordance with FED-STD-595. Pins, screws, and threads shall be coated with preservative conforming to MIL-C-16173, grade 1.

3.16 Workmanship.

3.16.1 Steel fabrication. Steel used in the fabrication of the horizontal connecting tool shall be free from lamination, kinks, and sharp bends. The straightening of material shall be done by methods that will not cause injury to the metal. Shearing and clipping shall be done neatly and accurately. Corners shall be square and true. Flame cutting with a tip suitable for the thickness of metal may be employed instead of shearing or sawing. Burned surfaces of flame-cut material shall be ground or machined sufficiently to remove ash and cooling checks. All bends shall be made with metal dies or fixtures to insure uniformity of size and shape. Precautions shall be taken to avoid overheating, and heated metal shall be allowed to cool slowly. All burrs and rough edges shall be ground smooth.

3.16.2 Welders and welding.

3.16.2.1 Welders and welding operators. Before assigning any welder or welding operator to welding work covered by this specification, the supplier shall provide the contracting officer with certification that the welder or welding operator has passed qualification tests as prescribed by either of the following listed codes for the materials joined and the type of welding operation to be performed and that such qualification is effective as defined by the particular code:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:07Z
Check the source to verify that this is the current version before use.

ASME Boiler and Pressure Vessel Code, Section IX.
AWS D1.1 Structural Welding Code - Steel.

In the event of evidence of poor welds, the Government reserves the right to require recertification of any welder or welder operator. The test results shall be made available for review by the contracting officer or the contracting officer's representative.

3.16.2.2 Welding. The surfaces of parts to be welded shall be free from scale, paint, grease, and other foreign matter. Welding shall be done by the shielded metal-arc or gas metal-arc (MIG) process and shall conform to the provisions of either ASME or AWS code. All welded parts shall be free from cracks and other imperfections that may reduce the effectiveness of the part. Work shall be positioned for flat welding when practicable. Before welding over previously deposited weld metal, all traces of slag shall be removed, and the deposit and adjoining base metal shall be wire brushed clean.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.1.2 Component and material inspection. The supplier is responsible for ensuring that components and materials used are manufactured, examined, and tested in accordance with referenced specifications and standards.

4.2 Classification of inspections. Inspection shall be classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).
c. Inspection of packaging (see 4.6).

4.3 First article inspection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:07Z
Check the source to verify that this is the current version before use.

4.3.1 Examination. The first article horizontal connecting tool shall be examined for the defects specified in 4.5.1. Presence of one or more defects shall be cause for rejection.

4.3.2 Test. The first article horizontal connecting tool shall be tested as specified in 4.5.2. Failure to pass the test shall be cause for rejection.

4.4 Quality conformance inspection.

4.4.1 Sampling for examination. Sampling for examination shall be in accordance with MIL-STD-105. Sample size shall be determined by using MIL-STD-105, table I and table IIa. A lot shall be accepted when zero defects are found and rejected when one or more defects are found.

4.4.2 Examination. Samples selected in accordance with 4.4.1 shall be examined as specified in 4.5.1. Presence of one or more defects shall be cause for rejection.

4.5 Inspection procedure.

4.5.1 Examination. The horizontal connecting tool shall be examined as specified herein, for the following defects:

Major

101. Nonconformance to the dimensions shown on the drawings (see 3.1.1).
102. Components missing or not as specified (see 3.1.1).
103. Materials not as specified (see 3.3).
104. Materials are not resistant to corrosion or deterioration or treated to be made resistant to corrosion or deterioration for the applicable storage and operating environment as specified (see 3.3.1).
105. Dissimilar metals as specified in MIL-STD-889 are not effectively insulated from each other as specified (see 3.3.1.1).
106. Contractor does not have documentation available for identification of material, material finishes, or treatments (see 3.3.1.2).
107. Used, rebuilt or remanufactured components, pieces, or parts incorporated in the horizontal connecting tool (see 3.3.2).
108. Workmanship not as specified (see 3.16).
109. Welders and welding operators not certified as specified (see 3.16.2.1).
110. Welding and welds not as specified (see 3.16.2.2).
111. Weld defects such as flux inclusions, spatter, undercutting, porosity, incorrect size, or lack of fusion with parent metal (see 3.16.2.2).

Minor

201. Identification marking incorrect, missing, or illegible (see 3.14).
202. Treatment and painting not as specified (see 3.15).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:07Z
Check the source to verify that this is the current version before use.

4.5.2 Horizontal connecting tool test. Place the tube hook and the chain hook of the horizontal connecting tool over separate edges (approximately 28-1/2 inches apart) of an unyielding surface. Install a 10,000-psi-minimum pump to the horizontal connecting tool incorporating the coupling set and a 10,000-psi, minimum-capacity gauge in the hydraulic line between the pump and tool. Pump hydraulic fluid into the tool until the gauge in the line indicates the pressure required to produce 10 tons. Maintain this pressure on the gauge for 5 minutes. Then release the pressure and disconnect the couplings at the swivel. Determine whether there is leakage through or around the seal. Connect the couplings again. Determine whether there is obstruction of flow. Evidence of any of the following shall constitute failure of this test:

a. Failure or damage to the horizontal connecting tool.
b. Any leakage from the couplings.
c. Any leakage through or around the coupling seals when the couplings are disconnected.
d. Any obstruction of hydraulic fluid flow when the couplings are connected.
e. Any leakage of hydraulic fluid or evidence of damage to the hydraulic ram.

4.6 Inspection of packaging.

4.6.1 Quality conformance inspection of pack.

4.6.1.1 Unit of product. For the purpose of inspection, a completed pack prepared for shipment shall be considered a unit of product.

4.6.1.2 Sampling. Sampling for examination shall be in accordance with MIL-STD-105. Sample size shall be determined by using MIL-STD-105 table I and table IIa. A lot shall be accepted when zero defects are found and rejected when one or more defects are found.

4.6.1.3 Examination. Samples selected in accordance with 4.6.1.2 shall be examined for the following defects. Presence of one or more defects shall be cause for rejection.

112. Materials and containers not as specified for level A or B. Each incorrect material or container shall be considered one defect (see 5.1.1 and 5.1.2).
113. Interior surfaces of the hydraulic ram not preserved as specified for level A or B (see 5.1.1 and 5.1.2).
114. Openings not sealed as specified for level A or B (see 5.1.1 and 5.1.2).
115. Contents not immobilized as specified for level A or B (see 5.1.1 and 5.1.2).
116. Box not waterproof sealed as specified for level A (see 5.1.1 and 5.1.2).
117. Quantities packed together exceed the weight or size limitations for level A or B (see 5.2.1 and 5.2.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:07Z
Check the source to verify that this is the current version before use.

118. Shipping containers not as specified for level A or B (see 5.2.1 and 5.2.2).
119. Strapping not zinc-coated for level A (see 5.2.1).
120. Packing for level C not as specified in accordance with the referenced document (see 5.2.3).
121. Marking missing, illegible, incorrect or incomplete for level A, B, or C (see 5.3).

5. PACKAGING

5.1 Preservation. Preservation shall be level A, B, or C as specified (see 6.2).

5.1.1 Level A. Interior surfaces of the hydraulic ram shall be coated with the hydraulic fluid recommended for operation and the excess fluid drained. Openings into the ram shall be sealed with tape conforming to PPP-T-60, type IV. The tool with couplings shall be packaged in a close fitting box conforming to PPP-B-636, W5c. The contents shall be immobilized within the box in a manner to prevent free movement or damage by the use of fiberboard inserts, pads, or cushions, fabricated from the same material as the box. The box shall be waterproof sealed with tape as specified for slotted style boxes in the appendix to the box specification.

5.1.2 Level B. Each tool with couplings shall be preserved as specified in 5.1.1 for level A except the box and the inserts, pads, or cushions used shall conform to PPP-B-636, type CF, class domestic, variety SW, grade 175, style optional.. Box closure shall be in accordance with the appendix to the box specification.

5.1.3 Level C. Each tool with couplings shall be preserved to afford protection against deterioration and damage from the supplier to the initial destination.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 Level A. Tools preserved as specified in 5.1, shall be packed together in a close fitting box conforming to PPP-B-601, overseas type, style optional in quantities not to exceed the weight limitation of the box. Box closure and strapping shall be in accordance with the appendix to the box specification. Strapping shall be zinc-coated.

5.2.2 Level B. Tools preserved as specified in 5.1, shall be packed together as specified in 5.2.1 except boxes shall be domestic type and strapping need not be zinc-coated. As an alternate the tools may be packed in a close fitting box conforming to PPP-B-640, class 2, style optional or PPP-B-636, V3c, V11c, V13c, or V15c, style optional. The gross weight or size of each box shall not exceed the limitations of the applicable box specification. Box closure and strapping shall be in accordance with the appendix to the box specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:07Z
Check the source to verify that this is the current version before use.

5.2.3 Level C. Tools preserved as specified in 5.1, shall be packed in a manner to assure carrier acceptance and safe delivery to destination at lowest ratings in a container complying with Uniform Freight Classification rules or National Motor Freight Classification rules.

5.3 Marking. In addition to any special marking by the contract or purchase order (see 6.2). Packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The horizontal connecting tool is to be used to horizontally align the deck sections of the Class 60 Floating Bridge. This item is a component of the following Supply Catalogs (SC), SC 5420-97-E30 and E45.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.
b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
c. Time frame required for submission of first article (see 3.2).
d. Level of preservation and level of packing required (see 5.1 and 5.2).
e. Any special marking (see 5.3).

6.3 First article. When a first article inspection is required, the item(s) should be a preproduction model. The first article should consist of one or more units. The contracting officer should include specific instructions in the acquisition documents regarding arrangements for examinations, approval of the first article test results and disposition of the first articles. Invitation for bids should provide that the Government reserves the right to waive the requirement for samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the Government, and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract. Bidders should not submit alternate bids unless specifically requested to do so in the solicitation.

6.4 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:07Z
Check the source to verify that this is the current version before use.

6.5 Subject term keyword listing.

Bridge
Erection
Floating

Custodians:
Army - ME

Review activity
DLA - CS

Preparing activity:
Army - ME

Project 5420-0182

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:07Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

RECOMMEND A CHANGE:	1. DOCUMENT NUMBER MIL-T-523328	2. DOCUMENT DATE (YYMMDD) 910925

3. DOCUMENT TITLE
Tool, Horizontal Connecting: Erection Equipment for Bridge, Floating, Pneumatic Float, Class 60

4. NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)

REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (if applicable) (2) AUTOVON	7. DATE SUBMITTED

8. PREPARING ACTIVITY

a. NAME Gerry Harlow	b. TELEPHONE (Include Area Code) (1) Commercial (703) 664-1806	(2) AUTOVON 354-1806
c. ADDRESS (Include Zip Code US Army Belvoir RDE Center ATN: STRBE-TSE Fort Belvoir, VA 22060-5606	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:07Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:07Z
Check the source to verify that this is the current version before use.