INCH POUND

MIL-T-52402D(ME)
12 June 1992
SUPERSEDING
MIL-T-52402C(ME)
3 August 1983

MILITARY SPECIFICATION

TOOL OUTFIT, PIONEER, PORTABLE ELECTRIC AND HYDRAULIC POWERED TOOLS, TRAILER MOUNTED

This specification is approved for use within the USA Belvoir Research, Development, and Engineering Center, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification establishes the requirements for manufacture and acceptance of the following equipment:

Equipment Level (see 6.2)	Description
1	Tool Outfit, Pioneer, Portable Power Tools, Trailer Mounted.
2	Body Assembly, Cargo Trailer, Tool Mounting.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: USA Belvoir Research, Development, and Engineering Center, ATTN: STRBE-TSE, Fort Belvoir, VA, 22060-5606 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 5180

AMSC N/A
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:08Z
Check the source to verify that this is the current version before use.

2.1.1 Specifications and standards. The following specifications and standards form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

FEDERAL

PPP-P-40	- Packaging and Packing of Hand Tools.
PPP-B-636	- Boxes, Shipping, Fiberboard.

MILITARY

MIL-P-116	- Preservation, Method of.
MIL-B-121	- Barrier Material, Greaseproofed, Waterproofed, Flexible.
MIL-P-514	- Plates, Identification, Instruction and Marking, Blank.
MIL-T-704	- Treatment and Painting of Materiel.
MIL-M-7866	- Molybdenum, Disulfide, Technical, Lubrication.
MIL-P-15024	- Plates, Tag and Bands for Identification of Equipment.
MIL-T-22085	- Tapes, Adhesive, Preservation and Sealing.
MIL-B-26195	- Box, Wood-Cleated, Skidded Load Bearing Base.
MIL-C-46168	- Coating, Aliphatic Polyurethane, Chemical, Agent Resistant.
MIL-C-53039	- Coating, Aliphatic Polyurethane, Single Component, Chemical Agent Resistant.
MIL-V-62038	- Vehicle, Wheeled, Preparation for Shipment and Storage.

STANDARDS

FEDERAL

FED-STD-H28	- Screw-Thread Standards For Federal Services.

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	- Marking for Shipment and Storage.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:08Z
Check the source to verify that this is the current version before use.

MIL-STD-209 - Slinging and Tiedown Provisions for Lifting and Tying Down Military Equipment.
MIL-STD-642 - Identification Marking of Combat and Tactical Transport Vehicles.
MIL-STD-810 - Environmental Test Methods and Engineering Guidelines.
MIL-STD-889 - Dissimilar Metals.
MIL-STD-913 - Military Standard Requirements and Procedures for the Certification of Externally Transported Military Equipment by Department of Defense Rotary Wing Aircraft.
MIL-STD-1472 - Human Engineering Design Criteria for Military Systems, Equipment, and Facilities.
MIL-STD-1473 - Standard General Requirements for Color and Marking of Army Material.
MIL-STD-1474 - Noise Limits for Military Materiel.
MIL-STD-1791 - Air Transport Requirement, General Specification.
MS35829 - Hinge, Continuous (Piano), .075 Thickness, .187 and .250 Pin Diameter.

(Unless otherwise indicated, copies of federal and military specifications and standards are available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Other Government drawings and publications. The following other Government drawings and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWINGS

ME

TA13229E9760 - Tool Outfit, Pioneer, Portable, Electric and Hydraulic Powered Tools, Trailer Mounted.
13229E9764 - Power Unit, Hydraulic, Skid Mounted.
13229E9765 - Power Unit, Hydraulic, Wheel Mounted.
13229E9777 - Alternator, Hydraulic.

(Copies of drawings required by contractors in connection with specific acquisition functions should be obtained from the USA Belvoir Research, Development, and Engineering Center, ATTN: STRBE-FMT, Fort Belvoir, VA 22060-5606.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:08Z
Check the source to verify that this is the current version before use.

AMERICAN TRUCKING ASSOCIATION, INC. (ATA)

Summary of Size and Weight Limits.

(Details on these legal limits are available from the Director, Military Traffic Management Command, Transportation Engineering Agency, ATTN: MTTE-TR, P.O. Box 6276, Newport News, VA 23606-0276.)

INTERNATIONAL ROAD FEDERATION (IRF)

Limits of Motor Vehicle Sizes and Weights

(Details on these legal limits are available from the Director, Military Traffic Management Command, Transportation Engineering Agency, ATTN: MTTE-TR, P.O. Box 6276, Newport News, VA 23606-0276.)

2.2 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

ASSOCIATION OF AMERICAN RAILROADS (AAR)

Rules Governing the Loading of DOD Materiel on Open Top Cars.

(Application for copies should be addressed to the Association of American Railroads, 50 F. Street, N.W., Washington, D.C. 20001.)

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3951 - Standard Practice for Commercial Packaging.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC. (NMFTA)

National Motor Freight Classification Rules.

(Application for copies should be addressed to the American Trucking Associations, Inc., ATTN: Traffic Department, 2200 Mill Road, Alexandria, VA 22314.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:08Z
Check the source to verify that this is the current version before use.

UNIFORM CLASSIFICATION COMMITTEE (UCC)

Uniform Freight Classification Rules.

(Application for copies should be addressed to the Uniform Classification Committee, ATTN: Tariff Publishing Officer; Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, (except for related associated detail specifications, specification sheets or MS standards), the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Description. Level 2 equipment (body assembly, cargo trailer) consists of the toolboxes, supporting steel members, and the steel subbase frame (see 3.12). The level 1 equipment (tool outfit) consists of the level 2 equipment and the components compiled from the supply catalog referenced herein (see 6.4). Both level 1 and level 2 equipment shall be as specified herein and:

a. In accordance with TA13229E9760.

b. Provided with the mounting and tiedown devices specified herein (see 3.13).

3.1.1 Drawings. The drawings forming a part of this specification are end product drawings. No deviation from the prescribed dimensions or tolerances is permissible without prior approval of the contracting officer. Where tolerances could cumulatively result in incorrect fits, the contractor shall provide tolerances within those prescribed on the drawings to ensure correct fit, assembly, and operation of the equipment. Any data (e.g. shop drawings, layouts, flow sheets, processing procedures, etc.) prepared by the contractor or obtained from a vendor to support fabrication and manufacture of the production item shall be made available, upon request, for inspection by the contracting officer or designated representative.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:08Z
Check the source to verify that this is the current version before use.

3.2 First article. The contractor shall furnish equipment for examination and test within the time frame specified (see 6.2) to prove prior to starting production, that his designs and production methods shall produce equipment that comply with the requirements of this specification (see 6.3). Level 1 equipment shall be furnished trailer-mounted with components, compiled from the supply catalog referenced herein (see 6.4), secured in place.

3.3 Material. Material shall be as specified herein and on the drawings. Materials not specified shall be selected by the contractor and shall be subject to all provisions of this specification.

3.3.1 Material deterioration prevention and control. Equipment shall be fabricated from compatible materials, inherently corrosion resistant or treated to provide protection against the various forms of corrosion and deterioration that may be encountered in any of the applicable operating and storage environments to which the equipment may be exposed. Cadmium plated fasteners shall not be used.

3.3.2 Dissimilar metals. Dissimilar metals shall not be used in intimate contact with each other unless protected against galvanic corrosion. Dissimilar metals and methods of protection are defined and detailed in MIL-STD-889.

3.3.3 Identification of materials and finishes. The contractor shall identify the specific material, material finish or treatment for use with component and subcomponent, and shall make information available upon request to the contracting officer or designated representative.

3.3.4 Recovered materials. For the propose of this requirement, recovered materials are those materials which have been collected from solid waste and reprocessed to become a source of raw materials, as distinguished from virgin raw materials. The components, pieces and parts incorporated in the equipment may be newly fabricated from recovered materials to the maximum extent practicable, provided the equipment produced meets all other requirements of this specification. Used, rebuilt or remanufactured components, pieces and parts shall not be incorporated in the equipment.

3.4 Safety. All rotating or reciprocating parts and other parts subject to high operation temperatures that are of such a nature or are so located as to be a hazard to operating personnel, shall be guarded or insulated to the extent necessary to eliminate the hazard. Protective devices shall not impair the operating functions. The body assembly shall be designed and fabricated to prevent injury to operator and maintenance

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:08Z
Check the source to verify that this is the current version before use.

personnel. Nonfunctional rough or sharp edges, projecting points, or excessive lengths of fasteners shall be avoided.

3.5 Human factors engineering. Level 1 and level 2 equipment shall conform to accepted human factors engineering design criteria as described in MIL-STD-1472. Special design emphasis shall be given, but not limited, to general requirements (4), control/display integration (5.1), visual displays (5.2), controls (5.4), labeling (5.5), design for maintainability (5.9), hazards and safety (5.13) of MIL-STD-1472, as applicable.

3.6 Noise limits. For level 1 equipment, the noise produced by the power tools and units shall conform with MIL-STD-1474 requirements when tested in accordance with 5.1.2, with the exception of 5.2, 5.3, and 5.4. The provisions of 4.2 and 4.3 of MIL-STD-1474 shall be provided, if and only if, procedures stated in 5.1.1.3 of MIL-STD-1474 have been pursued and documented to the satisfaction of the procuring activity and written permission to exceed the 85 Db(A) limit is obtained from the contracting activity. Hazard signs shall conform to 4.2 of MIL-STD-1474. For the purpose of the noise measurements, the operator position is defined as 20 feet from both the skid mounted and the wheel mounted power units.

3.7 Performance requirements. For level 1 equipment, the performance requirements shall be performed on both power units and on the tools.

3.7.1 Rated capacity. Within 5 minutes of operation after starting, both power units shall be capable of operating at full power when operating under all conditions specified herein.

3.7.2 Low temperatures. Both power units shall start and operate as specified herein for not less than 4 hours at rated capacity for an ambient temperature of -25 °F. Each hydraulic and electric tool shall be connected to the skid mounted power unit utilizing the necessary hydraulic hose and electrical assemblies and run for a period of one minute.

3.7.3 High temperatures. Both power units shall start and operate as specified herein for not less than 10 hours at rated capacity for an ambient temperature up to +120 °F. Each hydraulic and electric tool shall be connected to the skid mounted power unit utilizing the necessary hydraulic hose and electrical assemblies and run for a period of one minute.

3.8 Maintainability. All major assemblies and installed attachments shall be accessible for maintenance repair and replacement without removal of other major assemblies and installed attachments not normally removed. Design for

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:08Z
Check the source to verify that this is the current version before use.

maintainability shall comply with 3.5. Cover plates which must be removed for component adjustment shall be equipped with quick-disconnect fastenings. Cover plates shall be labeled with nomenclature for items accessible through them in accordance with MIL-STD-1472, 5.9.9.3 (see 3.5). All fasteners shall be of corrosion-resistant material or shall be tested to be corrosion resistant. All screw threads shall be in accordance with FED-STD-H28. Maximum-use shall be made of interchangeable hardware and fastening devices. Means for drainage of lubricants, fuel, and condensate traps shall be in an accessible location and shall drain without splashing on any component or on operating personnel. The drain outlets shall be so located to facilitate complete drainage into a suitable container. Each maintenance, assembly or disassembly operation performed as a result of testing shall be accomplished by not more than two persons using common tools and specified tools furnished with the pioneer tool outfit.

3.9 Power units. For level 1 equipment, the skid mounted hydraulic power unit shall meet the requirements of 13229E9764 and operate as specified herein. For level 1 equipment, when provided (see 6.2 and 6.5), the wheel mounted power unit shall meet the requirements of 13229E9765, and operate as specified herein. The hydraulically driven alternator shall meet the requirements of 13229E9777 and shall operate as specified herein.

3.10 Chassis. Level 1 equipment shall be mounted on a Government-furnished M353, 3-1/2-ton, 2 wheel, trailer chassis (see 3.17). Trailer chassis shall be modified by the contractor in accordance with applicable drawings.

3.11 Tools. For level 1 equipment, each hydraulic and electric tool shall be capable of operation when connected to either power unit utilizing the necessary hydraulic hose and electrical assemblies.

3.12 Tool boxes. The number, location, and design of the toolbox shall be in accordance with drawing 13229E9760. The toolboxes shall provide compartments, drawers, or tiedowns for securing all components of the tools outfit. Fuel- and oil-resistant elastomer sheet material shall be permanently affixed to the bottom of the toolboxes to prevent contact of the tools in excess of 1/2-inch in any direction. Instruction plates(s), (see 3.15.2), depicting the arrangement, and identification of each tool, shall be permanently affixed to the underside of the toolbox cover(s). A continuous wrap-around bumper of 3-inch 6-pound-per-foot steel channel shall be welded or bolted along the exterior lower portion of the rearmost-side and rear-center toolboxes from fender-well to fender-well. Padlocks shall be provided to secure the toolboxes.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:08Z
Check the source to verify that this is the current version before use.

3.13 Component mounting and tiedown. The contractor shall be responsible for the design and installation of the necessary mounting and tiedown devices to properly anchor the tools and equipment, to prevent movement during transit. Sensitive items shall be protected against shock. Tool anchorage devices shall be constructed for a general tool or instrument configuration to allow interchange of like items from different manufacturing sources.

3.13.1 Components furnished in carrying cases. Components furnished in carrying cases shall be strapped to the floor of the body assembly. Accessories to be used with the item shall be stored within the carrying case whenever possible. Otherwise, the accessory items shall be secured with straps, clamps or brackets, or shall be stored in small metal boxes on the body assembly panels or floor as close as practicable to the parent item.

3.13.2 Components furnished without carrying cases. Components furnished without a carrying case shall be strapped or clamped securely to the body floor or body panels of the assembly. Accessory items shall be secured with straps, clamps or brackets, or shall be stored in small metal boxes on the body assembly panels or floor as close as practicable to the parent item.

3.13.3 Fire extinguisher brackets. The fire extinguisher brackets shall be permanently secured in the area as shown on the applicable drawing.

3.13.4 Component location. The contractor shall be responsible for the design, method of attachment and location of the instruction plates specified in 3.15.2.

3.14 Padlocks. The contractor shall furnish and install padlocks with shackle and chain in accordance with applicable drawings.

3.15 Identification marking and instruction plates.

3.15.1 Identification marking. Level 1 and 2 equipment shall be identified in accordance with MIL-P-15024 and applicable drawings.

3.15.2 Instruction plates. The identification of each component (see 6.4) and the component's proper location shall be marked by plates conforming to MIL-P-514, type III, composition C, of type I, grade A, class 1 material.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:08Z
Check the source to verify that this is the current version before use.

3.15.3 Vehicle marking. Registration and other marking shall be applied in accordance with MIL-STD-642. The actual gross vehicle weight (GVW) shall be determined by the contractor and the weight in pounds shall be applied to each side near the front of the body. The recommended tire pressure for the actual GVW shall be marked on the body above the tires.

3.16 Treatment and painting. The portions of the tool outfit normally painted internally and externally shall be cleaned, treated, and painted in accordance with MIL-T-704, type F or G, as applicable. Unless otherwise specified (see 6.2), top coat color shall be camouflage green 383, conforming to MIL-C-46168 or MIL-C-53039 as applicable.

3.17 Government-furnished property. The following property in the quantities indicated will be furnished by the Government (see 6.7):

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:08Z
Check the source to verify that this is the current version before use.

LEVEL 1 EQUIPMENT

Description	Quantity
Chassis, Trailer, 3-1/2 Ton, 2 Wheel, Military Design, M353	As required

3.18 Government-loaned property. The following property in the quantities indicated will be loaned by the Government (see 6.8):

LEVEL 2 EQUIPMENT

Item no.	Description	Quantity
1	Components per supply catalog (see 6.4)	1 each
2	Chassis, Trailer, 3-1/2 Ton, 2 Wheel, Military Design, M353	1

3.19 Transportability. Level 1 and level 2 equipment shall be capable of being transported by military or commercial trailers, trains, aircraft and must be capable of withstanding the impact forces encountered in shipment without damage or permanent deformation. Level 1 and level 2 equipment shall be equipped with tiedown and slinging provisions.

3.19.1 Highway transportability. Level 1 and level 2 equipment prepared for transport shall not exceed legal size and weight limits imposed by the states and North American Treaty Organization (NATO) countries. The pioneer tool outfit shall be capable of being towed over paved roads, unimproved surfaces, and cross-country terrain at the towing speeds described in 4.5.2.2.1. United States and NATO statutory road limitations are available in the American Trucking Association, and the International Road Federation, respectively. Details on these legal limits are available from the Military Traffic Management Command.

3.19.2 Rail transportability. Level 1 and level 2 equipment shall be rail transportable in CONUS and NATO countries without restrictions. The equipment shall have a dimensional profile within the Gabarit International de Chargement (GIC) in accordance with AAR outline diagram when loaded on a 50-inch (127 cm) high rail car. The equipment shall be capable of withstanding shock loads resulting from rail impact testing in accordance with 4.5.2.2.2 without failure, damage, or permanent deformation.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:08Z
Check the source to verify that this is the current version before use.

3.19.3 Air transportability. Level 1 and level 2 equipment shall meet the requirements of MIL-STD-1791 for air transport. When required (see 6.2), the contractor shall provide sufficient data to the Government (see 6.12), to confirm that the equipment being supplied can be loaded and transported in the C-130 or C-141. In addition, level 1 and level 2 equipment prepared for transport shall meet the criteria of MIL-STD-209 and MIL-STD-913 for helicopter transport and be externally transportable by CH-47 helicopters.

3.19.4 Slinging provisions. The slinging provisions shall conform to MIL-STD-209, class 1 or 3, type III. The provisions shall enable level 1 and level 2 equipment to be lifted in the normal operating position. The provisions shall be located so that not less than one inch clearance is maintained between slings and all exterior parts and shall be fastened to members which shall withstand stresses in the amount and direction of pull specified for the provisions without weld failure, permanent deformation, cracking, loosening, or breaking of the provision or its connecting structural components. Slinging provisions may also be used as tiedown provisions when such provisions meet the requirements specified in 3.19.5. Lift points shall be labelled "LIFT HERE". The labels shall conform to the requirements 3.5.

3.19.5 Tiedown provisions. The tiedown provisions shall conform to MIL-STD-209, class 2 or 3, type III equipment, and to MIL-STD-1791 for equipment restraint criteria. The tiedown provisions shall satisfactorily complete the pull testing as specified without weld failure, permanent deformation, cracking, loosening, or breaking of the provision or its connecting structural components. Tiedown points shall be labelled "TIEDOWN HERE" and combination lift/tiedown points shall be labelled "LIFT/TIEDOWN HERE". The labels shall conform to 3.6.

3.20 Workmanship. The equipment shall be free from defects such as incomplete welds, rust, cracks, and other defects that could impair the operation or serviceability of the equipment.

3.20.1 Fabrication. Metal used in fabrication shall be free from kinks and sharp bends. The straightening of material shall be done by methods that shall not cause injury to the metals. Flame cutting of steel may be employed instead of shearing or sawing. Burned surfaces of flame-cut steel shall be ground or machined to remove ash and cooling checks. All burrs and rough edges shall be removed. Overheating shall be avoided. All bends of a major character shall be made with metal dies or fixtures to ensure uniformity or size and shape.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:08Z
Check the source to verify that this is the current version before use.

4. QUALITY CONFORMANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.1.2 Component and material inspection. The contractor is responsible for ensuring that components and materials are manufactured, examined, and tested in accordance with referenced specifications and standards, as applicable.

4.1.3 Disassemble inspection. Failure of any first article model test shall be cause for disassembly, in the presence of a Government representative, of the preproduction model to the extent necessary to determine the cause of the failure. Each disassembled part shall be examined in detail for compliance with this specification and referenced drawings in regard to materials, dimensions, tolerances, and workmanship. Parts not complying with such requirements shall be rejected.

4.1.4 Parts and components. Parts and components detailed on the drawings shall be inspected in accordance with the quality assurance provisions (QAP) (see 6.9.1) shown on the drawings. The drawings specify the characteristics requiring QAP inspection, the sampling plan, and the basis for acceptance and rejection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:08Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article (preproduction model) inspection (see 4.3).
b. Quality conformance inspection (see 4.4).
c. Comparison inspection (see 4.6).
d. Inspection of packaging (see 4.7).

4.3 First article inspection.

4.3.1 Examination. Equipment shall be examined for the defects marked "X" in column 2 of table I. Presence of one or more defects shall be cause for rejection or shall be cause for performing the disassembly inspection specified in 4.1.3.

4.3.2 Tests. Upon successful completion of the examination specified in 4.3.1, the first article shall be subjected to the tests marked "X" in column 2 of table II. Failure of any test shall be cause for rejection or shall be cause for performing the disassembly inspection specified in 4.1.3.

4.4 Quality conformance inspection.

4.4.1 Sampling. Sampling for examination shall be in accordance with MIL-STD-105, inspection level II.

4.4.2 Examination. Samples selected in accordance with 4.4.1 shall be examined for defects marked "X" in column 3 of table I. Presence of one or more defects shall be cause for rejection.

4.4.3 Tests. Samples selected in accordance with 4.4.1 shall be subjected to the tests marked "X" in column 3 of table II. Failure of any test shall be cause for rejection.

4.5 Inspection schedule.

4.5.1 Examination. Examinations shall be in accordance with table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:08Z
Check the source to verify that this is the current version before use.

TABLE I. Examination schedule.

Equip. level	First article	Qual. conf.	Defect	Requirement paragraph
1	2	3	4	5
1	X	X	101. Tools and equipment missing or not as specified.	3.1
1 & 2	X	X	102. Material not as specified.	3.3, Applicable dwgs.
1 & 2	X	X	103. Materials not resistant to corrosion and deterioration or treated, to be resistant to corrosion and deterioration of the applicable storage and operating environments.	3.3.1
1 & 2	X	X	104. Cadmium plated fasteners used.	3.3.1
1 & 2	X	X	105. Dissimilar metals as defined in MIL-STD-889 are not effectively insulated from each other.	3.3.2
1 & 2	X	X	106. Contractor does not have documentation available for identification of materials, material finishes, or treatment.	3.3.3
1 & 2	X	X	107. Used, rebuilt or remanufactured components, pieces, or parts incorporated in the tool kit.	3.3.4
1 & 2	X	X	108. Safety not as specified.	3.4
1 & 2	X	X	109. Accessibility of fire extinguisher.	3.4
1 & 2	X	X	110. Human factors engineering not as specified.	3.5
1	X	X	111. Power units not as specified.	Applicable dwgs. and 3.9
1 & 2	X	X	112. Tool anchorage or storage provisions not as specified.	3.13
1 & 2	X	X	113. Components identified and located.	3.13.4
1 & 2	X	X	114. Padlocks missing or not as specified.	3.14
1 & 2	X	X	115. Identification marking not as specified.	3.15.1
1 & 2	X	X	116. Instruction plates not as specified.	3.15.2
1 & 2	X	X	117. Vehicle marking not as specified.	3.15.3
1 & 2	X	X	118. Physical dimension exceed highway transport limits.	3.19.3
1 & 2	X	X	119. Incomplete welds, weld cracks.	3.20
1 & 2	X	X	120. Metal fabrication not as specified.	3.20.1

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:08Z
Check the source to verify that this is the current version before use.

TABLE I. Examination schedule. (continued)

Equip. level	First article	Qual. conf.	Defect	Requirement paragraph
1	2	3	4	5
1 & 2	X	X	121. Major paint runs, bare spots, flaking, or peeling of the paint.	Applicable dwgs. and 3.16.
1 & 2	X	X	122. Any part of component not in accordance with the QAP requirements shown on the drawings.	Applicable dwgs.
1 & 2	X	X	123. Any dimensions, other than those identified by the QAP requirements shown on the drawings, not as specified.	Applicable dwgs.
1 & 2	X	X	124. Assembly not complete or not correct.	Applicable dwgs.
1 & 2	X	X	125. Rivets or other fasteners missing.	Applicable dwgs.

4.5.2 Tests.

4.5.2.1 Test schedule. Test shall be in accordance with table II.

TABLE II. Test schedule.

Equipment level	First article	Test	Requirement paragraph	Test paragraph
1	2	3	4	5
1 & 2	X	Road test	3.19.1	4.5.2.2.1
1 & 2	X	Rail impact test	3.19.2	4.5.2.2.2
1 & 2	X	Slinging provisions	3.19.4	4.5.2.2.4
1 & 2	X	Tiedown provisions	3.19.5	4.5.2.2.5
1	X	Noise level	3.6	4.5.2.3
1	X	Low temperature	3.7.2	4.5.2.4
1	X	High temperature	3.7.3	4.5.2.5
1	X	Interface of tools	3.11	4.5.2.6

4.5.2.2 Transportability.

4.5.2.2.1 Road test. Tow the pioneer tool outfit for a distance of 100 miles at maximum safe speeds. Twenty miles of this travel shall be on cross-country terrain (see 6.9.3),

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:08Z
Check the source to verify that this is the current version before use.

40 miles shall be on secondary roads, and 40 miles shall be on primary roads. Operation on smooth, paved surfaces shall include not less than 15 abrupt stops from a speed of 25 mph in the forward direction, not less than five abrupt stops from a speed of 2 mph in the reverse direction, and not less than 10 sharp turns to the left and 10 to the right at not less than 25 mph. Radii of the sharp turns shall be not greater than 150 feet. Displacement or damage to welded, bolted, or riveted connections or failure to operate as specified shall constitute failure of this test. For level 1 equipment, during the above road test, start and operate both power units at rated capacity for 15 minutes after every 20 miles.

4.5.2.2.2 Rail impact test. Equipment shall be tested in accordance with MIL-STD-810, method 514.4, procedure III, and method 516.4, procedure VIII, except the item shall be impacted on each direction at speeds of 8 and 10 miles per hour, ±5 percent. Examine the equipment at the completion of each phase of this test. Any displacement (see 6.9.2), any loosening or breaking of holddowns, ties, stays, blocking or bracing, or any visual damage to the equipment shall constitute failure of this test.

4.5.2.2.3 Air transportability. The air transportability requirement for the C-130 and C-141 aircraft, in accordance with MIL-STD-1791 (see 3.19.3), shall be certified. Inability to provide certification shall constitute failure for meeting this requirement.

4.5.2.2.4 Slinging provisions. The slinging provisions shall be tested in accordance with MIL-STD-209 to prove conformance to 3.19.4. Inability to meet the requirements of 3.19.4 shall constitute failure of this test.

4.5.2.2.5 Tiedown provisions. The tiedown provisions shall be tested in accordance with MIL-STD-209 to prove conformance to 3.19.5. Inability to meet the requirements of 3.19.5 shall constitute failure of this test.

4.5.2.3 Noise level test. Noise levels shall be measured in accordance with MIL-STD-1474 requirements and reported in the format indicated by MIL-STD-1474, figure 11. As a minimum, noise levels shall be measured when equipment is operating under full load. MIL-STD-1474, 5.1.2.1.4 contours shall be taken at not fewer than 12 equal (horizontal) arc increments; one increment shall include data from the noisiest position. Additionally, the noise level at the typical operating position shall be provided as dB(A) level. Failure to comply with MIL-STD-1474 provisions shall constitute failure of this test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:08Z
Check the source to verify that this is the current version before use.

4.5.2.4 Low temperature. Subject the pioneer tool outfit to an ambient temperature of -25 ±5 °F until all components have stabilized at this temperature. Then start and operate the hydraulic power units and the hydraulically driven alternator at rated capacity for not less than 4 hours while maintaining -25 ±5 °F ambient temperature. Adjustments to the power units and the alternator shall not be permitted after the first hour of operation. Each hydraulic and electric tool shall be connected to the skid mounted power unit utilizing the necessary hydraulic hose and electrical assemblies and run for a period of one minute. Failure of the power units to start and operate at rated capacity or failure of a tool to operate shall constitute failure of this test.

4.5.2.5 High temperature. Subject the pioneer tool outfit to an ambient temperature of 120 ±5 °F until all components have stabilized at this temperature. Then start and operate the hydraulic power units and the hydraulically driven alternator at rated capacity for not less than 10 hours while maintaining 120 ±5 °F ambient temperature. Adjustments to the power units and the alternator shall not be permitted after the first hour of operation. Each hydraulic and electric tool shall be connected to the skid mounted power unit utilizing the necessary hydraulic hose and electrical assemblies and run for a period of one minute. Failure of the power units to start and operate at rated capacity or failure of a tool to operate shall constitute failure of this test.

4.5.2.6 Interface of tools. Assemble the hydraulic power unit(s), hose assemblies, hydraulic tools, and the hydraulically driven alternator, electric power cable assemblies and electric tools in accordance with appropriate installation and operating instructions. Operate each tool for at least 15 minutes. Any inoperative components shall constitute failure of this test.

4.6 Comparison inspection. The Government may select equipment at any time during the contract production period and subject that equipment to the examination specified in 4.5.1 and all the tests specified in 4.5.2 to determine conformance to the requirements of this specification. The inspection will be performed by the Government, at a site selected by the Government, on units selected at random from those which have been accepted by the Government and will not include the previously inspected first article model. In addition to any test specified as part of the inspection, the Government reserves the right to conduct any and all other tests contained in this specification as part of the inspection. Failure of such additional tests shall have the same effect as failure of those tests specified as comparison inspection.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:08Z
Check the source to verify that this is the current version before use.

4.6.1 Inspection failure. Failure of a comparison inspection equipment to meet any requirement specified herein during and as a result of the examination and tests specified in 4.6 shall be cause for rejection of the inspection equipment and shall be cause for refusal by the Government to continue acceptance of production equipment until evidence has been provided by the contractor that corrective action has been taken to eliminate the deficiencies. Correction of such deficiencies shall be accomplished by the contractor at no cost to the Government on equipment previously accepted and produced under the contract. Any deficiencies found as a result of the inspection shall be considered prima facie evidence that all equipment accepted prior to the completion of inspection are similarly deficient unless evidence to the contrary is furnished by the contractor and such evidence is acceptable to the contracting officer.

4.7 Inspection of packaging.

4.7.1 First article pack inspection.

4.7.1.1 Examination. The first article pack shall be examined for the defects specified in 4.7.2. Presence of one or more defects shall be cause for rejection.

4.7.2 Quality conformance inspection of pack.

4.7.2.1 Examination. The preservation, packing, and marking shall be examined for the following defects. Presence of one or more defects shall be cause for rejection.

126. Materials, methods, and containers not as specified for level A.
127. Carrying cases for sets and kits not utilized to the maximum extent as specified for level A or C (see 5.2.1.1.3).
128. Mounting brackets and holders not utilized to the maximum extent as specified for level A or C (see 5.2.1.1.4).
129. Unpainted exterior, unfinished metal surfaces not coated with preservative for level A (see 5.2.1.1.5).
130. Exposed exterior machined surfaces not coated with preservative, wrapped, or covered with barrier material and barrier material not secured as specified for level A or C (see 5.2.1.1.5.2 and 5.2.2.1).
131. Trailer components not preserved in accordance with the referenced document for level A or C (see 5.2.1.1.6 and 5.2.2.1).
132. Power units not preserved in accordance with the referenced document for level A or C.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:08Z
Check the source to verify that this is the current version before use.

133. Hand tools not preserved in accordance with the referenced document for level A or C (see 5.2.1.1.7 and 5.2.2.1).
134. Electrical cables not placed on the reels, coiled or hanked and secured as specified for level A or C.
135. Interior of padlocks not coated as specified for level A or C (see 5.2.1.1.8 and 5.2.2.1).
136. Keys not preserved and secured as specified for level A or C (see 5.2.1.1.8 and 5.2.2.1).
137. Fire extinguisher not preserved and secured in the mounting bracket for level A or C (see 5.2.1.1.9 and 5.2.2.1).
138. Consolidation not as specified for level A (see 5.2.1.1.12 and 5.2.2.1).
139. Packing not as specified for level A or C (see 5.3.1 and 5.3.2).
140. Marking missing, illegible, incorrect, or incomplete for level A or C (see 5.4).
141. When only level 2 equipment is procured: fenders and hardware not placed and secured within the body as specified for level A or C (see 5.2.1.2 and 5.3.2.2).

5. PACKAGING

5.1 First article. The contractor shall furnish a first article pack for examination within the time frame specified (see 6.2) to prove prior to starting production packaging that the applied preservation, packing and marking comply with the packaging requirements of this specification. Examination shall be as specified in section 4 and shall be subject to surveillance and approval by the Government (see 6.10). The first article pack may be accomplished utilizing either first article or production equipment. If a first article model is utilized, any preservation, and packing shall be removed by the contractor at no expense to the Government when requested by the Government to facilitate comparison between the first article and production equipment.

5.2 Preservation. Preservation shall be level A or C as specified (see 6.2).

5.2.1 Level A.

5.2.1.1 When level 1 equipment is procured.

5.2.1.1.1 Preservatives. Preservatives specified herein shall conform to the applicable specifications listed in and shall be applied in accordance with MIL-P-116.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:08Z
Check the source to verify that this is the current version before use.

5.2.1.1.2 Preservation methods. Methods of preservation indicated herein by symbols shall conform to the applicable symbols listed in MIL-P-116.

5.2.1.1.3 Sets or kits. When items are furnished in sets or kits with a carrying case, the items shall be preserved as specified herein, and when possible replaced in the case.

5.2.1.1.4 Items having mounting brackets or holders. Items furnished with mounting brackets or holders shall be preserved as specified herein, and when possible, replaced in the bracket or holder and secured to prevent movement and damage.

5.2.1.1.5 Unprotected surfaces. Unprotected exterior metal surfaces of components not specifically specified herein requiring the application of a contact preservative in accordance with MIL-P-116 shall be preserved as follows.

5.2.1.1.5.1 Unfinished surfaces. Unfinished surfaces shall be coated with type P-1 or P-19 preservative.

5.2.1.1.5.2 Machined surfaces. Exposed exterior machined surfaces shall be coated with type P-6 or P-11 preservative. The coated surfaces shall be wrapped or covered with barrier material conforming to MIL-B-121, type I, grade A, class 2 and secured in place with tape conforming to MIL-T-22085, type II.

5.2.1.1.6 Trailer. The trailer components shall be preserved in accordance with the level A (mobile) requirements of MIL-V-62038.

5.2.1.1.7 Hand tools. All hand tools and similar equipment shall be preserved in accordance with the level A requirements of PPP-P-40.

5.2.1.1.8 Padlocks and keys. Interiors of padlocks shall be coated with molybdenum disulfide conforming to MIL-M-7866 and the padlocks operated to assure penetration of the lubricant. Padlocks not attached to the body assembly and the required keys shall be preserved method IC-1 or IC-3 and secured within the body assembly. Attached padlocks shall be additionally protected by a wrap of barrier material conforming to MIL-B-121, type I, grade A, class 2 and the wrap secured with tape conforming to MIL-T-22085, type II. Keys shall be preserved method IC-1 or IC-3 and secured within the body in a conspicuous location.

5.2.1.1.9 Fire extinguisher. Exterior metal surfaces requiring the application of a contact preservative in accordance with MIL-P-116 shall be coated with type P-1 preservative. The extinguisher shall be placed in the mounting bracket and secured.

Source: https://assist.dla.mil -- Downloaded: 2026l0-26T04:08Z
Check the source to verify that this is the currentversion before use.

5.2.1.1.10 Technical publications. Technical publications shall be preserved by method IC-1 or IC-3 without preservative.

5.2.1.1.11 Miscellaneous supplies and equipment. Items of equipment and components not specifically identified herein that require protection from corrosion, mechanical, or physical damage shall be preserved as specified for items, equipment, and components of similar design and construction.

5.2.1.1.12 Consolidation. The preserved and unpreserved components and items of equipment shall be placed and secured within the body assembly utilizing the mountings provided whenever possible. Components and items of equipment that cannot be secured by the mountings provided, because of the preservation requirements, shall be consolidated together in boxes conforming to PPP-B-636, W5c. Available space within the body assembly shall determine the size of the boxes. The boxes shall be placed within the body assembly and secured in place in a manner to prevent damage to the items or to the body assembly.

5.2.1.2 When level 2 equipment is procured. When level 2 equipment is procured, the fenders shall not be installed. The fender mounting hardware and the body to trailer mounting hardware shall be placed in a close fitting box conforming to PPP-B-636, W5c. The fenders and the boxed hardware shall then be placed within the body assembly and secured in a manner to prevent movement, damage or abrasion to the painted surfaces of the fenders.

5.2.2 Level C.

5.2.2.1 When level 1 equipment is procured. When level 1 equipment is procured, all components shall be preserved as specified for level A except boxes shall be domestic and the trailer shall be preserved in accordance with the level C requirements of MIL-V-62038.

5.2.2.2 When level 2 equipment is procured. When level 2 equipment is procured, preservation shall be as specified in 5.2.1.2.

5.3 Packing. Packing shall be level A or C as specified (see 6.2).

5.3.1 Level A.

5.3.1.1 When level 1 equipment is procured. Each complete trailer-mounted tool outfit, with all tools and equipment enclosed, shall be prepared for unboxed mobile shipment in a manner to assure carrier acceptance and safe delivery to

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:08Z
Check the source to verify that this is the current version before use.

destination at lowest ratings in compliance with Uniform Freight Classification Rules or National Motor Freight Classification Rules. Preserved and unpreserved items and equipment, equipment installed within the body assembly, and any other movable equipment or items shall be cushioned, blocked, braced, and anchored to prevent damage to the equipment or to the body assembly and to prevent pilferage. All toolbox covers and opening panels of equipment shall be secured in a suitable manner to prevent accidental opening and to prevent pilferage of contents. The padlocks shall not be used for securing the toolbox covers and opening panels of equipment.

5.3.1.2 When level 2 equipment is procured. Each complete body assembly shall be packed in a box conforming to MIL-B-26195, type II, style optional, class 2, with rubbing strips and plywood superstructure. The body assembly shall be secured to the base, to prevent movement or damage, by bolting through the body assembly trailer by way of the securement holes.

5.3.2 Level C.

5.3.2.1 When level 1 equipment is procured. When level 1 equipment is procured, the packing shall be as specified in 5.3.1.1.

5.3.2.2 When level 2 equipment is procured. Each complete body assembly shall be packed as specified in 5.3.1.2 except the box shall be type I for domestic shipment.

5.4 Marking. In addition to any special marking specified in the contractor purchase order (see 6.2), marking shall be in accordance with MIL-STD-129.

6. NOTES
(This section contains information of a general or explanatory nature that may be helpful, but is mandatory.)

6.1 Intended use. The tool outfit, (equipment level 1) is intended for use by personnel engaged in operations requiring the use of portable electric and hydraulic driven tools for pioneer and construction work.

6.1.1 Body assembly, cargo trailer. The body assembly, cargo trailer is a component of the tool outfit. Level 2 equipment is intended to provide only replacement bodies for the tool outfit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:08Z
Check the source to verify that this is the current version before use.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, equipment level, and date of this specification.
b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
c. Time frame required for submission of the first article (see 3.2).
d. When the Government will conduct any or all of the first article examination and tests. When the Government will conduct some but not all of the first article model examination and tests, the contracting officer should specify which examination and tests will be conducted by the Government and which examination and tests shall be conducted by the contractor (see 3.2).
e. When a wheel mounted power unit is required (see 3.9 and 6.5).
f. When top coat color is other than camouflage green 383 (see 3.16).
g. When air transportability data is required (see 3.19.3 and 3.12).
h. Time frame required for submission of the first article pack (see 5.1).
i. Level of preservation and level of packing required (see 5.2 and 5.3).

6.3 First article. First article inspection item(s) should be a preproduction model. The first article should consist of one or more units. The contracting officer should also include specific instructions in acquisition documents regarding arrangements for examinations, approval of the first article test results and disposition of the first articles. Invitation for bids should provide that the Government reserves the right to waive the requirement for samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the Government, and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract. Bidders should not submit alternate bids unless specifically requested to do so in the solicitation.

6.4 Components list. The contracting officer should arrange to furnish information concerning items specified in the supply catalog as compiled from SC 5180-97-E23.

6.5 Wheel mounted power unit. Before a solicitation is made requiring a wheel mounted power unit, the contracting officer

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:08Z
Check the source to verify that this is the current version before use.

should contact the technical office. The technical office's address is Commander, Belvoir RDE Center, ATTN: STRBE-FMT, Fort Belvoir, VA 22060-5606.

6.6 Replacement parts on equipment already in service. For replacement parts only, pioneer tool outfit, portable, electric power tools built in accordance with prior revisions (basic and revisions A, B, and C) should use SC 5180-97-CL-E21 and top assembly drawings 13217E0400 and 13226E6073.

6.7 Government-furnished property. The contracting officer should arrange to furnish the contractor the property as specified in 3.17.

6.8 Government-loaned property. The contracting officer should arrange to loan the contractor the property specified in 3.18.

6.9 Definitions.

6.9.1 Quality assurance provisions (QAP). A QAP is a contractual requirement that supplements section 4 of the specification. QAP indicates the minimum requirement which must be inspected on the product drawings to verify the design objectives of the product and assure interchangeability of repair parts.

6.9.2 Displacement. Displacement is defined as dislodgment of any tool or item or equipment from its designated position. Movement of a tool or item of equipment within its designated position without any dislodgment is permitted.

6.9.3 Cross-country terrain. Cross-country terrain shall consist of generally level or improved open fields, broken ground, loose sand, or gravel road.

6.10 First article pack. Any changes or deviations of first article packs from the approved pack will be subject to the approval of the contracting officer. Approval of the first article pack will not relieve the contractor of his obligation to preserve, package, pack, and mark the equipment in accordance with this specification.

6.11 Data requirements. The contracting officer should include requirements for such data as technical publications, instructional materials, illustrated parts lists, and contractor's maintenance and operation manual to be furnished with each item of equipment.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:08Z
Check the source to verify that this is the current version before use.

6.12 Consideration of data requirements. The following data requirements should be considered when this document is applied on a contract. The applicable Data Item Description (DIDs) should be reviewed in conjunction with the specific acquisition to ensure that only essential data are requested/provided and that the DIDs are tailored to reflect the requirements of the specific acquisition. To ensure correct contractual application of the data requirements, a Contract Data Requirements List (DD Form 1423) must be prepared to obtain the data, except where DOD FAR Supplement 27.475-1 exempts the requirement for a DD Form 1423.

Reference paragraph	DID Number	DID Title
3.19.3	DI-PACK-80880	Transportability Report

The above DIDs were those cleared as of the date of this specification. The current issue of DOD 5010.12-L, Acquisition Management Systems and Data Requirements Control List (AMSDL), must be researched to ensure that only current, cleared DIDs are cited on the DD Form 1423.

6.13 Subject term (key word) listing.

Electric tools
Hydraulic power tools
Hydraulic tools
Tool kits

6.14 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodian:
Army - ME

User activity:
Army - GL

Preparing activity:
Army - ME

Project 5180-A144

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:08Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3 e preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

RECOMMEND A CHANGE:	1. DOCUMENT NUMBER MIL-T-52402D(ME)	2. DOCUMENT DATE (YYMMDD) 920612

3. DOCUMENT TITLE
Tool Outfit, Pioneer, Portable Elecric and Hydraulic Powered Tools, Trailer Mounted

4. NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (if applicable) (2) AUTOVON	7. DATE SUBMITTED

8. PREPARING ACTIVITY

a. NAME Carolyn B. Johnson	b. TELEPHONE (Include Area Code) (1) Commercial (703) 704-3468 (2) AUTOVON 654-3468
c. ADDRESS (Include Zip Code Army Belvoir RDE Center : STRBE-TSE t Belvoir, VA 22060-5606	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:08Z
Check the source to verify that this is the current version before use.