INCH-POUND
MIL-M-38510/762A
AMENDMENT 1
28 APRIL 1999

MILITARY SPECIFICATION

# MICROCIRCUITS, DIGITAL, ADVANCED CMOS, MULTIPLEXERS, MONOLITHIC SILICON, POSITIVE LOGIC

Inactive for new design after 9 August 1996

This amendment forms a part of MIL-M-38510/762A, dated 14 October 1997, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 5

Table I, high level output voltage, $V_{OH3}$, device type column, RHA levels M, D, L, and R; replace “02, 03, 07” with “01, 02, 03, 07”.
Table I, high level output voltage, $V_{OH5}$, device type column, RHA levels M, D, L, and R replace “02, 03, 07” with “01, 02, 03, 07”.
Table I, high level output voltage, $V_{OH7}$, device type column, RHA levels M, D, L, and R; replace “02, 03, 07” with “01, 02, 03, 07”.
Table I, low level output voltage, $V_{OL3}$, device type column, RHA levels M, D, L, and R; replace “02, 03, 07” with “01, 02, 03, 07”.

PAGE 6

Table I, low level output voltage, $V_{OL5}$, device type column, RHA levels M, D, L, and R; replace “02, 03, 07” with “01, 02, 03, 07”.
Table I, low level output voltage, $V_{OL7}$, device type column, RHA levels M, D, L, and R; replace “02, 03, 07” with “01, 02, 03, 07”.
Table I, positive input clamp voltage, $V_{IC+}$, device type column, RHA levels M, D, L, and R; replace “02, 03, 07” with “01, 02, 03, 07”.
Table I, negative input clamp voltage, $V_{IC-}$, device type column, RHA levels M, D, L, and R; replace “02, 03, 07” with “01, 02, 03, 07”.
Table I, input current high, $I_{IH}$, device type column, RHA levels M, D, L, and R; replace “02, 03, 07” with “01, 02, 03, 07”.
Table I, input current low, $I_{IL}$, device type column, RHA levels M, D, L, and R; replace “02, 03, 07” with “01, 02, 03, 07”.
Table I, quiescent supply current output high, $I_{CCH}$, device type column, RHA level M; replace “02” with “01, 02”.
Table I, quiescent supply current output high, $I_{CCH}$, device type column, RHA level D; replace “02, 07” with “01, 02, 07”.
Table I, quiescent supply current output high, $I_{CCH}$, device type column, RHA level R; replace “03, 07” with “01, 03, 07”.

PAGE 7

Table I, quiescent supply current output low, $I_{CCL}$, device type column, RHA level M; replace “02” with “01, 02”.
Table I, quiescent supply current output low, $I_{CCL}$, device type column, RHA level D; replace “02, 07” with “01, 02, 07”.
Table I, quiescent supply current output low, $I_{CCL}$, device type column, RHA level R; replace “03, 07” with “01, 03, 07”.



FSC 5962

AMSC N/A
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:05Z
Check the source to verify that this is the current version before use.

PAGE 8

Table I, truth table test, device type column, RHA levels M, D, L, and R; replace “02, 03, 07” with “01, 02, 03, 07”.
Table I, propagation delay time, select to output, $t_{PHL1}$, $t_{PLH1}$, $V_{CC}$ = 3.0 V; add the following row:

“

| | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| | | | M, D, L, R | 01 | | 9 | 1.0 | 18.0 | |

“

Table I, propagation delay time, select to output, $t_{PHL1}$, $t_{PLH1}$, $V_{CC}$ = 4.5 V; add the following row:

“

| | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| | | | M, D, L, R | 01 | | 9 | 1.0 | 13.0 | |

“

PAGE 9

Table I, propagation delay time, data input to output, $t_{PHL2}$, $t_{PLH2}$, $V_{CC}$ = 3.0 V; add the following row:

“

| | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| | | | M, D, L, R | 01 | | 9 | 1.0 | 15.0 | |

“

Table I, propagation delay time, data input to output, $t_{PHL2}$, $t_{PLH2}$, $V_{CC}$ = 4.5 V; add the following row:

“

| | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| | | | M, D, L, R | 01 | | 9 | 1.0 | 11.0 | |

“

Table I, propagation delay time, enable to output, $t_{PHL3}$, $t_{PLH3}$, $V_{CC}$ = 3.0 V, device type column, RHA levels M, D, L, and R; replace “02, 03” with “01, 02, 03”.
Table I, propagation delay time, enable to output, $t_{PHL3}$, $t_{PLH3}$, $V_{CC}$ = 4.5 V, device type column, RHA levels M, D, L, and R; replace “02, 03” with “01, 02, 03”.

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force - 11
NASA - NA
DLA - CC

Preparing activity:
DLA - CC

Review activities:
Navy - AS, CG, MC, OS, SH
Army - AR, MI, SM
Air Force - 19, 99

(Project 5962-1848)



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:05Z
Check the source to verify that this is the current version before use.