INCH-POUND
MIL-M-38510/763A
AMENDMENT 1
24 November 1997

MILITARY SPECIFICATION

MICROCIRCUITS, DIGITAL, ADVANCED CMOS, COUNTERS, MONOLITHIC SILICON, POSITIVE LOGIC

Inactive for new design after 9 August 1996

This amendment forms a part of MIL-M-38510/763A, dated 7 November 1994, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 5

Table I, high level output voltage, V_{OH3}, device type column; replace “02, 05” with “02, 04, 05” for RHA levels M, D, and R.
Table I, high level output voltage, V_{OH5}, device type column; replace “02, 05” with “02, 04, 05” for RHA levels M, D, and R.

PAGE 6

Table I, high level output voltage, V_{OH7}, device type column; replace “02, 05” with “02, 04, 05” for RHA levels M, D, and R.
Table I, low level output voltage, V_{OL3}, device type column; replace “02, 05” with “02, 04, 05” for RHA levels M, D, and R.
Table I, low level output voltage, V_{OL5}, device type column; replace “02, 05” with “02, 04, 05” for RHA levels M, D, and R.

PAGE 7

Table I, low level output voltage, V_{OL7}, device type column; replace “02, 05” with “02, 04, 05” for RHA levels M, D, and R.
Table I, positive input clamp voltage, V_{IC+}, device type column; replace “02, 05” with “02, 04, 05” for RHA levels M, D, and R.
Table I, negative input clamp voltage, V_{IC-}, device type column; replace “02, 05” with “02, 04, 05” for RHA levels M, D, and R.
Table I, input current high, I_{IH}, device type column; replace “02, 05” with “02, 04, 05” for RHA levels M, D, and R.
Table I, input current low, I_{IL}, device type column; replace “02, 05” with “02, 04, 05” for RHA levels M, D, and R.

PAGE 8

Table I, quiescent supply current outputs high, I_{CCH}, device type column; replace “02, 05” with “02, 04, 05” for RHA levels M, D, and R.
Table I, quiescent supply current outputs low, I_{CCL}, device type column; replace “02, 05” with “02, 04, 05” for RHA levels M, D, and R.

PAGE 9

Table I, truth table test output voltage, device type column; replace “02, 05” with “02, 04, 05” for RHA levels M, D, and R.

FSC 5962

AMSC N/A
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:05Z
Check the source to verify that this is the current version before use.

PAGE 10

Table I, propagation delay time, CP to Qn ($\overline{PE}$ input high or low) tPHL, tPLH, VCC = 3.0 V, device type column; RHA level M add “04” after “02”, RHA level D add “04” after “02”, RHA level R add “04” after “02”.

Table I, propagation delay time, CP to Qn (PE input high or low) tPHL, tPLH, VCC = 4.5 V, device type column; RHA level M add “04” after “02”, RHA level D add “04” after “02”, RHA level R add “04” after “02”.

PAGE 11

Table I, propagation delay time, CP to TC, tPHL, tPLH, VCC = 3.0 V, device type column; RHA level M add “04” after “02”, RHA level D add “04” after “02”, RHA level R add “04” after “02”.

Table I, propagation delay time, CP to TC, tPHL, tPLH, VCC = 4.5 V, device type column; RHA level M add “04” after “02”, RHA level D add “04” after “02”, RHA level R add “04” after “02”.

Table I, propagation delay time, CET to TC, tPHL, tPLH, VCC = 3.0 V, device type column; RHA level M add “04” after “02”, RHA level D add “04” after “02”, RHA level R add “04” after “02”.

PAGE 12

Table I, propagation delay time, CET to TC, tPHL, tPLH, VCC = 4.5 V, device type column; RHA level M add “04” after “02”, RHA level D add “04” after “02”, RHA level R add “04” after “02”.

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force - 17
NASA - NA

Preparing activity:
DLA - CC

Review activities:
Navy - OS, TD, AS, CG, MC, SH
Army - AR, MI, SM
Air Force - 19, 85, 99

(Project 5962-1806)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:05Z
Check the source to verify that this is the current version before use.