MILITARY SPECIFICATION

CARRIER, PERSONNEL, FULL-TRACKED: ARMORED, M59

1. SCOPE

1.1 Scope. - This specification covers a front-sprocket-driven, full-tracked, armored vehicle, designed as a personnel carrier for cross-country and amphibious operation.

2. APPLICABLE DOCUMENTS

2.1 The following specifications, standards, and drawings of the issue in effect on date of invitation for bids, form a part of this specification.

SPECIFICATIONS

Federal

VV-M-561	-	Gasoline, Automotive/Motor Fuel M.

Military

MIL-L-644	-	Lubricating-Oil, Preservative, Special.
MIL-G-3056	-	Gasoline, Automotive, Combat.
MIL-L-3150	-	Lubricating-Oil, Preservative, Medium.
MIL-G-3278	-	Grease; Aircraft and Instrument (for Low and High Temperatures).
MIL-V-3329	-	Vehicles, Combat, Self-Propelled and Towed, General Requirements for.
MIL-H-6083	-	Hydraulic Fluid, Petroleum Base, Preservative.
MIL-L-6085	-	Lubricating Oil; Aircraft Instrument, Low Volatility.
MIL-L-10295	-	Lubricating Oil, Internal-Combustion Engine, Sub-Zero.
MIL-S-10379	-	Suppression, Radio Interference, General Requirements for Vehicles (and Vehicular Sub-Assemblies).
MIL-G-10924	-	Grease, Automotive and Artillery.
MIL-S-11352	-	Block, Vision: Bullet Resistant.
MIL-S-12158	-	Sealing Compound, Noncuring, Polybutene.
MIL-P-13396	-	Periscope M17.
MIL-P-13525	-	Plates; Designation, Identification, and Instruction, for Tank and Automotive Material.
MIL-H-13919	-	Hydraulic Fluid, Petroleum Base, Fire-Control.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:29Z
Check the source to verify that this is the current version before use.

MIL-G-14461 - General Quality Control Requirements for Ordnance Materiel.
MIL-C-16173 - Corrosion Preventive, Solvent Cutback, Cold-Application.
MIL-L-21260 - Lubricating Oil, Internal-Combustion Engine, Preservative.
MIL-P-45054 - Carrier Personnel, Full-Tracked, Armored, M59 and Mortar, Self-Propelled, Full-Tracked, 4.2 Inch, M84: Preparation for Storage and Shipment of.
MIL-C-45168 - Cupola, Commander's Machine Gun; M13.

STANDARDS
Federal
FEDERAL STD NO. 595 - Colors.

Military
MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-417 - Rubber Composition, Vulcanized General Purpose, Solid (Symbol and Tests).

DRAWINGS
Ordnance Corps
F6550295 - Painting Procedures, Tracked Vehicles and Tactical Wheeled Vehicles.

ENGINEERING PARTS LIST
8340039 - Vehicle, Armored Infantry, Full-Tracked, M59, Front Elevation.

SQAP INDEX
8340039 - Supplemental Quality Assurance Provisions.

(Copies of specification, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. - The following documents form a part of this specification. Unless otherwise indicated, the issue in effect on date of invitation for bids shall apply.

NATIONAL BUREAU OF STANDARDS
Handbook H28 - Screw-Threads Standards for Federal Service.

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington 25, D.C.)

3. REQUIREMENTS

3.1 Preproduction model. - When specified (see 6.2), a preproduction model of the complete vehicle shall be submitted to the Government for approval in

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:29Z
Check the source to verify that this is the current version before use.

conformance with applicable drawings, specifications, requirements and tests specified herein.

3.2 Materials. - Materials shall be as specified herein, and on the standards, specifications, and drawings listed or referred to in Engineering Parts List (EPL) 8340039. In addition to requirements shown on the drawings, all rubber items which are under tension or flexed in any manner shall be ozone-proofed to meet the "C" test requirements of Standard MIL-STD-417.

3.3 Construction. - Vehicles, components, sub-assemblies and assemblies shall be fabricated and assembled into a complete vehicle in accordance with drawings listed or referred to in EPL 8340039.

3.3.1 Screw threads. - All screws, bolts, nuts, and studs shall be threaded in accordance with Handbook H28.

3.3.2 Sealing and seals. - Sealer conforming to type II of Specification MIL-S-12158 shall be used for sealing of vehicle in accordance with the water sealing diagram drawing. The leakage of water into the hull shall be not more than 1 quart per minute with vehicle standing in water of insufficient depth to float vehicle for 30 minutes or with vehicle afloat in calm water for 30 minutes or longer. Seals shall exclude water and other foreign matter from bearings to the extent of contamination allowable in 3.5.6.

3.3.3 Winterization equipment. - When specified and installed (see 6.2), the winterization equipment shall assure satisfactory starting and vehicle operation in ambient temperature of minus 25° to 65°F.

3.3.4 Power plants. - Each power plant, consisting of engine, transmission, and cooling systems for engines and transmissions, when mounted on test stand unit shall operate as a complete unit for tests and engine tune up. The power plants shall operate satisfactorily throughout all gear and speed ranges without unusual noises, and lubrication, fuel, and cooling systems shall evidence no leaking.

3.3.4.1 Engines. - Each engine shall be of 6-cylinder, liquid-cooled, four-stroke-cycle, internal-combustion, spark ignition type; shall be equipped with all necessary accessories; and shall be of 145 gross horsepower rating. Engine governed speed with no load shall be set to operate at 3600 r.p.m. and with full load governor shall operate at 3400 r.p.m.

3.3.5 Power train. - The power train shall operate satisfactorily when operated through all gear and speed ranges without unusual noises and evidence no lubricant leaking.

3.3.6 Cooling systems.

3.3.6.1 Engine cooling. - Each engine cooling system shall maintain engine coolant at not more than 215°F. when operated in ambient temperature of 100°F. under full load.

3.3.6.2 Transmission lubricant cooling. - Built-in transmission (oil-to-water) lubricant cooling system shall maintain lubricant temperature in the sump, below 275°F. when operated in ambient temperature of 100°F., under full load; except stall or excessive braking.

3.3.6.3 Differential lubricant cooling. - Differential (oil-to-air) lubricant cooling shall maintain lubricant temperature at heat exchanger inlet, in the sump below 300°F. when operated in ambient temperature of 100°F., under full load; except stall or excessive braking.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:29Z
Check the source to verify that this is the current version before use.

3.3.7 Exhaust system. - The exhaust system shall to the maximum practicable extent prevent exhaust leakage into engine and crew compartments.

3.3.8 Fuel system. - The fuel system shall maintain fuel supply to the engines when ascending and descending 60 percent grades in forward and reverse gear and when vehicle is being operated on 30 percent side slope in ambient temperatures of minus 65° and plus 125°F.

3.3.8.1 Fuel tanks. - The fuel tanks shall be free of rust, scale, welding spatter, slag, and leaks.

3.3.8.2 Fuel lines. - Prior to final assembly the fuel lines shall be blown with high pressure dry air to expel all foreign matter and shall evidence no leaking.

3.3.9 Lights. - The lights as specified on applicable drawings shall operate satisfactorily through all vehicle operating conditions.

3.3.10 Adjustment mechanisms. - All the adjustment mechanisms shall function smoothly without interference and maintain adjustments during all operating conditions.

3.3.11 Controls. - All electrical, mechanical, and hydraulic controls shall operate with ease and without interference throughout all operating conditions.

3.3.12 Stowed equipment. - All on vehicle equipment (O.V.E.) items shall be stowed (combat loaded) on the vehicle in the spaces provided so that items will not interfere with the use and operation of vehicle and components in any manner (see 4.6.2).

3.3.13 Cupola. - Cupola shall be in conformance with MIL-C-45163.

3.3.14 Sighting devices. - Provisions shall be made for installation of 3 periscopes, drivers vision, M17 conforming to Specification MIL-P-13396; 1 periscope drivers IRM19 and 1 periscope sighting M28.

3.3.15 Welding. - Welding repairs shall be made only when, and to the extent, specifically authorized by the procuring activity.

3.3.16 Standard products. - Military standard products conforming to the following specifications shall be used within the indicated types or grades specified in table I. Specific applications by grades or types for various expected temperature ranges shall be as specified in production lubrication charts or other applicable drawings.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:29Z
Check the source to verify that this is the current version before use.

Table I. - Table of specifications covering Military standard products

Fuel, lubricants and Preservative Materials	Specification	Types or Grades
Corrosion Preventives on Lubricating	MIL-C-16173	Grade 1, 2, 3
Engine Oils:		
Operational and Preservative	MIL-L-21260	Grade 1, 2, 3
Subzero	MIL-L-10295	One Grade
Fuels:		
Gasoline, Combat	MIL-G-3056	Type I, II
Gasoline, Automotive	VV-M-561	Premium
Grease:		
Automotive and Artillery	MIL-G-10924	One Grade
Aircraft and Instrument	MIL-G-3278	One Grade
Hydraulic Oils:		
Fire Control	MIL-H-13919	One Grade
Preservative	MIL-O-6083	Type I
Lubricating Oils:		
Aircraft Instrument	MIL-L-6085	One Grade
Preservative, Medium	MIL-L-3150	One Grade
Preservative, Special	MIL-L-644	One Grade

3.3.17 Vision devices. - Vision blocks shall be in conformance to Specification MIL-B-11352.

3.4 Break-in run.

3.4.1 Preparation. - Prior to break-in run, the vehicle shall be completely assembled and adjustments completed. Vehicle including all components requiring lubricating, shall be lubricated and serviced with fuels and fluids conforming to specifications specified in table I. The engine governors shall be set to operate as specified in 3.3.4.1.

3.4.2 Oil pressure and temperature. - Prior to start of, or any time during break-in run after the engine(s) has been stopped for at least 30 minutes, engine shall be restarted and operated at 250 to 1000 r.p.m. until lubricating oil is at operating pressure and temperature.

3.4.3 Distance operated. - Prior to tests, each vehicle shall be given a break-in run on smooth, level, hard-surfaced roads; except a section of the road shall be Government approved undulating (bump) road. The vehicle shall be operated as specified in table II and over the undulating section in a and b division of break-in run in both directions for the purpose of observing the function and performance of various parts, assemblies, gun locks, controls, and the suspension system.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:29Z
Check the source to verify that this is the current version before use.

Table II. - Speeds and distances for break-in run

Division of run	Speed m.p.h.	Distance miles
a	0 to 10	3
b	11 to 20	5
c	21 to maximum	10

3.4.4 Reverse operation. - After each division of the break-in run, vehicle shall be stopped, the engine allowed to idle for not less than 2 minutes, and the vehicle driven in reverse for a distance of not less than 50 feet.

3.4.5 Condition after run. - After completion of the break-in run, the engine shall idle smoothly. Prior to vehicle being submitted to the Government for acceptance all suspension bearings shall be checked and readjusted if necessary. There shall be no defects indicative of damaged components, or maladjustments that may cause faulty vehicle operation.

3.5 Performance. - Vehicles, components, and special equipment, serviced with specified fuels, lubricants, grease, and fluids, and carrying intended or simulated load, shall perform as specified herein. Vehicle serviced and equipped for existing climatic conditions shall operate at temperatures of minus 25° to plus 100°F., without external aids; and down to minus 65°F., with external aids (see 3.3.3).

3.5.1 Speeds. - Vehicle shall operate at 25 m.p.h. for extended periods, and at 30 m.p.h. or more for short periods, on smooth, level, hard-surfaced roads, with transmission and controlled differential in high range. Vehicle shall operate at sustained speeds of no more than 4 m.p.h. on smooth, level, hard-surfaced roads. A speed of 6.5 m.p.h., shall be attainable in reverse gear. Speed in calm water shall be a minimum of 4 m.p.h.

3.5.2 Acceleration. - Vehicle shall accelerate from a standing start to 20 m.p.h., in not more than 20 seconds, on smooth, level, hard-surfaced roads.

3.5.3 Climbing. - Vehicle shall ascend and descend a 60 percent grade from a standing start on the grade in forward and reverse gear.

3.5.3.1 Engine starting on slopes. - Engines shall start with vehicle standing on a 60 percent grade, head-up-and-down-grade, and on side slopes up to 30 percent.

3.5.4 Braking.

3.5.4.1 Stopping. - Vehicle shall stop by service brake application within a distance of 55 feet from point of break application, when traveling at a speed of 20 m.p.h., on smooth, level, hard-surfaced roads free of loose material.

3.5.4.2 Holding. - Brakes shall hold vehicle stationary on a 60 percent grade, on all types of roads and terrains when brake levers are held or locked for parking.

3.5.5 Turning. - On a generally smooth, relatively level, hard surface, vehicle shall make continuous, full 360-degree turns, to right and to left, with midpoint of outer edge of outer track at all times in contact with or within a 50-foot diameter circle.

3.5.6 Water crossing. - Vehicle shall ford hard-bottom, salt or fresh water crossings of depths less than depth required to float vehicle. Combat loaded, the vehicle shall negotiate water of unlimited depth, with height of waves not exceeding 2 feet. After water operation there shall be not more than 2 percent contamination of lubricants, transmission, engine, accessories, final drives and the suspension system.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:29Z
Check the source to verify that this is the current version before use.

3.5.7 Trench crossing. - Vehicle shall cross trenches up to 66 inches wide.

3.5.8 Vertical obstacles. - Vehicle shall cross vertical obstacles up to 18 inches high when operated in forward and reverse gears.

3.5.9 Radio suppression. - Vehicle shall be radio interference suppressed in conformance to applicable provisions of Specification MIL-S-10379.

3.6 Painting and marking.

3.6.1 Painting. - The exterior and interior of vehicle, components, assemblies, sub-assemblies, and parts that require painting shall be prepared and painted in accordance with Drawing F6550295. Vehicle exterior paint and non-skid paint shall be olive drab matching color chip 24087 of Standard Federal STD NO. 595 (see 6.3).

3.6.2 Marking. - Vehicle marking shall be as specified by procuring activity.

3.6.3 Identification and data plates. - Identification and data plates shall conform to Specification MIL-P-13525.

3.7 Workmanship. - Workmanship shall be of a quality to assure vehicle free of defects resulting from improper manufacturing or assembly practices and shall conform to requirements and tests herein specified.

4. QUALITY ASSURANCE PROVISIONS

4.1 Contractor's inspection. - Except as otherwise specified herein, the contractor shall conduct and perform all inspection specified herein. The quality control requirements shall be in accordance with Specification MIL-G-14461.

4.2 Government inspection. - The Government shall witness the contractor's inspection (examination and tests) or verify the contractor's inspection records. Additional Government inspection within the scope of section 4 of the specification, necessary to assure conformance with Quality Assurance Provisions specified herein, shall be performed depending on quality of material presented by contractor for acceptance.

4.3 Preproduction sample. - A preproduction sample with simulated payload, shall be submitted for inspection and tests as specified in 3.1. Inspection shall be performed at the place of manufcature. Failure of the preproduction sample to comply with any of the requirements specified, shall be cause for refusal of the Government to conduct a retest until corrective measures satisfactory to the Government have been taken.

4.4 Sampling.

4.4.1 Lot size. - A lot shall consist of all vehicles of one type from an identifiable production period submitted at one time for inspection.

4.4.2 Sampling for inspection. - For the purpose of visual, dimensional and primary functional inspection, a representative sample shall be selected from each lot in accordance with inspection level II of Standard MIL-STD-105, **using the following table of classification of defects and acceptable quality levels.**

CHARACTERISTIC	MAJOR AQL 15 DEFECTS/100 UNITS	METHOD OF INSPECTION
1. Power plant	Malfunction-Unusual Noise, leaks, engine mounting improper, damage	Visual & Functional
2. Fuel system Components	Malfunction, damage, Leaks	Visual & Functional

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:29Z
Check the source to verify that this is the current version before use.

CHARACTERISTIC		MAJOR AQL 15 DEFECTS/100 UNITS	METHOD OF INSPECTION
3.	Oil lines, valves	Defective, Malfunction, Leaks	Visual & Functional
4.	Engine differential Transmission Cooling System	Malfunction, damage, Leaks	Visual
5.	Seals & Sealing	Damage, excessive leakage, contamination of lubricants, transmission, engine accessories, final drives and suspension system	Visual
6.	Water Crossing	Excessive leakage	Visual
7.	Lights	Malfunction	Visual & Functional
8.	Controls & adjusting mechanism	Malfunction, improper clearance	Visual & Functional
9.	Braking ability (Parking & Service)	Stopping distance or grade holding non-conformance, equalization, improper, unusual noise	Functional
10.	Turning & Steering Ability	Non-conformance, wander Unusual Noise	Functional
11.	Speed	Non-conformance	Functional
12.	Acceleration	Non-conformance	Functional
13.	Climbing	Non-conformance	Visual
14.	Engine starting on slopes	Non-conformance	Visual
15.	Vision & Sighting Devices	Malfunction, damage	Functional
16.	Cupola	Malfunction, damage	Visual & Functional
17.	Workmanship	Improper fastening of nuts, screws, bolts, washers, cotter pins, safety wires, chain & lock pins, wiring clips, ground straps, grommets, grease fittings, stripped threads and loose items	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:29Z
Check the source to verify that this is the current version before use.

CHARACTERISTIC	MINOR AQL 100 DEFECTS/100 UNITS	METHOD OF INSPECTION
101. Power plant	Improper component assembly or installation	Visual & Functional
102. Fuel System	Improper assembly or installation	Visual & Functional
103. Oil line valves	Improper assembly or installation	Visual & Functional
104. Engine, differential, transmission Cooling System	Improper assembly & installation	Visual & Functional
105. Lights	Malfunction, improper assembly & installation	Visual & Functional
106. Controls & Adjusting Mech-	Improper assembly & installation Malfunction	Visual Functional
107. Sealing & Seals	Improper assembly, malfunction & Installation	Visual
108. Paint	Improper application & color	Visual
109. Decals, Marking Data & Instruction Plates	Incomplete, data missing, improper location & size	Visual
110. Vision Devices	Improper Assembly & Installation	Functional
111. Exhaust System	Leakage, Damage	Visual
112. Workmanship	Loose nuts, & screws, bolts, washers, cotter pins, safety wires, chain & lock pins, wiring clips, ground straps, grommets, grease fittings, stripped threads, damaged, defective, improperly installed, binding & interference	Visual

4.4.3 Parts and components. - Parts, components, and assemblies shall be inspected in accordance with Supplemental Quality Assurance Provisions listed in SQAP INDEX 8340039.

4.5 Tests.

4.5.1 Performance. - After specified break-in run (see 3.4), vehicles shall be subjected to road and other performance tests as specified in table III. Vehicles shall be serviced with fuel, lubricants and fluids as specified in table I, but

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:29Z
Check the source to verify that this is the current version before use.

shall not be combat loaded for tests at place of manufacture. Prior to actual tests, engines shall be operated between 800 to 1200 r.p.m. to warm engine and lubricants to operating temperature. Operation of vehicles, unless otherwise indicated, shall be on smooth, leveel, hard-surfaced roads; except a section shall be of an approved undulating (bump) condition. Vehicle tests shall be conducted at location or locations shown in table III.

4.5.1.1 Eight-mile test. - Each vehicle shall be driven 8 miles or more. For this test vehicles shall be completely assembled and serviced, but need not be loaded to gross combat load weight. Operation shall be on smooth, level, hard-surfaced roads; except that the course shall include a section of approved undulating (bump) road intended to test functioning of suspension and shock absorbers. During this 8-mile test vehicle shall be subjected to all the tests specified in table III for place of manufacture. After the tests, vehicle shall be thoroughly examined for evidence of fuel or lubricant leakage, or other deficiencies.

Table III - Location of performance tests for Government acceptance

TITLE	TEST PARAGRAPH, NUMBER	PLACE OF MANUF.	GOV'T. PROVING GROUND
Road test - 8 Miles	4.5.1.1	X	-
Road test - 500 Miles	4.6.5	-	X
Maneuvering test	4.5.1.2	X	X
Speed test	4.5.1.3	X	X
Acceleration test	4.5.1.4	X	X
Climbing test	4.5.1.5	X	X
Engine starting	4.5.1.6	X	X
Braking test (stopping)	4.5.1.7	X	X
Braking test (holding)	4.5.1.8	X	X
Turning test	4.5.1.9	X	X
Water operation test	4.5.1.10	X	X
Trench-crossing test	4.5.1.11	-	X
Vertical-obstacle test	4.5.1.12	-	X
Cooling test	4.5.1.13	-	X

NOTE: "X" marks in the above table indicate where the tests are to be made.

4.5.1.2 Maneuvering tests. - Maneuverability of vehicle shall be in conformance to applicable test provisions of Specification MIL-V-3329.

4.5.1.3 Speed tests. - Each vehicle shall be operated at such speeds and under such conditions as to assure conformance to 3.5.1.

4.5.1.4 Acceleration test. - Vehicle shall be accelerated, to determine conformance to 3.5.2.

4.5.1.5 Climbing. - Vehicle shall be driven in forward and reverse gear up an approved 60 percent grade, to determine conformance with 3.5.3.

4.5.1.6 Engine starting. - Engine shall start on a 60 percent grade in accordance with 3.5.3.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:29Z
Check the source to verify that this is the current version before use.

4.5.1.7 Stopping test. - Results of three tests shall be averaged to assure conformance to 3.5.4.1.

4.5.1.8 Holding test. - Parking brakes shall hold vehicle with engine stopped for not less than 1 minute on an approved 60 percent grade to assure conformance to 3.5.4.2.

4.5.1.9 Turning tests. - Turning tests, to right and to left, shall be made to determine conformance to 3.5.5.

4.5.1.10 Water operation tests. - Vehicle shall be driven into and floated in, or operated in, water of sufficient depth to assure conformance to 3.5.6. Bilge pump shall be tested for operation.

4.5.1.11 Trench-crossing test. - Tests (see table III) shall be made to assure conformance to 3.5.7.

4.5.1.12 Vertical-obstacle test. - Tests (see table III) shall be made to assure conformance to 3.5.8.

4.5.1.13 Cooling-system tests. - One or more vehicles, selected from the first 10 submitted, shall be tested in a manner and under such conditions necessary to assure conformance to 3.3.6 through 3.3.6.3.

4.6 Control tests (see 6.2).

4.6.1 Frequency. - To determine conformance to 3.3.3 and 3.3.12, the first vehicle off the production line, or 1 of the first 10 vehicles produced; and thereafter 1 from each 100 shall be checked in accordance with paragraphs 4.6.2, 4.6.3 and 4.6.4.

4.6.2 Stowed equipment. - Vehicle selected in accordance with 4.6.1 shall be combat loaded with all on vehicle equipment stowed in their applicable spaces and vehicle and stowed equipment checked for completeness, functioning, and for interference with any other component.

4.6.3 Winterization equipment. - Vehicle selected in accordance with 4.6.1 shall have the winterization equipment installed and checked for completeness and function of equipment.

4.6.4 Radio suppression test. - To determine conformance to 3.5.9, vehicle selected in accordance with 4.6.1, shall be subjected to a suppression test.

4.6.5 Test failure. - If a vehicle fails to pass any tests specified herein, the Government inspector shall stop acceptance of subsequent lots until objective evidence has been provided by the contractor that corrective action has been taken.

4.6.6 Proving ground test. - One vehicle from the first 10 submitted for acceptance, and thereafter additional vehicles in accordance with a schedule specified by the procuring activity shall be selected by the Government inspector for proving ground tests; which shall include, but not be limited to, the tests specified in table II for Government proving ground.

5. PREPARATION FOR DELIVERY

5.1 Preparation for delivery and storage shall be in accordance with Specification MIL-P-45054.

6. NOTES

6.1 Intended use. - Vehicles covered by this specification are intended as armored infantry personnel carriers, and are adaptable for the following uses:

Cargo Carrier	Command Post Vehicles
Litter Carrier	Reconnaissance Vehicle

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:29Z
Check the source to verify that this is the current version before use.

6.2 Ordering data. - Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Preproduction sample if required (see 3.1).
(c) Winterization equipment and installation if required (see 3.3.3).
(d) Control test as required (see 4.6).

6.3 Color chips. - Until such time as the color chip of Standard FEDERAL STD NO. 595 is corrected, color number 2430 of Specification TT-C-595 should be used in lieu of color number 24087 (see 3.6.1).

6.4 Safety precautions. - Caution should be exercised in handling carbon dioxide fire-extinguisher cylinders. They should not be dropped, permitted to strike each other, or be handled roughly. Extreme care should be exercised during reinstallation to avoid tripping fire-extinguisher control system since physical injury is highly probable.

Notice. - This specification, together with specifications and drawings pertaining to it and bearing a "Notice" of similar restrictions, is intended for use only in connection with procurement by the United States Government; and shall not be reproduced either wholly or in part except when authorized in connection with Government procurement, nor be used for any other purpose except when specifically authorized by the Chief of Ordnance, Department of the Army.

Custodian:
Army - Ordnance Corps

Preparing Activity:
Army - Ordnance Corps

GPO 860971

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:29Z
Check the source to verify that this is the current version before use.