INCH-POUND

MIL-C-45150J
AMENDMENT 2
30 July 1992

SUPERCEDING
Amendment 1
23 Jun 1992

# MILITARY SPECIFICATION

## CHASSIS, TRAILER 2-WHEEL CART TYPE 1/4 TO 3 1/2 TON

This amendment forms a part of MIL-C-45150J, dated 17 September 1986, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

1.2: Add to table:

| | |
|---|---|
| "M116A2E1 | 3/4 TON |
| M116A3 | 1 Ton " |

PAGE 2

2.1.1: Delete "MIL-C-46164" and substitute "MIL-R-46164".

PAGE 3

2.1.1: Add parenthetical note:

"(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Navy Publication and Printing Service Office, Standardization Documents Order Desk, Bldg 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)"

2.1.2: Add to table:

| | |
|---|---|
| "8750204 | -Chassis, Trailer, 3/4 Ton, 2-Wheel, M116A2E1 |
| 8750253 | -Chassis, Trailer, 1 Ton, 2-Wheel, M116A3" |



AMSC N/A This document contains no deliverble data. FSC 2330
DISTRIBUTION STATEMENT A. Approved for public release: distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:27Z
Check the source to verify that this is the current version before use.

PAGE 5

3.3: Add to table:

| | |
|---|---|
| "8750240 | -M116A2E1 |
| 8750253 | -M116A3" |

PAGE 7

3.4, TABLE II: Add under the indicated headings:

| Chassis | Prime mover | Payload | Highway | Gravel roads | Cross-country |
|---|---|---|---|---|---|
| "M116A2E1 | CUCV | 2420 | 50 | 35 | 15 |
| M116A3 | HMMWV | 2360 | 50 | 35 | 15" |

PAGE 11

3.5.1: Delete in its entirety and substitute:

"3.5.1 Painting. Unless otherwise specified (see 6.2), chassis, components assemblies, and parts which require painting shall be prepared and painted with a chemical agent resistant coating (CARC) in accordance with MIL-STD-193. The materials used for the specific service, as specified in MIL-STD-193, shall match the specified color chip of FED-STD-595. When specified (see 6.2), camouflage pattern shall conform to the pattern stipulated (see 4.8.1, 4.8.2, and 4.8.5)."

3.5.2, Line 2: Delete "MIL-C-46164" and substitute "MIL-R-46164".

PAGE 14

Table IV: Add "X"'s in QCI column so that it is identical to the FPCI column.

PAGE 15

Table IV, line 2, under "Treatment and painting" in inspection column: Add "4.8.5", and place "X" under FPCE, IPT, QCI, and control columns.

PAGE 16

4.4: Delete and substitute:

"4.4 Quality conformance inspection (QCI). QCI shall be performed utilizing and approved Final Inspection Record (FIR). To determine conformance to applicable drawings and section 3 requirements, visual, dimensional, and primary functional examination shall be performed on each chassis for defects specified in Table V. These examinations shall be performed during all phases of manufacturing and subsequent to road test (see 4.4.4)."

Source: https://assist.dla.mil -- Downloaded: 202640-22T02:27Z
Check the source to verify that this is the current version before use.

PAGE 17

Table V: Add "118 Improper paint, compounding/curing adhesion, thickness, Functional".

PAGE 19

4.4.4: Delete and substitute:

"4.4.4 Road test. Chassis shall be completely assembled, serviced, and operated for a distance of not less than 5 miles, without payload, by the contractor. Performance of chassis shall be demonstrated on relatively smooth, hard-surfaced roads. After completion of 5 mile road test, chassis shall be examined for leaks, brake adjustments, and any other deficiencies. NOTE: If sampling for QCI (see 4.4.2.1.2) is authorized, road test will not be waived, but will be performed on every chassis by contractor for safety purposes."'

4.5: Delete in its entirety and substitute:

"4.5 Control test.

4.5.1 Frequency. The Government shall select at random, one production vehicle per month as a minimum or one out of each 100 vehicles produced per month, but not more than two in any given 30 day period. Contractor shall conduct a 50 mile road test on each vehicle selected.

4.5.2 Fifty mile test. Chassis shall be loaded with full or simulated payload, operated for a distance of 50 miles, and subjected to all control tests specified in table IV. These tests shall be performed at the place of manufacture by the contractor. The test course shall be a relatively smooth, level, hard surfaced road.

4.5.3 Test failure. If the chassis fails to pass any control test, the Government shall stop acceptance examination ant testing on subsequent vehicles until all conditions causing the failure have been remedied. Any defect found during or as a result of the test shall be prima facie evidence that chassis accepted subsequent to the previously accepted control test chassis are similarly defective, unless evidence satisfactory to the contracting officer is furnished by the contractor that they are not similarly defective. Such defects on all chassis shall be corrected by the contractor at no cost to the Government. Another chassis, with corrective actions implemented, shall be subjected to the control test."



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:27Z
Check the source to verify that this is the current version before use.

PAGE 21

Add as new paragraph 4.8.5:

"4.8.5 Paint adhesion. Unless otherwise specified (see 6.2), the paint adhesion test of MIL-STD-193 shall be used to determine conformance to 3.5.1."

5. Delete and substitute:

"5. PREPARATION FOR DELIVERY.

5.1 Preservation, packaging, packing, and marking. Preservation, packaging, packing, and marking for the desired level shall be in accordance with the applicable packaging requirements and MIL-V-62038, as specified by the contracting authority (see 6.2)."

PAGE 22

6.2o: Delete and substitute:

"o. Selection of applicable level and packaging requirements (see 5.1)."

6.2 Add as new paragraph 6.2p:

"p. If paint adhesion test is other than as specified (see 4.8.5)."

Custodians:
Army - AT
Navy - MC

User activities:
Army - ME
Navy - CG

Preparing activity:
Army - AT

(Project 2330-0127)



Source: https://assist.dla.mil -- Downloaded: 202610-22T02:27Z
Check the source to verify that this is the current version before use.