MIL-T-45169D(AL)
19 February 1989
SUPERSEDING
MIL-T-45169C(AL)
13 June 1983

MILITARY SPECIFICATION

TANK, PRESSURE, AIR, PORTABLE

This specification is approved for use by all Department and Agencies of the Department of Defense

1. SCOPE

1.1 Scope. This specification covers a portable air pressure tank for the retention, conveyance, and dispensing of compressed air.

2. APPLICABLE DOCUMENTS

2.1 Specifications, standards, and handbooks. Unless otherwise specified, the following specifications, standards, and handbooks of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

PPP-B-601	- Boxes, Wood, Cleated Plywood
PPP-B-621	- Box, Wood, Nailed and Lock Corner
PPP-B-665	- Boxes: Paperboard, Metal Edged and Components
PPP-C-843	- Cushioning Material, Cellulosic
PPP-F-320	- Fiberboard: Corrugated and Solid, Sheet Stock (Container Grade) and Cut Shapes
PPP-T-60	- Tape, Packaging, Waterproof

MILITARY

MIL-P-116	- Preservation, Methods of
MIL-C-5501	- Cap and Plug, Protective, Dust and Moisture Seal

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research, Development and Engineering Center, ATTN: SMCAR-EST-S, Rock Island, IL 61299-7300 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 4940

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:29Z
Check the source to verify that this is the current version before use.

STANDARDS

FEDERAL

FED-STD-H28 - Screw-Thread Standards For Federal Services

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking For Shipment and Storage
MIL-STD-130 - Identification Marking of US Military Property
MIL-STD-889 - Dissimilar Metals
MIL-STD-1186 - Cushioning, Anchoring, Bracing, Blocking and Waterproofing; With Appropriate Test Methods
MIL-STD-1189 - Standard Department of Bar Code Symbology
MIL-STD-1190 - Minimum Guidelines for Level C Preservation, Packing and Marking

2.2 Other Government documents and publications. The following other Government documents and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

US DEPARTMENT OF LABOR

29 Code of Federal Regulation (CFR), Chapter XVII, Parts 1900 to 1910 - Occupational Safety and Health Standards Act (OSHA)

(Copies of specifications, standards, handbooks, drawings, and publications required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.

(Industry association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal Agencies.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection (see 4.3 and 6.2.1).

3.2 Design. The tank shall be of the latest standard commercial design meeting the performance requirements specified herein. The tank shall be a steel fabricated, cylindrically shaped, portable, hand-carried tank that retains compressed air of a known pressure. Facilities shall be provided to fill the tank by the injection of compressed air from an air supply source and to dispense the air from the tank through an air hose and air chuck. all parts subject to wear, breakage, or distortion shall be accessible for adjustment, repair, or replacement.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:29Z
Check the source to verify that this is the current version before use.

3.2.1 Threads. The design, manufacture and configuration of threads shall be examined and inspected to conform with FED-STD-H28 and the applicable detailed standards referenced therein. No testing in FED-STD-H28 shall be required.

3.3 Material. Materials not specifically designated herein or in the contract shall be of a quality commensurate with best commercial practices, shall be suitable for the intended purpose in the design and fabrication of the Portable Air Pressure Tank, and shall meet all requirements specified herein. Materials shall be free form defects which would affect the performance, maintainability, reliability, durability, or longevity of the individual components or the Portable Air Pressure Tank itself. When dissimilar metals are used in contact with each other, suitable protection against galvanic corrosion shall be applied in accordance with MIL-STD-889.

3.3.1 Reclaimed materials. The contractor is encouraged to use reclaimed materials for fabricating new parts without jeopardizing the chemical and physical properties, design integrity and intent of the materials originally selected or specified. The reclaimed materials shall have been reprocessed, remanufactured, or recycled in a manner that shall restore them to the same chemical composition and physical properties as the materials originally selected for use. It shall not be permissible to use reclaimed parts as is, or rebuilt from scrap or other used equipment. Reclaimed parts shall not be used in the equipment.

3.4 Construction. The portable air pressure tank shall be constructed of parts which are new, without defects and free of repairs, sharp edges and burrs. The pressure tank shall withstand all forces encountered during operation in its intended environment, to the pressure tanks maximum rating and capacity, without deformation or degradation.

3.4.1 Welding, brazing, and soldering. All welding, brazing and soldering shall be free of defects and of a quality which shall sustain all requirements of the welded, brazed or soldered parts. Defects shall include but are not limited to such things as bubbles, cracks, holes, insufficient material used, etc.. All flux or other such materials used during these operations shall be thoroughly removed (cleaned), from the part(s) immediately upon completion of the operation. These operation shall not be employed as repair measures for defective parts.

3.4.2 Fastening devices. All screws, pins, bolts, and similar parts shall be installed in the portable air pressure tank with means for preventing loss of tightness. All such parts, when subject to removal or adjustment, shall not be swaged, peened, staked, or otherwise permanently deformed.

3.4.3 Safety and health requirements. Safety devices shall be provided for all parts presenting safety hazards which can be guarded without substantial interference to operation of the tank. All guards shall be removable to provide easy access to guarded parts. Except as otherwise specified by the procuring activity, the tank shall comply with the standards promulgated under Title 29, Code of Federal Regulations (CFR); applicable to the tank itself. Exceptions and additional requirements for safety and health shall be as specified (see 6.2.1 and 6.4).

3.4.4 Mercury restriction. The tank shall not contain mercury or mercury compounds nor be exposed to free mercury during manufacture.

3.4.5 Asbestos restriction. Asbestos and materials containing asbestos shall not be used on or in the tank.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:29Z
Check the source to verify that this is the current version before use.

3.5 Performance and product characteristics.

3.5.1 Functional requirements. The tank shall be a horizontal portable unit capable of being conveyed by one operator. The tank shall retain compressed air at the working pressure specified in 3.5.2 and shall include standard means for filling the tank and for dispensing the compressed air from the tank.

3.5.2 Pressure. The tank shall operate at a working pressure of 150 pound per square inch gage (psig).

3.5.3 Safety factor requirement. The portable air pressure tank itself shall be subjected to a hydrostatic pressure of not less than 600 psig for a period of not less than one (1) minute without distortion, degradation, or leakage. After this hydrostatic pressure requirement is completed, attach safety pressure relief valve (see 3.6.5).

3.5.4 Capacity. The tank shall have a volumetric capacity of not less than 8.5 gallons.

3.5.5 Diameter, length and weight. The tank assembly shall have an outside diameter (O.D.) of not more than twelve (12) inches. The tank assembly shall have an overall length (less air hose) of not more than 30 inches. The total weight of the tank assembly shall not exceed 42 pounds.

3.6 Details of components.

3.6.1 Air tank. The air tank shall be cylindrical in shape and fabricated of steel not less than Manufacturer's Standard Gage No. 13. The cylindrical axis of the tank shall remain in a steady, horizontal position when placed on a level surface. The tank shall have an attached, fabricated, carrying handle(s) providing a full hand grip for lifting and conveying the complete air pressure tank unit.

3.6.2 Filler valve. The tank shall be fitted with a filler valve to permit injection of compressed air into the tank from the air source. The valve shall permit filling the tank utilizing an air chuck of the size specified in 3.6.4. The valve shall be depressed when subjected to the air chuck to permit free passage of air into the tank. Upon removal of the chuck, the valve shall automatically close. The valve shall comply with the pressure requirements specified in 3.5.2.

3.6.3 Air pressure gage. The tank shall include an air hose not less than 2-1/2 feet in length with not less than 1/4 (.25) inch and not more than 3/8 (.38) inch inside diameter (I.D.). The air hose shall have 200 psi maximum working pressure with 800 psi burst pressure and shall be oil and grease resistant. The hose shall be fitted to the tank mounted coupling with a male 1/4-18 or 3/8-18 NPT quick disconnect coupling. Dial scale increments shall not be more than 20 psi, with numerical markings not exceeding 50 psi intervals. Dial background and increments shall be in contrasting color. Gage location shall permit observation of the gage reading during filling of the portable air tank. The gage crystal shall be either glass or clear plastic with a minimum thickness of 1/16 inch.

3.6.4 Air hose and air chuck. The tank shall include an air hose not less than 2 and 1/2 feet in length with 1/4-inch minimum and 3/8-inch maximum inside diameter. The hose shall be oil and grease resistant. The hose shall be fitted to the tank with a male tapered pipe thread coupling. The free end of the hose shall be fitted with a ball foot air chuck. The air chuck shall be suitable for use with tire

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:29Z
Check the source to verify that this is the current version before use.

valves employing standard threads (0.302-32). The chuck shall fit over the tire valve mouth with the chuck deflator pin tripping (depressing) the valve core and permitting a flow of air from the tank into the tire. Upon removal of the chuck from the tire valve, the chuck shall automatically close, stopping the flow of air from the tank. The coupling and chuck shall be able to withstand 400 psig proof pressure without such damage as bulging, coupling or chuck separation, leakage, splitting, bursting, or deformation.

3.6.5 Safety valve. The tank shall be fitted with a safety pressure relief valve. The safety pressure relief valve shall release the pressure in the tank when the pressure in the tank is not less than 152 psig and not more than 162 psig. The safety pressure relief valve shall be automatically reset itself to the position at a pressure of not less than 150 psig.

3.7 Painting. Unless otherwise specified (see 6.2.1), painting and finishing of the tank shall be in accordance with standard commercial practice provided the following minimum criteria are met or exceeded: All surfaces to be painted shall have been cleaned to be free of all foreign matter detrimental to painting, and at least one coat of primer and one coat of enamel, or equivalent, applied.

3.8 Product identification. The tank shall be marked for product identification in accordance with MIL-STD-130 and, unless otherwise specified (see 6.2.1), shall include the National Stock Number.

3.9 Safety precaution decal. A decal, permanently and legibly marked with safety precautions and basic operating restrictions, shall be securely affixed to the tank near the air pressure gage.

3.10 Workmanship. Standards of workmanship shall assure that the air pressure tank shall have the safety, stability, and efficient operating characteristics found in standard commercial units and as specified in Section 3 herein.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specifications where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of Sections 3 and 5. The inspections set forth in this specification shall become part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the government for acceptance comply with all requirements of the contract. Sampling of quality conformance does not authorize submission of known defective material either indicated or actual, nor does it commit the government to acceptance of defective material.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:29Z
Check the source to verify that this is the current version before use.

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article inspection. When specified in the contract or purchase order, first article inspection shall be applied to the preproduction model or initial production item (see 3.1). Unless otherwise specified (see 6.2.1), first article inspection shall consist of the examinations in 4.5 and all tests under 4.6. Failure of the first article to pass an examination or any of the tests shall be cause for rejection.

4.4 Quality conformance inspection. Quality conformance inspection shall be applied to production units being offered for acceptance under the contract. The inspection shall consist of a., b., and c. as follows and failure of any unit to pass these inspections or tests shall be cause for rejection of the unit.

a. Product examination (see 4.5).
b. Tests (see 4.6).
c. Packaging inspection (see 4.7).

4.4.1 Sampling. Sampling for quality conformance inspection shall be in accordance with MIL-STD-105 using the following:

Inspection or Test	Inspection Level	AQL
Product examination (4.5)	II	1.0
Pressure gage accuracy test (4.6.3)	II	1.0
Performance test (4.6.6)	II	1.0
Packaging inspection (4.7)	S-4	4.0

All other tests under 4.6 shall be performed on each item offered for acceptance. For purposes of quality conformance inspection, lot size shall be no more than 150 air tanks.

4.5 Product examination. Visually, dimensionally and manually examine the air tank to determine conformance with the requirements of 3.2 through 3.4.5, 3.6.1, through 3.6.4, and 3.7 through 3.10. Visual examination shall include verification of completeness of manufacture, conformance to specified standards, adequacy of markings, proper cleaning, and freedom from identified defects. Dimensional examinations shall include all dimensions specified in 3.5.5 and 3.6.4. Manual examination shall include the operation of movable parts by hand to assure proper functioning. The examination provisions may be applied at the earliest practical point in manufacture at which it is feasible to inspect for acceptance without risk of change in the characteristic by subsequent operations. Failure of the contractor to provide objective evidence that the air tank has passed the examinations prescribed for it by the contractor's inspection system shall be cause for rejection.

4.6 Tests.

4.6.1 Order of testing. The safety factor requirement test (4.6.2), shall be performed before installing the pressure gage and safety valve. The pressure gage accuracy test (4.6.3), and the safety valve test (4.6.4), shall be conducted after installation of these items. The air hose pressure test (4.6.5), shall be conducted before assembling the air hose, coupling and air chuck to the tank. The performance test (4.6.6) shall be the last test conducted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:29Z
Check the source to verify that this is the current version before use.

4.6.2 Safety factor requirement test. This test shall be performed on each unit offered for acceptance. The pressure gage and safety valve holes shall be plugged for this test. The tank shall be subjected to an internal hydrostatic pressure of not less than 600 psig for not less than one minute. Evidence of any distortion of the tank, or any leakage from the tank, welded seams or fittings shall be cause for rejection (3.5.3).

4.6.3 Pressure gage accuracy test. The air pressure gage shall be tested for accuracy at every numerical marking from zero to, and including, the 150 mark with a measuring device having an accuracy within 0.5 psig of the value being measured. Failure of the gage to indicate the correct pressure within plus/minus 5 psig shall be cause for rejection (3.6.3).

4.6.4 Safety pressure relief valve test. This test shall be performed on each unit offered for acceptance. A measuring device having an accuracy within 0.3 psig of the value being measured shall be used as reference for this test. The air pressure in the tank shall be gradually increased until the safety pressure relief valve releases. Air flow into the tank shall then be stopped. The pressure at which the safety pressure relief valve opens and closes shall be noted. Failure of the safety pressure relief valve to open in the range of 152 to 162 psig, or failure to close at no less than 150 psig shall be cause for rejection (3.6.5).

4.6.5 Air hose pressure test. This test shall be performed on each unit offered for acceptance. The air hose, complete with its coupling and air chuck, shall be subjected for a minimum of five seconds, to a proof pressure test of not less than 400 psig. The hose shall be observed during the test. Failure of the test as evidenced by leakage, bulging, splitting, bursting, deformation, or coupling or chuck separation, shall be cause for rejection (3.6.4).

4.6.6 Performance test. The tank shall be filled with air to a pressure of 150 plus/minus 3 psig. The tank and its hose shall be used to inflate a fully deflated tire having a valve stem with standard thread (0.302-32). Leakage of air from the tank, hose, or connections during the filling or inflating operation; instability of the tank while on a level surface; inability of the operator to read the pressure gage while inflating the tire; or failure of the chuck valve to completely stop the flow of air when the chuck is removed from the tire, shall be cause for rejection (3.5.1 through 3.6.4).

4.7 Packaging inspection. The items shall be inspected before and after packaging to determine compliance with the preservation, packaging, packing, and marking requirements specified in Section 5.

5. PACKAGING.

5.1 Preservation. Preservation shall be Level A or Level C, as specified (see 6.2.1).

5.1.1 Level A.

5.1.1.1 Cleaning and drying. Components and the complete tank shall be cleaned and dried in accordance with the procedures of MIL-P-116.

5.1.1.2 Preservative application. Immediately after cleaning and drying, apply a coat of type P-1 or P-19 preservative to all exterior ferrous metal surfaces of the tank that have not been painted or plated. The interior surface of the pressure tank shall be fogged with preservative oil P-10, grade 30, of MIL-P-116.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:29Z
Check the source to verify that this is the current version before use.

5.1.1.3 Unit packs. The unit method of protection for the basic tank shall conform to method I of MIL-P-116. The gage crystal shall be covered with a piece of fiberboard conforming to PPP-F-320, type CF, class weather-resistant, variety SW, grade optional. Secure the fiberboard in place with tape conforming to PPP-T-60, type optional. The pressure gage, filler valve, air hose, and safety valve shall be disassembled from the basic unit. Wrap each disassembled part with cushioning material conforming to PPP-C-843, type II and individually package in accordance with method IC-1 of MIL-P-116. Place the packaged components in a box conforming to PPP-B-636, class 2, or PPP-B-636, class weather-resistant. Seal all openings in the pressure tank with tape or plastic cap-plugs conforming to PPP-T-60, type IV, or MIL-C-5501, respectively. Place the tank and packaged components in a fiberboard box conforming to PPP-B-636, class weather-resistant. The tank shall be braced inside the unit container with fiberboard of PPP-F-320 formed into pads or cut shapes. Any technical publications furnished shall be packaged in accordance with method IC-1 and placed inside the unit container.

5.1.2 Level C. Level C preservation and packaging shall be as specified in MIL-STD-1190.

5.2 Packing. Packing shall be Level A, B or C, as specified (see 6.2.1).

5.2.1 Level A. Pressure tanks shall be packed in exterior shipping containers conforming to PPP-B-621, class 2, or PPP-B-601, overseas type. The weight of each shipping container shall not exceed the weight limitations of the applicable box specification. As far as practicable, containers shall be uniform in size and contain like quantities. Blocking, bracing, anchoring and cushioning shall be in accordance with MIL-STD-1186.

5.5.2 Level B. Level B packing shall be the same as Level A except that domestic containers shall be used in lieu of overseas containers.

5.2.3 Level C. Level C packing shall be as specified in MIL-STD-1190.

5.3 Marking. All interior packages and exterior shipping containers shall be marked in accordance with MIL-STD-129. Bar code markings are required and shall be applied in accordance with MIL-STD-129 and MIL-STD-1189.

6. NOTES

6.1 Intended use. The portable air pressure tank covered by this specification is intended to be used by a single operator for inflating vehicle tires.

6.2 Ordering data.

6.2.1 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.
b. First article when required (see 3.1).
c. Special safety devices, when required (see 3.4.3 and 6.4).
d. Painting if different (see 3.7).
e. First article, if different (see 4.3).
f. Identification marking if different (see 3.8).
g. Preservation, packing, and marking as required (see 5.1, 5.2, and 5.3 respectively).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:29Z
Check the source to verify that this is the current version before use.

6.2.2 Contract data requirements. Required technical data such as operator's manuals, parts lists, and other instructions for operations and maintenance, as identified on a numbered DD Form 1664, should be specified on a DD Form 1423 incorporated in the contract.

6.3 Subject term (key word) listing.

AMSC number
Design
First article
First article inspection
Materials
Ordering data
Performance
Protective finish
Scope

6.4 Safety and health determination. In order that equipment integrated into the user's operational environment will comply with OSHA limitation and control of noise levels, radiation electromagnetic emission, noxious vapors, heat, etc., as applicable, specific requirements concerning guarding the point(s) of operation, and other safety and health requirements should be specified by the user/requisitioner (see 6.2.1).

6.5 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of changes.

Custodian:
Army - AL

Preparing activity:
Army - AL

Review activity:
Army - SM

Project No. 4940-A569

User activity:
Army - ME

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:29Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Armament Munitions and Chemical command
Armament Research and Development Center (ARDC)
ATTN: SMCAR-est-S
Rock Island, Il 61299-7300

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:29Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-T-45169 D	

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:29Z
Check the source to verify that this is the current version before use.