MIL-F-45133B(Ord)
18 January 1962
SUPERSEDING
MIL-F-45133A(Ord)
8 June 1959

MILITARY SPECIFICATION

FIRE CONTROL COMPONENTS AND ASSEMBLIES

1. SCOPE

1.1 Scope. - This specification covers requirements for the procurement of components and assemblies used in fire control materiel, which are not otherwise covered by a detail specification.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of Invitation for Bids, form a part of this specification to the extent specified herein:

SPECIFICATIONS

Military

MIL-I-45208	Inspection Requirements General Specification for

STANDARDS

Military

MIL-STD-10	Surface Roughness Waviness and Lay
MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-1242	Machining Standards for Fire Control Materiel

OTHER DOCUMENTS

ORD CORPS	All documents contained in Invitation for Bid, Request for Proposal, Contract or other procurement document.

FSC
GROUP 12

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:25Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards and drawings required by contractors in connection with specific procurement functions should be obtained from the procuring activity, or as directed by the contracting officer)

2.2 Other publications.- The following publication forms a part of this specification insofar as the contract may require the supply of threaded components. Unless otherwise indicated in the contract, the issue in effect on date of Invitation for Bids shall apply.

NATIONAL BUREAU OF STANDARDS PUBLICATIONS

Handbook H28	Screw-Thread Standards for Federal Services

(Application for copies should be addressed to Superintendent of Documents, Government Printing Office, Washington 25, D. C.)

3. REQUIREMENTS

3.1 Detailed requirements. - Detailed requirements shall be as specified on pertinent drawings and specifications referenced in the contract.

3.2 Order of precedence. - Should any conflict exist between the contract, the drawings, or any applicable specification, the order of precedence shall be as follows:

a. Contract, except technical data incorporated by reference

b. Detail Drawings

c. SQAP for Components

d. Assembly Drawings

e. SQAP for Assembly Drawings

f. This Specification

g. Detailed Specifications and Standards for Parts, Materials and Processes

3.3 Dimensions and tolerances. - The contractor shall adhere to the dimensions and tolerances on the drawings; and in no case shall the drawing be scaled. Tolerances for flatness, perpendicularity, parallelism, concentricity and other machining requirements for components, where not specified on the drawing, shall be in accordance with Standard MIL-STD-1242(Ord).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:25Z
Check the source to verify that this is the current version before use.

Should additional dimensions and tolerances be required, application therefore shall be made through the Contracting Officer. Where dimensional tolerances are not indicated on the drawings by either a general tolerance note, or by specific tolerance limits, and the contractor had not applied for clarification prior to contract award, tolerances will be determined by the Government based upon essential functional and assembly requirements.

3.3.1 Tolerances. - Tolerances specified on drawings have been selected for maximum producibility consistent with the intended function and level of interchangeability desired. In general, tolerances have been selected with the intent that no functional interferences will exist, and that all functional requirements will be met within the limits selected. Where this was found to result in impractical tolerances, selection of tolerances was made on the basis of probability that the accumulated buildup will be equal to the square root of the sum of the squares of the individual tolerances. Reasonable precautions shall be taken by the contractor to insure that manufacturing processes assure normal statistical distribution within specified tolerances.

3.3.2 Assembly functional or performance requirements. - Where functions or performance requirements of an assembly are specified on drawings, these requirements shall take precedence over the pertinent component dimensional tolerances upon which such requirements are dependent. It shall be the contractor's responsibility to insure that maximum tolerances are not permitted to accumulate so as to result in assembly difficulties or unacceptable performance of the assembly.

3.3.3 Incompatibility of requirements. - The provisions of 3.3.2 shall not be construed as authorization to deviate in any manner from the dimensional limits imposed by applicable Government drawings. A dimensional incompatibility will be said to exist only if the component cannot be made to assemble or function properly even if manufactured to the most advantageous size within the specified tolerance range; or conversely, if, in order to assemble and function properly, the part cannot be manufactured so as to meet the detailed drawing requirements. If, under these criteria, an incompatibility is found to exist between functional or performance requirements and the detailed drawings, the Government shall be expeditiously advised in order that appropriate corrective action can be taken.

3.3.4 Screw threads. - Unified and American National Standard threads shall conform with dimensions and tolerances specified in Handbook H28. Where National Standard threads are specified on drawings for nuts, bolts, and screws, the Unified or American National Standard thread of the same pitch and class of fit may be substituted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:25Z
Check the source to verify that this is the current version before use.

3.4 Machine finish.- Where letter symbols for roughness designation of machined finishes are specified on Ordnance drawings, maximum roughness height rating as defined in Standard MIL-STD-10 shall be in accordance with Table I.

TABLE I- SURFACE ROUGHNESS CONVERSION VALUES

Letter Symbol		Roughness Height Rating
lap	-	8
fg	-	16
ff	-	32
f	-	63
cf	-	250
g	-	500

3.5 Inorganic protective surface finishes. - Unless otherwise specified on the pertinent drawing, dimensions and roughness height ratings for finished surfaces shall include inorganic protective finish or plating. The contractor shall be responsible for controlling finish thickness and initial machine finish so that the dimensions of the final finished product shall fall within the tolerances and roughness ratings indicated on drawings. Protective finish may be omitted or removed from tapped holes smaller than 0.250 inch major diameter.

3.6 Commercial quality. - Parts and materials specified as "commercial quality" or specified by merely a name in general commercial use, such as "steel", "forged steel", "bronze", "cast iron", "brass", "drill rod", "leather" and "wood", shall be as used in first-class commercial constructions, free from any defect that would render them unsuited for normal commercial use.

3.7 Electrical and electronic assemblies

3.7.1 Electron tubes. - Each assembly that is procured with electron tubes shall be furnished with the same tubes used when the assembly was tested. Unless separate packaging of tubes is specified, they shall remain in the respective sockets occupied during the tests.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:25Z
Check the source to verify that this is the current version before use.

3.7.2 Insulation resistance. - Unless otherwise specified, the insulation resistance between ungrounded electrical circuits and the body or frame of individual units and between isolated circuits shall be not less than 10 megohms at a DC potential of 800 volts.

3.8 Part identification and marking.

3.8.1 Marking information. - Parts shall be individually marked with the applicable identifying number except the following:

a. Parts which do not have suitable or sufficient surface, as determined by the Contracting Officer.

b. Unmodified commercial items.

c. Components of inseparable assemblies which are permanently brazed, welded, molded, riveted, nailed, sewn, glued, or bonded.

3.8.2 Method of application. - Whenever possible, the marking shall be applied to the surface of the part by a steel stamp, acid or electric etching, engraving, branding, embossing, casting or molding. When these methods are certified by the contractor to be impossible or impractical, the marking shall be applied by rubber stamp, stencil, silk screen, decalcomania transfer or metal wrap-around tag. Marking shall be accomplished in a manner which will not adversely affect the life and utility of the part. The marking shall be as permanent as the normal life expectancy of the part and shall be capable of withstanding the same environmental tests required of the part.

3.9 Workmanship. - Workmanship shall be of a quality consistent with the highest existing instrument production standards and practices. All finished surfaces shall be protected against corrosion or damage during manufacture prior to delivery. All fins and other excess material shall be removed from castings and forgings. All surfaces, including threads, shall be free from burrs and sharp edges. All material shall be sound, of uniform quality and condition, and free from seams, cracks, and other defects which may adversely affect the strength, endurance, or wear resistance of the part. Any material which has been treated in any manner to conceal defects therein, shall not be offered for Government acceptance. Welding or other means for the repair of defects in materials shall not be performed unless specifically authorized by the Contracting Officer.

3.9.1 Rivets. - Riveted parts shall be tight and undamaged. Rivet heads shall be seated firmly against their surface. Loose, cracked, or badly formed rivets, including protruding countersunk rivet heads, will not be acceptable. Excess metal shall be removed from countersunk head rivets.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:25Z
Check the source to verify that this is the current version before use.

3.9.1.1 Ferrous rivets. - When riveting is to be accomplished by the pressure method, ferrous rivets 3/8 inch diameter and smaller may be driven cold. Ferrous rivets larger than 3/8 inch diameter shall be driven hot unless special authorization is otherwise granted by the Contracting Officer.

3.9.1.2 Non-ferrous rivets. - Non-ferrous rivets shall be driven cold. Age-hardened aluminum-alloy shall be driven by heavy blows or high pressure to avoid hardening of the surface before the head is formed and the hole completely filled. Quenched or refrigerated aluminum-alloy rivets shall be driven in accordance with recommended commercial practice.

3.9.2 Cleaning. - All interior parts and bearing surfaces of items shall be thoroughly cleaned, dried, and free of dust, burrs, chips, and grinding compound before lubrication or assembly. Grinding compounds which may impregnate or adversely affect the specified finish shall not be used. Completed metal parts shall be cleaned in accordance with good commercial practice, except where specific techniques are required by applicable documents. Cleaning process shall have no visible or latent deleterious effect on the items. After assembly, (or before assembly if necessary) components shall be cleaned thoroughly and shall be free from particles of solder, flux, and other foreign material.

3.9.3 Welding and brazing.

3.9.3.1 Welding.- Parts to be welded shall be clean, free from rust, scale, corrosion, oil, and other foreign substances before welding operations are performed. Welds shall show good fusion without overlapping, burning, or undercutting and shall be stress relieved.

3.9.3.2 Brazing.- Surfaces of parts to be brazed shall be clean and free of all grease, oil, dirt, oxides, and other foreign substances before the brazing operation is performed. The finished brazed joint shall show visual evidence of soundness by exhibiting a uniform distribution of the specified filler metal by capillary action.

3.9.4 Soldering of electrical joints. - Soldered electrical connections shall be neat. There shall be no sharp points or rough surfaces resulting from insufficient heating. The solder shall feather out to a thin edge, indicating proper flowing and wetting action, and shall not be crystallized, overheated, or underheated. Corrosive fluxes shall not be used. The minimum necessary amount of flux and solder shall be used for electrical connections, resulting in visible wire contour for the finished joint. Material subjected to heating during the soldering operation shall be undamaged and parts fastened thereto shall not become loosened. The connection shall not depend on the solder for mechanical strength. At the point where wires are terminated by soldering, the wires shall be hooked, wrapped around or otherwise mechanically secured to the terminals prior to soldering.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:25Z
Check the source to verify that this is the current version before use.

3.9.4.1 Tinning. - The leads of all untinned wires shall be tinned prior to soldering to a distance of 1/16 inch from the point of egress of the lead from the body of the terminal or component unless otherwise specified.

3.9.5 Bonded joints. - Cemented and bonded joints shall be processed in accordance with recommended practice of the material manufacturer unless specific techniques are prescribed on drawings or referenced specification.

4. QUALITY ASSURANCE PROVISIONS

4.1 The supplier is responsible for the performance of all inspection and test requirements as specified herein. Except as otherwise specified, the supplier may utilize his own or any other inspection facilities and services acceptable to the Government. Inspection records of the examination and tests shall be kept complete and available to the Government as specified in the contract or order. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Categories of inspection. - Inspection of items covered by this specification shall be in accordance with one of the following categories of inspection:

a. Category A - Inspection System

b. Category B - Statement of Findings

c. Category C - Certification

Applicable category shall be as specified in the contract for item being procured. When no category is specified, Category A shall apply.

4.3 Category A - Inspection System. - The contractor shall provide and main ain an Inspection System in accordance with Specification MIL-I-45208.

4.3.1 Examination. - Examinations included in the contractor's inspection plan shall include, as a minimum, the requirements in 4.6.

4.4 Category B - Statement of Findings. - Where Category B inspection is authorized in the contract, the contractor shall perform such examinations and test as are required by this specification and other documentation referenced in the contract, and shall submit a Statement of Findings recording satisfactory compliance with all requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:25Z
Check the source to verify that this is the current version before use.

4.4.1 A separate statement of findings shall be submitted for each lot of components to be presented for acceptance. If an assembly is being supplied, a separate statement of findings shall be submitted for each lot of assembled items, plus a statement of findings covering inspection of each lot of the components comprising the assembly. Each statement shall include the following data as a minimum:

a. Purchase Order or Contract No.

b. Item nomenclature and part number

c. Applicable drawings and specifications, and revision level of each (including Supplementary Quality Assurance Provisions, inspection equipment data and packaging data, as applicable).

d. Sampling Plan

1. Lot number and lot size

2. Sample size, and acceptance criteria (acceptance number, and rejection number)

e. Description of each characteristic for which inspection is required by this specification, applicable drawings and other documents referenced in the contract.

f. Method of inspection of each characteristic

g. Authorized deviations, if any

h. Statement that inspection has been conducted in accordance with above criteria, and the item has been found to conform with all requirements. Quantitative results of inspection shall be shown for each characteristic, including the measured limits of the lot, number of rejects, and reason for rejection.

i. Signature of a responsible officer of the contractor

4.4.2 Government inspection and acceptance. - Items being procured will be accepted upon proper identification with an acceptable Statement of Findings. The Government reserves the right, however, to independently inspect for conformance with all contractual requirements prior to acceptance. The Government further reserves the right to conduct 100 percent inspection and to reject any individual non-conforming items.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:25Z
Check the source to verify that this is the current version before use.

4.4.3 Supply and maintenance of test equipment. - Unless otherwise specified in the contract, the contractor shall supply all test equipment necessary for performance of inspection requirements of the contract. The contractor shall be responsible for the maintenance of the equipment including surveillance, calibration, and rehabilitation, on a regularly scheduled basis, and shall have available all calibration equipment and other instrumentation essential for calibration and certification of the inspection equipment. The Government reserves the right to certify inspection equipment, and to use it for Government verification or acceptance inspection, to the extent that such usage by the Government will not unduly affect contractor's production schedules.

4.4.4 Examination. - Examination shall be performed in accordance with 4.6.

4.5 Category C - Certification. - Where Category C Certification is authorized in the contract, the contractor shall certify that the product being supplied has been determined to be in full compliance with all requirements of the drawings and specifications cited in the contract and that workmanship and materials conform with recognized standards of commercial quality. The certification shall reference the contract or purchase order number, part number, and applicable drawings and specifications together with their revision or amendment numbers and shall be signed by a responsible officer of the contractor.

4.6 Examination under Category A and Category B inspection.

4.6.1 Components and assemblies covered by SQAP. - Where SQAP are specified in the contract, the examination and inspection requirements of the SQAP shall represent the contractor's minimum inspection requirements for those components and assemblies to which the SQAP pertain, and shall be the basis of acceptance or rejection by lot. Where a SQAP is specified for an assembly of components, that SQAP, in the absence of any SQAP covering components comprising the assembly, will be construed to cover the minimum inspection requirements for the assembly and its components. In such cases, documented evidence of component inspection beyond that required by the SQAP will not constitute a condition of acceptance by the Government.

4.6.2 Components and assemblies not covered by SQAP. - For components and assemblies not covered by SQAP, all characteristics delineated on drawings shall be subject to examination by the contractor. The minimum amount of inspection shall be determined by the classification of defects in accordance with criteria specified in 4.6.3 and 4.6.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:25Z
Check the source to verify that this is the current version before use.

4.6.3 Class 1 Defects. - For purposes of inspection, any defect in the following types of specified characteristics will be classified as a Class 1 Defect:

a. Performance requirements specified in notes appearing on drawings, such as torque, backlash, environmental functional requirements, output, phase relationship, signal-to-noise ratio, etc.

b. Linear or diametral dimensions having tolerances of 0.001 inch or less, or less than 0.0005 inch per inch.

c. Angular dimensions having a tolerance of 5 minutes of arc or less.

d. Machine finishes of 32 micro-inches RMS or finer.

e. Concentricity requirements of 0.001 inch total indicator reading (T.I.R.) or less.

f. Parallelism and perpendicularity requirements of 0.0005 per inch or less.

g. Screw threads, Class 3 or better

h. Mandatory load requirements for springs

i. Tooth-to-tooth and total composite error in AGMA Commercial Class 4 and Precision classes of gears.

j. Tooth-to-tooth and angular error, in gears, of less than 200 seconds of arc.

k. Worm lead accuracy when tolerance is 0.0005 inch or less.

l. Lubrication requirements including dry lubricant finishes.

m. Chemical analyses and physical properties of materials when specified on drawings.

n. Centering errors of lenses, 3 minutes or less.

o. Deviation angle of prisms, 3 minutes or less.

p. Surface quality of all reticles.

q. Resolution requirements of optical elements.

r. Back focal length of lenses.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:25Z
Check the source to verify that this is the current version before use.

4.6.4 Class 2 defects. - Unless otherwise specified by the Contracting Officer, defects in characteristics not listed under 4.6.3 shall be classified as Class 2 defects.

4.6.5 Submittal of product.

4.6.5.1 Lot. - The term "lot" shall mean "inspection lot", i. e. a collection of units of product from which a sample is drawn and inspected to determine compliance with the acceptability criterion.

4.6.5.2 Formation of lots. - The product shall be assembled into identifiable lots, sublots, or in such other manner as may be prescribed. Each lot or sublot shall as far as is practicable, consist of units of product of a single type, grade, class, size, or composition manufactured under essentially the same conditions.

4.6.5.3 Lot size. - The lot size is the number of units of product in a lot, and may differ from the quantity designated in the contract or order as a lot for production, shipment, or other purposes.

4.6.6 Examination procedures.

4.6.6.1 SQAP specified in contract. - Where SQAP are specified in the contract, examination for Major and Minor defects shall be in accordance with MIL-STD-105, based on AQL specified in pertinent SQAP. One hundred percent examination shall be performed for all critical defects.

4.6.6.1.1 Alternate procedure. - The contractor may, at his option, perform examination for major and minor defects, on a defect basis, using the sampling plans specified in Tables II and III in lieu of MIL-STD-105, and in lieu of AQL's specified in SQAP. For an individual defect (single characteristic), the criteria in Table II shall be used. The total limiting defects within a class (Major or Minor), shall be as specified in Table III. No change in classification of defects specified in SQAP may be made by the contractor except as otherwise authorized by the Contracting Officer.

4.6.6.2 Components not covered by SQAP. - For components not covered by SQAP examination for Class 1 and Class 2 defects shall be performed, on a defect basis using the sampling plans and criteria specified in Tables II and III. For an individual defect (single characteristic), the criteria in Table II shall be used. The total limiting defects within a class (Class 1 or Class 2), shall be as specified in Table III.

4.6.6.3 Non-conforming material. - All non-conforming material detected during examination shall be rejected by the contractor.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:25Z
Check the source to verify that this is the current version before use.

TABLE II - SINGLE SAMPLING PLAN ON CHARACTERISTIC BASIS

Lot - Size	Sample - Size	Acceptance Numbers	
		Major and Class 1	Minor and Class 2
0 - 25	100% Exam.	--	--
26 - 180	25	0	1
181 - 500	40	1	2
501 - over	110	2	6

TABLE III - MAXIMUM ALLOWABLE DEFECTS PER SAMPLE

No. of Defects in Class	MAJOR AND CLASS 1 DEFECTS Sample - Size		
	25	40	110
2 -	0	1	3
3 - 6	0	1	4
7 - 18	0	2	6
19 - 45	0	3	8
over - 45	0	5	12
No. of Defects in Class	**MINOR AND CLASS 2 DEFECTS Sample - Size**		
	25	40	110
2 - 3	2	3	8
4 - 7	3	5	12
8 - 19	5	7	18
20 - 43	7	10	26
over - 43	11	15	40

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:25Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Packaging, packing and marking. - Packaging, packing and marking shall be in accordance with the applicable requirements of documents specified in the contract.

6. NOTES

6.1 Intended use. - This specification is primarily intended for the procurement of components and assemblies on low dollar value "small business" contracts where maximum simplicity and a minimum of cross-referencing to other documents is desirable. It also provides for utilization of Specification MIL-I-45208 where higher dollar value or special considerations require the establishment and approval of a formal contractor inspection system. This specification is not intended for use in connection with procurement of items which are covered by existing detail Military Specifications.

6.2 Ordering data. - Procurement documents should specify the following:

a. Title, number, and date of this specification

b. Category of Inspection (See 6.2.1)

c. Distribution instructions for Statement of Findings and Certification, if applicable (See 6.2.2)

6.2.1 Determination of category of inspection. - The category of inspection for each contract will normally be selected by technical personnel of the agency initiating the procurement action based on an evaluation which includes, but is not limited to, the following criteria:

6.2.1.1 Category A - Category A (Inspection System) will normally be specified for non-commercial items under one or more of the following conditions:

a. Estimated total dollar value of contract is $1500 or higher.

b. Estimated unit cost of item is $100 or higher.

c. Item involves precision processes and manufacturing techniques approaching limits of the current "state of the art".

d. Defects in item may result in critical safety hazard.

e. Inspection requirements are critical or complex.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:25Z
Check the source to verify that this is the current version before use.

f. Mandatory inspection equipment design is specified.

g. Government inspection at destination is impractical.

Category A may also be specified for commercial items on contracts estimated at $10,000 or more, where establishment and approval of a formal contractor inspection system is not impractical.

6.2.1.2 Category B - Category B (Statement of Findings) may be specified for non-commercial items which do not warrant establishment and approval of a Category A Inspection System under criteria specified in 6.2.1.1, and where Government inspection at destination is practical.

6.2.1.3 Category C - Category C (Certification) may be specified for unmodified commercial items on contracts estimated at less than $10,000 where bids may be expected from wholesale distributors, jobbers, and retailers as well as manufacturers. This category is intended to apply only to those truly commercial items which are obtainable by the general public through catalog listings or other means of public advertising, at a predetermined range of price. Industry-designed items manufactured and sold exclusively for military and space applications and not generally available through distributors and supply houses are not normally included in this category.

6.2.1.4 NOTE -

Since criteria for the selection of category of inspection are advisory only; since factors other than cost enter into the selection; and since technical estimates may be at unlimited variance with actual cost, procurement officers and bidders are cautioned that the category of inspection can in no manner be construed as an indication of possible procurement cost.

6.2.2 Distribution of statement of findings or certification - Where Category B or Category C is specified, procurement documents should include instructions for distribution of Statement of Findings or Certification, as follows: one copy with Bill of Lading for each shipment; one copy to Contracting Officer; one copy to Quality Assurance element of the agency initiating procurement.

6.3 Definitions

6.3.1 SQAP - (Supplementary Quality Assurance Provisions). A SQAP is an engineering document which prescribes minimum contractor inspection requirements for components and assemblies. The SQAP pertinent to each component and assembly is identified by the drawing number of the item prefixed by "SQAP".

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:25Z
Check the source to verify that this is the current version before use.

6.3.2 Abbreviations. - SME and STE appearing on SQAP forming a part of this specification are defined as follows:

6.3.2.1 Standard Measuring Equipment (SME) - Standard Measuring Equipment (SME) is defined as the common hand-type measuring devices which are usually stocked by commercial supply houses for ready supply (shelf items), and which are normally used by an inspector to perform dimensional inspection of items under procurement. This category also includes commercial testing equipment such as meters, optical comparators, etc.

6.3.2.2 Special Test Equipment (STE) - Special Testing Equipment is defined as special inspection fixtures, instruments, and modified standard measuring equipment. Appearance of "STE" on a SQAP does not imply that the equipment is available, or that a suitable design for such equipment is currently in existence.

NOTICE: When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any invention that may in any way be related thereto.

Custodian:

Army-Ord

Preparing activity:

Army-Ord

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:25Z
Check the source to verify that this is the current version before use.