MILITARY SPECIFICATION

INCREMENTS, PROPELLANT
M5, T8 AND T9

This amendment forms a part of Military Specification MIL-I-45170(AR), dated 8 August 1958, and is approved for use by the US Army Armament, Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

Page 2, paragraph 2.1, drawings: Delete "71-12-28" and substitute "8839494". Make this same change wherever "71-12-28" is used in this specification.

Page 3, paragraph 4.1 and all sub-paragraphs: Delete and substitute the following:

*4.1 General quality assurance provisions.-The supplier is responsible for the performance of all inspection requirements specified herein. Except as otherwise specified, the supplier may utilize his own or any other inspection facilities and services acceptable to the Government. Inspection records of the examinations and tests shall be kept complete and available to the Government as specified in the contract or order. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements. Reference shall be made to Standard MIL-STD-109 in order to define the terms used herein. Inspection shall be performed in accordance with this specification and other specifications referred in any of the contractual documents.

*4.1.1 Contractor quality assurance system.-The contractor shall provide and maintain an effective quality assurance system acceptable to the Government covering the supplies procured under this specification and shall perform all inspections required by the system. A current written description of the system shall be submitted to the contracting officer, and meet his approval, prior to initiation of production. It shall include a description covering controls for lot formation and identification, inspections to be performed, inspection stations, sampling procedures, methods of inspection (gages, measuring and testing equipment), and provisions for control and disposition of non-conforming material.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.
Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:29Z
Check the source to verify that this is the current version before use.

The written description will be considered acceptable when, as a minimum, it provides the quality assurance required by the provisions of 4.2 and 4.3 (except proving ground tests), and the other documents referenced herein. The contractor shall not be restricted to the inspection station nor the method of inspection listed in this specification provided that an equivalent control is included in the approved quality assurance procedure. In cases of dispute as to whether certain procedures of the contractor's system provide equal assurance, the comparable procedure of this specification shall apply. The contractor shall notify the Government of, and obtain approval for, any change to the written procedure that affects the degree of assurance required by this, or other documents referred to in this specification.

*4.1.2 Submission of product.-At the time the completed lot of product is submitted to the Government for acceptance the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

a. A statement that the lot complies with all quality assurance provisions of the approved current written description of the system.

b. Number of units of product inspected.

c. Results obtained for all inspection performed.

d. Drawing, specification number and date, together with an identification and date of changes.

e. Certificates of analyses on all material, covered by referred Government specifications, procured directly by the contractor.

f. Number of items in the lot.

g. Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

*4.1.3 Government verification.-Using the contractor's written quality assurance procedure, this detailed specification, the applicable drawings and other contractual documents as a guide, the Government inspector shall verify at unscheduled intervals all quality assurance operations performed by the contractor. Verification shall consist of: (a) Surveillance of contractor operations to determine that the methods and procedures of the written procedure are being properly applied and (b) Government product inspection. The Government inspector shall also ascertain prior to acceptance that the product complies with all the quality assurance provisions of other specifications referred in any of the contractual documents.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:29Z
Check the source to verify that this is the current version before use.

*4.1.3.1 Surveillance.-Surveillance shall include, but is not limited to:

a. Observation of procedures concerning lot formation and identification.

b. Observation of sampling procedures and application of acceptance criteria.

c. Determination that all required examinations and tests are performed in accordance with the prescribed procedures of this specification, or approved equivalents thereto.

d. Review of procedures for control and disposition of non-conforming material.

*4.1.3.2 Product inspection.-Physical inspection by the Government of contractor accepted product will be performed to the extent necessary to assure contractor compliance with the requirements of this specification and to determine the reliability of contractor records. Severity of Government inspection of individual characteristics will be directly related to the seriousness classification assigned. In no instance will a characteristic classified "critical" be accepted solely on the basis of the contractor's records, Specification MIL-G-2550 will apply.

*4.1.3.3 Deviations and deficiencies.-Deviations from the prescribed or agreed upon procedures, or instances of poor practice which might have an effect on the quality of the product, shall be called to the attention of the contractor immediately. To avoid interference with operation, the contractor shall designate a responsible official, or officials, to whom the Government inspector will report such instances. Failure of the contractor to correct deficiencies promptly shall be cause for suspension of acceptance until correction has been made or until conformance to prescribed criteria has been demonstrated.

Page 4, paragraph 4.2.2.1: Delete critical defect "a.".

Page 5, paragraph 4.2.2.1: Delete major defect number 1.

Page 5: Add the following:

4.2.3 Testing.

4.2.3.1 Weight of propellant: under min. - Critical defect; over max. - Major defect (see dwg. 8839494).-The propellant increment weight shall be determined 100 percent and check-weighed 100 percent. The check-weighing shall be accomplished independently of the original weight determination, and if performed manually shall be performed by a different operator. Any propellant increment which fails to comply with the applicable requirements shall be classed defective and removed from the lot. Equipment shall be in accordance with 4.3.1.

* Asterisk indicates changes in addition to those accomplished by Amendment 2.

Custodian:
Army - AR

Preparing Activity:
Army - AR

(Project 1376-A292)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:29Z
Check the source to verify that this is the current version before use.