MIL-M-45147F (PA)
Amendment 2
10 October 1975
Superseding
MIL-M-45147F (PA)
Amendment 1
21 March 1975

MILITARY SPECIFICATION

MINE, AT, NM, M19
PARTS FOR

This Amendment forms a part of military specification MIL-M-45147F (PA) dated 3 August 1973, and is approved for use by all departments and agencies of the Department of Defense.

*Paragraph 3.3 - Delete this paragraph in its entirety and substitute the following:

"3.3 Internal air pressure. - The mine plastic parts assembly shall withstand an internal air pressure high enough initially to assure a final pressure of 2.00 psig with maximum leakage rate of .02 psi in 10 seconds when tested as specified."

Paragraph 3.4 - Delete this paragraph in its entirety and substitute the following:

"3.4 Lug Pull. - The carrying cord handle lugs shall withstand a one hundred (100) pound, min. load without evidence of cracking or separation."

*Paragraph 3.5 - Delete this paragraph in its entirety and substitute the following:

"3.5 Susceptibility to cracking. - The mine plastic parts assembly shall not crack when subjected to temperature condition- at minus 65 degrees Fahrenheit for a period of 15 hours as evidenced by failure to comply with 3.3."

*Paragraph 4.4.1 - Delete this paragraph in its entirety and substitute the following:

FSC: 1345

Source: https://assist.dla.mil -- Downloaded: 202610-22T02:27Z
Check the source to verify that this is the current version before use.

"4.4.1 Internal air pressure. - The mine plastic parts assemblies shall be subjected to an internal air pressure introduced through the filler opening of a sufficiently high initial pressure to assure a final pressure of 2.00 psig, min. after a period of 10 sec min. with a maximum leakage rate of .02 psi in 10 seconds. Observation shall be made to determine compliance."

Paragraph 4.4.2 - Delete this paragraph in its entirety and substitute the following:

"4.4.2 Lug pull. - The lugs of the mine assemblies shall be subjected to a static load at one hundred (100) pounds, min. Observation shall be made to determine compliance with applicable requirement."

*Paragraph 4.4.3 - Delete this paragraph in its entirety and substitute the following:

"4.4.3 Susceptibility to cracking at cold termperature. - The mine plastic parts assembly shall be placed in a cold temperature chamber in such a manner that no external mechanical stresses are applied. The assembly shall be maintained at a temperature of minus 65 degrees Fahrenheit plus or minus 5 degrees for a period of 15 hours plus or minus one half hour. Observation shall be made for evidence of cracks, including hairline cracks, as evidence of noncompliance.

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:
Army-PA

Preparing Activity:
Army-PA

Project Number: 1345-A-143

Source: https://assist.dla.mil -- Downloaded: 2026l0-22T02:27Z
Check the source to verify that this is the currentversion before use.