MIL-M-45151C

2 December 1974
SUPERSEDING
MIL-M-0045151B(WC)
18 July 1974
MIL-M-45151A
27 September 1966

MILITARY SPECIFICATION

MOUNT, TRIPOD, MACHINE GUN, CAL. .50, M3

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers one type of portable tripod ground mount designed for use with the caliber .50, M2 heeavy barrel flexible machine gun.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

Military	
MIL-w-13855	Weapons: Small Arms and Aircraft Armament Subsystems, General Specification For.
MIL-P-14232	Parts, Equipment and Tools For Army Materiel, Packaging and Packing Of.
MIL-I-45607	Inspection Equipment, Acquisition Maintenance and Disposition Of.

STANDARDS

Military	
MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-109	Quality Assurance Terms and Definitions.

FSC 1005

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:28Z
Check the source to verify that this is the current version before use.

DRAWINGS

ROCK ISLAND ARSENAL	
D11012879	- Gage, Flush Pin.
F6507135	- Mount, Tripod, Machine Gun, Cal. .50, M3.
IEL7101187	- Index of Inspection Equipment Lists.

PUBLICATIONS

ROCK ISLAND ARSENAL	
P6507135	- Packaging Data Sheet for Mount, Tripod, Machine Gun, Cal. .50, M3.

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 First article. Requirements for submission of first article shall be as specified in the contract (see 6.1). Unless otherwise specified, the first article shall include the pilot pack (see 5.1).

3.2 Materials, contruction and design. The mount shall conform to the materials, construction, and design requirements specified herein, on Drawing F6507135 and in MIL-W-13855.

3.2.1 . Leg assemblies. With the leg clamping handles loosened and the indexing levers depressed (see 3.2.1.3 and 3.2.1.6), the lower leg assemblies (front, left rear, and right rear) shall move throughout their full range of travel in the upper leg assemblies without binding.

3.2.1.1 Front leg assembly. The front leg assembly shall be retained to the tripod head by the front leg clamping screw nut and front leg clamping screw. With the front leg clamping screw nut loosened (see 3.2.2), the front leg assembly shall pivot about the front leg clamping screw throughout its full range of travel without binding.

3.2.1.2 Rear leg assemblies, left and right. The left and right rear leg assemblies shall be retained to the tripod head assembly by the bolts and shall pivot about the bolts through their full range of travel without binding when the sleeve lock latch is released.

3.2.1.3 Leg clamping handles. The leg clamping handle shall tighten sufficiently to retain the lower leg assemblies (front, left rear, and right rear) in any of the indexed positions (see 3.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:28Z
Check the source to verify that this is the current version before use.

3.2.1.4 Sleeve lock latch. The sleeve lock latch shall rotate about the sleeve lock pin throughout its full range of travel, and when released shall return to its original position under spring action. The sleeve lock latch shall retain the sliding sleeve in the lock position and shall disengage the sliding sleeve when the sleeve lock latch is manually rotated.

3.2.1.5 Sliding sleeve. The sliding sleeve shall slide on the right rear leg throughout its full range of travel without binding, except that it shall require manual forcing into the locking position for a distance within the range specified on Drawing F6507135.

3.2.1.6 Indexing lever assembly. The indexing lever shall rotate about the pin throughout its full range of travel, and wvhen released shall return to its original position under spring action. The indexing pin shall engage in the holes of the lower leg assemblies (front, left rear, and right rear) to retain the lower leg assemblies in any of the five indexed positions.

3.2.2 Front leg clamping screw nut. The front leg clamping screw nut shall be retained to the front leg clamping screw by the pin and shall be capable of being manually rotated throughout its full range of travel. When the front leg clamping screw nut is loosened, it shall release the tension in the front leg yoke assembly to allow the serrations of the front leg yoke assembly to disengage from the serrated-plates on the tripod head to allow movement of the front leg. When the front leg clamping screw nut is tightened it shall create a clamping action of the front leg yoke assembly causing the serrations of the front leg yoke assembly to engage the serrated plates on the tripod head and shall securely lock the front leg assembly in any position set (see 3,3)₀

3.2.3 Pintle. With the pintle lock engaged in the groove of the pintle, the pintle shall rotate in the sleeve bearing throughout the full 360 degrees and there shall be no vertical movement. With the pintle lock disengaged from the groove of the pintle, the pintle shall disassemble from the sleeve bearing without binding. The pintle shall be capable of being assembled to the sleeve bearing when the pintle lock is in the locked position.

3.2.4 Pintle lock assembly The pintle lock assembly shall be securely retained to the tripod head assembly by the two screws so that there shall be no relative movement.

3.2.4.1 Pintle lock. The pintle lock shall be capable of engaging in the corresponding groove of the pintle, retaining the pintle, and remaining in this position by spring action. The pintle lock shall be capable of being disengaged from the groove of the pintle by manually rotating the pintle lock release cam, and shall be capable of being held in the disengaged position by action of the pintle lock release cam.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:28Z
Check the source to verify that this is the current version before use.

3.2.4.2 Pintle lock release cam. The pintle lock release cam shall be capable of rotating throughout its full range of travel without binding.

3.2.5 Traversing and elevating mechanism. With the traversing slide lock lever loosened, the elevating mechanism assembly shall be capable of moving on the traversing bar assembly to the 400 mil mark on the left and to the 400 mil mark on the right. The left side of the elevating mechanism sleeve shall be in alinement with the 400 mil marks.

3.2.5.1 Quick release pin assembly. The quick release pin assembly shall be securely attached to the upper elevating screw yoke by the chain assembly. The quick release pin assembly shall assemble to and disassemble from the upper elevating screw yoke without binding and when assembled shall be retained in position by action of the ball detents.

3.2.5.2 Lower elevating screw stop. When the lower elevating screw stop is in the relaxed position, it shall prevent the elevating mechanism sleeve from being manually unscrewed from the lower elevating screw. The lower elevating screw stop shall move throughout its full range of travel, and when released shall return to its original position by spring action.

3.2.5.3 Micro elevating mechanism. The micro elevating mechanism shall have a minimum adjustment of 100 mils elevation and 250 mils depression from zero on the upper elevating screw designation plate. The elevating handwheel shall turn through the full range of adjustment and shall produce a perceptible click for each mil indication on the elevating handwheel. The elevating handwheel shall remain in the position selected (see 3.3).

3.2.5.4 Micro traversing mechanism. The micro traversing mechanism shall have a minimum adjustment of 45 mils to the right and 45 mils to the left. The traversing handwheel shall turn through the full range of adjustment and shall produce a perceptible click for each mil indication on the traversing mechanism scale dial. The traversing handwheel shall remain in the position selected (see 3.3).

3.2.5.5 Traversing mechanism scale dial and locking nut. With the traversing scale dial locking nut loosened, the traversing mechanism scale dial shall rotate about the traversing screw throughout the full 360 degrees without binding and shall be capable of being adjusted to any position. With the traversing scale dial nut tightened, the traversing mechanism scale dial shall remain locked securely in the position set. Retightening is allowed each 100 rounds of endurance (see 3.3).

3.2.5.6 Traversing slide lock lever assembly. The traversing slide lock lever shall be capable of being manually rotated throughout its full range of travel without binding and when released shall return to its original open position by spring action. When the traversing slide lock lever is in the open position, the elevating mechanism assembly shall be capable of being assembled to and disassembled from the traversing bar

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:28Z
Check the source to verify that this is the current version before use.

assembly and shall be held securely in place on the traversing bar assembly when the lever is tightened to the lock position.

3.2.5.7 Upper elevating screw stop. The upper elevating screw stop shall prevent the lower elevating screw from being manually unscrewed from the upper elevating screw.

3.2.6 Traversing bar assembly. The scale on the traversing bar shall be clear and legible and shall be accurately inscribed in accordance with divisions specified on the applicable drawing. The sleeve lock latch shall hold the traversing bar in locked position when the mount is in firing position. The traversing bar assembly shall be adjusted in accordance with Drawing F6507135 to require manual forcing into the lock position in order to increase the rigidity of the mount when in firing position.

3.3 Endurance. While attached to a Government standard caliber .50, M2 heavy barrel machine gun, the mount shall be capable of withstanding the firing of 10,000 rounds of Government standard caliber .50, M2 or M33 ball cartridges, using M2 or M9 links, without parts deformation, mount malfunctions or unserviceable parts (an unserviceable part is one that causes malfunctions or impairs the safety of the mount). Parts shall not loosen or move from preset positions (see 3.2.1.3, 3.2.2, 3.2.5.3, 3.2.5.4 and 3.2.5.5). Retightening of the dial scale locking nut is permitted following each 100 rounds of firing.

3.3.1 Firing schedule. Firing shall be accomplished using 100 round belts. The firing schedule shall be approximately 50 rounds spasmodic fire, followed by one continuous burst for the remainder of the belt, Testing shall be as specified in 4.5.2.2.

3.4 Interchangeability. Unless otherwise specified on the drawings, all replacement parts shall be interchangeable. Testing shall be as specified in 4.5.2.3.

3.5 Marking. Bipeds shall be marked in accordance with MIL-W-13855.

3.6 Workmanship. Workmanship shall be in accordance with MIL-14-13855.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:28Z
Check the source to verify that this is the current version before use.

The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Quality assurance terms and definitions. Quality assurance terms and definitions used herein are in accordance with MIL-STD-109.

4.3 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.4).
b. Quality conformance inspection (see 4.5).

4.4 First article inspection. The first article (initial production unit(s)) shall be submitted for inspection in accordance with the contract (see 6.1). The first article shall be representative of the production processes to be used during quantity production. The first article shall be subjected to the quality conformance inspection specified herein and such other inspection as is necessary to determine compliance with the requirements of the contract.

4.5 Quality conformance inspection.

4.5.1 Examination.

* 4.5.1.1 Component parts and concurrent repair parts. Examination of component parts and concurrent repair parts shall be as specified in the contract (see 6.1). The contractor's examination of these parts shall be prior to assembly into the end item or submission for acceptance as repair parts.

4,5,1,2 Mounts. Each mount shall be examined as specified below. Each step in the examination shall include a visual examination for proper cleaning and presence of the specified protective coating and to determine the general quality, completeness of manufacture, assembly, and workmanship. Tme examination provisions shall be applied at the earliest practical point in manufacture at which it is feasible to inspect for acceptance without risk of change in the characteristic by subsequent operations. Reinspection of these characteristics on the completed product is not required provided assurance exists that the characteristic has not been changed, degraded or damaged by subsequent manufacturing, assembly or handling and that adequate inspection records are maintained. Mounts failing to meet the requirements shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:28Z
Check the source to verify that this is the current version before use.

4.5.1.2.1 Leg assemblies.

a. Manually examine the leg assemblies (front, rear left, and rear right) to determine compliance with 3.2.1, 3.2.1.3 and 3.2.1.6.
b. Manually examine the front leg assembly and the front leg clamping screw nut to determine compliance with 3.2.1.1 and 3.2.2.
c. Manually examine the left rear leg assembly, the right rear leg assembly, the sleeve lock latch, and the sliding sleeve to determine compliance with 3.2.1.2, 3.2.1.4 and 3.2.1.5.

4.5.1.2.2 Pintle and pintle lock assembly.

a. Manually examine the pintle and pintle lock assembly to determine compliance with 3.2.3, 3.2.4, 3.2.4.1 and 3.2.4.2.
b. Disassemble the pintle and visually examine to assure freedom from burs and mutilations on the bearing surfaces of the pintle and sleeve bearing.

4.5.1.2.3 Traversing bar assembly.

a. Visually and manually examine the traversing bar assembly to determine compliance with 3.2.6.
b. Visually examine for proper staking of the screw and two bolts to determine compliance with Drawing F6507135.

4.5.1.2.4 Traversing and elevating mechanism.

a. Manually examine the traversing and elevating mechanism to determine compliance with 3.2.5.1 through 3.2.5.7.
b. Visually examine the graduations on the traversing mechanism scale dial and the elevating handwheel to assure they are clear and legible.
c. Visually examine to assure that the externally. threaded ring is securely staked in position in accordance with the applicable drawing.
d. Manually examine the elevating mechanism assembly to determine compliance with 3.2.5.

4.5.1.2.5 Mount assembly.

a.. Visually examine for proper staking of the nuts retaining the rear legs and the nuts retaining the tripod head spacers to determine compliance with Drawing F6507135.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:28Z
Check the source to verify that this is the current version before use.

b. Visually examine for proper staking of the setscrew retaining the sleeve bearing in the tripod head to determine compliance with Drawing F6507135.
c. Visually examine staked areas for proper touch up in accordance with Drawing F6507135.
d. Visually examine for proper marking as specified on Drawing F6507135.
e. Visually examine sleeve bearing after finish reaming for compliance with surface roughness requirement specified on Drawing F6507135.
f. Examine to assure sleeve bearing conforms to dimensions specified on Drawing F6507135 after finish reaming using inspection equipment conforming to Drawing D11012879.

4.5.2 Testing.

* 4.5.2.1 Failure data. Unless otherwise specified herin, all tests shall be conducted on a complete mount. If test requirements cited herin are not met, acceptance of the mount shall be deferred and the contractor shall accomplish as applicable, the following actions:

a. Conduct a failure analysis study performing a dimensional physical and visual examination of the components which are suspected to be the cause of failure or malfunction.
b. Evaluate and correct the applicable production processes and procedures to prevent recurrence of the same defect(s) in future production.
c. Examine mounts, partially assembled mounts, and components (including components and subassemblies at in-process or final assembly) to insure that material containing the same defect is purged from the inventory and not presented to the Government for acceptance.
d. Submit the results of the failure analysis and the corrective actions taken to the Government for review and approval prior to submitting a reconditioned mount for retest.

* 4.5.2.2 Endurance testing. One mount selected at random from each month's production shall be tested for endurance (see 3.3) using the test method specified in 4.6.1. It the endurance requiremens are not met, the month's production shall be rejected. When three successive month's production meet the requirements, endurance testing will be discontinued.

4.5.2.3 Interchangeability testing.

4.5.2.3.1 In plant.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:28Z
Check the source to verify that this is the current version before use.

4.5.2.3.1.1 Mounts. Ten mounts randomly selected from each month's production shall be tested for interchangeability using the test method specified in 4.6.1.1.1. Mounts taken for interchangeability testing shall have been found satisfactory in all other examinations and tests. Failure of the interchangeability test shall cause retest or rejection of the represented log. At the discretion of the Government representative, an interchangeability retest may be allowed without reconditioning the lot of mounts. Failure in the retest shall cause rejection of the represented lot subject to reconditioning and further test as a reconditioned lot. A sample of 20 mounts from each retest or reconditioned lot shall be tested using the same procedure described above except that hand refinement will be allowed on not more than four mounts.

4.5.2.3.1.2 Concurrent repair parts. At least two parts from each inspection lot of concurrent repair parts shall be subjected to the interchangeability test specified in 4.6.2.1.2. Failure of any part to meet the requirements shall be cause for rejection of the represented lot of parts subject to reconditioning and further test as a reconditioned lot. A sample of double the number of parts used in the original test shall be tested from each reconditioned lot using the test method specified in 4.6.2.1.2.

4.5.2.3.2 Interplant. When mounts are manufactured concurrently by more than one contractors each contractor shall forward monthly six mounts and a sufficient quantity of concurrent repair parts (if applicable) for the assembly of two mounts for the interplant interchangeability test specified in 4.6.2.2 (see 6.1). The contractor will be informed of the results of the test which indicates failure of the mounts or parts to meet prescribed requirements.

4.5.2.4 Component parts and concurrent repair parts testing. Raw material testing, part testing, and certification shall be perform in accordance with the criteria specified in the contract (see 6.1). This will include chemical analysis and physical tests of materials, and tests of protective finiish, heat treatmnt, bonding, and function of parts as applicable. These tests shall be accomplished prior to assembly of parts into the end item.

4.5.2.5 Certification. Unless otherwise specified, the contractor shall furnish the Government representative with certified statements that each inspection lot conforms to applicable drawings, specification of the materials and processes specified on Drawing F6507135 and drawings applicable thereto.

4.5.3 Inspection equipment.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:28Z
Check the source to verify that this is the current version before use.

* 4.5.3.1 Acquisition, calibration, maintenance and disposition. Unless otherwise specified (see 6.1), responsibility for acquisition, calibration, maintenance and disposition of acceptance inspection and test equipment prescribed on the List of Inspection Equipment, IEL and for all other inspection equipment required by applicable specifications, shall be in accordance with MIL-I-45607.

* 4.5.3.2 Accuracy of standard measuring equipment. When commercial and modified commercial inspection and test equipment is used, it must be capable of repetitive measurements to an accuracy of 10 percent of the total tolerance of the characteristic being inspected.

* 4.5.4 Packaging examination and testing. Unless otherwise specified (see 6.1), the packaging and marking examination and testing shall be in accordance with MIL-P-14232.

4.6 Test methods.

* 4.6.1 Endurance. The mount and the cal. .50, M2 heavy barrel machine gun to be used in the test shall be lubricated and examined prior to the test. Testing shall be accomplished with the machine gun locked on the mount so that the line of sight and the front tripod leg are in approximately the same vertical plane. The feet of the tripod legs shall be in approximately the same horizontal plane and shall be held in place to prevent movement of the mount during firing. Ammunition, links and firing schedule shall be as specified in 3.3. At least two barrels shall be used during the test and not more than 5000 rounds shall be fired in any one barrel. Following each 100 rounds of firing, the mount shall be checked to assure that the leg clamping handles and the front leg clamping screw nut have not loosened and that the elevating handwheel, traversing handwheel, dial scale, and locking nut have not moved from the position selected prior to firing (see 3.2.1.3, 3.2.2, 3.2.5.3, 3.2.5.4 and 3.2.5.5.). Following each 100 rounds of firing, the dial scale locking nut shall be retightened. The machine gun shall be cooled to ambient temperature (approximately) by forced air after each 100 rounds of firing. The machine gun shall be cleaned and oiled after each 1,000 rounds of firing, and at the close of each day's firing the machine gun and mount shall be protected against corrosion. Mount parts shall not be altered and only those parts broken or worn to the extent that they are unserviceable shall be replaced. Complete accurate records shall be kept for each endurance test, showing each malfunction and part replacement including the number of the round at which each occurred. Malfunctions attributable to ammunition, links, or the test machine gun shall not be counted against the mount being tested, however, such malfunctions shall be recorded. At the completion of the endurance test, mounts shall be disposed of as specified in the contract (see 6.1).

4.6.2 Interchangeability test.

4,6.2.1 In plant

Source: https://assist.dla.mil -- Downloaded: 2026t0-22T02:28Z
Check the source to verify that this is the currentversion before use.

4.6.2.1.1 Mounts. Mounts shall be tested by disassembling and then reassembling parts using the parts and prearranged system specified below. Interchange of parts shall be accomplished by dividing the parts of each mount into 10 groups of nonmating parts as showm below and distributing the groups into 10 different trays until each tray contains parts for a complete mount. Groups of parts from the first mount shall be taken in order and placed in trays 1 through 10; groups of parts from the second mount shall be taken in order and placed in trays 2 through 10 to 1; groups of parts from the third mount shall be taken in order and placed in trays 3 through 10 to 2, etc. Commercial parts such as screws, spring pins, etc., shall be placed in the same tray as their mating or associate part. Any commercial part rendered unserviceable by disassembly shall be replaced without penalty to the interchangeability test. The mounts shall be reassembled using only those parts which are in the same tray.

Groups of Non-mating Parts

Group I

Head, tripod, assembly (5559419) (with bearing, sleeve-6108397)
Mechanism assembly, elevating (5574621). (with dial-5171492, handwheel-6158375, lever-5194313, nut-5171491, pin-5171495, screws-5139989 and 5140383, and springs-11010547 and 8412295 removed)

Group II

Handwheel, traversing (6158375)
Screw, front leg clamping (6108395)
Screw, locking, traversing slide (5140383)
Screw, machine (5140237) (8 required) (used with plates-6108396)

Group III

Bolt, machine, hexagon head (5170484) (2 required) (used with bar assembly-7149678)
Pintle, tripod mount (5559332)
Screw, machine, button head (5139989) (used with lever assembly-5194313)

Group IV

Bar assembly, traversing (7149678)
Bolt, machine, hexagon head (5170485) (2 required) (used with spacers-5140219)
Bolt, machine, hexagon head (5170486) (2 required) (legs-6507136 and 6507137 tO head 5559419)

Group V

Dial, scale (5171492)
Leg, tripod mount, rear left (6507137) (with leg section-11010426 and screw-5140213 removed)
Spring, helical, compression (11010547) (used with pin-5171495)

Group VI

Bolt, machine, hexagon head (5139973) (used with pintle-5559332)
Nut, front leg clamping screw (6193782)
Screw, machine, hexagon head (5141950) (2 required) (used with lock assembly-6108402)

Source: https://assist.dla.mil -- Downloaded: 2026l0-22T02:28Z
Check the source to verify that this is the currentversion before use.

Group VII

Leg section, tripod mount, rear (11010426) (2 required)
Leg, tripod mount, front (5559423) (with leg-11010424 and screw-5140213 removed)
Spacer, sleeve (5140219) (2 required)

Group VIII

Leg, front, lower (11010424)
Leg, tripod mount, rear right (6507136) (with leg section-11010426 and screw-5140213 removed)
Nut, union, round (5171491)

Group IX

Nut, slotted, hexagon (5139964) (used with bolt-5139973)
Plate, serrated (6108396) (2 required)
Spring, helical, torsion (8412295) used with-5140383)

Group X

Lever assembly, traversing slide lock (5194313)
Lock assembly, pintle (6108402)
Pin, click, elevating and traversing mechanism (5171495)
Set screw, alignment (5140213) (3 required)

4.6.2.1.2 Concurrent repair parts. Concurrent repair parts shall be tested by disassembling two mounts, previously tested in 4.5.2.3.1.1, as necessary and then reassembling them using the concurrent repair parts. No hand refinement of parts will be allowed, and the mounts shall operate and function properly. This test may be performed independently of the mount interchangeability test specified in 4.5.2.3.1.1 and at more frequent intervals using accepted mounts taken from current production.

4.6.2.2 Interplant.

4.6.2.2.1 Mounts. Mounts to be subjected to the interplant interchangeability test shall be given a preliminary hand functioning to assure proper operation before parts are interchanged. Parts shall then be disassembled from the mounts, and identified as to manufacturer. Mounts shal be interchanged in a manner similar to the detailed plan specified in 4.6.2.1.1 except that parts shall be divided into six groups and that when disassembling, every other mount used shall be one produced by a different manufacturer. After interchange of parts, the mounts shall be examined for function of traverse and elevation micro adjustment mechanism for the requirements specified in 3.2.5.3 and 3.2.5.4. Before mounts are returned to the contractors, the original parts shall be reassembled to their respective mounts.

4.6.2.2.2 Repair parts. The concurrently manufactured repair parts submitted for tests shall be assembled in the mounts previously tested in 4.6.2.2.1 without hand fitting or altering any part. Mounts shall be assembled using different combinations of parts to the extent deemed necessary to assure that parts are interchangeable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:28Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

* 5.1 Pilot pack. The pilot pack shall consist of a complete mount packaged in accordance with Packaging Data Sheet P6507135 for the level of protection specified in the contract (see 6.1), packed level C and forwarded in accordance with 3.1.

* 5.2 Preservation, packaging, packing and marking. The mount shall be preserved, packaged, packed and marked in accordance with packaging data sheet P6507135 for the level of protection specified in the contract (see 6.1).

* 5.3 Repair parts. Repair parts shall be preserved, packaged, packed and marked in accordance with the Packaging Data Sheet or other requirements for the level of protection specified in the contract (see 6.1).

6. NOTES

6.1 Ordering data. 'Procurement documents should specify:

6.1.1 Procurement requirements:

a. Title, number and date of this specification.
b. Lists of drawings and specifications pertinent to the mount, showing applicable revision dates.
c. Shipping instructions for first article and pilot pack (see 3.1, 4.4 and 5.1).
d. Inspection criteria for components (see 4.5.1.1 and 4.5.2.4).
e. Index to lists of inspection gages and parts gaged pertinent to the mount, showing applicable revision dates.
f. Shipping instructions for mounts and parts when an interplant interchangeability test is required (see 4.5.2.3.2).
g. List of acceptance inspection equipment to be furnished the contractor (see 4.5.3.1) and responsibilities for other Government property to be furnished the contractor (guns, barrels, links and ammunition).
h. Packaging examination and testing, if different (see 4.5.4).
i. Disposition of endurance tested mounts (see 4.6.1).
j. Selection of applicable levels of packaging and packing (see 5.1 and 5.2).
k. Packaging instructions for repair parts (see 5.3).

6.1.2 Contract data requirements. When warranted, requirements for reports of the results of examination and testing shall be specified on a DD Form 142 included in the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:28Z
Check the source to verify that this is the current version before use.

6.2 Unless otherwise specified (see 6.1.), the contract should specify the application of MIL-I-45607 on the Management Control System Summary List, DD Form 1660.

6.3 When warranted, the contract should specify the application of MIL-Q-9858 or MIL-I-45208 on the Management Control System Summary List, DD Form 1660.

6.4 Revision A of this specification included the requirements of SAPD-275A, dated 11 June 1965.

6.5 The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:
Army - WC
Navy - MC
Air Force - 84

User Activity:
Navy - OS

Review Activities:
Navy - MC
Air Force - 84

Preparing Activity:
Army - WC

Project number:
1005-0531

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T02:28Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE
MIL-M-45151C; Mount, Tripod, Machine Gun, Cal. .50, M3

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A
☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?
   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426

REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 202610-22T02:28Z
Check the source to verify that this is the current version before use.