MILITARY SPECIFICATION

CONTAINER, INSERT (INSERT)

This specification is approved for use within the United States Marine Corps, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification establishes the requirements for the manufacture and acceptance of the insert container (INSERT). The insert is designed to fit into a container rack within the pallet container (PALCON) and quadruple container (QUADCON) to form a bin/drawer container. Six inserts will fit within the PALCON and 36 within the QUADCON.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards and handbooks form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation:

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commandant of the Marine Corps, Code LMA-2, Washington, D.C. 20380, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 8145

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T23:12Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

MILITARY

MIL-T-704	Treatment and Painting of Materiel
MIL-C-5541	Chemical Conversion Coatings on Aluminum Alloys
MIL-Q-9858	Quality Program Requirements
MIL-C-46168	Coating, Aliphatic Polyurethane, Chemical Agent Resistant
MIL-P-52192	Primer Coating, Epoxy
MIL-C-29444(MC)	Container, Pallet (PALCON)
MIL-C-29445(MC)	Container, Quadruple (QUADCON)
MIL-C-29447(MC)	Container Rack, Pallet (PALCON Rack)
MIL-C-29448(MC)	Container Rack, Quadruple (QUADCON Rack)

STANDARDS

MILITARY

MIL-STD-129	Marking for Shipment and Storage
MIL-STD-130	Identification Marking of U.S. Military Property
MIL-STD-810	Environmental Test Methods and Engineering Guidelines
MIL-STD-831	Test Reports, Preparation of
MIL-STD-889	Dissimilar Metals
MIL-STD-1186	Cushioning, Anchoring, Bracing, Blocking and Waterproofing, with Appropriate Test Methods

2.1.2 Other Government documents, drawings and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

Source: https://assist.dla.mil - Downloaded: 2026-10-20T23:12Z
Check the source to verify that this is the current version before use.

DRAWINGS

MARINE CORPS

835043A0000	Container, Insert (INSERT)

(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Other publications. The following documents(s) form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be in the issue of the nongovernment documents which is current on the date of the solicitation.

AMERICAN SOCIETY FOR TESTING AND MATERIALS

ASTM-E-162	Surface Flammability of Materials Using a Radiant Heat Energy Source
ASTM-D-229	Rigid Sheet and Plate Materials Used for Electrical Insulation
ASTM-D-256	Impact Resistance of Plastic and Electrical Insulating Materials
ASTM-D-570	Water Absorption of Plastics
ASTM-D-638	Tensile Properties of Plastics
ASTM-D-648	Deflection Temperature of Plastics of Under Flexural Load
ASTM-D-695	Compressive Properties of Rigid Plastics
ASTM-D-790	Flexural Properties of Unreinforced and Reinforced Plastics and Electrical Insulating Materials
ASTM-D-792	Specific Gravity and Density of Plastics by Displacement
ASTM-D-1043	Stiffness Properties of Plastics as a Function of Temperature by Means of a Torsion Test

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T23:12Z
Check the source to verify that this is the current version before use.

ASTM-D-2583 Indentation Hardness of Rigid Plastics by Means of a Barcol Impressor

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, Pennsylvania 19103).

(Industry association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets, or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified in the contract or purchase order a sample shall be subjected to first article inspection (see 4.4 and 6.3). The first articles shall be manufactured using the same procedures and tooling proposed for production. Approval of the first articles by the acquiring activity shall not relieve the Contractor of the obligation to supply equipment conforming to this specification. Changes or deviations in production units from the approved first article baseline shall require written authorization by the acquiring activity.

3.2 Materials. Materials and components shall conform to the requirements specified herein and in Drawing Number (No.) 835043A0000.

3.2.1 Fiberglass reinforced plastic. The entire insert, including the lid and dividers, shall be fabricated from fiberglass reinforced plastic commonly known as sheet molding compound (SMC). The SMC sheet shall be formed by chopping continuous fiber-glass rovings into 2-in lengths and blending with a thermosetting resin. The composite sheet shall contain not less than 42 percent glass and a maximum of 58 percent polyester resin by weight. The chopped glass rovings shall be randomly deposited to achieve structural uniformity. The exterior panel surfaces shall be ultraviolet; weather, mildew, oil, and chemical resistant; and shall conform to the color and finish requirements of 3.9. The physical properties of the SMC shall meet the requirements specified in Table I. The fiberglass reinforced plastic shall be smooth or embossed and shall be free from bubbles, glazing, cracks, and discontinuities.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T23:12Z
Check the source to verify that this is the current version before use.

3.2.2 Dissimilar materials. Intimate contact of dissimilar materials, as defined in MIL-STD-889, which can be expected to cause galvanic corrosion, shall be avoided. When such contact cannot be avoided, an interposing insulating material shall be provided to minimize the corrosive effect.

TABLE I. Physical Properties of SMC

PROPERTIES	TEST METHOD	VALUES
Impact, izod notched, ft/lb/in	ASTM-D-256	15.0
Impact, izod unnotched at room temperature	ASTM-D-256	12.0
Flexural strength psi	ASTM-D-790	20,000
Flexural modulus x 10^6 psi	ASTM-D-790	1.50
Tensile strength psi	ASTM-D-638	20,000
Tensile modulus x 10^6 psi	ASTM-D-638	1.50
Compressive strength psi	ASTM-D-695	28,000
Water absorption percent in 24 hrs/73°F	ASTM-D-570	.50
Specific gravity	ASTM-D-792	1.50
Heat deflection at 264 psi/°F	ASTM-D-648	+430
Flame spread (radiant panel)	ASTM-E-162	15 or less
Barcol, hardness (minimum)	ASTM-D-2583	40
180°F torsional modulus, psi		
at 10 sec	ASTM-D-1043	1.25 (10^6)
at 100 sec	ASTM-D-1043	1.1 (10^6)
Hot coil ignition test		
a) Time to ignition, sec	ASTM-D-229 Method II	> 50
b) Burn time, sec	ATSM-D-229 Method II	< 50
Wan abrasion (4 hr test with 2 lb shoe)	--	< 99.6% retention

3.3 Design and construction.

3.3.1 Insert. The insert shall be fabricated in accordance with Drawing No. 835043A0000. The insert shall be constructed of SMC conforming to 3.2.1. The insert shall not contain recesses or voids in which moisture could accumulate or contraband could be concealed. No part of the insert (with the lid in place) shall protrude beyond the overall projection of the lid which will cause interference with the PALCON and QUADCON container racks.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T23:12Z
Check the source to verify that this is the current version before use.

3.3.2 Dividers. The dividers shall be fabricated of SMC conforming to 3.2.1, and shall be keyed to the insert side walls for structural rigidity in accordance with Drawing No. 835043A0000. Each divider shall have provisions for handling by personnel wearing cold weather gloves/mittens.

3.3.3 Handles. Handles shall be provided on each 17 in. (432 mm) end of the insert for handling by one or two persons. Each handle and attaching hardware shall be capable of supporting the full weight of the insert.

3.3.4 Lid. The lid shall be fabricated of SMC conforming to 3.2.1. No part of the insert (with the lid in place) shall protrude beyond the overall projection of the lid which will cause interference with the PALCON and QUADCON container racks.

3.3.5 Container racks, PALCON and QUADCON. The insert shall be capable of fitting into the PALCON and QUADCON container racks built in accordance with MIL-C-29447(MC) and MIL-C-29448(MC), respectively. When the respective racks are fully erected within the PALCON and QUADCON, built in accordance with MIL-C-29444(MC) and MIL-C-29445(MC) respectively, six inserts shall fit within the PALCON and 36 within the QUADCON with the doors closed. Testing shall be in accordance with 4.7.1.

3.3.6 Interchangeability. Like demountable hardware and components of the insert shall be interchangeable.

3.3.7 Metal fabrication. Metal used in the fabrication of equipment shall be free from kinks and sharp bends. The straightening of material shall be done by methods that will not cause injury to the metal. Shearing and punching shall be done neatly and accurately. Corners shall be square and true. All bends shall be made with controlled means in order to ensure uniformity of size and shape.

3.3.8 Bolted and riveted connectors. Bolt and rivet holes shall be accurately punched or drilled and have the burrs removed. Washers, lockwashers, or locknuts shall be provided where necessary and all bolts, nuts, and screws shall be tight. Rivet heads, when not countersunk or flattened, shall be of uniform size and shape for the same diameter rivet, concentric with the rivet holes, and in full contact with the surface of the members.

3.3.9 Seals. Seals shall be installed so that the fit is snug and continuous contact is maintained with mating seal faces. Ends of horizontal seal runs shall be accurate, and gaps shall be sealed as specified on the applicable drawings.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T23:12Z
Check the source to verify that this is the current version before use.

3.4 Maintainability. The insert has been designed so that as much of the maintenance, as possible, may be performed as far forward (preferably by the using unit).

3.5 Transportability. The insert shall be capable of being transported without damage by all forms of military vehicles capable of transporting such loads either dimensionally or by load rating. These vehicles include the 5 ton cargo truck, the Logistics Vehicle System (LVS), helicopter, C-130 cargo aircraft, railroad train, or ships as well as by commercial carriers.

3.6 Environmental requirements.

3.6.1 Weatherproofness. The insert shall withstand testing as described in paragraph 4.7.4.1 without leakage at any location.

3.6.2 Temperature-humidity. The insert shall be capable of functioning and withstanding exposure to temperatures of -65° F to 125°F at any possible relative humidity from 0 to 100 percent. In storage, the insert shall be capable of withstanding exposure to temperatures of -70°F to 160°F at any possible relative humidity from 0 to 100 percent without cracking, corroding, delamination, or peeling of paint. Testing shall be in accordance with 4.7.4.2 and 4.7.4.3.

3.6.2.1 Thermal shock. The insert shall be capable of withstanding sudden temperature changes up to and including from 160°F to -70°F to 160°F without degradation of physical properties. Testing shall be in accordance with 4.7.4.4.

3.6.3 Snow and ice. The insert shall be capable of functioning in accordance with the requirements specified herein during periods of snow and ice storms. The insert shall inhibit the collection of snow and ice such that its primary function is not degraded. The insert shall be capable of withstanding snow loads up to 10 lbs. per square foot (478.7 N/m^2) in addition to its internal load.

3.6.4 Wind. The insert shall be capable of withstanding wind speeds of up to 65 miles per hour (mph) (104 kilometers per hour (km/hr)) and gusts of up to 120 mph (192 km/hr). In winds in excess of 55 mph (88 km/hr), ground anchors are required.

3.6.5 Sand and dust. The insert shall withstand the effects of sand and dust on all external moving parts without degradation or infiltration of particles inside the unit. Testing shall be in accordance with 4.7.4.5.

Source: https://assist.dla.mil - Downloaded: 2026-10-20T23:12Z
Check the source to verify that this is the current version before use.

3.6.6. Sunshine. The insert shall withstand the effects of ultraviolet radiation (sunshine) without degradation or effect on serviceability of the insert's components or materials during the service life, and shall withstand the test requirements of MIL-STD-810, Method 505.1. Testing shall be in accordance with 4.7.4.6.

3.6.7 Solar load. The insert shall withstand a solar heat load on its roof sufficient to raise the outer skin to at least 200°F without any evidence of delamination or permanent deformation. Testing shall be in accordance with 4.7.4.7.

3.6.8 Marine environment. The insert shall be fully serviceable when exposed to sea-salt fallout equivalent to 25 pounds/acre/year (2.8 grams/m^2/year). All fasteners, seals, or other hardware shall show no evidence of corrosion or degradation affecting serviceability when tested as required by 4.7.4.8.

3.6.9 Drop shock.

3.6.9.1 Flat drop. The insert shall withstand a flat drop of 12 in.(305 mm) from the ground onto a concrete surface. Testing shall be in accordance with 4.7.5.1.

3.6.9.2 Rotational drop. The insert shall withstand rotational drops with one edge placed on a 4 in. (102 mm) block and the opposite edge raised 12 in. (305 mm) and allowed to free fall onto a concrete surface with the 4 in. (102 mm) block acting as a pivot. The insert shall withstand this drop on each bottom edge. Testing shall be in accordance with 4.7.5.2.

3.7 Dimensions. The applicable drawings fully describe all pertinent dimensions and tolerances. Should any dimensions and tolerances result in a component or assembly which will not meet the requirements of this specification, the supplier is responsible for fabrication techniques which will prevent the occurrence of such dimensions and tolerances. Testing shall be in accordance with 4.7.2.

3.8 Weight. The tare weight of the insert, including all dividers and the lid, shall be 30 lbs. ± 5 percent. The gross weight shall not exceed 155 lbs. The actual tare weight shall be stamped on the nameplate. Testing shall be in accordance with 4.7.3.

3.9 Finish.

3.9.1 Surface preparations. All surfaces shall be prepared as specified on the applicable drawings. All aluminum alloy materials shall be protected by a chemical film conforming to MIL-C-5541.

Source: https://assist.dla.mil - Downloaded: 2026-10-20T23:12Z
Check the source to verify that this is the current version before use.

3.9.2 Priming and final finish. All surfaces to be painted shall be cleaned and treated in accordance with MIL-T-704 (Table II), type B, except that all surfaces or ferrous components shall be coated with a primer coat conforming to MIL-P-52192 and a top-coat in number 383 green in accordance with MIL-C-46168.

3.10 Identification marking.

3.10.1 Identification. Each insert shall have the following information provided on a serial plate permanently affixed to the insert in accordance with MIL-STD-130:

Manufacturer:

Model:

Type:

Serial No: (As assigned by the Contracting Activity)

Tare Weight:

3.10.2 Markings. Markings shall be in accordance with Drawing No. 835043A0000.

3.11 Workmanship. All parts, components, and assemblies of the insert, including molded parts, stampings, seals and sealing agents, shall be clean and free from any defects that will reduce the capability of the insert to meet the requirements specified herein. Any components and assemblies which have been repaired or modified to overcome deficiencies or deficient components or assemblies which are determined to be used "as is" shall not be used unless authorized by the contracting activity. External surfaces shall be free from burrs, slag, sharp edges and corners, except where sharp edges and corners are required.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the Contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the Contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T23:12Z
Check the source to verify that this is the current version before use.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the Contractor's overall inspection system or quality program in accordance with MIL-Q-9858A. The absence of any inspection requirmeents in this specification shall not relieve the Contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.4)

b. Quality conformance inspection (see 4.5)

c. Individual inspection (see 4.6)

4.3 Inspection conditions. Unless otherwise specified, all inspections shall be performed in accordance with the test conditions specified in 4.4, 4.5 and 4.6.

4.4 First article inspection. Prior to beginning production of the insert, the Contractor shall fabricate thirty-six inserts and subject them to all tests specified in Table II.

4.5 Quality conformance inspection. From each shipping lot as defined in the contract, a single insert shall be chosen at random by the Government and subjected to the tests specified in Table II. Failure of any test shall be cause for inspection of the entire lot at the Contractor's expense for similar defects. Defective inserts shall not be delivered without correction of the deficiency and then only with the permission of the Contracting Officer.

4.6 Individual inspection. Each insert shall be subjected to the inspections and tests specified in Table II. Failure to meet the requirements specified herein shall be cause for rejection. No insert shall be reworked and retested without the expressed permission of the contracting activity.

Source: https://assist.dla.mil - Downloaded: 2026-10-20T23:12Z
Check the source to verify that this is the current version before use.

TABLE II. Tests

INSPECTION	REQ PARA	TEST PARA	1ST ART	QUAL CONF	IND
Compatibility	3.3.5	4.7.1	X		
Dimensional	3.7	4.7.2	X	X	X
Weight	3.8	4.7.3	X	X	X
Weatherproofness	3.6.1	4.7.4.1	X	X	
Humidity resistance	3.6.2	4.7.4.2	X		
Temperature range	3.6.2	4.7.4.3	X		
Temperature shock	3.6.2.1	4.7.4.4	X		
Sand and dust	3.6.5	4.7.4.5	X		
Sunshine	3.6.6	4.7.4.6	X		
Solar load	3.6.7	4.7.4.7	X		
Marine atmosphere	3.6.8	4.7.4.8	X		
Flat Drop	3.6.9.1	4.7.5.1	X	X	
Rotational drop	3.6.9.2	4.7.5.2	X	X	

4.7 Tests.

4.7.1 Compatibility. A PALCON or QUADCON container rack built in accordance with MIL-C-29447(MC) or MIL-C-29448(MC) respectively, and a PALCON or QUADCON built in accordance with MIL-C-29444(MC) or MIL-C-29445(MC) respectively, shall be required for this test. Assemble the respective rack into the PALCON or QUADCON and assure compatibility of six or 36 insert locations by installing the insert into each location.

4.7.2 Dimensional. The length, width, and height shall be measured and recorded for each insert. The requirements of 3.7 shall be satisfied.

4.7.3 Weight. The weight of each insert, including all dividers and the lid, shall be taken. The requirements of 3.8 shall be satisfied.

4.7.4 Environmental tests.

4.7.4.1 Weatherproofness. A stream of water shall be applied on all exterior joints and seams of the insert under test from a nozzle of 0.5 in. (12.7 mm) inside diameter at a pressure of about 1 bar (corresponding to a head of about 33 ft. (10m)) of water on the upstream side of the nozzle. The nozzle shall be held at a distance of 5 ft. (1.5) from the container under test, and the

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T23:12Z
Check the source to verify that this is the current version before use.

stream shall be traversed at a speed of 4 in/s (100 mm/s). Procedures involving the use of several nozzles are acceptable provided that each joint or seam is subjected to a water loading no less than that which would be given by a single nozzle. At the conclusion of this test, the insert shall be examined and show no evidence of leakage at any location.

4.7.4.2 Humidity resistance. The insert shall be subjected to MIL-STD-810, Method 507.1, Procedure II, excluding steps 2-4, 7, and 8. After cycling, the insert shall be examined and show no evidence of delamination, cracking, or deterioration of any part of the insert.

4.7.4.3 Temperature range. The insert shall be cold soaked in a mechanically refrigerated cold chamber at -70°F for a minimum of 16 hours. The chamber temperature shall then be raised to -65°F. The insert lid will be opened and closed. Any malfunction shall be recorded and reported. The insert shall then be visually examined both internally and externally for material degradation. There shall be no damage to seals or other components and all hardware shall operate as specified during and upon completion of this test.

4.7.4.4 Temperature shock. A representative insert panel specimen measuring 12 in. by 24 in. (305 mm by 610 mm) shall be subjected to MIL-STD-810, Method 503.1. Upon completion of this test, there shall be no separation, cracks, delamination, or degradation of physical properties. Superficial cracks in the glazing which will not affect serviceability of the material are acceptable. The Government may require testing to confirm that the physical properties are not affected.

4.7.4.5 Sand and dust. The insert shall be subjected to MIL-STD-810, Method 510.1, Procedure I. There shall be no damage to seals or other components upon completion of this test. All hardware shall operate as specified during and upon completion of this test.

4.7.4.6 Sunshine. Representative samples of all gaskets and seals, as well as a 12 in. by 12 in. (305 mm by 305 mm) panel sample, shall be subjected to MIL-STD-810, Method 505.1, Procedure I. Upon completion of this test, the samples shall be visually examined and any evidence of degradation of physical properties shall constitute failure of this test.

4.7.4.7 Solar load. The insert shall be subjected to a simulated solar load sufficient to raise the outer skin temperature to a minimum of 200°F uniformly over the lid. The uniform solar load temperature should be gradually attained within 4 hours and shall be maintained for an additional 4 hours. As a minimum, one thermocouple per 10 square feet (one square meter) shall be uniformly

Source: https://assist.dla.mil - Downloaded: 2026-10-20T23:12Z
Check the source to verify that this is the current version before use.

distributed on the entire area of the lid. All of the thermocouples should read 200°F ± 15°F throughout the 4 hour period that the solar load shall be maintained. Upon completion of this test, the lid panel shall be examined and any evidence of delamination or deformation shall constitute failure of this test.

4.7.4.8 Marine atmosphere. One representative sample of each fastener, seal, and panel which will be exposed to the atmosphere in the operation and storage modes shall be finished in accordance with the applicable drawings and subjected to tests as described in MIL-STD-810, Method 509.1, except that the salt solution shall have a concentration of 10 percent and the exposure period shall be 96 hours. Upon completion of this test, the test items shall show no evidence of delamination, cracking, corrosion, or deterioration.

4.7.5 Shock tests.

4.7.5.1 Flat Drop. The insert shall be uniformly loaded to the rated gross weight of 155 lbs. (689 Newtons). The insert shall be lifted 12 in. (305 mm) above a flat concrete surface. The distance between the concrete surface and each corner of the insert under test shall not vary more than 0.5 in. (12.7 mm) at the time of the drop. The insert shall then be allowed to free fall to the concrete surface. Upon completion of this test, the insert shall show neither permanent deformation nor abnormality which will render it unsuitable for use and the dimensional requirements of 4.7.2 shall then be satisfied.

4.7.5.2 Rotational drop. The insert shall be uniformly loaded to the rated gross weight of 155 lbs. (689 Newtons). The insert shall be tested with one edge supported 4 in. (102 mm) above a flat concrete surface. The opposite edge shall be lifted a distance of 12 in. (305 mm) above the concrete surface and allowed to free fall onto the surface. This procedure shall be repeated until each edge has been allowed to free fall. Upon completion of this test, the insert shall show neither permanent deformation nor abnormality which will render it unsuitable for use and the dimensional requirements of 4.7.2 shall then be satisfied.

4.8 Test reports. The results of all testing shall be reported and written in compliance with MIL-STD-831 fully describing and illustrating the test procedures and test results.

5. PACKAGING

5.1 Preservation. The insert requires no additional preservation.

Source: https://assist.dla.mil Downloaded: 2026-10-20T23:12Z
Check the source to verify that this is the current version before use.

5.2 Packing. Unless otherwise specified in the contract, no protective media need be installed prior to shipment. Conventional methods of blocking, bracing, and strapping are to be employed during shipment by rail, road, ship and air as described in MIL-STD-1186.

5.3 Marking. In addition to the marking required by 3.10, each insert shall be marked for shipment in accordance with the requirements of MIL-STD-129. A removable data plate shall be installed to show cube, weight and destination specified by the contracting activity.

6. NOTES

6.1 Intended use. The insert covered by this specification is one of a family of containers intended for use by the Fleet Marine Forces to house and support the storage and movement of organizational property and consumable supplies in the field and in garrison.

6.2 Ordering data.

6.2.1 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.

b. When first article testing is required (see 3.1).

c. When quality control system is required (see 4.1.1).

6.2.2 Data requirements. When this specification is used in an acquisition and data are required to be delivered, the data requirements identified below shall be developed as specified by an approved Data Item Description (DD Form 1664) and delivered in accordance with the approved Contract Data Requirements List (CDRL), incorporated into the contract. When the provisions of DOD FAR Supplement, Part 27, Sub-Part 27.410-6 (DD Form 1423) are invoked and the DD Form 1423 is not used, the data specified below shall be delivered by the contractor in accordance with the contract or purchase order requirements. Deliverable data required by this specification are cited in the following paragraphs.

4.8	Test procedures end reports	DI-T-4909	N/A

(Data item descriptions related to this specification and identified in section 6 will be approved and listed as such in DoD 5000.19L, Vol. II, AMSDL. Copies of data item descriptions required by the Contractor in connection with specific acquisition functions should be obtained from the Naval Publications and Forms Center or as directed by the Contracting Officer).

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T23:12Z
Check the source to verify that this is the current version before use.

6.3 First article. First Article test items shall be forty-two sample items manufactured using the same procedures and tooling proposed for production. The Contractor shall submit a First Article test plan and receive Government approval prior to testing. The First Articles shall be examined and tested for approval at the Contractor's plant or at an independent laboratory acceptable to the Government. First Article tests shall be witnessed by a Government representative of the acquiring activity. After completion of First Article testing, the Contractor shall submit a separate test report. The Government reserves the right to waive the requirement for First Article testing for items that have previously been tested and accepted by the Government.

6.4 Subject Term (Key Word) Listing. The following subject term (key word) listing is furnished for retrieval searches.

Container

Container, Insert

Container Racks, PALCON and QUADCON

Preparing activity
Navy-MC
Project No. 8145-0037

Source: https://assist.dla.mil - Downloaded: 2026-10-20T23:12Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS. In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE. This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE NAVY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO 12503 WASHINGTON D C

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE NAVY

Commanding General
Marine Corps Research, Development
and Acquisition Command
Washington, D.C. 20380-0001

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T23:12Z
Check the source to verify that this is the current version before use.

(FOLD ON THIS LINE, CUT ALONG THIS LINE)

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-C-29446(MC)	CONTAINER, INSERT (INSERT)

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)* _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording

b. Recommended Wording

c. Reason/Rationale for Recommendation

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T23:12Z
Check the source to verify that this is the current version before use.