MILITARY SPECIFICATION

CONTAINER CONNECTOR, HORIZONTAL (CONNECTOR)

This specification is approved for use by the United States Marine Corps, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification establishes the requirements for the manufacture and acceptance of the horizontal container connector, referred to herein as the connector.

2. APPLICABLE DOCUMENTS

2.1 Government documents

2.1.1 Specifications, standards, and handbooks. The following specifications, standards and handbooks form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation:

SPECIFICATIONS

MILITARY

MIL-C-29445(MC)	Container, Quadruple (QUADCON)
MIL-Q-9858	Quality Program Requirements
MIL-C-46168	Coating, Aliphatic Polyurethane, Chemical Agent Resistant
MIL-P-52192	Primer Coating, Epoxy

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commandant of the Marine Corps, Code LMA-2, Washington, D.C. 20380, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 8145

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T23:12Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	Marking for Shipment and Storage
MIL-STD-810	Environmental Test Methods and Engineering Guidelines
MIL-STD-831	Test Reports, Preparation of
MIL-STD-889	Dissimilar Metals

2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issue of documents not listed in the DODISS shall be in the issue of the nongovernent documents which is current on the date of the solicitation.

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION (ISO)

ISO 668	Freight Containers--External Dimensions and Ratings
ISO 1161	Series 1 Freight Containers--Corner Fittings --Specification
ISO 1496/I	Series 1 Freight Containers--Specification and Testing--Part I: General Cargo Containers

(Application for copies should be addressed to International Organization for Standardization, P.O. Box 56, 1211 Geneva 20, Switzerland.)

AMERICAN SOCIETY FOR TESTING AND MATERIALS

ASTM-D-3951	Commercial Packaging, Practice for

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, Pennsylvania, 19103.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T23:12Z
Check the source to verify that this is the current version before use.

(Industry association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets, or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specified exemption has been obtained.

3. REQUIREMENTS

3.1 Qualification. Prior to contract award, the Contractor shall furnish qualification articles for an operational capability demonstration when specified in the contract or purchase order. Examination and tests shall be those specified herein (see 4.4 and 6.3). Qualification articles shall be manufactured using the same procedures and tooling used for production. Approval of qualification articles by the acquiring activity shall not relieve the Contractor of the obligation to supply equipment conforming to this specification. Changes or deviations in delivery units from the approval qualification article baseline shall require written authorization by the requiring activity.

3.2 Materials. Materials shall be free from defects that would adversely affect the performance or maintainability of the connector.

3.2.1 Dissimilar materials. Intimate contact of dissimilar materials, as defined in MIL-STD-889, which can be expected to cause galvanic corrosion, shall be avoided. When such contact cannot be avoided, an interposing insulating material shall be provided to minimize the corrosive effect.

3.3 Design and construction. The connector shall provide a 3 in. (+0, -0.06 in) separation between containers of 1D, 1E, or 1F size to create the 1C size as specified in ISO 668. No part of the 1C connector shall project beyond the overall external dimensions of the 1C configuration when used to couple the smaller sizes into the size as specified in ISO 1496/I. Testing shall be in accordance with 4.6.1.

3.3.1 Parts. The connector may consist of any number of fixed or moving parts, but all parts shall be fully assembled. The connector may be operated by a common mechanics tool, such as a wrench. A unique tool, separate from the connector shall not be required or permitted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T23:12Z
Check the source to verify that this is the current version before use.

3.3.2 Compatibility. The connector shall interface with the end faces of the corner fittings specified in ISO 1161. Four connectors will be used at each container interface, two at the top and two at the bottom; therefore, the connector shall be compatible with top corner fittings and with bottom corner fittings. The blend radii on the inside of the cavity of the bottom corner fittings will not exceed 1/8 inch between the end aperture wall and the bottom wall and between the end aperture wall and the top wall. The 1/8 inch limit applies only to bottom corners, not tops; only at ends, not sides; and only the thickened part of the wall around the aperture. Testing shall be in accordance with 4.6.2.

3.3.3 Load capacity. The ultimate load capacity of the connector shall not be less than 54,000 pounds (lbs) in tension between bottom corner fittings, 16,900 pounds (lbs) in tension between top corner fittings, 46,100 pounds (lbs) in compression, and 16,600 pounds (lbs) in single vertical shear between bottom corner fittings. Testing shall be in accordance with 4.6.3, 4.6.4, 4.6.5, and 4.6.6.

3.3.4 Use with quadruple containers. The connectors shall be capable of use as part of the test apparatus when four Marine Corps quadruple containers (QUADCON's) are coupled together and then certified as an ISO type 1CX container in accordance with ISO 1496/I. The gross weight rating, R, for the quad of QUADCON's (four QUADCON's coupled end-to-end by means of the connectors) shall be 44,800 pounds (lbs). The certification tests in ISO 1496/I cover the marine, highway, and rail modes of transportation. Testing shall be in accordance with 4.6.7. When, or if, the connector is procured separately from the QUADCONs, the four QUADCONs required for testing will be furnished to the Contractor by the Government.

3.3.5 Operation. Each connector shall be capable of being fastened to one of the containers before two containers are brought together to facilitate docking of the containers. The containers shall be docked and coupled in no more than four minutes. Testing shall be in accordance with 4.6.8. In addition, the connector's mechanism shall be operable in cold weather by persons wearing gloves or mittens.

3.3.6 Interchangeability. Each and every connector supplied in accordance with these requirements shall be interchangeable with all other connectors and shall be capable of use in both the upper and lower horizontal corner fittings of the containers.

3.3.7 Bolted and riveted parts. Bolt and rivet holes shall be accurately punched, drilled, or cast and have the burrs removed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T23:12Z
Check the source to verify that this is the current version before use.

Washers, lockwashers, or locknuts shall be provided where necessary and all bolts, nuts, and screws shall be tight. Rivet heads, when not countersunk or flattened, shall be of uniform size and shape for the same diameter rivet, concentric with the rivet holes, and in full contact with the surface of the members.

3.3.8 Welding. The surface of the parts to be welded shall be free from dust, scale, paint, grease, or other foreign matter. Weld penetration shall be such as to provide transference of maximum design stress through the base metal juncture.

3.3.9 Castings. Castings shall be sound and free from patching, misplaced coring, warping, or defects that might render the castings unsound for use.

3.4 Environmental requirements.

3.4.1 Temperature-humidity. The connector shall be capable of functioning and withstanding exposure to temperatures of -65°F to 125°F at any possible relative humidity from 0 to 100 percent. In storage, the connector shall be capable of withstanding exposure to temperatures of -70°F to 160°F at any possible relative humidity from 0 to 100 percent without cracking, corroding, or peeling of paint. Testing shall be in accordance with 4.6.10.1 and 4.6.10.2.

3.4.1.1 Thermal shock. The connector shall be capable of withstanding sudden temperatures changes up to and including from 160°F to -70°F to 160°F without degradation of physical properties. Testing shall be in accordance with 4.6.10.3.

3.4.2 Snow and ice. The connector shall be capable of functioning in accordance with the requirements specified herein during periods of snow and ice storms. However, the coupling and uncoupling rates need not be measured under conditions of extreme temperatures.

3.4.3 Sand and dust. The connector shall withstand the effects of sand and dust on all external moving parts without degradation of physical properties. Testing shall be in accordance with 4.6.10.4.

3.4.4 Marine environment. The connector shall be fully serviceable when exposed to sea-salt fallout equivalent to 25 lbs/acre/year (2.8 grams/m^2/year). All components shall show no evidence of corrosion or degradation when tested as required by 4.6.10.5.

3.5 Weight. The weight of each connection shall not exceed 18 lbs. (to the nearest 1/2 lb). Testing shall be in accordance with 4.6.9.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T23:12Z
Check the source to verify that this is the current version before use.

3.6 Finish. All exterior surfaces except threaded surfaces shall be coated with a primer coat in accordance with MIL-P-51292. All primed surfaces shall be finished painted with number 383 green in accordance with MIL-C-46168.

3.7 Identification marking. The Contractor's part number shall be embossed, etched, or engraved on each connector.

3.8 Workmanship. All parts, components, and assemblies of the connector, including castings, forgings, stampings, machined surfaces, and welded parts, shall be clean and free from any defects that will reduce the capability of the connector to meet the requirements specified herein. Any components and assemblies which have been repaired or modified to overcome deficiencies or deficient components or assemblies which are determined to be used "as is" shall not be used unless authorized by the contracting activity. External surfaces shall be free from burrs, slag, sharp edges and corners, except where sharp edges and corners are required.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the Contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the Contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the Contractor's overall inspection system or quality program in accordance with MIL-Q-9858. The absence of any inspection requirements in this specification shall not relieve the Contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Classification of inspections. The inspections requirements specified herein are classified as follows:

a. Operational capability demonstration (see 4.4)

b. Quality conformance inspection (see 4.5)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T23:12Z
Check the source to verify that this is the current version before use.

4.3 Inspection conditions. Unless otherwise specified, all inspections shall be performed in accordance with the test conditions specified in 4.4 and 4.5.

4.4 Operational capability demonstration. Prior to beginning production of the connector, the Contractor shall fabricate sixteen connectors and subject them to the tests specified in Table I.

4.5 Quality conformance inspection. Sampling for quality conformance testing shall be in accordance with MIL-STD-105, Level II, acceptable quality level (AQL) 1.5 percent defective. Lot size shall be as specified in the contract. Samples shall be chosen at random and subjected to the tests specified in Table I.

TABLE I. Tests

INSPECTION	REQ PARA	TEST PARA	OCD ART	QUAL CONF
DIMENSIONAL	3.3	4.6.1	X	X
COMPATIBILITY	3.3.2	4.6.2	X	X
TENSION CAPACITY, BOTTOM	3.3.3	4.6.3	X	X
TENSION CAPACITY, TOP	3.3.3	4.6.4	X	X
COMPRESSION CAPACITY	3.3.3	4.6.5	X	X
SHEAR CAPACITY	3.3.3	4.6.6	X	X
QUADCON CERTIFICATION	3.3.4	4.6.7	X	
OPERATION	3.3.5	4.6.8	X	X
WEIGHT	3.5	4.6.9	X	
HUMIDITY RESISTANCE	3.4.1	4.6.10.1	X	
TEMPERATURE RANGE	3.4.1	4.6.10.2	X	
TEMPERATURE SHOCK	3.4.1.1	4.6.10.3	X	
SAND AND DUST	3.4.3	4.6.10.4	X	
MARINE ATMOSPHERE	3.4.4	4.6.10.5	X	
FINISH	3.6	4.7	X	X

4.6 Tests

4.6.1 Dimensional. Measure the gage of the connector to the nearest 0.01 inch to validate compliance with the dimension (3 in) and tolerance (+0, -0.06 in) in 3.3. Mount and completely close the connector in the correct orientation between one right-hand bottom corner fitting and one left-hand bottom corner fitting and then visually inspect to confirm that the connector does not extend beyond the planes of the side surfaces and bottom surfaces of the fittings. Mount and completely close the connector in the

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T23:12Z
Check the source to verify that this is the current version before use.

correct orientation between one right-hand top corner fitting and one left-hand top corner fitting and then visually inspect to confirm that the connector does not extend beyond the planes of the side surfaces and top surfaces of the fittings. All corner fittings used in this test shall conform to ISO 1161.

4.6.2 Compatibility. Concurrent with the dimensional test in 4.6.1, visually inspect the connector to confirm compliance with 3.3.2 by ensuring that the connector closes completely and seats firmly.

4.6.3 Tension capacity between bottom corner fittings. The connector shall be mounted and completely closed in the correct orientation between one right-hand bottom corner fitting and one left-hand bottom corner fitting and then subjected to 54,000 lbs of axial tension, applying the force to the corner fittings at a rate not to exceed 10,000 lbs/min. This test shall be repeated four times, each time on a different connector. Each of the four specimens shall be serviceable after this test as determined by the performance of the tests described in 4.6.1. The corner fittings used in this test shall conform to ISO 1161.

4.6.4 Tension capacity between top corner fittings. The connector shall be mounted and completely closed in the correct orientation between one right-hand top corner fitting and one left-hand top corner fitting and then subjected to 16,900 lbs of axial tension, applying the force to the corner fittings at a rate not to exceed 10,000 lbs/min. This test shall be repeated four times, each time on a different connector. Each of the four specimens shall be serviceable after this test as determined by the performance of the tests described in 4.6.1. The corner fittings used in this test shall conform to ISO 1161.

4.6.5 Compression capacity. The connector shall be mounted and completely closed in the correct orientation between one right-hand bottom corner fitting and one left-hand bottom corner fitting and then subjected to 46,100 lbs of axial compression, applying the force to the corner fittings at a rate not to exceed 10,000 lbs/min. The test shall be repeated two times, each time on a different connector. Each of the tow specimens shall be serviceable after this test as determined by the performance of the tests described in 4.6.1. The corner fittings used in this test shall conform to ISO 1161.

4.6.6 Shear capacity. The connector shall be mounted and completely closed in the correct orientation between on right-hand bottom corner fitting and one left-hand bottom corner fitting and then subjected to 16,600 lbs of single shear, applying the force to the corner fittings at a rate not to exceed 10,000 lbs/

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T23:12Z
Check the source to verify that this is the current version before use.

min. The test shall be repeated four times, each time on a different connector. Each of the four specimens shall be serviceable after this test as determined by the performance of the tests described in 4.6.1. The corner fittings used in this test shall conform to ISO 1161. (In this test, it will be important to provide sufficient stiffness in the test apparatus to prevent rotation of the corner fittings, and this combined forces.) These tests may be conducted two at a time to create a symmetrical loading condition and sufficient bending resistance in the test apparatus.

4.6.7 QUADCON certification. Twelve connectors shall be used to couple together four QUADCONs built in accordance with MIL-C-29445(MC) into a 1CX configuration as defined in ISO 668 and ISO 1496/I. The assembly of QUADCONs and connectors shall be subjected to the tests that are used to certify the assembly as an ISO 1CX container.

4.6.7.1 Transverse and longitudinal rigidity. Four QUADCONs shall be coupled together to form a 1C container and placed on four level supports, one under each extreme end corner fitting, and shall be restrained against lateral and vertical movement by means of anchor devices, acting through the bottom corner fittings. Lateral restraint shall be provided only at a bottom corner fitting diagonally opposite to and in the same end frame as a top corner fitting to which force is applied. When testing two end frames separately, vertical restraint shall be applied only at the end frame under test. A force of 33,600 lbs (149,460 Newtons) shall be applied spearately to each of the top corner fittings on one side of the QUADCONs under test in lines parallel to both the base and to the planes of the ends. The force shall be applied first towards, then away from the top corner fittings. Upon completion of this test, each QUADCON, and the assembly, shall show neither permanent deformation nor abnormality which will render it unsuitable for use, and shall meet the dimensional requirements of 4.7.11 of MIL-C-29445(MC). This test shall be repeated with the forces of 16,800 lbs (74,730 Newtons) acting parallel to the planes of the sides of the QUADCONs.

4.6.7.2 Lifting from top. The four QUADCONs under test shall be coupled together to form a 1C container and shall then have a load uniformly distributed over the floor in such a way that the combined weight of the four QUADCONs and the test load is equal to 89,600 lbs (398,540 Newtons). The QUADCON assembly shall then be carefully lifted from the top corner fittings at the ends of the assembly (four only) in such a way that no significant acceleration or deceleration forces are applied. The QUADCON assembly shall be suspended by the lifting mechanism for 5 minutes and then carefully lowered to the ground. Upon completion of this test, each QUADCON, and the assembly, shall show neither permanent deformation

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T23:12Z
Check the source to verify that this is the current version before use.

nor abnormality which will render it unsuitable for use and the dimensional requirements of 4.7.11 of MIL-C-29445(MC) shall then be satisfied for each QUADCON individually and as an assembly.

4.6.7.3 Lifting from bottom. The four QUADCONs under test shall be coupled together to form a 1C container and shall then have a load uniformly distributed over the floor in such a way that the combined weight of the four QUADCONs and the test load is equal to 89,600 lbs (398,540 Newtons). They shall then be carefully lifted from the side apertures of the four bottom corner fittings at the ends of the assembly in such a way that no significant acceleration or deceleration forces are applied. Lifting forces shall be applied at 45° from the vertical, parallel to the long sides of the QUADCON assembly. In each case, the line of action of the lifting force and the outer face of the corner fitting shall be no further apart than 1.5 in (38 mm). The lifting shall be carried out in such a manner that the lifting devices bear on the bottom corner fittings only. The QUADCON assembly shall be suspended for 5 minutes and then lowered carefully to the ground. Upon completion of this test, each QUADCON, and the assembly shall show neither permanent deformation nor abnormality which will render it unsuitable for use and the dimensional requirements of 4.7.11 of MIL-C-29445(MC) shall then be satisfied for each QUADCON individually and as an assembly.

4.6.7.4 Longitudinal restraint. The four QUADCONs under test shall be coupled together to form a 1C container and placed on four level supports, one under each extreme outer corner fitting, and shall then have a load uniformly distributed over the floor in such a way that the gross weight of the four QUADCONs and the test load is 44,800 lbs (199,270 Newtons). The QUADCON assembly shall then be restrained by rigid anchor points, two on one end only. These anchors shall be through the bottom apertures of the bottom corner fittings. A force of 89,600 lbs (398,540 Newtons) (twice the gross weight of the QUADCON assembly) shall be applied horizontally to the QUADCON assembly through the bottom apertures of the other two corner fittings, first towards, and then away from the anchor points. Upon completion of this test, each QUADCON, and the assembly, shall show neither permanent deformation nor abnormality which will render it unsuitable for use and the dimensional requirements of 4.7.11 of MIL-C-29445(MC) shall then be satisfied.

4.6.7.5 Coast Guard Certification. The QUADCONs shall be tested for Coast Guard Certification. If there is any damage to the QUADCONs due to these tests, it will be the responsibility of the contractor to repair the damage or make any correction necessary for the QUADCONs to pass Coast Guard certification at his own expense. A certification of Coast Guard approval shall be furnished and Coast Guard certification plates shall be attached to each delivered QUADCON.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T23:12Z
Check the source to verify that this is the current version before use.

4.6.7.6 Dimensional. The length, width, height, and diagonals (K1 and K2) shall be measured and recorded for each QUADCON. During first article testing, the length, width, height, and diagonals (K1 and K2) shall be measured and recorded for the four QUADCONs when coupled together to form a 1C container. The requirements of 3.7 shall be satisfied.

4.6.8 Operation. Measurement shall be made of the time required for four men with a forklift truck and four connectors to dock and couple two QUADCONs. The time period shall start with the containers adjacent and correctly oriented, but not touching, and with the connectors at the side fully opened. The time period shall end when the containers are fully docked and coupled, with all four connectors fully closed and seated. The reverse procedure shall be used to measure the uncoupling time. To pass the test, coupling shall be completed within 4 minutes, and uncoupling shall be completed within 4 minutes.

4.6.9 Weight. The weight of each connector shall be taken. The requirements of 3.5 shall be satisfied.

4.6.10 Environmental tests.

4.6.10.1 Humidity resistance. Two connectors shall be subjected to MIL-STD-810, Method 507.1, Procedure II, excluding steps 2-4, 7, and 8. After cycling, the connector shall be examined and show no evidence of cracking, corrosion, peeling of paint, or deterioration of any part of the connector.

4.6.10.2 Low temperature range. Two connectors shall be cold soaked in a mechanically refrigerated cold chamber at -70°F for a minimum of 16 hours. The chamber temperature shall then be raised to -65°F. The connector mechanisms will then be opened and closed. The connectors shall operate as specified during and upon completion of this test and successfully pass the tests described in 4.6.1.

4.6.10.3 Temperature shock. Two connectors shall be subjected to MIL-STD-810, Method 503.1. Upon completion of this test, the connectors shall be serviceable as determined by successful completion of the test described in 4.6.3 and shall show no evidence of degradation of physical properties.

4.6.10.4 Sand and dust. Two connectors shall be subjected to MIL-STD-810, Method 510.1, Procedure I. Upon completion of this test, the connectors shall show no evidence of deterioration of physical properties and the tests described in 4.6.1 shall be successfully passed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T23:12Z
Check the source to verify that this is the current version before use.

4.6.10.5. Marine atmosphere. Two connectors shall be subjected to MIL-STD-810, Method 509.1, except that the salt solution shall have a concentration of 10 percent and the exposure period shall be 96 hours. Upon completion of this test, the connectors shall show no evidence of corrosion.

4.7 Finish. The connectors shall be inspected for completeness and adequacy of finish. Painted components shall be fully covered with a uniform coat of paint, and show no runs, sags or blisters, or overspray.

4.8 Test reports. The results of all testing shall be reported and written in compliance with MIL-STD-831 fully describing and illustrating the test procedures and test results.

5. PACKAGING

5.1 Preservation. The connector requires no additional preservation.

5.2 Packing. The connectors shall be packaged in accordance with ASTM-D-3951.

5.3 Marking. In addition to the marking required by 3.7, each connector shall be marked for shipment in accordance with the requirements of MIL-STD-129, paragraph 4.4.8.

6. NOTES

6.1 Intended use. The connector covered by this specification is intended for the end-to-end coupling of intermodal shipping containers and containerized shelters into arrays up to 20 feet long in accordance with the ISO 668 and 1496/I. It is to be employed throughout the Marine Corps field logistics system for coupling 10-foot shelters, half-container (HALFCON) frames, quadruple containers (QUADCONs), and six-part-container (SIXCON) tanks and frames.

6.2 Ordering data.

6.2.1 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.

b. When first article testing is required (see 3.1).

c. When a quality control system is required (see 4.1.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T23:12Z
Check the source to verify that this is the current version before use.

6.2.2 Data Requirements. When this specification is used in an acquisition and data are required to be delivered, the data requirements identified below shall be developed as specified by an approved Data Item Description (DD Form 1664) and delivered in accordance with the approved Contract Data Requirements List (CDRL), incorporated into the contract. When the provisions of DoD FAR Supplement, Part 27, Sub-Part 27.410-6 (DD Form 1423) are invoked and the DD Form 1423 is not used, the data specified below shall be delivered by the contractor in accordance with the contract or purchase order requirements. Deliverable data required by this specification are cited in the following paragraphs.

Para No.	Data Requirement Title	Applicable DID No.	Option

(Data item descriptions related to this specification, and identified in section 6 will be approved and listed as such in DoD 5000.19L, Vol. II, AMSDL. Copies of data item descriptions required by the contractors in connection with specific acquisition functions should be obtained from the Naval Publications and Forms Center or as directed by the contracting officer.)

6.3 Qualification. Operation capability demonstration (OCD) articles shall be sixteen sample items manufactured using the same procedures and tooling as production items. OCD sample articles shall be tested and approved at the Naval Civil Engineering Laboratory (NCEL), Port Huemene, CA. OCD tests will be witnessed by a Government representative of the acquiring activity. Contract award will be made only after successful completion of OCD.

6.4 Subject term (keyword) listing. The following subject term (keyword) listing is furnished for retrieval searches.

Connector

Container Connector

Container Connector, Horizontal

Horizontal Connector

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T23:12Z
Check the source to verify that this is the current version before use.

6.5 International standardization agreements. Certain provisions of this specification (see 3.1) are the subject of international standardization agreement ISO/DIS 668 and are regulated by the Coast Guard. When amendments, revision, or cancellation of the specification is proposed which will modifty the international agreement concerned, the preparing activity will take appropriate action through international standardization channels including departmental standardization office to change the agreement or make other appropriate accommodations.

Preparing Activity
Navy - MC
Project No. 8145-0035

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T23:12Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE NAVY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO 12503 WASHINGTON D C

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE NAVY

Commanding General
Marine Corps Research, Development
and Acquisition Command
Washington, D.C. 20380-0001

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T23:12Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-C-29449(MC)	Container Connector, Horizontal (Connector)

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
	☐ USER
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ MANUFACTURER
	☐ OTHER *(Specify)* _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording

c. Reason/Rationale for Recommendation

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil – Downloaded: 2026-10-20T23:12Z
Check the source to verify that this is the current version before use.