MILITARY SPECIFICATION
BEACON, RADIO AN/APN-69

This amendment forms a part of Military Specification MIL-B-25084 (USAF), dated 21 July 1955.

PAGE 1

*2.1, Federal Specifications: Delete QQ-P-416 Plating, Cadmium (Electrodeposited) and add: QQ-Z-325 Zinc Coating, Electrodeposited.

*2.1, Military Specifications: Delete "JAN-J-641", "MIL-C-3608", "MIL-E-4682" and "MIL-W-5274" and add:

"MIL-J-641 Jack, Telephone, General Specification for"
"MIL-F-3922 Flange, Waveguide, General Purpose, General Specification for"
"MIL-W-81381A Wire, Electric, Polymide Insulated, Copper and Copper Alloy"

PAGE 2

2.1, Military Specification: Delete "MIL-P-7094", "MIL-E-7894" and "MIL-T-8212" and add:

"MIL-C-7439 Coating System, Elastomeric, Rain Errosion Resistant and Rain Errosion Resistant with Antistatic Treatment for Exterior Aircraft and Missile Parts"
"MIL-C-39012 Connector, Coaxial, Radio Frequency, General Specification for"

2.1, Military Standards: Delete "MS90058" and "MS91236" and add:

"MIL-STD-143 Standards and Specifications, Order of Precedence for the Selection of"
"MIL-STD-200 Electron Tubes, Selection of"
"MIL-STD-704 Electric Power, Aircraft, Characteristics and Utilization of"

2.1, Air Force-Navy Aeronautical Standards: Delete "AN3102" and substitute:

"MS3452 Connector, Receptacle, Electric, Box Mounting, Rear Release"

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T03:33Z
Check the source to verify that this is the current version before use.

2.1, Air Force drawings: Add the following:

"65046434 Control, Radio Beacon, C-182C/APN-69A"
"66045796 Receiver-Transmitter, Radio RT-204B/APN-69A"

PAGE 3

2.1, Publications: Delete "Air Force-Navy Aeronautical Bulletin 143".

PAGE 4

3.3.1.1: Delete "ANA Bulletin 143" and substitute "MIL-STD-143".

PAGE 5

3.3.2.1: Delete "JAN-J-641" and substitute "MIL-J-641".

*3.3.4.1: Delete and substitute:

"3.3.4.1 Standard parts, zinc plated in accordance with specification QQ-Z-325 and supplied only with type I zinc plating shall not be used unless given the type II treatment (or type III, if painted) before assembly into equipment, or unless used within pressurized or sealed space not exposed to the deteriorating effects of moist air".

PAGE 6

3.3.10.1: Delete specification "MIL-E-7894" and substitute "MIL-STD-704".

PAGE 7

3.3.11: Delete specification "MIL-E-4682" and substitute "MIL-STD-200".

PAGE 8

3.3.17.1: Delete specification "MIL-E-7894" and substitute "MIL-STD-704".

PAGE 10

3.5.1.5: Delete "MIL-C-3608" and substitute "MIL-C-39012".

PAGE 11

3.5.1.5.1, subparagraphs d, e, and f: Delete "MIL-C-3608" and substitute "MIL-C-39012".

3.5.1.5.1, subparagraph g: Delete "JAN-J-641" and substitute "MIL-J-641".

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T03:33Z
Check the source to verify that this is the current version before use.

PAGE 13

3.5.1.8: Add new paragraph after subparagraph p: "q. R-371". A screwdriver control, located on the pulse control chassis of the RT-204B/APN-69 built in accordance with drawing 66C45796, shall be provided to permit pulse-length descrimination adjustment".

PAGE 15

3.5.1.11.7: Delete "MIL-T-8212" and substitute "MIL-E-1/1704".

3.5.1.13.1: After the last sentence, add "An additional pulse length descrimination circuit, selected by a switch on the Control Radio Beacon C-812(C)/APN-69 built in accordance with drawing 65C46434, shall be provided for the RT-204(B)/APN-69 built in accordance with drawing 66C45796. This circuit shall accept pulses between 0.25 and 2.3 microseconds duration. An adjustment shall be provided to shift the upper rejection limit when so desired. The lower limit shall be fixed".

PAGE 20

Add new paragraph after paragraph 3.5.2.2.3: "3.5.2.2.4 LONG-SHORT selector. A toggle switch shall be provided on the Control Radio Beacon C-812(C)/APN-69 built in accordance with drawing 65C46434 to switch pulse length descrimination circuits of the pulse control chassis in the RT-204/APN-69 built in accordance with drawing 66C45796".

PAGE 22

3.5.3.1: Delete "MIL-P-7094" and substitute "MIL-C-7439".

3.5.3.1: Delete and substitute: "3.5.3.1.1 Coupling. The antenna assembly shall be terminated with a waveguide flange part M3922/59-008 built in accordance with MIL-F-3922".

PAGE 24

3.5.6.1: Delete standard "MS91236" and substitute "MIL-C-39012/1".

3.7: Add the following:

Materials: "Recycled and recovered raw material should be used to the maximum extent possible in lieu of virgin raw material as long as these materials do not jeopardize the intended use and fully comply with all contract requirements. Materials used shall be free from defects which would adversely affect the performance or maintainability of individual components or the overall assembly. Materials not specified herein shall be of the same quality used for the intended purpose in commercial practice. None of the above shall be interpreted to mean that the use of used or rebuilt products will be allowed".

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T03:33Z
Check the source to verify that this is the current version before use.

PAGE 25

4.2: Delete specification "MIL-E-7894" and substitute "MIL-STD-704".

PAGE 31

4.3.2.4.1.1: Delete specification "MIL-E-7894" and substitute "MIL-STD-704".

NOTE: The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment(s) were made. This was done as a convenience only and the government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationships to the last previous amendment.

Change the preparing activity and custodian as follows:

Custodian:
Air Force - 99

Preparing Activity:
Air Force - 99

Project No: 5826-F166

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T03:33Z
Check the source to verify that this is the current version before use.