INCH-POUND
MIL-DTL-25038/1E
w/AMENDMENT 1
19 April 2016
SUPERSEDING
MIL-DTL-25038/1E
1 December 2000

DETAIL SPECIFICATION SHEET


WIRE, ELECTRICAL, HIGH TEMPERATURE, FIRE RESISTANT, FLIGHT CRITICAL, NORMAL WEIGHT

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-25038.

REQUIREMENTS:

Design and construction: See figure 1.



Note: 1/ The outer two layers may be reversed in their sequence.

FIGURE 1. Wire, electrical.

Temperature rating:	260 °C.
Voltage:	600 V rms.
Color:	Unless otherwise specified by the Part or Identifying Number (PIN), the color shall be white.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T03:25Z
Check the source to verify that this is the current version before use.

. Thermal shock:
Maximum change in insulation measurement:
.060 inch for sizes 22 through 10.
.125 inch for sizes 8 through 1.
.187 inch for sizes 0 through 0000.

PIN: M25038/1 – (wire size from table 1) – (color code designator in accordance with MIL-STD-681 and MIL-DTL-25038.)

Examples: Size 20 AWG, white: M25038/1-20-9;
Size 20 AWG, white with orange stripe: M25038/1-20-93.

TABLE I. Finished wire construction and performance details.

Wire Size 1/	Conductor stranding			Maximum conductor diameter (inch)	Maximum dc resistance 1,000 feet at 20 °C (ohms)	Finished wire diameter (inch)		Weight lbs/1,000 feet (max)	Performance details	
	Number of strands	AWG size	Nominal diameter (inch)			Min.	Max.		Bend and cold bend test mandrel	
									Mandrel OD (inches)	Load on mandrel (pounds)
22	19	34	.0063	.033	23.700	.100	.116	10	6	2
20	19	32	.0080	.041	14.600	.109	.125	12	6	2
18	19	30	.0100	.052	9.140	.119	.135	15	6	2
16	19	29	.0113	.061	6.850	.127	.147	19	8	3
14	19	27	.0142	.074	4.320	.150	.170	25	8	3
12	19	25	.0179	.093	2.780	.165	.185	35	8	3
10	49	27	.0142	.128	1.680	.210	.230	55	10	5
8	133	29	.0113	.176	.936	.256	.280	85	12	5
6	133	27	.0142	.218	.591	.318	.342	127	14	10
4	133	25	.0179	.272	.375	.383	.407	192	16	10
2	665	30	.0100	.345	.241	.460	.484	291	20	15
1	817	30	.0100	.384	.196	.497	.533	347	22	15
0	1045	30	.0100	.432	.153	.537	.573	415	24	20
00	1330	30	.0100	.490	.120	.595	.635	520	24	25
000	1672	30	.0100	.548	.096	.660	.700	648	24	30
0000	2109	30	.0100	.615	.077	.730	.770	793	24	30

Notes: 1/ Wire sizes 22 through 12 are inactive for new design; for new design use MIL-DTL-25038/3.

Amendment notations. The margins of this specification are marked with vertical lines to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Referenced documents: This document references MIL-DTL-25038 as well as:

MIL-DTL-25038/3
MIL-STD-681

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T03:25Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - AS
Air Force – 85
DLA - CC

Review activities:
Army - AR, MI
Navy - OS
Air Force – 99

Preparing activity:
DLA - CC

(Project 6145-2016-030)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, please verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T03:25Z
Check the source to verify that this is the current version before use.