MILITARY SPECIFICATION

PIPE THREADS, TAPER, AERONAUTICAL NATIONAL FORM, SYMBOL ANPT, GENERAL REQUIREMENTS FOR

This amendment forms a part of Military Specification MIL-P-7105B, 6 January 1965, and is mandatory for use by all Departments and Agencies of the Department of Defense.

Page 6, paragraph 3.3: Delete the formulae under "Taper Plugs" and "Taper Rings" and substitute:

"Taper Plugs

D = Minor diameter at E_3 with max trunc

D = E_{3*} - Col 4

B_t = L_1 + L_{3*}

B = B_t - Length equiv. of max trunc - Min trunc

B = B_t - Col 5

MN = B - Col 3 (one turn)

MN_t = B_t - Col 3

MX = B + Col 3

MX_t = B_t + Col 3

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T08:07Z
Check the source to verify that this is the current version before use.

"Taper Rings

D = Major diameter at E_2 with max trunc

D = E_{2*} + Col 4

B_t = L_{2*}

B = B_t - Length equivalent of max trunc - min trunc

B = B_t - Col 5

MN = B + Col 3

MN_t = B_t + Col 3

MX = B - Col 3

MX_t = B_t - Col 3

*Product figured to 5 significant decimal places"

Custodians:
Army - WC
Navy - None
Air Force - 11

Review activities:
Army - MO, WC
Navy - None
Air Force - 11, 69, 70

User activities:
Air Force - 67, 71

Preparing activity:
Air Force - 11

Project No. 4730-0561

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T08:07Z
Check the source to verify that this is the current version before use.