MIL-I-3575 / 38C
24 July 1985
SUPERSEDING
MIL-I-3575 / 38B
31 March 1969

MILITARY SPECIFICATION SHEET

INSIGNIA, OFFICER CANDIDATE SCHOOL, ARMY

This specification is approved for use by all Departments and Agencies of the Department of Defens
The complete requirements for procuring the item(s) described herein shall consist of this document and the issue in effect of Specification MIL-I-3575.

PIERCED

DASH NO.
-1: Regular
-2: Subdued

MATERIAL:
-1: RED BRASS
-2: RED BRASS OR ZINC ALUMINUM
DIMENSIONS (INCHES):
HEIGHT: 7/16 (REF)
WIDTH: 1-7/32 (REF)
THICKNESS: .080 ± .005
FINISH:
-1: GOLD PLATED MIRROR-LIKE POLISHED FINISH
-2: RED BRASS, DULL FLAT BLACK ENAMEL FINISH

ZINC ALUMINUM - SEE NOTE 3

NOTES:
1. ATTACHING DEVICE SHALL BE PRONG AND CLUTCH TYPE. PRONGS SHALL BE LOCATED ON THE HORIZONTAL CENTER LINE, 1-1/16 ± 1/64 INCH ON CENTERS.

2. AREAS AROUND PERIODS SHALL NOT BE TRIMMED, BUT SHALL BE AS SHOWN.

3. IN ADDITION TO THE FINISH SPECIFIED, THE ZINC ALUMINUM SHALL BE BRASS PLATED TO BEGIN THE PROCESS.

CUSTODIANS:	REVIEW ACTIVITIES:	USER ACTIVITIES:	PREPARING ACTIVITY:
ARMY	IH		THE INSTITUTE OF HERALDRY, UNITED STATES ARMY
AIR FORCE			
NAVY			
OTHER	CT		

Project No. 8455 - A180

/FSC 8455/

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T18:24Z
Check the source to verify that this is the current version before use.